

ELECTRONICS Australia

August, 1967

Incorporating RADIO, TELEVISION & HOBBIES

Vol. 29 No. 5



30c

3/- N.Z.
35c (3/6) N.G.

INERTIAL GUIDANCE COMPONENTS

Guitar "fuzz box" • Relay stations in space
New telescope for Aust. • All-wave receiver

Registered in Australia for transmission by post as a periodical

*Elegance
in Design
Luxury
in Performance*

AKAI

**80 watts AA7000
Tuner-Stereo Amplifier**



*** Low Silhouette Styling
* Inbuilt Tuner * Solid State**

\$493.33

SPECIFICATIONS AA 7000

FREQUENCY RECEPTION

FM : 87 to 109 MC
AM : 536 to 1,605 KC

SENSITIVITY

FM : 1.6 μ V (98 MC, S/N 30 db)
AM : 30.0 μ V (1 MC, S/N 20 db,
1 KC, 30% modulation)

IMAGE RATIO

FM : Over 60 db (98 MC)
AM : Over 50 db (1MC)

FM SECTION

Multi-separation : Over 35 db (1 KC)
Distortion : Below 0.8% (1 KC, 100% modulation)

OUTPUT

Effective output : 30 W/30 W(1 KC, 1% distortion)
Music power output : 40 W/40 W(1 KC, 1% distortion)

INPUT SENSITIVITY

Phono : 3.5 mV
AUX-H : 1.2 V
AUX-1 : 400 mV

TAPE TERMINAL

Recording output : 350 mV
Tape monitor : 400 mV

TONE CONTROL

Bass : 100 cps \pm 11 db
Treble : 10 KC \pm 10 db

LOUDNESS

CONTROL : 100 cps \pm 6 db, 10 KC \pm 4 db
at - 20 db volume position

S/N RATIO

AUX : Over 70 db
Phono : Over 60 db

OVERALL

DIMENSIONS : 20 $\frac{3}{4}$ " (W) x 17 $\frac{1}{2}$ " (D) x 4 $\frac{1}{2}$ " (H)
WEIGHT : 32.4 lbs

The Famous AA5000 Amplifier

55 Watts per channel. 20-35000 C.P.S. frequency response. Inputs for Magnetic and ceramic pick-ups. Individual Bass and Treble controls. Loudness control. Low and high cut filters. Ideal for use with the Akai X100D tape deck. \$298.00

AK2

**MAGNECORD AUSTRALASIA PTY. LTD.,
CHAPMAN HOUSE, 210 CLARENCE ST
SYDNEY. PHONE 29-1704.**

Interstate Agents: Maurice Chapman Magnecord Pty. Limited.
Telephone No. 85-4654, Melbourne. Neil Muller Pty. Limited.
Telephone No. 71-1162, Adelaide. Chandlers Pty. Ltd.
Telephone No. 31-0341, Brisbane.

ELECTRONICS Australia

Incorporating "RADIO, TELEVISION and HOBBIES"

ABC certified circulation in excess of 47,000.

Volume 29, No. 3

Editor:
NEVILLE WILLIAMS, M.I.R.E.E. (Aust.)
(VK2XV).

Assistant Editor:
PHILIP WATSON, A.M.I.R.E.E. (Aust.)
(VK2ZPW).

Technical Editor:
JAMIESON ROWE, B.A. (Syd.), B.Sc.
(Technology, N.S.W.), A.M.I.R.E.E. (Aust.).

Technical Staff:
IAN POGSON (VK2AZN).
ANTHONY LEO (VK2ZHK).
HARRY TYRER.
JOHN HORSFIELD.
ROBERT FLYNN.
LEO SIMPSON.

Editorial Office,
12th Floor, 235-243 Jones Street,
Broadway, Sydney, Australia.
2-0944. Ext. 2531, 2525-6-7. Phone

Postal Address:
Box 2728, G.P.O., Sydney, Australia.

Advertising:
SELWYN SAYERS, Mgr.
BILL SUMMONS, Rep., Sydney.
Offices: 8th Floor, 235-243 Jones Street,
Broadway, Sydney, Australia. Phone
2-0944. Ext. 2931, 2508, 2943.
CLARRIE LEVY, Rep., Melbourne, 392
Little Collins Street. Phone 67-8131.

Circulation:
A. PARKER, Mgr.
Offices: 9th Floor, 235-243 Jones Street,
Broadway, Sydney, Australia. Phone
2-0944. Ext. 2505, 2509.

Subscription Rates—See back page.

Representation:
Melbourne—John Fairfax & Sons Ltd.,
392 Little Collins St. Phone 67-8131.
Brisbane—Sungrave Pty. Ltd., 78
Elizabeth Street. Phone 2-6688.
Adelaide—John Fairfax & Sons Ltd.,
104 Currie Street. Phone 51-3502.
Perth—Sungrave Pty. Ltd., 847 Hay
Street—Phone 23-4513.
Newcastle, N.S.W.—Associated News-
papers Ltd., 22 Bolton Street. Phone
2-3696.
London—John Fairfax & Sons (Aust.)
Ltd., Reuter Building, 85 Fleet Street,
New York — "The Sydney Morning
Herald" Ltd., "Times Annex," 229 West
43rd Street.

Distribution:
Distributed in N.S.W. by Sungrave
Pty. Ltd., Jones St., Broadway, Sydney,
N.S.W.; in Victoria by Sungrave Pty.
Ltd., 392 Little Collins Street, Mel-
bourne; in South Australia by Sun-
grave Pty. Ltd., 104 Currie Street,
Adelaide; in Western Australia by
Western Press; in Queensland by
Gordon and Gotch (A'sia) Ltd.; in New
Zealand by Truth (N.Z.) Ltd.; in Tas-
mania by Davies Bros. Ltd., "Mercury,"
Hobart.

Talking To Machines



Featured on television recently was a brief segment showing a computer responding to the spoken commands of its operator and, in turn, re-expressing information in its own synthesised version of a human voice. In a way, it was a primitive demonstration of that bizarre concept of a man talking with a machine.

Technically, the gulf between such a demonstration and the ultimate concept is vast. It does not follow, however, that it will ever need to be bridged in terms of ordinary, conversational speech.

To create a machine with the capacity to carry on a normal, human conversation would be a fantastic undertaking and, in large degree, an exercise in inefficiency. The fact is that normal conversation contains an enormous amount of wordage, superfluous to the basic purpose of exchanging information. A great deal of what we say has to do with social pleasantry—or unpleasantry—or is the result of an urge to fill an awkward silence. Even when we set out to convey information, our statements are loaded with superfluous words and ill-chosen phrases.

Just as writing compels an economy of expression and a more careful choice of words, so our involvement in computer technology must bring about a further rationalisation in the way we seek, express, store and recover information. Instead of aiming at machines which can cope with all idiosyncrasies of human conversation, we may well have to learn to express ourselves in the more factual and objective language of the machine.

It is well to remember, in this context, that it is becoming an everyday occurrence for machines to "talk" between themselves. When there is a brief opening or breakdown in a data transmission circuit, one "machine" will instruct another to go ahead, or pause, or repeat for purposes of checking. A central computer can co-operate with many peripheral equipments to handle multiple tasks simultaneously. By comparison with this kind of information exchange, what happens at the computer/operator interface seems cumbersome in the extreme.

Perhaps the radio amateur has something when, instead of a formal farewell speech, he can simply tap out: "73's OM."

N. Williams

August, 1967

Radio Relay Stations in Space	8
Australia's Giant Telescope	12
PCM for Britain's Telephones	15
Computer Draws IC Masks	17
Automated TV Master Control	18
Broadcasting in Fiji	21
Review—Parametric Amplifier for Far-Infrared Light	23
Review—Forerunner of TV	25
Scientific and Industrial News	29
67 All-Wave Three Receiver	36
Aegis Pre-Wound SW Coils	48
Forum	57
Basic Radio Course—Chapter 26	63
Fuzz-Box for Electric Guitars	73
Answer Man	79
Magnetic Preamp for Play- master 118	83

Serviceman	87
Frequency and Wavelength	91
Reader Built It	95
Audio Topics — Less Noise, More Dynamic Range	97
Know Your Gramophone — Part 11	101
Classical Reviews	104
Documentary Records	109
Variety Fare	113
Trade Reviews and Releases	129

Technical Books, Publications	141
Amateur Band News and Notes	149
Australis Satellite	157
Listening Around the World	161
Answers to Correspondents	169
Classified Advertisements	175
Classified Advt's. Form	176
Subscription Form	176
Advertisers Index	176
Errata and Notes	77

COVER PICTURE: Cleanliness is a strict necessity for the assembly and servicing of delicate sub-systems to do with the inertial guidance equipment being fitted to F-111 aircraft. This picture was taken at Litton Industries Guidance and Control Systems Division at Woodland Hill, California, U.S.A.

Everything for the Audio enthusiast . . .





BROADWAY ELECTRONICS

HI-FI outfits... to suit most homes

Here are two popular combinations
from our extensive range

- INSTROL-PLAYMASTER No. 106 AMP/TUNER
and
- DUAL 1010A HI-FI RECORD CHANGER
(Both fitted in handsome table cabinet with hinged
perspex cover).
- plus
- 2 INSTROL-PLAYMASTER "BOOKSHELF"
SPEAKER SYSTEMS. All in Scandinavian oiled
teak veneer finish (or Qld. maple/walnut if preferred)
tested and fully operative.

COMPLETE PRICE \$282.90.






- INSTROL AT1 AMPLIFIER/
TUNER.
- DUAL 1009SK RECORD
CHANGER with SHURE or
ADC Magnetic cartridge fitted
hinged perspex cover.
- WHARFEDALE SUPER 8RS/
DD SPEAKERS fitted in INST-
ROL 8" DP speaker enclosures
to WHARFEDALE specifications.
- All in Scandinavian oiled teak
veneer finish (Qld. maple/walnut
if preferred). Tested and fully
operative.

COMPLETE PRICE \$400.00


Yes, we carry a range of imported loudspeakers, players, amplifiers and tape recorders.
Please state your requirements and we will gladly quote. All well-known brands stocked.

- INSTROL
- PLAYMASTER
- FISHER
- ROLAND
- TRIO
- SANSUI
- WHARFEDALE
- GOODMAN'S
- SHURE
- A.D.C.
- DECCA






- LABCRAFT
- ALL BALANCE
- DUAL
- ELAC
- GARRARD
- SONY
- BRENNELL
- MINICONICS
- AKAI
- TEMPO
- LEAK
- QUAD



INSTROL — FINE AUDIO FURNITURE...




**make your own
cabinets and
save \$ \$ \$**



A complete range of high quality Hi-Fi Cabinets. Tailored to suit the equipment of your choice, and most economical. In the Instrol range there are over 20 equipment and speaker cabinet designs. Each is available, built and polished or in Kit form to make yourself. A hammer, screwdriver, and a few hours of your time is all you require to make your own. All parts pre-cut, best quality materials, full instructions supplied—all for little more than half the cost of ready made cabinets. It's great fun too—but why not send or call for the free Instrol Cabinet Brochure? Profusely illustrated with full specifications and measurements.

PLAYER STANDS AND PERSPEX COVERS

Rigidly constructed using only best quality veneered panels in oiled Teak, Queensland Maple and Walnut, these Instrol Player/Changer Stands are widely accepted throughout the Hi-Fi Trade for most makes and models of players and changers. Size of player's top is 15½" wide by 14½", and the inside depth is 3". A neatly set-in protective base with rubber feet is included. For a small extra charge, we can supply the base ready cut for your player or changer. High grade perspex covers, as illustrated are available either grey tinted or clear and in two sizes: 15" x 14" x 3½" and 15" x 14" x 5½". The cover can be supplied fitted with stay-up type hinges if required.



PLAYER STANDS

Oiled Walnut or Queensland Maple \$8.00
Oiled Teak or matching colour \$9.65
Extra for cutting to template \$0.75

PERSPEX COVERS

15in x 14in x 3½in .. \$9.00
15in x 14in x 5½in .. \$10.50
Ready hinged extra .. \$1.50

WHEN ORDERING PLEASE ADD REG. POSTAGE

	N.S.W.	QLD., VIC., TAS.	OTHER STATES
Player Stand	70c	95c	\$1.20
Perspex Cover	95c	\$1.20	\$1.60

BROADWAY ELECTRONICS

(SALES) PTY. LTD.

32 GLEBE PT. RD., GLEBE, N.S.W.

Phone: 68-1171.

(Only 100 yards from Broadway and open Saturday mornings.)

PLEASE NOTE: Our Hi-Fi Store is at Glebe, and the Phone is 68-1171. This does not yet appear in the telephone directory. The spare parts, test equipment, kit sales, etc., are still at the original address, 206 Broadway — Phone 211-4224 (3 lines). Only the Glebe Store is open on Saturday mornings.

PHONE, CALL OR POST COUPON
FOR CATALOGUE REQUIRED.

NAME

ADDRESS

.....

.....

☐ Playmaster HI-FI ☐ Instrol Cabinets

SENIOR EXPERIMENTAL OFFICER (A number of vacancies)

Interesting professional jobs are available on the Woomera Range for experienced graduates or diplomates in Science or Engineering who wish to participate in experimental work associated with trials of guided weapons, satellite launching vehicles and high altitude test rockets. The field of work embraces the measurement of performance of rockets launched in flight trials and the gathering of experimental data required for physical research and for weapons development.

SALARIES:

The salaries payable will depend upon the qualifications and experience of the successful applicants, but will be within the following range: Experimental Officer Class 3, \$6,118/6,880 (actual) per annum.

DUTIES:

Responsible for the direction of professional and technical staff engaged in the operation, maintenance and continued development of one or more electronic instrumentation systems. These systems are used in obtaining measurement data in flight trials on the Range and include the following:

- (a) VHF radar used in high altitude research.
- (b) Digital and analogue computers used in impact prediction and other in flight calculations.
- (c) VHF flight telemetry ground receiving and recording systems.

QUALIFICATIONS:

A degree or diploma in Science or Engineering or equivalent qualifications with experience relevant to one of the above fields of activity, or in the development or operation and maintenance of electronic equipment.

ALLOWANCES:

In addition to the above salaries the following allowances are paid to employees at Woomera:

- (1) A special allowance of \$280 per annum is payable to a married man maintaining a family, others receive \$160 per annum.
- (2) An amount of \$90 plus 1/12 of the claim for dependants is allowable for taxation purposes provided at least six (6) months of the financial year are spent residing at Woomera.
- (3) Payment is made in lieu of excess travelling time.

CONDITIONS:

- (1) Married accommodation will be made available within a reasonable period after taking up duty.
- (2) Successful applicants may be required to fly in fixed or rotary wing aircraft and to drive a Commonwealth vehicle whilst on duty.

APPLICATIONS:

On forms available from the State Controller's Office, Department of Supply, in each capital city, from whom further information can be obtained, should be lodged with:


The Director,
Weapons Research Establishment,
Box 1424H, G.P.O.,
ADELAIDE, S.A.
by 24th August, 1967.



Commonwealth
of Australia



DEPARTMENT of SUPPLY
WEAPONS RESEARCH ESTABLISHMENT
WOOMERA



She doesn't know it,
but she's sitting on
the very thing that
revolutionized
electronics



Just released! - extra low cost silicon planar transistors and diodes - from 15 cents

NPN AUDIO DRIVER

	Package	V _{CB0} (max.)	V _{CE0} (max.)	h _{FE} (min.)	V _{CE} (SAT) (max.)	1-99	100-999	1000
AY1113	TO-5 Epoxy	40 Volts I _c = 100 μ A	30 Volts I _c = 30 mA	50 I _c = 10 mA V _{CE} = 10V	1.0V I _c = 100 mA I _B = 10 mA	46c	32c	28c

PNP RF AMPLIFIER

	Package	V _{CE0} (max.)	h _{FE} (min.)	f _T (min.)	C _{ob}	1-99	100-999	1000
AY1114	TO-18 Epoxy	-20V I _c = 10 mA	60 I _c = 1.0 mA V _{CE} = -1.0V	400 MHz I _c = 10 mA V _{CE} = -20V	4.5 PF V _{CE} = -10V	40c	28c	24c

LOW-NOISE GENERAL PURPOSE PNP AUDIO AMPLIFIER

	Package	V _{CB0} (max.)	V _{CE0} (max.)	h _{FE} (min.)	NF	1-99	100-999	1000
AY1115	TO-18 Epoxy	-30V I _c = 10 μ A	-30V I _c = 5 mA	50 I _c = 100 μ A V _{CE} = -5V	2 dB (max.) I _c = 100 mA V _{CE} = -5V f = 1 KHz	40c	28c	24c

COMPLEMENTARY PAIR (100 Milliwatt audio complementary output pair)

	Package	V _{CB0} (max.)	V _{CE0} (max.)	h _{FE} (min.)	V _{CE} (SAT) (max.)	1-99	100-999	1000
AY1116	TO-5 Epoxy	15V I _c = 100 μ A	15V I _c = 10 mA	40 I _c = 10 mA V _{CE} = 5V	0.5V I _c = 100 mA I _B = 10 mA	45c	30c	27c
AY1117	TO-5 Epoxy	-15V I _c = 100 μ A	-15V I _c = 10 mA	40 I _c = 10 mA V _{CE} = -5V	0.5V I _c = 100 mA I _B = 10 mA	45c	30c	27c

NPN RF AMPLIFIER

	Package	V _{CE0} (max.)	h _{FE} (min.)	f _T (min.)	C _{ob}	1-99	100-999	1000
AY1119	TO-18 Epoxy	15V I _c = 10 mA	35 I _c = 10 mA V _{CE} = 1.0V	400 MHz I _c = 10 mA V _{CE} = 10V	4 PF V _{CB} = 5V	40c	28c	24c

COMPENSATING DIODE


	Package	V _F	V _F	V _R (max.)	1-99	100-999	1000
AN1102	TO-18 Epoxy	0.60 (min.) @ 3 mA 0.64 (max.) @ 3 mA	0.65 (min.) @ 8 mA 0.69 (max.) @ 8 mA	5 Volts	45c	30c	25c

DETECTOR DIODE

	Package	I _R (max.)	V _F (max.)	V _R	1-99	100-999	1000
AN1101	TO-18 Epoxy	0.5 μ A V _R = 40 V	1.0 @ 10 mA	60 max.	40c	24c	15c


All these devices are optimised for auto radio, portable radio, radiogram tuner and general purpose applications.

Please order now from:—Fairchild Australia Pty. Ltd., 420 Mt. Dandenong Road, Croydon, Victoria.



SILICON!

FAIRCHILD
AUSTRALIA PTY. LTD.



Artist's impression of a typical space probe, built by the Lockheed Missiles and Space Company for the U.S.A. Air Force.

SPACE TROJANS—

By James Strong, B.Sc. (Eng.), A.C.G.I.

Radio "periscopes" which would remain permanently fixed in certain discrete locations in space could be the answer to a problem which has so far hindered space research — how to receive radio signals from space probes when their orbits carry them behind the sun.

If the currently debated proposal to survey the Solar System with the aid of interplanetary probes is shown to be feasible, some awkward problems in two-way radio communication will have to be faced. For although the successful Mariner flights to Mars and Venus might suggest that a straightforward improvement in radio range is all that is needed to cope with more distant probes, the problem is now seen to be more fundamental.

Primarily the difficulty stems from the orbital motion of the Earth, which each year bears it to a region behind the Sun, relative to any probe, where it can no longer "see" the radio aerials of the spacecraft. In such circumstances direct, line-of-sight communication becomes impossible and there is nothing the radio engineer can do about it. Nor is it merely a question of waiting a day or so until the occulted probe reappears in view; weeks may elapse before attenuated signals can penetrate the background noise due to the solar corona.

It could be argued, of course, and with some justification possibly, that by choosing another launch "window" the crucial moment of encounter with a distant world could be put off to a more convenient date. This may be true enough in some instances, but it is expediency pure and simple and, with the hope for expansion in future space activity, can we afford to accept a hiatus in communication every time the Earth finds itself in conjunction with a transmitting source?



If planetary orbiters are to do their work efficiently, year in, year out; if solar probes are to travel within 0.1 astronomical unit* of the other side of the sun; if comets have to be intercepted anywhere in space at rapid notice, talk of convenient launch dates becomes meaningless. And with the possible establishment of manned bases on other worlds, including trip times of 400-500 days, continuous communication, with no reservations, becomes imperative.

However, before proposing a possible solution to the difficulty, it is worth studying the communication techniques used for each of the Mariner interplanetary flights. This will then reveal why similar methods cannot be applied to, say, a "flyby" mission to Jupiter, one of the survey projects now being studied.

The essence of long-range radio communication lies in concentrating whatever radiated power is available into as narrow an aerial beam as possible. It follows that the second essential must be precision alignment of the beam with the target tracking system, i.e. the Earth. Mariner II on its journey to Venus used an Earth sensor, a photomultiplier boresighted to its high gain aerial, which served to lock the aerial beam on to the Earth's disc. Even so, there was a risk that the sensor would mistakenly come to rest on the Moon when it searched initially, and provision was made for ground signals to override the spacecraft's internal circuits, causing it to break the lock and search again if the signal strength proved less than expected.

*One astronomical unit equals the mean distance of the Earth from the Sun.

LEFT: Figure 1, showing how the Trojan relays would be positioned in relation to the Earth and the Sun. RIGHT: Figure 2, showing how the relays would prevent contact being lost with spacecraft behind the Sun.



In the case of the Mariner IV flight to Mars this method could not be adopted as the Earth moved in orbit inside Mariner IV's flight trajectory, and in trying to follow the Earth's disc the sensor would almost certainly be "blinded" by the Sun. Instead, and because the trajectory was opportune, it was found possible to fix the axis of the high gain aerial with respect to the flight path and still cover the Earth adequately within the aerial beam for most of the 228-day journey.

To bring the aerial to bear in the right direction, now it was fixed, quite an elaborate attitude control manoeuvre had first to be executed. Shortly after being launched on course, and having freed itself from its Agena boost stage, Mariner IV spread its solar panels, searched for the Sun and locked on to it. It could then draw power and dispense with its internal batteries. Because a second reference axis was also needed the spacecraft then slowly rolled about its solar-pointing axis until its star-tracker had acquired Canopus, a large-magnitude star conveniently close to the south ecliptic pole. Once these two reference axes were secured, mutually at right angles, the vehicle's attitude was fixed in space and its aerial system automatically pointed directly toward Earth. Apart from some concern early on, when the star-tracker repeatedly lost lock and came to rest on another star, the system performed with merit once the trouble had been identified and effectively isolated.

Turning now to the requirements for a probe surveil-

The gravitational and centrifugal forces that hold an Earth equilateral body in space require, as a prime condition of equilibrium, that the body should be moving at the same speed and direction as the Earth and along its orbital path. With these conditions fulfilled, the body will then remain in its relative position indefinitely and only force can dislodge it.

Remarkable proof of the three-body problem has been found in the so-called Trojans of Jupiter, two groups of small asteroids (named after the heroes of the Trojan War—Hector, Achilles, Troilus, etc.) that are unmistakably travelling along Jupiter's path, ahead and behind the planet. Once wandering asteroids, they must have been captured in the remote past and are now prisoners for all time at Jupiter's equilaterals, perhaps better known as the Trojan Positions.

From this it follows that if we deliberately station satellites at the equilaterals of the Earth they also will be subject to the same natural laws, and there may be other benefits to be had. First, the satellites will possess an inherent, self-compensating ability to remain "on station," and we can forget the need to correct any tendency to drift, as we do in the case of satellites in synchronous orbit above the Earth. Secondly, and equally important, since they flank the Earth they enable us to "see" around the Sun where it blocks our radio view. In effect they would act

Solar System Radio Relay Stations

lance of Jupiter, whose orbit lies beyond Mars, some 400 million miles away, neither of the two Mariner methods of aerial pointing are of any use. Calculations show that even when propelled by the powerful Saturn boosters soon to become available, an interplanetary probe will still take 2½ years to reach Jupiter. Consequently the Mariner IV fixed aerial principle would be unable to cope with a situation in which the Earth twice circled the Sun during the trip time, while Earth sensing is plainly confined to trajectories that lie inside the Earth's orbit where the sensor looks away from the Sun.

No doubt a steerable aerial, programmed to follow a year-long, simple harmonic sweep would fit the bill, provided enough fuel for the continuous operation of small thrust jets could be carried. Alternatively, the aerial could be locked on to the Sun, but we should then have to resign ourselves to communicating with the probe only when the Earth passed through the aerial beam. This is not as bad as it sounds, for contact would be made during the critical period up to four months after the launch date, when course corrections might be necessary. Thereafter contact would take place during the seventeenth and thirtieth months after launch, the latter period coinciding with an encounter with Jupiter.

During the somewhat prolonged intervals of silence between these dates, environmental data accumulated en route would have to be stored and played back when the opportunity presented itself. Either way, whichever scheme were adopted, all contact would still be lost when the Earth was in conjunction on the other side of the Sun. On the face of it there seems only one way to circumvent this dilemma, but it is a concept that calls for as much courage and imagination as it does careful thought.

One of the lesser known theorems of celestial mechanics is the three-body problem, first published as an essay by the French mathematician, Lagrange, in 1772. In it he showed that if a planet, such as the Earth, revolved in a circular or elliptical orbit around a massive second body, such as the Sun, there were two positions in space where, if a third body were introduced, this body would remain in dynamic equilibrium. Both positions lie along the planet's orbital path, one leading and the other lagging behind the planet by 60 degrees respectively. They are known as "planet equilaterals" for they form, together with the sun and (in our case) the earth, the apices of two giant equilateral triangles whose sides are 93-million miles long (see figure 1).

Britain's latest space aerial and radio telescope at Chilbolton, Cheshire, which was recently commissioned for the Radio and Space Research Station of the Science Research Council. Prime contractors were AEI Electronics.


as radio periscopes, relaying incoming signals we should otherwise never receive, and relaying outgoing instructions in the same manner. Because of their unique position, they could be called Trojan relays.

It might be asked whether the dynamic equilibrium of a Trojan relay would be disturbed by the gravitational pull of planets passing in adjacent orbits. Undoubtedly it would be perturbed to some extent, for every planet exerts some influence on every other body in the solar system, but with Venus never closer than 25 million miles, and Mars rarely less than 40 million miles away, their influence would







NATIONAL RF-5000 RADIO



**If it's on the AIR (anywhere)
this portable radio will pick it up**



You can tune into the world with National's RF-5000. It has no less than 11 bands, including FM, AM, Short Wave, and amateur bands, **plus 30 transistors and diodes**. Five highly efficient antennae match every frequency. Two hi-fi speakers provide superior sound. Ultra linear transistors give an output of 2,000 mW—five times the normal wattage of portables!

Without any doubt, it is the best portable radio in the world — made for those who want the very best. Price: \$495.

DESCRIPTIVE LITERATURE FREE!



To HACO DISTRIBUTING AGENCIES PTY. LIMITED
57/69 Anzac Parade, Kensington, N.S.W.

Please send me further information on the RF-5000.

Name.....

Address.....

be negligible. In these circumstances it is doubtful whether the orbital shift they might induce would be observable in much less than a century, and certainly there seems little need for qualms on this score.

Though Trojan relays will help to solve the difficulty of solar occultation, it is only fair to admit they are bound to bring other problems in their train. These may be grouped under the headings of reliability, attitude control, power supplies and long life. Placing the Trojans in position is the least of our worries, a matter of propulsive effort and navigational accuracy that is well within the capability of existing space equipment.

Until spaceflight becomes commonplace, and orbiting satellites are serviced periodically like Trinity House navigational buoys, a long and durable life, coupled with absolute reliability is essential. This would be especially pertinent to a Trojan relay for, at a distance from the Earth equal to the Sun itself, inspections would be most infrequent. It would probably be more economic to launch a replacement than go to the trouble of refurbishing one that has ceased to function for any reason. Consequently circuit redundancy, duplicate sub-systems, long-life power supplies and maximum protection from meteorite and radiation hazards must take priority in the design.

Ideally, of course, all electrical power should be drawn from the Sun, but it may be some while before solar cells are efficient enough to satisfy all needs completely. Meanwhile, contacting interplanetary probes launched in the next decade or so, with the prospect of reaching Saturn or even Uranus, 2,000 million miles from the Sun, will demand prodigious amounts of power. To meet this requirement large and improved nuclear-powered generators would have to be developed, even though their reliability in space is still an unknown quantity.

Attitude control, so vital to accurate aerial-pointing, will present the toughest problem of all, for any form of orientation by means of small thrust jets sets a limit on the life of the relay when the fuel is exhausted. The alternative seems to lie in the progressive development of gravity-gradient stabilisation, using the Sun's gravitational field to exert erecting forces on the relay via four long, slender booms at the end of which are fluid dampers. Initially the relay might have to be oriented by jets, but once a series of star-trackers had locked on to specific sources they could control the vehicle electrically, counteracting small oscillations by lengthening or shortening appropriate booms. Any forces or torques generated in the system as a result of swinging the aerial about an axis would naturally have to be balanced by moving counterweights.

Stabilising the relay by deliberately spinning it, as in the Intelsat satellites, is possible but perhaps not useful because of aerial-beam orientation problems. It is probably better to provide the relay with enough nitrogen fuel to stabilise itself with the aid of small gas jets. Without too great a weight penalty, enough fuel could be carried to last five years, and by then everyone will be anxious to replace the relay with something better anyway. Equipped with duplicate Canopus sensors, Earth sensors and Sun sensors, the relay should have no difficulty in orienting itself in space with sufficient accuracy to direct its aerals precisely when commanded to.

On the question of radio range it is now known that communication between such a relay station and earth is feasible. This can be seen from the fact that Mariner IV's 10-watt travelling-wave-tube transmitter supplied adequate signal strength over a distance of 134 million miles, and subsequently was detectable at 191 million miles, more than twice the distance from Earth to a Lagrangian "point" on the Earth's orbit.

However, it is conceivable that an interplanetary probe will have reached the vicinity of Uranus by the late 1980s and if a Trojan relay is in position and operational by then it will be expected to reach out to a distance of some 2,000 million miles. All things being equal, on applying the inverse-square law to the basic transmission formula it will be found that RF power of some 2.24 KW will have to be radiated. While future developments can perhaps be expected to reduce this figure, refinement of detail, as in other aspects of space flight, usually turns out to be less important than accepting the inevitable and learning how to generate copious amounts of energy.

Lastly, if so large and heavy a satellite is to be placed where it becomes the focal point for other, improved ver-




Figure 3. A network of Trojan relays stationed at the equilaterals of the inner planets Mercury and Venus would provide complete coverage for space activities inside the Earth's orbit. The diagram shows how data from a solar probe on the other side of the Sun would be relayed to Earth.

sions that may wish to occupy the same space one day, it must be possible to destroy the station completely so as not to constitute a hazard to its replacement. Admittedly space is large, and there is little risk of physical contact, but a few ounces of high explosive and a radio frequency combination lock will put an end to any chance interference or future embarrassment.

This leaves only the problem of launching and positioning the relays along the Earth's orbit. Perhaps contrary to expectation, both relays would be launched in a forward direction, relative to the Earth's motion, one swinging outwards along an arc that returned to intersect the orbital path, the other inwards to enter a perihelion orbit round the Sun before coming up behind the Earth. On reaching their stations, both relays would be slowed by retro-rockets to the same speed as the Earth. Their final position would not be important to within a degree or so, but the resultant velocity vector should be substantially correct.

The safe deployment of Trojan relays on either side of the Earth still leaves unresolved the question of how an interplanetary probe will recognise in which direction to aim its aerals. Circumstances will vary, and the only safe decision is to provide it with a steerable aerial and a set of reference axes. Direction co-ordinates would be transmitted from Earth when the time came, via a Trojan relay possibly, but now with sure knowledge that an answer should come back wherever Earth was (Figure 2).

Nevertheless, even with two Trojans operational, there still would be blind areas that could not be viewed, especially the region between the orbit of Mercury and the Sun. However, if Trojans can be set up at the Earth equilaterals they can be stationed just as easily at the equilaterals of the inner planets, Venus and Mercury. Being closer to the Sun, they would orbit more rapidly: Venus equilateral in 225 days and Mercury equilateral in 88 days. One or other of the six Trojans then in motion should ensure that solar system coverage was complete (Figure 3).

No doubt many aspects of this Trojan relay scheme are debatable and some people may well regard the whole idea as outrageous. But, equally, there may be other unsuspected advantages in the scheme that only the future can disclose. Possibly not until these have been realised will someone have the courage to propose putting the Trojans to work. ■

(This article was originally published in "Wireless World," March, 1967 issue, and is reproduced by arrangement with the U.K. Central Office of Information.)

PROBING THE SECRETS OF THE SOUTHERN SKIES

Astronomers all over the world are excited by the news that Australia is to have a giant 150in astronomical reflector telescope, the first of any significant size in the Southern Hemisphere. The availability of this instrument to study the constellations and galaxies visible in the southern skies is likely to have interesting developments.

by Patrick Moore, Director of the Armagh Planetarium

The news that a large reflecting telescope is to be set up in Australia is welcome for many reasons. It will be able to tackle various problems which have not yet been properly studied, and it will, of course, mean that the Commonwealth will continue to play a leading role in the ever-widening science of astronomy.

Astronomical telescopes were used in Britain at a very early stage. It is usually said that the first telescope in history was built by a Dutch optical worker, Hans Lippershey, about 1608, and that the first telescopic astronomer was the Italian scientist Galileo about a year later. Yet there is strong evidence that Thomas Harriott was using an astronomical telescope in Britain well before Galileo—and Harriott's map of the moon was certainly completed before the end of 1609. These early telescopes were feeble by our standards, and were not nearly so good as powerful modern binoculars. Even so, they caused a complete revolution in astronomy.

Galileo's telescope was a refractor—that is to say, it collected its light by means of a glass lens known as an

object-glass. Unfortunately, it and subsequent refractors suffered from the defect that they produced false colour round any bright object such as a star. When the great Sir Isaac Newton investigated the nature of light, in 1666, he came to the conclusion that no cure for this trouble could be found, and so he developed an entirely new principle—that of the reflector, in which the light from the object to be studied is collected not by a lens, but by a mirror.


With reflectors, the false colour nuisance does not arise, and Newton's first reflector, completed about 1671, was a great success. Its mirror was only one inch in diameter, but the principle of the instrument is still valid today. Incidentally, Newton was not the first to suggest the reflector idea; this is to the credit of a Scot, James Gregory. Ironically enough, Newton was making one of his rare mistakes when he abandoned the idea of a large refracting telescope. Later, an English amateur, Chester More Hall, found a partial cure by making a compound object-glass. The achromatic refractor, as it is termed, was developed by John Dollond, and for many years

British telescope-makers were in a class of their own. On the other hand, the British climate is not really favourable for astronomical work; there is too much cloud and rain. Gradually, equipment in Britain was surpassed by the great telescopes erected in the U.S.A.

Nowadays, the main emphasis is upon reflectors. It is easier to make a large mirror than a large lens, and in astronomy it is size which matters most. In 1917 a new reflector, with a 100-inch mirror, was set up at Mount Wilson in California, and this was followed in 1948 by the 200-inch Palomar reflector. This telescope is named in honour of George Ellery Hale, whose skill and enthusiasm was largely responsible for its construction. Hale, a leading American astronomer, was also responsible for the Mount Wilson 100-inch, as well as various other giant instruments. He persuaded friendly American millionaires to finance the projects; but one must add, regretfully, that astronomically minded millionaires are not nearly so common nowadays as they used to be!

It is wrong to suppose that the modern astronomer spends much time in looking through his telescopes. Generally speaking, almost all the work is carried out by means of photography, so that the telescopes are used together with special cameras, and every hour spent in taking photographs means hours of desk-work analysing the results. Also, the main attention is upon the distant stars and star-systems. It is not often that a large telescope is turned toward our near neighbours in space, the moon and planets.

The sun is an ordinary star, and is merely one of a hundred thousand



Automatic control by simple dial setting has replaced lengthy manual operation on the new automatic twin 16-inch telescope at the Royal Observatory, Edinburgh, Scotland, which represents an important advance in the automation of telescopes. Automation permits the telescope to be operated by a single person with all measurements recorded directly onto computer tape.

million suns in our star system or galaxy. All these stars are immensely remote, and their distances are measured in light-years. A light-year is the distance covered by a ray of light in one year: almost six million million miles. Even the nearest star (not counting the sun, of course) lies at over four light-years from us. No telescope yet built will show a star as anything but a dot of light; a dot which must be analysed with the aid of complex auxiliary equipment.

During the 1920s, it was found that certain misty-looking patches in the night sky, known as spiral nebulae, were in fact separate star systems, or galaxies. This discovery was made by detailed studies of some of the unusual stars contained in them, and would not have been possible without the help of the Mount Wilson 100-inch reflector, which was then the most powerful telescope in the world. It became clear that these galaxies were millions of light-years away, and with the arrival in 1948 of the Palomar telescope the limits of the observable universe were pushed out to over 5,000 million light-years. The light now being received from these remote galaxies started upon its journey before the earth came into existence as a separate body.

There have been all sorts of by-products of this research. For example, in 1963 it was found that certain innocent-looking objects, which had always been taken for ordinary stars, are immensely remote and powerful. They are known as quasars, and it seems that a single quasar may shine as brilliantly as 200 complete galaxies put together. The problem is to understand how a relatively small object can produce so staggering an amount of energy, and once again we have to confess our ignorance. Quasars are thought to be at distances of thousands of millions of light-years and, like the remote galaxies, they are racing from us at thousands of miles per second. If modern ideas are right, then the whole universe is expanding.

If we are to make any serious attempt to solve problems of this kind, it is essential to study the very distant, dim-looking galaxies and quasars. Even the Palomar reflector, with its 200-inch mirror, cannot collect enough light to satisfy astronomers. To build a larger telescope would be a very difficult matter; but, oddly enough, the main need at the moment is for more reflectors of the 100-inch to 200-inch class. Observing time on the few existing telescopes of this size is very much at a premium, and in fact there are simply not enough giant telescopes to cope with the amount of research to be done.

This alone would make the Australian 150-inch reflector an important addition, but there is another point to be borne in mind also. Up to now the largest telescopes have been set up in the northern hemisphere of the earth and so cannot be used to observe objects which lie near the south pole of the sky. The Southern Cross can never be seen from Europe or the U.S.A. Neither can the two Clouds of Magellan, which look like luminous patches, but which we know to be the nearest of the important outer galaxies.

It so happens that the Clouds of Magellan are of vital interest. They are about 180,000 light-years away, so that we are seeing them as they used to be 180,000 years ago; yet they are

Chasing the Sun

Men on the earth can now experience the same problems astronauts will face in space when they aim orbiting telescopes at specific spots on the earth, sun, or at pinpoint light sources in deep space.

The Lockheed Missiles and Space Co. has announced the completion of a system that simulates telescope aiming tasks astronauts will be called on to perform on space missions of the future. NASA is currently studying several programs which would involve orbiting telescopes, including Apollo Applications Programs in which the Apollo Telescope Mount (A.T.M.) will investigate solar phenomena. The Lockheed simulation device is a computer-driven astronaut control station with a television display system which shows where and how well the telescopes, or cameras in the case of the A.T.M., are aimed at various celestial bodies, sun spots, or other solar activity.

In simulating the A.T.M. aiming, a man in the control station moves the controls, and a computer adjusts the sun's image on the display screen to show how the A.T.M. would react in space to those control movements.

Dr Robert L. Martindale, who supervised construction of the system, explained that many points will be considered in building real aiming systems, including the necessity for astronauts to point telescope and camera mounts quickly and accurately. "Because of the importance of future astronomical experiments in space," he said, "and particularly those up-coming with the A.T.M., we must thoroughly understand the workings of man and equipment long before we go into space." He said that the Lockheed-developed device could simulate the dynamics of hardware like the A.T.M. and that numerous possibilities in aiming such hardware could be studied by programming control variations into the simulator's computer.

"One variation we'll study," said Dr Martindale, "is coupling, where a control adjustment in one axis causes movement in one of the other axes. For instance, you might adjust the roll of the A.T.M. and that might cause a change in the pitch. We must study the ability of man to control these movements to get the fine aiming necessary for the experiments."

much closer than the other large galaxies, and they contain objects of all sorts. For instance, the large cloud contains one "celestial searchlight," which is a star one million times as luminous as the sun, even though it is so remote that it cannot be seen without a telescope. There are gas clouds, clusters of stars, exploding stars and many other features, all spread out for our inspection. Studying the clouds can tell us much more about our own galaxy and the other systems.

Up to now, the clouds have not been surveyed in as much detail as is needed,



Reacting to the slightest movement of this "space cabin's" controls, a computer adjusts the sun's image on the screen to show how a telescope mount would react in space to similar control.



He added that other variations to be studied would be slewing rates, or how fast telescope mounts would move during an adjustment, and the lag times in the control system, or the time that passed between the astronaut's moving of the controls and the hardware responding to those controls.

"To study A.T.M. aiming, a man in the control station of our simulator will be able to 'monitor' on his display screen the scenes that all of the cameras are photographing in the sun. This is possible because the A.T.M. film cameras will each have a television camera mounted alongside with a lens of the same focal length. By using the TV camera, the astronaut can 'monitor' the scenes being photographed by the film cameras.

"Since the simulator will let him switch from camera to camera, zoom lenses for closer shots, and make fine aiming adjustments, we should develop excellent data for timing research with orbiting telescopes. More important, we can use the data to evaluate methods of aiming control with respect to man's ability to do the job."

simply because they cannot be seen with the world's largest telescopes. The 150-inch Australian reflector will put a very different complexion upon matters. In size, and hence in light-grasp, it will be inferior only to the Palomar telescope, and in the southern hemisphere it will be supreme. Astronomers all over the world await its completion with undisguised eagerness.

Theories can be drawn up and discussed, but no theory is of the slightest use unless it is backed up by observed facts. To gather these facts is the main task of the new Australian giant. ■



ISEP Low-cost Modular Mechanical Mounting and Connecting System


ISEP (International Standard Equipment Practice) now 90% Australian produced can provide a low-cost, comprehensive system of racks, sub-racks, plugs, sockets, and accessories for the housing of electronic equipment.

ISEP is manufactured and marketed by STC and can be supplied to meet exactly the requirements of equipment manufacturers.


The ISEP modular system offers the ultimate in simplicity and flexibility in sub-racks. It is assembled with four screws; guard rails and socket sup-

ports are fixed into the sub-rack by four special screws. Plugs and sockets are rated at 250 V. r.m.s., 4 A. per connector, have a contact resistance of less than 5m Ω and meet the highest professional specification. Whether mass-producing or making equipment to special order, you can obtain the benefits of high quality at low cost by using ISEP.


For illustrated technical booklet, write to: Standard Telephones & Cables Pty. Limited, Components Division, Moorebank Avenue, Liverpool, N.S.W. (Phone 602-0333).



Four-Rail Sub-Rack



Two-Rail Sub-Rack



Typical Installation



world-wide telecommunications and electronics

AN **ITT**
ASSOCIATE

G543

PULSE CODE MODULATION

will modernise Britain's telephone network

In eight areas throughout Britain, 350 pulse code modulation systems are being incorporated into the telephone network by the Post Office. This is the initial stage of a widespread scheme expected to cost \$A15 million.

The Marconi Company is to supply a large part of the equipment for the first stage, for which the Post Office has already placed contracts worth \$A6.25-million. Marconi's will supply the equipment for three regions, including London.

Pulse code modulation (PCM) is new to telephone transmission systems and greatly increases the capacity of existing inter-exchange circuits.

In the 24-channel multiplex PCM system adopted by the G.P.O., analogue signals from a telephone receiver are sampled about 8,000 times per second, over twice the rate of the highest audio frequencies at which telephones operate. Each time, the polarity and the magnitude of the audio signals are measured and coded digitally. The polarity of the wave is represented by one digit (indicating positive or negative) and the amplitude by an additional six digits, allowing 2^6 (64) different values to be identified. A further pulse is used for synchronising and signalling purposes making a complete eight-digit signal composed of bi-polar pulses. This is a binary system using alternate positive and negative pulses (1 and -1) to replace the '1' digit of a conventional 1,0 binary code. It allows the equipment to operate within a more limited frequency spectrum, resulting in simplified equipment, particularly the repeaters.

The eight digit code takes a few millionths of a second to send, and before the next sample is taken, 8 digit codes from 23 other speech channels can be sent along the same telephone circuit. At the other end, a similar terminal installation separates all these telephone signals and reproduces each in the original form.

Sorting out the signals is achieved by the synchronising system which is entirely automatic. The signalling system ensures that when a subscriber hangs up, and the line becomes clear, the equipment will allow the normal telephone clearing and dialling signals to be sent along the line.

Owing to the very high pulse repetition rate at which the system operates, it is necessary to design the equipment to accept signals with a bandwidth of hundreds of times that of an ordinary audio speech signal. Due to this and the fact that the digital-analogue conversion techniques are relatively complex the equipment is itself complicated. However, the advantages gained from PCM far outweigh this consideration and make it superior to any other form of multiplexing on normal telephone cables. The same coding and decoding equipment is used for all 24 channels and, as a result,

the cost of terminal equipment is considerably less than with other methods of channel multiplication. For example, Frequency Division Multiplex (FDM) has individual modulators and demodulators and expensive filters for each channel.


PCM signals are regenerated by repeaters at 2000yd intervals with relatively simple devices. All other multiplex systems so far devised require more complex regeneration methods.

The Marconi Series U1310 to be supplied to the U.K. Post Office achieves exceptional compactness and reliability through the extensive use of microcircuits. In a typical installation, equipment capable of coping with the demand from trunk circuits from several other ex-

an alarm sounds and simultaneously the system ceases to send further signals. In addition, it can be arranged that the alarm is given in the event of other faults which do not necessarily mean closure of the system.

The number of times such an alarm system would be operated is minimised by the equipment's inherent reliability. In addition, routine testing is provided for checking the line repeaters and this equipment can be operated from the exchange. A special test signal is sent along the line and an audio note is returned from each repeater, the frequency of which depends on the specific repeater which is being monitored. The frequency is governed by a special bandpass filter which is installed at each repeater point solely for test purposes. The absence of the appropriate audio note from one of these filters gives immediate identification of faulty equipment, contrasting with other testing methods which might involve a special journey to open up man-holes and make on-the-spot checks.

The Marconi Company is working on



A PCM unit destined for one of Britain's telephone exchanges under test in the Marconi factory at Chelmsford, U.K. The module the engineer is testing is a timing card.


changes can be accommodated in about six to ten equipment racks, about nine feet tall. The flexibility of this type of construction permits a number of different layouts, depending on customer's requirements. In addition, less floor space is taken up and yet very efficient air cooling is obtained.

Comprehensive alarm facilities are provided, such that in the event of loss of synchronisation, too high an error rate, failures in transmission, or power failure,

further applications of digital techniques to the telephone systems. Current development is directed to putting more than 24 channels over one circuit and the extension of PCM to long distance circuits. The company says it expects to make a significant contribution to the improvements to the U.K.'s telephone system now being brought about by the increasing application of electronics, of which PCM and the new electronic telephone exchanges are examples. ■

NEW

The "BIG" sound behind electric guitars



SPECIFICATION

TYPE No. 53348/12UA/15	
Max. Power Handling	15W
Frequency Range	45-6000 Hzs
Resonance	50 Hz
Magnet Material	Alnico V.
Flux Density	13,000 gauss
Total Flux	100,000 lines
V. C. Diameter	1 3/4"
Impedence	15 ohms
Mounting Hole Centres	1 1/2" P.C.D.
Maximum Depth	4 3/4"



A new speaker design which matches perfectly to the full sound colour of the guitar and yet can handle large amplifier power outputs with great ease.

Sounds plucked from a guitar string have very special characteristics that have challenged the speaker designers capability for many years — M.S.P. now has what the world's best guitarists have been waiting for.

Four completely new 12" Hi-Flux speakers in an enclosure specially designed for large power handling. This new M.S.P. combination is rated at 60 watts and outperforms all other units tested including some very elaborate, expensive models.

Write for the name and address of your nearest demonstration centre or for details of the M.S.P. home constructor's kit.

MANUFACTURERS SPECIAL PRODUCTS PTY. LTD.


47 YORK STREET, SYDNEY. 2-0233

Computer Makes Masks for Integrated Circuits


Research workers of International Business Machines Corporation have overcome a major difficulty in making complex arrangements of integrated circuits. They have largely automated the design and fabrication of the circuit masks, cutting the time of these operations by more than a factor of ten.

In the process, most of the usual manual steps in design and fabrication of the circuit masks have been eliminated. The system has been used to generate sets of masks for complex integrated circuit chips containing over 100 NOR circuits. The time required to generate circuit masks of this complexity has been reduced to a matter of hours instead of hundreds of hours as formerly. The NOR Circuitry was implemented with insulated-gate field-effect transistors, but the mask generating technique has been applied to bipolar integrated circuits as well.

Traditionally, circuit masks are made by a laborious and time-consuming manual process. First an exact scale drawing (200 or 500 times final size) is made from a rough sketch of the circuit layout. Then the drawing is separated into a set of overlays — one for each processing step, such as metallisation, diffusion and contact holes. Each overlay pattern is cut on an opaque material with a transparent backing. After stripping the opaque layer from the



A diagram of the light table used to draw the mask patterns at 10 to 20 times final size on high-resolution photographic plates. The movements of the X-ray table and the flashing of the lamp are both controlled by commands prepared by computer.



An integrated circuit chip of 55 NOR circuits made using masks generated automatically, shown with salt grains for size comparison.

pattern areas, the overlays are reduced photographically to 10 times final size, ready for the step-and-repeat camera.

In the new process, the design and fabrication of masks consists of five basic steps. First the designer draws a rough pencil sketch of the circuit layout. Then he translates this into digital form by describing the circuitry in a symbolic notation — a specially developed high-level language for the mask designer. In step three, this symbolic language is fed to a computer and processed. In processing, the circuit structures are automatically assigned to their appropriate masks. The computer then generates a set of commands which can be used to drive a "light table" to draw the patterns for each layer of the mask set.

In the fourth step, the actual patterns are drawn on high-resolution photographic plates by the light table at 10 to 20 times final size. The plates are mounted on an x-y platform, which is driven by stepping motors. As the table is moved, under commands prepared by the computer, a light beam from a xenon flash lamp draws the mask pattern on the plate. The flashing of the lamp also is controlled by commands from the computer.

The light table can be moved in steps of $\frac{1}{4}$ mil over a field of 2.2 x 2.2 inches at a rate of 200 steps per second. The absolute accuracy of the table within this range is ± 75 microinches, and repeatability is better than ± 50 microinches. When used with a high quality step-and-repeat camera and lens system, masks with 0.1 mil lines over 200 mil fields can be made with positional repeatabilities of ± 15 microinches. In the final step, the exposed and developed plates are placed in a step-and-repeat camera to form a complete array of chip patterns at final size on photographic plates which, in turn, are used to expose the array of chip patterns on the semiconductor wafer.

The key development in the new process is the experimental language, which was designed to describe, easily, the circuit patterns from a rough sketch. With this language it is possible to define, by a simple code, anything that may appear in the circuitry, ranging from a small diffusion area to a complex arrangement of devices making up a logic gate. Having made these definitions and stored them in a tape library, the designer can specify the circuit layout in a skeleton form, forgetting about the details of geometry, such as line spacing and diffusion widths.

The language contains a hierarchy, so that a transistor can be defined by a simple instruction built up from a set of instructions which specify its detailed structure. In turn, a higher level circuit configuration of many transistors can be defined with a single instruction. Such a facility permits a gradual accumulation of a library of parts which can be used over and over in different mask structures.

The language also contains a replication feature, so that a circuit or structure can be defined, and, with a simple command code, it can be replicated at any desired interval over the mask.

The efficiency of the new technique was proved in a trial exercise, during which four patterns of an insulated gate field effect transistor chip of 122 circuits were written in about one hour. Over 100 hours would be required to cut artwork by commercial techniques. ■

AUTOMATED TV MASTER CONTROL

An automatic master control for the studios of Albury/Upper Murray TV station AMV4 has been designed and built by the station engineering staff and is now in operation.

This equipment was designed and built entirely at AMV4 by the technical department under chief engineer Bob Jones. About three months were spent at the drawing board and actual construction started in January, 1966. The work of building and installing the equipment had to be carried out in between operational requirements and normal maintenance and as a result took a little over a year. Excluding the cost of labour, the complete equipment fully installed and integrated with the existing system cost about \$4,000 and was very close to the estimated cost.

Fairchild Australia Pty. Ltd., has awarded the station its inaugural Fairchild Project Award, which is to be awarded to one of its customers every two months.

To appreciate the problems which the automatic control system is designed to overcome, it is an advantage to have some idea of the way a studio control room functions. In a manual controlled studio, separately manned sound and vision mixers are required, equipped with remote controls for operating telecine and tape equipment. Switching operations to bring these various sources on air in sequence at precisely the right moment are often complex and have to be carried out rapidly, so are subject to error.

The new electronic control unit at AMV-4 is designed to carry out these

functions automatically. The control unit, which contains a 10-event memory bank, controls the operation of all the equipment used in program presentation, and switches program video and audio. It can operate entirely automatically from cues on films, cartridge tape and videotape; or manually by means of a "cue" or "take" push-button; or part manually and part automatically. The unit allows the studio to be operated by only two technicians, who are required only to reload telecine, video tape and cartridge tapes, and recode program information into the memory banks as the events are used, by means of push-button type controls on the console.

The equipment records the information fed to it by the console operator in digital code, and each program source is assigned a specific code. For instance, the station has two film projectors and one slide projector in its telecine chain. The codes for these are:

Projector 1	0001
Projector 2	0010
Slide	0011

Each memory cell can record any one of 16 (2⁴) different program sources, thus allowing considerable scope for future expansion.

Each memory cell uses four bistable multivibrators (flip-flops). Initially, all four flip-flops are steered into the same

stable state by means of the reset inputs. When access to this memory is required, any code generated by the encode push-button is passed to the set inputs of the flip-flop. If this code is 0001, flip-flop 4 will change to the second stable state. Each memory is read out in turn to become the next event, and when this memory is read out, the code 0001 recorded in the flip-flop is transferred to decoders.

The information stored in digital code is displayed to the operator by means of a bank of indicator lamps. The next event to go to air is displayed in the indicating push buttons used to code up the memories.

The operation of the next event to go to air is controlled by a 10 - second count, derived by dividing the 50Hz vertical drive pulse from the station synchronising pulse generator to produce a one second count. This is further counted by a modulo 10 counter, with each count decoded to produce the 10-second cycle. At minus 10 seconds (the arrival of the cue pulse) the projector begins to roll. At minus 2 seconds, the "projector show" is operated, and the vision and sound switch occurs. This allows an eight-second run-up time (really intended to ensure video tape stability, when program is taken from this source, but also applied to the film projectors for convenience). At minus 1 second, the read out is stepped on to the next memory and at 0 second the count resets, ready for a new cue.


To achieve maximum flexibility in presentation, vision source and sound source are recorded independently in the memory bank, and random access is available to individual memories to allow last minute program changes. Transition between two events, by means of cut, fade or wipe, is recorded in the memory bank. The equipment controls circuits are integrated with the vision and sound switching circuits and a single board for, say, a telecine chain, could contain all gates for film and slide projector operations and interlock as well as vision and sound control, and could be repeated for the number of telecine chains required.

The equipment is designed for the minimum of maintenance. There is no setting up procedures, and only a few pre-set controls are used. It is entirely solid state, and uses microcircuits for all memory, gating and counting functions; switching transistors for operating indicator lights and controlling program equipment; and MOSFET transistors for switching video and audio. More than 500 microcircuits and 250 transistors are mounted in a single matrix board measuring 30 x 18in. This high packing density is achieved only because direct wiring between microcircuits is required and relatively few additional components are needed.

The "open plan" type of layout for the logic matrix was chosen so that changes in design could be readily made in the light of experience, but it is clear that modular construction could be used with advantage. For instance, each memory circuit in the sound and vision sections are identical; 20 of them are required for a 10 event store. ■



The memory is programmed by push buttons on the control console. Indicator lights tell the operator how many events are still in the memory.



TRUVOX R44 SEMI-PROFESSIONAL RECORDER

A brilliant new fully transistorised recorder for 240V AC operation. All controls interlock, VU meter provides positive indication of recording level. Three speeds, 7 $\frac{1}{2}$ -3 $\frac{1}{2}$ -1 $\frac{1}{2}$ i.p.s. Takes 7" spools. Frequency response is 40-15,000 Hz, plus or minus 3 db. at 7 $\frac{1}{2}$ i.p.s. Signal to noise is better than 46 db. Output is conservatively rated at 3 watts R.M.S. (6 watts peak) into a 15 ohm load. Wow and flutter is less than 0.15% at 7 $\frac{1}{2}$ i.p.s. Independent microphone and radio/pick-up controls are standard—full mixing is hereby simplified. See the review in "Amateur Tape Recording", Oct., '66, and "Audio and Record Review", Aug., '66. Encel price **\$139**

Ask for copies of reviews.

TRUVOX MONO RECORDERS— MODEL R 104

Features three heads, three motors, three speeds. Frequency response at 7 $\frac{1}{2}$ i.p.s. is 30-17,000 Hz., plus or minus 2 db. Write for details and copies of reviews. Price now reduced. R 104 **\$189**

NEW SYDNEY ENCEL STEREO CENTRE A MUSIC LOVER'S MECCA!

Although only just over one year old, the Sydney branch of Encel Electronics is a very healthy infant. Situated on the Ground Floor of the 25M Building at 257 Clarence Street, the store incorporates a complete Service Centre. Harbor City music lovers are always welcome . . .



TRUVOX STEREO TAPE UNITS MODELS PD 102 and PD 104

With four independent pre-amplifiers, complete mono and stereo monitoring facilities are provided on the new TRUVOX PD-102 and PD-104. Twin VU meters. Mixing buttons for sound on sound. Separate solid state record and playback amplifiers. Three motors, including papst drive motor, three speeds. Sensitivities match any ancillary equipment of any make. Frequency response — 30-17,000 Hz at 7 $\frac{1}{2}$ i.p.s. — plus or minus 2 db. Signal to noise is better than 50 db. Input sens. are . . . Microphone — 1 mV at 50k ohms, Radio Tuner or Pick-up — 50 mV at 100k ohms.

A recent British technical review says . . . "At last we have an all British recorder which equals the best Continental and Scandinavian products in accurate equalisation and wide frequency response, and which at the same time gives that subtle subjective satisfaction and impression of smoothness and effortless dynamic range which is so difficult to define and measure."

Write for complete specifications and copies of reviews; both the PD 102 (2 track) and PD 104 (4 track) are now in stock **\$248**

GET THE ENCEL FACTS

Pamphlets and technical specifications are usually available for most Encel merchandise. Write or call for further information.

TAPE RECORDERS

Although our range of recorders is wide, Encel prices have assured a speedy turnover . . . ask for EMQ's or trade-in valuations. Save more at Encel Electronics!

WHARFEDALE SPEAKERS


A complete range of world famous Wharfedale sound reproducers is always available at Encel Stereo Centres . . . write or call for an EMQ or a trade-in valuation. Models in stock include: Super 3, Super 5, Super 8 RS/DD, Super 10 RS/DD, Super 12 RS/DD, W12/FRS, W15/RS, PST/4, 8 in. Bronze RS/DD, 10 in. Bronze RS/DD, Golden 10 RS/DD and the RS 12/DD.

TAPE BULK ERASERS

Now available . . . WAL bulk erasers! Spools may be wiped absolutely clean . . . in only a few seconds. Use **\$24.50** any AC power point . . .

SPEEDY MAIL ORDER SERVICE

Please give us your name and address in BLOCK LETTERS when ordering. All Encel equipment is BRAND NEW and Sales Tax is included in Encel prices. We care-pack and freight anywhere. Service is available at the Encel Service Centre in Melbourne and also at the Encel Stereo Centre, 257 Clarence Street, Sydney.



THE NEW COSMOS SW-30C STEREO AMPLIFIER

8 watts R.M.S. or 15 watts I.H.F.M. per channel. P.P. 6BM8's. Wide frequency response. Speaker matching 4, 8 and 15 ohms. Sens. for p.u. 5 mV. Headphone jack. Encel price . . . **\$69.50**

"ARISTOCRAT" RECORDING TAPE—WELL KNOWN U.S. TAPE AT LOW COST!

"Aristocrat" mylar tape is available in these sizes: 7 in. 1800 ft. \$3.70. 7 in. 2400 ft. \$5.60. 7 in. 3600 ft. \$7.65. Other "Aristocrat" sizes: 5 in. 900 ft. \$2.10. 5 in. 1800 ft. \$4.40. 4 in. 600 ft. \$1.35. 3 in. 225 ft. \$0.95. This is the first time high quality recording tape has been offered in Australia at these prices.

NEW JANSZEN SPEAKER SYSTEMS WITH ELECTROSTATIC ELEMENTS

The all new Janszen Z600 speaker system is revolutionary in design and construction — provides a magnificent "transparent" sound. Response is 30 to beyond 30,000 Hz. The natural treble response results from the use of Series 130 Janszen mid/high range radiators—electrostatic units with 176 push-pull sheathed conductors. The bass reproducer is the Janszen Model 350B dynamic. Impedance is 8 ohms only. Encel price is \$178 for the Z600 . . . and the cabinet can only be described as a masterpiece. Finish is oiled walnut. Truly an audiophile's delight. **\$178** Ask for copies of elated reviews



NOW . . . A PRECISION TONE ARM FOR ONLY \$19!

The Nikka-Lustre tone arm Model C.P.3 is a beautifully engineered instrument which will track down to 1 gram with suitable cartridges. An open-front head shell accepts all standard 1" mounting cartridges — and the arm takes Ortofon and SME shells without modification. Miniature ball races are used throughout — an outrigger bias adjustment sets stylus pressure. A tailored lifting/lowering device is now available for this arm (\$7.50). See the review in "Electronics Australia", p. 123, October, 1966. Write for copies **\$19**

Celestion

Studio
Series

CELESTION "STUDIO SERIES" LOUDSPEAKERS

The "Celestion" Deluxe Model CX2012 is rated at 20 watts RMS and frequency response is conservatively quoted as 30-18,000 Hz. A special "Brilliance" control operates in the tweeter circuit — the electrical cross-over is at 4 kHz. See reviews in the "Gramophone" p.511, April, '65, and "Hi-Fi News" p.75, June, '65. ENCEL PRICE: **\$59** CX2012


Celestion 12" co-axial loudspeakers have been received most enthusiastically by audio enthusiasts and music lovers in Australia. Clarity, transient performance and attack are particularly satisfying. Both models feature co-axial tweeters with electrical cross-overs at 4 kHz. The Standard Model CX1512 has a frequency response conservatively quoted at 30-15,000 Hz and it rated at 15 watts RMS. Encel Price **\$39.50** CX1512

SUPERLATIVE IMPORTED WOOFERS—BOTH 15" and 18" AVAILABLE NOW!

Rugged and powerful Celestion woofers are particularly suited to public address, guitar and electronic organ applications — and for the bass registers in multiple speaker systems. In Europe both speakers are very popular . . . often they are supplied as standard equipment with expensive imported electronic organs and guitar amplifiers. G15C. A 35 watts RMS 15" speaker, this new Celestion unit has been designed for use with organs, guitars and public address systems. Ferroba II ceramic magnet, total flux 180,000 maxwells. This powerful reproducer is Encel priced at only **\$68.50**

OUTSTANDING NEW 18" BASS SPEAKER WITH 20 Hz. BASIC RESONANCE

Use of a new type rubber surround reduces the resonance of the new Celestion G18C to 20 Hz. Total flux is 285,000 maxwells, power handling capacity is 100 watts R.M.S. This massive woofer is ideal for the sophisticated audiophile who is seeking the ultimate in bass reproduction at relatively modest price. Also suitable for electronic organs, electric guitars, etc. Write for specifications **\$98.50**



IF THERE'S A BATTLE OF THE COMPACTS . . . THE CELESTION "DITTON 10" IS WELL TO THE FORE

Many music lovers require compact speaker systems . . . and tape recording enthusiasts find the addition of external speaker systems makes an astounding difference to performance. Although only 12" x 6 $\frac{1}{2}$ " x 8 $\frac{1}{2}$ " the "Ditton 10" incorporates two units, the bass reproducer being a specially designed "long throw" model which extends LF response. Power handling capacity is 10 watts R.M.S. Both 3 and 15 ohm impedances are available . . . the 3 ohm model is ideal for use with solid state amplifiers and tape recorders. See the reviews in "Hi-Fi News", p.433, Oct., '65, and the "Gramophone", p.41, June, '65. Write for copies of these enthusiastic reports. The "Ditton 10" is beautifully finished in teak or walnut veneers. These compact systems are used by one of Australia's leading universities to reinforce sound in the auditorium . . . **\$59**

Encel

ELECTRONICS PTY. LTD.

Head Office: 431 Bridge Rd., Richmond, Vic. Tel. 42 3762
Sydney Store: 257 Clarence St., Sydney. Tel. 29 4563, 29 4564
Australia's Greatest Hi-Fi Centre
* Wholesalers * Trade-Ins Accepted

New low cost professional silicon planar epitaxial TO18 NPN transistors . . .


have been designed for use in scientific, professional and communications equipment—where there's much more at stake than a favourite radio or T.V. programme.

They're made in Australia, life tested to the highest professional standards, and the price is right. Call Miniwatt for full details.

- ☐ Silicon Planar Epitaxial TO18 NPN Transistors
- ☐ Made in Australia
- ☐ Fully Life Tested to Professional Standards
- ☐ Low Collector-Emitter Saturation Voltage
- ☐ High Gain
- ☐ High Transition Frequency
- ☐ Low noise

	BCY56	BCY57	
V_{CBO}	45	25	V
V_{CEO}	45	20	V
I_C	100	100	mA
h_{FE} at I_C 2mA V_{CE} 5V	100- 450	200- 800	
f_T	85	100	MHz
NOISE (typical)	1.5	1.5	dB

when there's serious work afoot— think 'professional'



"Miniwatt"



ELECTRONICS DIVISION OF PHILIPS
ELECTRICAL PTY. LIMITED.

Sydney • Melbourne • Brisbane
Adelaide • Perth • Canberra

38.2962

FIJI — radio hub of the South Pacific

Radio plays an important part in the everyday life of Fiji, one of the jewels of the Pacific, and one of the last of Britain's Crown Colonies.

by Michael Terry



The Australian who visits Fiji will find the broadcasting set-up very different to that which exists in Australia, with its network of national and commercial stations. The Fiji Broadcasting Commission operates all the stations, but finances their operation from advertising revenue. With three ethnic groups to be catered for — European, Fijian and Indian — broadcasts have to be on a trilingual basis. Since the total population is only half a million, it is surprising to learn that the organisation made a profit of £F21,500 in 1965. In that year, the FBC collected £F131,000 — £F45,000 from radio licences and a further £F86,000 from advertising revenue — and operating costs amounted to £F110,000.

The licensing system is rather different to that used in Australia. Each set has to be licensed, regardless of how many are possessed by a household, but whereas F25/ is charged for the first licence, each additional licence costs only F15/. The large number of unlicensed receivers is a problem, and the figure is thought to have risen sharply since the arrival of the battery operated transistor radio. Now it is possible for every bure (thatched native hut) to operate a radio, since mains power is no longer a factor, and the impossibility of policing every village is tacitly acknowledged by the authorities.

Broadcasting began in 1936 when station ZJV was inaugurated by Amalgamated Wireless (Asia) Ltd., with English language programs only. All broadcasting became a Government controlled monopoly with the formation of the Fiji Broadcasting Commission, and the Fijian broadcasts were introduced to cater for the native population. Hindustani was added during World War II for the large Indian community. In 1954 the programs were rescheduled and expanded and the staff reorganised. In view of the similarities between the Fijian and New Zealand broadcasting systems, staff was trained by New Zealanders. There are now 9 Fijians, 11 Indians and 17 Europeans keeping Radio Fiji on the air.

At present Radio Fiji is operating on five medium wave and four short wave frequencies, with simultaneous broadcasts in the English, Fijian and Indian languages. I use the word "languages" guardedly, as there are dialects in use of all three languages, as well as the standard languages. When Ratu Cakobau ceded Fiji to Queen Victoria in 1874 there already existed dialects among the tribes, and these still persist. In more recent years, a general tongue has de-

veloped which all Fijians understand, but despite this spelling has not yet been formalised, and divergences between the spelling and pronunciation of some words is apt to puzzle the visitor. Some attempt has been made to introduce a phonetic spelling, but this has only compounded the confusion, since both forms now exist in print.

The main snag in the traditional spelling is that there is an "n" hidden behind every "d" and an "m" behind every "b". For example, the town of Labasa is pronounced "Lambasa." Lakeba, is "Lakemba," Nadi (the international airport) is "Nandi." A European substituting for a Fijian as announcer or news reader has to be carefully trained in the idiosyncracies of the language, otherwise he would make a hash of a lot of words.

So much for the broadcasting. Whatever the Fijians may think of the set-up, they certainly have no cause for complaint in the colony's modern and efficient telephone network. Outside of the main cities, telephone poles are non-existent. The Post Office uses radio link equipment for inter-city and inter-island communication. Besides the two main islands of Viti Levu and Vanua Levu, there are some 361 smaller islands in the archipelago, and many of these are included in the telecommunications network, which provides 80 speech circuits.

The capital, Suva, is the communications hub of the South Pacific and the centre of the telephone network. It is also provided with a terminal linking into the Compac cable, so that it is possible to call Australia or London almost as easily as a local number. Calls are routed through Suva for less distant places such as Rarotonga, Pango-Pango, Apia, Nuku-Alofa, Wallis Island, Tarawa, Nauru, Honiara, and Noumea.



The transistor radio has proved a great boon to native Fijians without mains power.

One of the activities of the Posts and Telegraphs Department is the humanitarian one of maintaining a 24-hour-a-day radio watch for calls from vessels in distress. Flying boats of the Royal New Zealand Air Force based in Suva played an important part in air-sea rescue operations in the past, but the base has unfortunately now been closed.

Radio plays a big part in medical treatment in Fiji, as it does in Australia with its Flying Doctor Radio Service. Local medicos who are not sure how to handle a complex case contact medical authorities in Suva for specialist advice. Urgently needed medical supplies can also be flown to remote locations should circumstances demand it. Recently, a New Zealand Air Force plane flew oxygen in cylinders to an island north of Samoa to save the life of a child.


To round off this survey of radio in Fiji, here is a summary of the amateur radio activity in the colony. Although 24 amateurs are licensed, only eight are now active. At one time there was a Sunday morning "mosquito network" but this has gradually faded out. Bill Erick, a wealthy retired American cattleman from Nevada, operates a station on the small island that he now owns, not far from Suva. He uses a 50ft mast, and regularly contacts W6AL at Lodi, California, for the latest news from the States. On the occasions when he visits his homeland, Bill Erick keeps in touch with Fiji through VR2DI.

All the amateurs are on Viti Levu, the principal island of Fiji, except Frank Fleming, who is the caretaker on Nukula Island, a resort belonging to the Royal Suva Yacht Club, and located nine miles from the capital. Frank, call-sign VR2AU, was the first person to fly an aircraft to Fiji. Malcolm Gray, VR2BJ, contacts his brother in South Australia. Graeme Johnson, VR2FF formerly of the RNZAF, keeps in touch with his father in Timaru, who operates ZL3JO. The only Fijian amateur is Wangga-i-Rawai (spelt phonetically) whose call sign is VR2EP, and the sole Indian is Raj Singh, VR2ER.

It is not easy to obtain an amateur licence in Fiji, because the examination is a stiff one. The licence fee is only F30/ a year (equivalent to about \$A3.40). Receivers come in duty-free, but transmitters and parts used in their construction are subject to duty, amounting to 25 per cent on goods from Commonwealth countries, and 45 per cent elsewhere.

One last point—Fiji has no television service as yet—but who would want it in this tropical paradise.

The original
"DUST BUG"
(Regd.)



Automatic Record Cleaner. Easily fitted to any transcription type turntable — the "Dust Bug" provides a simple and effective method of removing static and dust while the record is being played. Surface noise and record and stylus wear is reduced resulting in cleaner reproduction.

The
"PARASTATIK"
DISC
PREENER
(Regd.)



Place 'Preener' on to recorded area and press lightly and evenly while the record slowly rotates.

Expressly designed for use with new records and is able to collect all dust from the record surface without the use of anti-static agents. The plush pile penetrates each groove giving ideal playing conditions for ultra-light stylus pressures. Reduces background noise ensuring greater listening pleasure.

The
"PARASTAT"
Manual Model
Mk. IIa.



Removes old residues from previous antistatic treatments—even from groove bottom.

Restores fidelity to older records. Nylon brush tips penetrate deep into the record groove removing dirt, grit and residue bringing old records to life and maintaining new records as new.

The
"HUMID MOP"



Rapidly cleans and conditions the 'Parastatik' bristles and velvet pads.

For use with the Manual "Parastatik". Improves its efficiency in critical playing conditions especially when ultra lightweight pickups tracking at less than 2 grammes are used. Ensures that the surface of the record groove walls is maintained in a perfect playing condition. Should be used each time the "Parastatik" is applied to the record.

NEW FORMULA
"PARASTATIK"
DISPENSER



For normal use with "Dust Bug"



Reactivates the 'Preener'



Activates the 'Humid Mop'

Cleans and controls static — without surface film.



Send today for your POST FREE copy of this informative WATTS publication . . . "Guide to the Better Care of your L.P. and Stereo Records". Price — 35c. Available from Simon Gray offices and representatives, good record stores and hi-fi centres.



Australian National Distributors:

Simon Gray Pty. Ltd.

Head Office: 28 Elizabeth Street, Melbourne, Vic. Tel. 63 8101

Sydney Office: 22 Ridge Street, North Sydney, N.S.W. Tel. 92 3890

INTERSTATE REPRESENTATIVES:

S.A.: Eilco Sales Pty. Ltd., 7-9 Osmond Terrace, Norwood, S.A. Tel. 63 4844

Q'land: Sydney G. Hughes, 154-158 Arthur St., New Farm, Brisbane. Tel. 58 1014

W.A.: Athol M. Hill, 613-615 Wellington Street, Perth. Tel. 21 7861

Tas.: K. W. McCulloch Pty. Ltd., 109 York Street, Launceston. Tel. 2 5322

A.C.T.: Australian Physical Laboratories, P.O. Box 225, Canberra City.


Tel. 4 3010 (Mr. J. E. Howe)

N.T.: Pfitzner's Music House, Smith Street, Darwin. Tel. 3801



**THE ONLY
COMPREHENSIVE
RANGE OF
RECORD
MAINTENANCE
EQUIPMENT
IN THE
WORLD**





Technical Review

Parametric Amplification of Far-Infrared Light

The first parametric amplification of far infrared light has been achieved. Tellurium, an elemental semiconductor, was used to achieve a 3dB gain in intensity of laser light at a wavelength of 17.9 microns.

Parametric amplification of far infrared light is important as a means of increasing the intensity of light from a weak source, and is a first step toward constructing a parametric oscillator. Optical parametric amplifiers and oscillators are of considerable interest for possible use in future laser communications systems and the study of the nature of optical materials.

In optical parametric amplification, three light waves of different frequencies interact within a nonlinear material (in this case, tellurium). Energy from one wave, at the "pump" frequency, is transferred to two other waves: the signal wave, which is amplified, and the "idler" wave, which is generated as a by-product of parametric amplification. The frequency of the idler wave always equals the pump frequency minus the signal frequency.

The energy source in the experiment, conducted by Dr C. Kumar N. Patel, of Bell Telephone Labs., is a carbon dioxide laser, which supplies the pump power — 10.6-micron radiation in 10-


kilowatt pulses, at a rate of 160 pulses per second. The light to be amplified, the signal frequency, is supplied by a helium-neon laser that generates 10 microwatts of continuous wave (CW) power at a wavelength of 17.9 microns. The idler wave has a wavelength of 25.9 microns.

Tellurium has two properties which make it especially effective as a medium for parametric amplification. First, it is the most nonlinear material known. That is, there is a nonlinear relationship between the amount of electric polarisation induced in the tellurium crystal and the electric field applied to the crystal by the laser light waves. Within a nonlinear material — the only type suitable for parametric amplification — light waves of different frequencies can interact, and energy from one light wave can be transferred to another. Because of tellurium's high co-efficient of nonlinearity, the energy transfer from the pump radiation to the signal frequency is very efficient.

Tellurium is also birefringent; that is,

it has different optical properties in different directions. The velocity of light passing through a birefringent crystal depends on the direction of its path through the crystal. For example, when Dr Patel directed both laser beams through the tellurium crystal at an angle of 7 degrees from its optic axis, he found that the interaction between the waves at the pump frequency, the signal frequency and the idler frequency was phase-matched. Phase-matching strengthens parametric amplification by lengthening the optical path along which the three light waves interact.

In the experiment, the light beams from the carbon dioxide laser and the helium-neon laser are combined into one beam and focused into a 7mm-long tellurium crystal. The light output from the crystal is passed through filters which block the 10.6-micron pump radiation and the 25.9-micron idler wave, but allow the 17.9 micron signal to pass with minimum attenuation. The 17.9-micron signal radiation, a CW input to the tellurium crystal, showed pulses of about 3dB gain at the output of the crystal. The pulses were coincident with the pump pulses from the carbon dioxide laser, verifying that parametric amplification had occurred in the tellurium crystal. ("International Electronics," April-May, 1967.)



Three light waves of different frequencies interact within crystal to produce amplification. Energy from one wave, at the "pump" frequency, is transferred to the signal wave, which is amplified, and the idler wave, which is a by-product of the parametric amplification. Pulses of about 3dB gain in the output signal coincide with the pump pulses

silicon planar

for audio, radio and hybrid television applications

Mullard now offer a comprehensive range of Silicon Planar transistors for all new design requirements. These devices are outstanding in performance and are available at competitive prices.

Further details are available from the addresses below:—

N.S.W. 35-43 Clarence St., Sydney, N.S.W. 29 2006
VIC. 123-129 Victoria Pde., Collingwood, N.S. Vic. 41 6644
QLD. 33 Bowen St., Brisbane, Qld. 2 8746
S.A. 266-270 Sturt St., Adelaide, S.A. 51 6341
W.A. 579 Murray St., Perth, W.A. 21 2561

Mullard-Australia Pty. Ltd.

Associated with MULLARD LIMITED, LONDON

BC107

Low-frequency high-gain driver.

BC108

Low-frequency high-gain amplifier.

BC109

Low-noise high-gain A.F. amplifier.

BF115

V.H.F. mixer and oscillator for television.

BF167

'Integrated Screen' transistor for television I.F. amplifiers (A.G.C.).

BF173

'Integrated Screen' transistor for large signal television I.F. amplifier stages.

BF177/8/9

High voltage transistors for video output stages.

BF180

Low-noise R.F. amplifier for U.H.F. and integrated tuners.

BF181

High-gain mixer and mixer/osc. for U.H.F. and integrated tuners.

BF184

High-gain I.F. amplifier for A.M., F.M. and television sound.

BF185

R.F. and I.F. amplifier for portable radios.

Mullard

M202



"DISTANT ELECTRIC VISION" ANTICIPATED MODERN TV

"Distant Electric Vision" was the name given by English scientist Mr. A. A. Campbell-Swinton to a system proposed by him in 1911 for instantaneous transmission by wire of motion picture images. The remarkable thing about the proposed system was that its operating principles were basically the same as those used in television today, as can be seen from the following extract from the address.

So long ago as the year 1908, in connection with a paper published in "Nature" by the late Mr Shelford Bidwell, I wrote a letter in that journal suggesting that the difficulty of obtaining the necessary enormous numbers of synchronised operation per second could possibly be solved by the employment of two beams of cathode rays, one at the transmitting and one at the receiving station, synchronously deflected by the varying fields of two electromagnets placed at right angles to one another and energised by two alternating electric currents of widely different frequencies, so that the moving extremities of the two beams would be caused to sweep synchronously over the whole of the required surfaces within the one-tenth of a second necessary to take advantage of visual persistence; and that, so far as the receiving apparatus was concerned, the moving cathode beam would only have to be arranged to impinge on a sufficiently sensitive fluorescent screen, and, given suitable variations in its intensity, to obtain the desired result.

As, since that date, I have several times been asked to explain more in detail this idea, I now propose to do so, though it must be distinctly understood that my plan is an idea only, and that the apparatus has never been constructed. Furthermore, I would explain that I do not for a moment suppose it could be got to work without a great deal of experiment, and probably much modification. It is, indeed, only an effort of my imagination, and can be useful merely as a suggestion of a direction in which experiment might possibly secure what is wanted. What, however, is claimed is that, so far as I am aware, it is the first suggested solution of the problem of distant electric vision in which the difficulty of securing the required extreme rapidity and accuracy of motion of the parts is got over by employing for these parts things of the extreme tenuity and weightlessness of cathode rays. Indeed, apart from the revolving armatures of the alternators employed for synchronisation which present no difficulty, there is no more material moving part in the suggested apparatus than these almost immaterial streams of negative electrons. Further, as will be seen, only four wires, or three wires and earth connections at each end, are required.

In the diagrammatic illustration the transmitter is shown on the left-hand


side and the receiver on the right-hand side. The transmitter consists of a Crookes tube A fitted with a cathode B, which sends a cathode-ray discharge through a small aperture in the anode C, the cathode rays being produced by a battery or other source of continuous electric current giving some 100,000 volts. D and E are two electromagnets placed at right angles to one another, which, when energised by alternating current, will deflect the cathode rays in a vertical and in a horizontal direction respectively.

The receiving apparatus consists similarly of a Crookes tube A' fitted with a cathode B', which, in circumstances to be further described, transmits cathode rays through an aperture in the anode.

the screen fluoresces with what appears to the eye as a uniform brilliancy.

Similarly, in the transmitting apparatus, the cathode rays fall on a screen J, the whole surface of which they search out every tenth of a second under the influence of the magnets D and E. Further, it is to be remarked that as the two magnets D and D' and the two magnets E and E' are energised by the same currents, the movements of the two beams of cathode rays will be exactly synchronous, and the cathode rays will always fall on the two screens H and J on each corresponding spot simultaneously.

In the transmitter the screen J, which is gas-tight, is formed of a number of small metallic cubes insulated from one another, but presenting a clean metallic surface to the cathode rays on the one side, and to a suitable gas or vapour, say sodium vapour, on the other. The metallic cubes which compose J are made of some metal, such as rubidium, which is strongly active photoelectrically in readily discharging negative electricity under the influence of light, while the receptacle K is filled with a gas or vapour, such as sodium vapour, which conducts negative electricity more readily



C', D' and E' are two electromagnets placed at right angles, similar to those in the transmitter, the two magnets D and D', which control the vertical motions of the cathode-ray beam, being energised from the same alternating dynamo F, which has a frequency, say, of ten complete alternations per second; while the other two magnets E and E', which control the horizontal movements of the cathode-ray beam, are energised by a second alternating dynamo G having a frequency of, say, 1,000 complete alternations per second.

In the receiver H is a fluorescent screen, upon which, under conditions to be further described, the cathode rays impinge, and the whole surface of which they search out every tenth of a second under the combined deflecting influence of the two magnets D' and E', with the result that under these conditions


under the influence of light than in the dark.

Parallel to the screen J is another screen of metallic gauze L, and the image to be transmitted of the object N is projected by the lens M through the gauze screen L on to the screen J through the vapour contained in K. The gauze screen L of the transmitter is connected through the line wire to a metallic plate O in the receiver, past which the cathode rays have to pass. There is, further, a diaphragm P fitted with an aperture in such a position as, having regard to the inclined position of B', to cut off the cathode rays coming from the latter and prevent them from reaching the screen H unless they are slightly repelled from the plate O, when they are able to pass through the aperture.

The whole apparatus is designed to function as follows:

PLESSEY

Mini-fi is revolutionary!
it's small 14"x8"x8"
it's powerful 15 Watts RMS
it has fantastic response
35 Hz to 18,000 Hz (± 6 db)



Listen to Mini-fi and wonder how such magnificent sound can come from so small an enclosure

Small enough to bring stereo into any home and powerful enough to handle the maximum output of most high fidelity amplifiers, the Mini-fi has proved to be eminently satisfying to even the most discerning hi-fi enthusiasts.

The new powerful high compliance, long excursion Rola C65-0 woofer (available only as an integral part of the Mini-fi system) and the improved Rola

5FX tweeter combine to produce Mini-fi's outstanding frequency response. When used with an amplifier supplying 6 db of bass boost at 100 Hz Mini-fi provides brilliant response from 35 Hz to 18,000 Hz (± 6 db under anechoic conditions). See the June edition of "Electronics Australia" for complete specifications on Mini-fi—or contact Rola Division direct.



Plessey Components Group

Rola Division The Boulevard

Richmond E1 Victoria Telephone 42 3921

NSW Plessey Components Group Rola Division Box 2 PO Villawood Telephone 72 0133

Assume a uniform beam of cathode rays to be passing in the Crookes tubes A and A' and the magnets D and E and D' and E' to be energised with alternating current, as mentioned. Assume, further, that the image that is desired to be transmitted is strongly projected through the lens M through the gauze screen L on to the screen J. Then, as the cathode rays in A oscillate and search out the surface of J, they will impart a negative charge in turn to all the metallic cubes of which J is composed. In the case of cubes on which no light is projected, nothing further will happen, the charge dissipating itself in the tube; but in the case of such of those cubes as are brightly illuminated by the projected image, the negative charge imparted to them by the cathode rays will pass away through the ionised gas along the line of the illuminating beam of light until it reaches the screen L, whence the charge will travel by means of the line wire to the plate O of the receiver. This plate will thereby be charged; will slightly repel the cathode rays in the receiver; will enable these rays to pass through the diaphragm P, and, impinging on the fluorescent screen H, will make a spot of light. This will occur in the case of each metallic cube of the screen J, which is illuminated, while each bright spot on the screen H will have relatively exactly the same position as that of the illuminated cube of J.

Consequently, as the cathode-ray beam in the transmitter passes over in turn each of the metallic cubes of the screen J, it will indicate by a corresponding bright spot on H whether the cube in J is or is not illuminated, with the result that H, within one-tenth of a second, will be covered with a number of luminous spots exactly corresponding to the luminous image thrown on J by the lens M, to the extent that this image can be reconstructed in a mosaic fashion. By making the beams of cathode rays very thin, by employing a very large number of very small metallic cubes in screen J, and by employing a very high rate of alternation in the dynamo G, it is obvious that the luminous spots on H by which the image is constituted can be made very small and numerous, with the result that the more these conditions are observed the more distinct and accurate will be the received image.

Furthermore, it is obvious that, by employing for the fluorescent material on the screen H something that has some degree of persistency in its fluorescence, it will be possible to reduce the rate at which the synchronised motions and impulses need take place, though this will only be attained at the expense of being able to follow rapid movements in the image that is being transmitted.

It is further to be noted that as each of the metallic cubes in the screen J acts as an independent photoelectric cell, and is only called upon to act once in a tenth of a second, the arrangement has obvious advantages over other arrangements that have been suggested, in which a single photoelectric cell is called upon to produce the many thousands of separate impulses that are required to be transmitted through the line wire per second, a condition which no known form of photoelectric cell will admit of.

Again, it may be pointed out that sluggishness on the part of the metallic



PORTABLE VIDEOTAPE RECORDER

A battery-powered portable videotape recorder and camera combination weighing less than 50lb and designed primarily for remote high speed taping of news events by a single operator has been placed on the market in U.S.A. by Ampex Corporation.

The new Model VR-3000 recorder is the smallest standard broadcast recorder ever built, according to Ampex. It produces either high-band or low-band monochrome tapes that may be immediately replayed on the air on any standard transverse (four-head) studio recorder. It also is capable of recording high band colour from studio colour cameras without modification. The recorder weighs only 35lb and in its attaché-type carrying case measures 23 x 12½ x 6in.

It records up to 20 minutes of video action and sound on an 8in reel of standard 2in wide video tape. The battery permits 20 minutes continuous recording without recharging, and an additional 20 minutes of preview operation of the camera only or live telecasting. Batteries are easily replaceable in the field, and a battery charger is included as a standard accessory. The camera employs a Plumbicon tube for high quality performance. It weighs 13 pounds, including an electronic viewfinder. It produces broadcast-quality monochrome pictures at light levels down to 30 foot-candles.

A shoulder harness attaches to the base of the camera with shoulder and abdomen supports to permit hand-held operation. The camera also may be used with a standard tripod. A standard lens mount permits use of various standard fixed or zoom lenses, which may

be interchanged quickly and easily. A 4-to-1 zoom is included as standard equipment.

Controls for operating the recorder are conveniently located on the camera for one-man operation. Using the electronic viewfinder, the operator sees exactly what is being recorded. A visual signal advises him of necessary lens setting changes while recording. A clock shows at all times how much recording has been done and how much recording time is left. Simultaneous high quality audio recording on the video tape is controlled from the camera. An automatic gain control assures constant level of sound without monitoring by the operator.

The VR-3000 may also be used with standard television cameras for high-band or low-band colour or monochrome recording. It is offered either in 525-line or 625-line versions and may be easily converted from one to the other to permit recording on international TV standards. An accessory kit has the same dimensions as the recorder case and weighs approximately 40lb fully equipped. It has space for two spare reels of tape and two spare batteries, and includes battery charger, an auxiliary control and test unit for operation apart from the camera, and a battery eliminator which permits the recorder and camera to be operated from any normal AC power source.


cubes in J or of the vapour in K, in acting photoelectrically, in no wise interferes with the correct transmission and reproduction of the image, provided all portions of the image are at rest; and it is only to the extent that portions of the image may be in motion that such sluggishness can have any prejudicial effect. In fact, sluggishness will only cause changes in the image to appear gradually instead of instantaneously.

Many modifications are, of course, possible in detail. For instance, the plate O of the receiver might perhaps better be replaced by an electromagnet or solenoid so arranged as to repel the cathode

beam when energised. Again, the somewhat crude form of photoelectric cell described, composed merely of insulated cubes of rubidium in contact with sodium vapour, might be improved upon. Indeed, it is highly probable that research will reveal much more sensitive materials, the use of which would vastly improve this part of the apparatus, which at present is probably the one least likely to give the desired results. ["Proceedings Of The Institute Of Radio And Electronics Engineers Australia," Vol. 27, No. 11 (November, 1966). The article was originally published in "Nature" in 1911.]

PLESSEY

Miniature lever key switches



Illustrated above Top left. Single action key type N9300 Series. Top right. Large capacity key type N9900 Series. Bottom. Multiple key unit.

The Ducon Division of Plessey Components Group offer a range of miniature lever key switches with the following features:—

Design Designed to meet the most demanding electrical, mechanical and styling requirements, these compact, space saving switches provide a ready solution to light-current switching problems. All are fully tropicalised and meet the requirements of both British Post Office Specification D2162 and Interservices RCL 153 Pattern 3.

Contacts There is a wide range of contact arrangements which are adequate for most general applications. Switches are normally supplied with silver

contacts. However, gold, platinum or palladium are available if required.

Key Handles Handles are available either in a standard black with ivory insert or from a choice of many self-colours with contrasting tip inserts to provide easy identification.

Reliability Extended life tests have indicated negligible wear or loss of contact pressure after one million operations.

Dimensions Width $39/64$ ", Depth $2-3/16$ ". Height — Single unit $13/4$ ", 2 unit $31/4$ ", 3 unit $43/4$ ", 4 unit $61/4$ ".


A standardised range is available ex stock. Literature is available on request to:—



Plessey Components Group

Ducon Division Box 2 PO Villawood NSW
Telephone 72 0133

SCIENTIFIC AND INDUSTRIAL NEWS



New TV translators

Three country areas in Victoria — Portland, Alexandria and Eildon — will receive better quality television soon, following a Government decision to allow the establishment of translator stations in these areas. Each area will have translators for both the national and commercial services.

Acting Postmaster-General, Senator K. Anderson, said the A.B.C.B. had recommended the establishment of the translators following a detailed investigation into the requirements of each area.

Rural telephones

Telecommunications Company of Australia Pty. Ltd. and its subsidiary Commonwealth Electronics Pty. Ltd. have been awarded P.M.G. contracts worth about \$270,000 for the supply of 150 single channel VHF and UHF radiotelephone terminals and associated equipment. The terminals, which are fully solid-state and provided with telephone dialling facilities, will be used for rural trunk line service by the Post Office.

The contract follows a previous order from the P.M.G. for 100 similar terminals. These are the first fully solid-state UHF and VHF radiotelephone terminals to be designed to trunk line standards in Australia. Included in the contract are VHF radiotelephone units which will be used to replace existing low-grade earth-return services to remote subscribers in rural areas.

Pyroelectric thermometers

A recent study at the N.B.S. Institute for Materials Research in U.S.A. investigated the feasibility of using pyroelectric materials as thermometer sensors to measure minute temperature changes in the cryogenic region. Pyroelectric materials are asymmetrical crystals that become polarized by changes in temperature. The bureau's investigation centred about the examination of three types of commercial ceramic materials for use as possible sensing elements. Two of the compounds were principally composed of lead zirconate titanate while the third compound consisted mainly of barium titanate.

The phenomenon of pyroelectricity was first observed in Europe in 1703 by Dutch traders who had acquired tourmaline crystals in Ceylon for gemstones. The traders noticed that the tourmaline, when placed in a fire, first attracted ashes and then repelled them. Since that time, scientific research has revealed that pyroelectric crystals can be regarded as having a built-in

or permanent electric polarisation. When such a crystal is held at constant temperature, this polarisation is not evident. However, when the temperature of the crystal is raised a small amount, the magnitude of the polarisation changes. Conversely, if the temperature of the material is lowered by the same amount, the absolute magnitude of the change in polarisation is the same, but the direction of the change is reversed. Research has shown that a thermometer employing such materials as sensors would make possible the measurement of temperature differences smaller than one millionth of a degree, a limit now unobtainable.

CRT development

The Marconi Company Ltd., of Chelmsford, Essex, U.K., has introduced a new electromagnetic lens which can produce a spot of light on a cathode ray tube screen so small that it can write a line finer than a human hair. It enables high concentration of data to be presented on CRT displays of the type used in radar and computer systems. The device, Type F 1500, operates with such accuracy that, in use with any high quality display tube, it can focus the electron beam to produce a spot size of one-fifth of a millimeter in the central region of the screen and in other areas a spot size never more than twice this diameter.


Throughout the whole assembly the magnetic parts are made of mumetal which minimises remanence or hysteresis effects which would otherwise complicate the adjustment of the unit when it was being set up. The focus coil is shielded with mumetal to ensure the best possible symmetry of the focusing field.

Thermistors are employed with the alignment and astigmatism correction coils to compensate for changes in temperature over the range from -10 deg. C. to +70 deg. C. The coils and the thermistors are encased in high compression plastic mouldings which have interlocking surfaces.

The assembly can be used with all types of magnetically deflected cathode ray tubes with neck diameters up to 35 millimetres. Where the neck of the tube cannot accommodate the whole of the unit one or two of the correction coils can be omitted.


The focus coil unit is made up of seven annular shaped sections, bolted together to form a compact cylinder which fits over the neck of a cathode ray tube. There are three alignment coils, a focusing coil, and two coils which correct for astigmatism in the electron beam. Furthest from the cathode ray

An inspector examines the "petal" housing of Britain's new 98in Isaac Newton telescope, which will shortly be completed at the Royal Greenwich Observatory. It will be the largest in Western Europe. Within the circular area, panels shaped like petals open when the telescope is in use, but close to protect the mirror from dust and other foreign matter when it is not in use. The moving parts of the telescope weigh 87 tons and the mirror, weighing nearly five tons and measuring 98in across, has been polished to an accuracy measured in millionths of an inch.



foster®

■ dynamic microphones



*MDF-600B cardioid microphone

SPECIFICATIONS
 Impedance : 50 kΩ
 Frequency Response : 100~10,000 c/s ± 8 dB
 †Sensitivity : -52 dB ± 3 dB,
 Dimensions : 148 × 48 × 34.5 mm without stand
 Cable : 4 φmm, 3 m
 Weight : 1¼ lbs (525 g)




DF-1DE

SPECIFICATIONS
 Impedance : 50 kΩ
 Frequency Response : 150~10,000 c/s ± 8 dB
 †Sensitivity : -57 dB ± 3 dB,
 Dimensions : 385.5 mm high
 21 mm diameter, microphone
 128 mm diameter, stand
 Cable : 4 φmm, 1.5 m
 Weight : 1½ lbs (840 g) with cable



*DF-14B

SPECIFICATIONS
 Impedance : 50 kΩ Variable
 Frequency Response : 100~10,000 c/s ± 8 dB
 †Sensitivity : -48 dB ± 3 dB,
 Dimensions : 136 × 75 × 47 mm
 Cable : 6 φmm, 4 m
 Weight : 2 lbs (900 g)



*DF-22B

SPECIFICATIONS
 Impedance : 50 kΩ
 Frequency Response : 50~12,000 c/s ± 7 dB
 †Sensitivity : -57 dB ± 3 dB,
 Dimensions : 32.5 mm diameter, 220 mm long
 Cable : 6 φmm, 4 m
 Weight : 1¼ lbs (575 g)



DF-1/*DF-1B

SPECIFICATIONS
 Impedance : 50 kΩ
 Frequency Response : 100~10,000 c/s ± 8 dB
 †Sensitivity : -57 dB ± 3 dB,
 Dimensions : 21 mm diameter, 82.7 mm long
 Cable : 3 φmm, 1.5 m
 Weight : 3.9 oz (110 g) with cable



DF-3

SPECIFICATIONS
 Impedance : 50 kΩ
 Frequency Response : 50~12,000 c/s ± 8 dB
 †Sensitivity : -56 dB ± 3 dB,
 Dimensions : 33.5 mm diameter, 133 mm long
 Cable : 4 φmm, 1.5 m
 Weight : 9.0 oz (255 g) with cable



DF-12/*DF-12B

SPECIFICATIONS
 Impedance : 50 kΩ
 Frequency Response : 80~12,000 c/s ± 8 dB
 †Sensitivity : -57 dB ± 3 dB,
 Dimensions : 23 mm diameter, 158 mm long
 Cable : 3 φmm, 1.5 m
 Weight : 6.3 oz (180 g) with cable



*DF-2B

SPECIFICATIONS
 Impedance : 50 kΩ
 Frequency Response : 100~10,000 c/s ± 10 dB
 †Sensitivity : -56 dB ± 3 dB,
 Dimensions : 75 × 53 × 30 mm
 Cable : 3 φmm, 1.5 m
 Weight : 4.8 oz (136 g) with cable



*DF-51B

SPECIFICATIONS
 Impedance : 50 kΩ
 Frequency Response : 150~8,000 c/s ± 7 dB
 †Sensitivity : -57 dB ± 3 dB,
 Dimensions : 98 × 58 × 36 mm
 Cable : 6 φmm, 1.6 m, Coiled
 Weight : 7.3 oz (207 g) with cable

* with switch :

† at 1,000 c/s, 0 dB = 1 V/μ bar


(SOLE AGENT)



ZEPHYR PRODUCTS PTY. LTD.

70 BATESFORD ROAD, CHADSTONE, VICTORIA—PHONE 56-7231

MANUFACTURERS OF RADIO & ELECTRICAL EQUIPMENT & COMPONENTS



tube screen is the coil which corrects for any slight misalignment of the aperture plate, which is commonly used on high quality tubes to direct the electron beam leaving the cathode. This coil is separated from the remaining sections of the unit by a blank section, which is followed by two more alignment coils, which deflect the beam along a path directly down the centre of the tube, along the axis of the focus coil unit. The focus coil itself, which is next in line, contains static and dynamic coils carefully layer wound to ensure very accurate focusing. The remaining sections correct for astigmatism arising from the effects of the previous coil units. These are mounted at the end of the assembly, nearest the face of the CRT.

Air-transportable satellite terminals

Complete air-transportable satellite communications terminals are now being manufactured in Britain. The stations are for military use in the Anglo-American Initial Defence Communications Satellite Project. Three stations are already in operation manned by British Service units. The stations can be quickly dismantled into major components for shipment by air. The aerial can be broken down into sub-units which will fit into large military transports. The 65ft high radome which houses the complete station is a double-walled, air-inflatable structure which can be collapsed and stowed in an aircraft. Transmitting, receiving and other equipment are all housed in air-conditioned, thermally insulated containers. The containers are disposed around the central aerial in use, and for flight are unplugged and the door closed on each container.

The station also includes a microelectronic computer which has a number of functions. One of these is to introduce a variable delay in the system to provide a consistent signal as if all satellites were at a range of 25,000 miles, irrespective of the actual range. Another function of the computer is to control the acquisition of new satellites as they appear over the horizon. The initial steering is provided from prediction data fed into the computer by paper tape. The equipment automatically scans until signals are received, when the normal tracking system locks the aerial to the satellite.



Two electronic devices developed in U.K. to help blind people overcome their handicap. Right: an "electronic pen" enables blind people to fill a teapot without overspilling, tell when a baby's bottle is nearly full, judge how much liquid is left in a medicine bottle or glass of beer, pick out ripe from unripe fruit and other similar activities. Various tips are available for different functions—detecting temperature changes, the lights of a car, variations from magnetic north, etc. Above: This ultrasonic "torch" for detecting obstructions in the path of a blind person is now in full production in U.K. Ultrasonic waves are projected in a narrow beam, and are reflected back by obstructions to a receiver in the "torch."

"Seeing" with sound

Electronics experts at the Palo Alto Research Laboratory of the Lockheed Missiles and Space Co. are experimenting with a sub-surface detection system using sound waves. The company's project engineers have conducted research based on the knowledge that sound waves can be directed through murky water at an object and are developing techniques for translating reflected waves into a faithful image of the object. Under the Lockheed system, a stream of sound waves is aimed in a given direction. Sound waves reflected from an object are received, through an acoustical lens, by an image converter which changes the sound waves into electrical impulses for display on a TV screen.

The type of application envisaged for the equipment is exemplified by the incident of the H-bomb lost off the coast of Spain, at Palomares. On that occasion, submersible searching devices stirred up so much mud that boats trying to drag the bomb up had to wait long periods to allow the mud to settle after each pass. Lockheed officials are confident the bomb could have been located and recovered quite quickly had the new search system been available then.

Ultra-modern hospital

A private hospital in U.K. is to be equipped with a widespread closed circuit television system, a comprehensive nurse-call network and computing facilities, says a report in "Electronics Weekly." CCTV in all rooms will be used for entertainment purposes—switching in the broadcast services—and as a two-way vision-communications link between patients, nurses and doctors.

Short-wave radio will be used for audio communication and this will be switched over to a patient monitoring system if very ill patients are to be left unattended. Any change in patient condition such as failing respiration or heart rate, will be transmitted to a "bleep-bleep" system carried by the nurse.

Data processing facilities are planned for the hospital. It is hoped that this will be in the form of a computer installation rather than having to make use of time on another machine. The computer will handle administration, accounting and other statistical work.

Other devices such as a vacuum monorail system for delivering meals and medicines, and electrically adjusted beds, are also envisaged.

Fuel cells in action

Fuel cells are being tested by U.S. forces in Vietnam as a substitute for diesel generators to provide power for communications use. A research scientist of the Shell Oil company in U.K., Mr Keith Williams, said the cells offer silent, portable power for military use. However, they would not be competitive with internal combustion engines for many years.


Fuel cells, regarded by many as the possible source of power for automobiles in the future, convert the energy of a fuel, such as hydrogen, directly into electricity by chemical action. Thus, it dispenses with the intermediate stage requiring fuel to be burnt to power an engine.

Mr Williams said the fuel cell had been a topic of speculation in the automobile industry for some time. However, the petrol engine was far from finished, and developments in petrol refining techniques would reduce the level of pollution from petrol engines to a low level.



NEW-MINISCOPE

THE REMARKABLE ANATOMY OF MINISCOPE...



Look how remarkable Miniscope really is. Faster—easier to handle. Allows easy access to confined areas with minimum risk of damage to miniature components. Remarkably versatile, it can be used for soldering work where the normal 75 watt 240 V. iron is used, or can be used on miniature components where minimum amount of heat is required.

SPEED: Five seconds from cold, thereafter instantaneous. **NO FATIGUE:** Weight only 1 1/4 ozs. complete. **CONVENIENT OPERATION:** Voltage range from 2.5 to 6.3 V. A.C. or D.C. or from 240 V. A.C. mains through a National Scope Transformer. The new model features a slotted nylon centre piece which is unbreakable and allows easy adjustment of switch lever travel.

Price still \$5.28

Only National Transformers are fully approved by manufacturer. Fitted with 6 ft. 3-core flex and 3-pin mains plug. National Scope Transformer \$7.65

AVAILABLE ALL ELECTRICAL TRADE SUPPLY HOUSES AND HARDWARE STORES
THE FULL GUARANTEE APPLIES WHEN IRON IS USED WITH A NATIONAL TRANSFORMER

AUSTRALIAN & OVERSEAS AGENTS:
Wm. J. McLELLAN & CO. PTY. LTD.
THE CRESCENT, KINGSGROVE, N.S.W. 50-0111



VICTORIA:
A. E. E. CAPACITORS PTY. LTD.
202 BELL STREET, PRESTON. 44-0491

TASMANIA: W. P. MARTIN PTY. LTD.
202 Argyle Street, HOBART

N.Z.: H. W. CLARKE (N.Z.) LIMITED
42-46 Cable Street, WELLINGTON, C.3

W. AUSTRALIA: I. W. HOLMAN & CO.
249 James Street, PERTH
QUEENSLAND: K. H. DORE & SONS
505-507 Boundary Street, BRISBANE
ALSO TOWNSVILLE AND ROCKHAMPTON

S. AUSTRALIA: COLLETT & CANT PTY. LTD
103 Halifax Street, ADELAIDE

N.Z.: H. W. CLARKE (N.Z.) LIMITED
10 Teed St., New Market, AUCKLAND, S.E.1

COUPON

Please forward free illustrated literature and specifications

Wm. J. McLellan & Co.
Pty. Ltd.

THE CRESCENT, KINGSGROVE,
N.S.W. 50-0111

Name.....

Address.....

My usual supplier is.....

SCOPE



Airborne computer

A new type of airborne computer said to be lighter, smaller, cheaper and more reliable than any comparable equipment used for navigational computation has been developed in U.K. by the Marconi Company. It will control the navigation of an aircraft to any predetermined point on the face of the earth. The equipment, Type AD670, is completely solid state and substantially microminiaturised. The computer is a Digital Differential Analyser type (D.D.A.) and although it has a wired-in program it can be set for a number of applications such as navigation, and guidance, flight management or weapon aiming.

The D.D.A. type of computer uses about 50 per cent of the logic circuitry and 18 per cent of the memory capacity of a comparable general purpose computer. In the AD670, further savings in space and weight and an even greater reliability are achieved through extensive microminiaturisation. The flexibility of the general purpose type of computer allows changes of program to be made during flight, for example, from a navigation role to a fuel flow management role. However, Marconi's belief that, in practice, once a computer has been programmed for a specific purpose, it will carry out that function for the whole flight and for this a fixed, wired-in program is sufficient. If necessary, the AD670 can be easily re-programmed in the workshop between flights.

Better weather forecasts

Weather information of vital importance to Australia's primary industries, airlines, shipping, tourism, and the private citizen, will soon be processed here by a new twin computer centre. The Commonwealth Bureau of Meteorology will install the central computing facility in Melbourne, where a large IBM computer complex, costing approximately \$4 million, will be linked by a communications system with meteorological data sources and information users throughout Australia and overseas.

The new centre will play an important role in the World Weather Watch, planned by the World Meteorological Organisation in response to a request of the United Nations General Assembly. It will have the responsibilities of a World Weather Centre, together with similar centres in Washington and Moscow, exchanging global weather data and charts.

To help Australia's weathermen in local

weather forecasting, the computers will process, round the clock, data from nearly 1,000 surface reporting stations supplying meteorological observations gathered in the Australian area, the southern hemisphere and the tropical region. Using these data, the computer centre will assist in issuing forecasts — including warnings of weather conditions likely to endanger life and property — plot weather charts, compile lists of selected observations, carry out statistical processing and research calculations including mathematical modelling, and generally apply the latest principles of electronic data processing to the Bureau's principal functions.

Automatic tracking radar

A new radar, the "BEARN," has been developed by the Compagnie Francaise Thomson-Houston at Bagneux, France. The object of this latest French radar is automatic tracking of fast moving craft or missiles whether equipped with radar responders or not. With skin-return echo, its range is claimed to exceed 200 miles for a target moving at 12,000 m.p.h. or about 15 times the speed of sound. Where the object is fitted with a responder, the range exceeds 2,500 miles. The radar will be used to compute the path followed by a missile and locate the exact spot where it will drop.

Modernising banking

Data transmission trials are being conducted by Plessey Automation for an Australian trading bank. The company has installed a medium-speed tape data transmission system to link the bank's head office in the heart of Sydney with one of its suburban branches. The system is designed to allow much more rapid cheque clearing and current account processing than has been available in Australia before. The operation is in the pilot stage and is understood to be one of a number of recent developments in data transmission in Australia.

Considerable growth in data transmission has taken place overseas, particularly in the U.K. and the U.S.A. Modern requirements for rapid transfer of information from one computer to another can necessitate transmission rates up to 200,000 times as fast as the ordinary telegraph system can provide. The Post Office last year advised that it would make lines and connecting equipment available for lease to allow operation of privately-owned data transmission systems.

Robot translators

Pocket-size translating machines were a development of the future suggested by Sir Leon Bagrit, Chairman of Elliott-Automation Limited, in one of his Reith Lectures on "The Age of Automation," broadcast by the B.B.C., in which he surveyed the vast range of computer application.

Although the idea of a complete translat-



A network of VHF radiotelephone stations is used in the W.A. State forests to assist in the spotting and control of forest fires. Many of the stations are situated on spotting towers, as illustrated here, but in some areas radio posts are mounted directly on the giant Karri trees, which often reach a height of more than 200ft. The radio network employs a number of talk-through repeater stations to enable the Perth control centre to talk directly with any one of the widely scattered observation posts and a large fleet of radio-equipped vehicles operating in the thousands of square miles of forest. The radio equipment was supplied by Telecommunication Company of Australia Pty. Ltd.

ing machine might sound a little fantastic at the moment, Sir Leon said: "We have already at our disposal means of converting human vocal sounds into numerical symbols. We also have some knowledge of how to convert numerical symbols into vocal sounds, so the time is not far away when the computer will be able to recognise the pattern of speech and to reproduce artificially a human voice. Once this stage is reached we shall be able to speak into a computer and get the sound translated into electronic symbols."

These symbols would not necessarily repeat the sound in English. They could repeat it in any other foreign language with which the sounds could be made compatible. So that it is quite reasonable to conceive a personal miniaturised translating machine which you would carry in your pocket and which would allow you to talk to a Chinese in English and allow him to reply in Chinese. But you would hear his reply in English. There would be limitations no doubt for a long time to come in the kind of vocabulary available and its size, and there would probably be technical hitches of various kinds, until perfection was ultimately reached."




Light screens have been installed at the Rolls-Royce plant in U.K. which enable engineers to communicate directly with computers. By using a light pen on the screen, an engineer can convey design information to a computer which then undertakes the stressing analysis and detailed design of engine components.

Grundig world-range radios

TR5000

The Grundig name has become a legend for quality in radio sound. And with radios like the extraordinary Grundig Satellit, it's no wonder! You can be an eavesdropper on the world. Two Superphon dynamic loudspeakers give you world-wide reception on thirteen wavebands—with an unbelievable depth and clarity of sound. Short wave, FM, bandspread, too! The Satellit TR5000 is designed to operate on batteries or AC mains, and receives VHF/FM, long, medium and short wavebands. The short wave coverage ranges from 10 to 187 m., split into four bands.



Additionally, six bandspread short wave ranges are provided, shown on a separate scale with a rotating drum selector. The Satellit is fitted with 17 transistors and 11 diodes. It features a short wave fine tuning dial, automatic frequency control on FM, R.F. stage, a switchable ferrite aerial, a double extension telescopic aerial, a separate control for the bandspread short wave tuner, duplex drive on FM/AM, a tuning and battery indicator, and two multi-octave loudspeakers. The Satellit also has an illuminated tuning scale and separate bass and treble controls. Sockets are provided for headphones, external aerial and earth, car aerial, record player, tape recorder and external battery power supply.

The Satellit transistor 5000 has a handsome padded graphite case with chrome and satin silver trim. It measures 16" x 10" x 4 3/4".



TR3000

The Ocean Boy TR3000 is not just a transistor radio, it is a perfect piece of precision engineering. The whole world's your oyster with the Grundig TR3000. Choose a wavelength by pressing one of the nine buttons and using the fine tuning control. See visually when you are at the point of best reception by the tuning indicator (which doubles as battery indicator). Adjust the bass and treble tone controls and you're hearing a radio that's built for listening to, not straining at. The Ocean Boy has two loudspeakers, 13 transistors, 8 diodes and 2 rectifiers. Provides matchless listening on VHF/FM, long, medium and 4 short wavebands (10 to 185 m.). Output is up to 2 watts (R.M.S.).



GRUNDIG SALES & SERVICE

By Goldring Engineering (A'sia) Pty. Ltd.

N.S.W.: 443 Kent St., Sydney 29-1275/6/7
VIC.: 368 Little Bourke St., Melbourne 67-1197
W.A.: 91 Hay St., Subiaco, Perth 8-4988/9
QLD.: King & King, 77 Queen St., Brisbane .. 2-3711
S.A.: 77 Wright St., Adelaide 51-5117

GEP344R

GRUNDIG . . . the world's largest manufacturer of tape recorders . . . stereograms . . . and dictating machines.




D.C.A. training aid

A Solartron radar simulator has been delivered to the D.C.A. Melbourne Training Facility for use in training future Air Traffic Controllers. The simulator provides 24 synthetic aircraft, each controlled by a "pilot" operating an aircraft control panel. The equipment works with normal radar PPI displays as used by D.C.A., so trainee controllers see realistic aircraft "paints" on their displays.

The heart of the equipment is a computer which continuously calculates the three-dimensional position of each aircraft simultaneously, in response to the speed, rate of climb, rate of turn and other signals

Electronic sandals for measuring loads on the feet have been developed in U.K. In orthopaedics, there is a need for quantitative data on the degree of incapacitation in patients suffering from arthritic hips, and because direct hip-load measurements are impractical foot loading has been substituted. The device operates by translating pressure on the sole to a voltage reading which is recorded on a paper roll by a pen recorder each time the patient takes a step.



fed to it by the aircraft control panels. "Exercise freeze" facilities are provided so that any particular traffic control situation can be held for analysis by instructional staff. The equipment incorporates the operating parameters for the present and future generations of aircraft, including the supersonic types to be introduced in the coming years.

Portable welding transformer

A portable air-cooled transformer for light-medium and medium-heavy ferrous arc welding and brazing is now being produced in U.K. for machinery maintenance on shop floors, for the repair of agricultural implements and for site work generally. The transformer, which is cooled by induced air flow, is housed in a cabinet of 1/8 in steel plate welded throughout and mounted on four castors. This is a single-phase machine which can be adapted for operation on one or two phases of a three-phase supply. The maximum welding current that can be used is 180 amps; the minimum 35 amps. The manufacturers are Ferrous Transformers Ltd., Church Road, Croydon, Surrey.

Versatile scintillation counter

A device, the M.K. II Universal Scintillation Counter, which can be adjusted to suit a great many routine radio-isotope tests employing Gamma-emitting isotopes such as I-131, Fe-59, Cr-51, Ca-47, Xe-133, has been developed by E. R. D. Engineering Co. Ltd., Kelpatrick Road, Cippenham, Slough, Bucks, U.K. When testing liquid samples, the assembly of the device need be only slightly altered to change from the assay, for example, of blood samples having a volume of 5-10mL, to the counting of large specimens (e.g., 24-hour urine collec-

tions in 2-litre bottle). Three basic arrangements can be made to suit different types of "in-vivo" counting, i.e., with live subjects. The first arrangement would suit, for example, liver function tests; the second, radiocardiography in adults; the third, radiocardiography in children and experimental animals.

Saving computer time

A new computer language that will cut time spent in technical information searches from hours or days down to minutes—or even seconds—has been developed by the Lockheed Missiles and Space Company. Completion of the new information retrieval language, known as DIALOG, was announced by the firm's Information Sciences group at the L.M.S.C. Palo Alto Research Laboratory in California. Lockheed's new language is an outgrowth of the need to provide quick access to literally millions of technical papers and files accumulated over the years by scientists and engineers—particularly in the aerospace industry.

Technical librarians in industries through-

out the United States spend thousands of hours annually combing indices for references to technical information required by scientists and engineers. But using DIALOG, the same librarians could query a computer system—in layman's terms—and receive the references they need in a matter of minutes.

More CCTV for R.N.

Marconi television systems will be used for flight deck surveillance on all British aircraft-carriers, following orders placed by the U.K. Ministry of Defence (Navy). H.M.S. Eagle and H.M.S. Ark Royal are the last R.N. aircraft carriers to be fitted, making a total of 30 British and U.S. aircraft carriers now equipped with Marconi closed circuit systems.

The two British ships will each have a single closed-circuit television channel with the camera mounted on the carrier superstructure. The lens angle and direction of this can be adjusted by remote control from the control tower, where a television monitor displays pictures of the flight deck.

Inexpensive but accurate

Low priced decade capacitor boxes having accuracies exact enough for most applications involving test equipment, timing circuits and electric wave filters, in addition to the conventional radio frequency and audio-frequency applications, have been developed by Lionmount & Co. Ltd., Bellevue Road, New Southgate, London, N.11. There are six standard units which together cover the range of electro-static capacitance from 9pF to 111uF and incorporate capacitors of silvered mica or plastic having low power factors and high insulation resistance. Ceramic wafer switches are used to keep leakage and losses to a minimum.

GARRARD'S CUEING

... the most wanted feature on record player units today ... a revolutionary development! The Garrard cueing controls eliminate the danger of accidental damage to records or stylus through manual handling; work three ways:

1. To lower the tone arm gently to the record without manual handling.
2. To pause (and then continue when ready) during single or automatic play.
3. To locate any record groove accurately and safely.

Built-in cueing controls are featured on three of Garrard's new automatic turntables:



These are only three of the wide Garrard range. For full particulars write to:—**United Radio Distributors Pty. Ltd.** Shop 32, Ash St., Angel Arcade, Sydney. Telephone 28.3718, 28.3926. Open Saturday morning.



The S meter and the knobs for AM-SSB, BFO and S meter Zero are not to be used at this stage.

The circuit opposite has been kept as simple, yet efficient as possible and should be easy to get going.

THE 67 ALL-WAVE THREE RECEIVER

In the June issue we presented the "67 All-Wave-Two," which we hoped would be the forerunner of a progressive series of all-wave receivers. The next step, the "67 All-Wave Three," is presented in this article. Unlike the All-Wave-Two, this one is a superheterodyne in about its simplest form and stripped of most refinements. It is planned to add to this unit in subsequent articles.

By Ian Pogson

Before proceeding with a description of this receiver, perhaps a few words of explanation would be in order, as to what we have in mind.

The plan is to finish up with a receiver having six valves in all. Planned line-up is a 6BL8 first mixer and oscillator, a 6BE6 amplifier and converter, 2 x 6EH7 IF amplifiers, with back-to-back IF transformers, a 6BE6 product detector and BFO and a 6GW8 audio amplifier. An S-meter is also incorporated in the complete receiver. This is the plan and it is possible that there may be modifications in the process of development, but it will indicate the direction in which we are heading.

Having decided on the general plan, it was then decided to lay out a chassis and front panel to suit a six valve receiver. Then we took a careful look at the proposed circuit for the six valve receiver and started to prune it down to the bare essentials. The result is the 67 All-Wave-Three, as featured here.

As will be apparent from the chassis photographs, the three valve receiver is built on the chassis and front panel which will ultimately accommodate the six valve receiver, and this leaves a number of unused holes on the chassis and panel. Our next proposed move is to provide double conversion for the two higher frequency bands, leaving the broadcast and the first short-wave band operating with single conversion. Having

added the valve and other components for this addition, we then will have the "67 All-Wave-Four."

After this move, the next logical step appears to be the addition of a product detector and BFO, using one extra valve. This will allow the reception of Morse Code and SSB signals.

Finally, we proposed to add an extra IF amplifier stage. This move will be accompanied by the addition of back-to-back IF transformers, to improve selectivity as well as gain. Somewhere along the line, an S-meter will be added. The final design should be capable of quite a high degree of performance and should satisfy most short-wave listeners.

The reasoning behind this approach to a series of receivers, is that one may start off with the three valve version and add to it as time goes on. This can be done as required and it is virtually just a matter of adding the extra parts, with possible minor alterations to adapt to the new arrangement.

There is another advantage: The arrangement is so flexible that you may build up the receiver with the combination of facilities which may best suit your needs, leaving out any which you consider superfluous. For instance, if you are not interested in SSB reception, or Morse Code, you could leave out the product detector and BFO. On the other hand, you may wish to have an S-meter on only the four valve version. In short,

you may "roll your own" just to your liking.

An alternative to the idea of using a common chassis and panel for the series, would be to have a separate chassis and panel for each receiver. We ruled this out, since it permits very little flexibility. Furthermore, manufacturers and stockists of metalwork would have to carry extra stock, which is uneconomical and reflected in the final cost.

Having outlined our plans, we can turn our attention to the circuit of the three valve version. The first stage uses a 6BL8, the pentode section as the mixer, with the triode section for the local oscillator. There are four sets of switched coils, covering the range fully, from the broadcast band to 30MHz. More will be said about the coils and switching a little later on.

The mixer-oscillator converts the incoming signal to an IF of 455KHz. This is passed through the first IF transformer, to the 6EH7 IF amplifier. The amplified signal then passes through the second IF transformer to an OA91 or similar diode detector. Included in the detector circuit, is a simple series type noise limiter, which is left permanently in circuit.

The recovered audio from the detector then passes on the audio stages via a 500K volume control. The audio amplifier is quite conventional, using a 6GW8 triode pentode. The output transformer is such that it provides a 7000 ohm load to the output stage, when operating into the correct voice coil impedance.

Automatic gain control is derived from the plate circuit of the 6EH7 IF amplifier. AGC is then fed back to the control grids of the 6EH7 and the 6BL8 pentode section. The RF gain control is closely associated with the AGC system.

The power supply is a voltage doubler type, which is in common use these days. This is followed by an inductance-capacitance filter. A "back bias" arrange-

Having covered the circuit in broad outline, let us now have a look at the details. Perhaps one of the most difficult problems to solve in a full coverage receiver of this type, is the question as to what coils to use and needless to say, we had to face this one. Fortunately, just at the right time, Aegis Pty. Ltd., of Melbourne came up with a novel idea and which appeared to be worth investigating.

Basically, the idea is what could be called "instant short-wave coils." Three different sizes of coils are ready wound, each including a primary and secondary winding. The start of each winding is soldered to its terminating lug. More than enough turns are wound on the former and the two finishes are loosely terminated on the appropriate lugs. The idea is to wind off the turns which are not needed and then terminate the ends, resulting in the required coil.


These basic coils can be modified so that they become an "aerial" coil, an "Rf" coil, or an "oscillator" coil, according to the need at hand. The three different sizes of coils differ from each other in that they have a graduated number of turns. This permits the use of the right basic coil for the frequency range to be covered. This selection makes it possible to provide suitable coils for all functions that will cover from about 1.5MHz to 30MHz.

Physically, the coil assembly consists of several parts: (1) An inner tube, which is in fact a 7mm former, with a tuning slug, with a spire clip at one end for mounting to the chassis; (2) An outer polystyrene former, $\frac{1}{4}$ in diameter and 1in long, which has the actual coils wound on it; (3) A collar, with four lugs for terminations, fitted to one end of the coil former. This collar in turn, is a push fit over the inner tube, resulting in a neat assembly. Elsewhere in this issue is an article which deals at some length with these coils and their application.

The coil switching involves the use of three switch banks. The bank at each end of the assembly is a 2-pole, 4-position, with a common shorting plate. The centre bank is a 2-pole, 4-position, without shorting plate. The bank nearest the clicker plate switches the primary and secondary of the aerial coils. The bank at the other end switches the primary and secondary of the oscillator coil. One pole of the centre bank is used as an auxiliary switch for the grid circuit of the aerial coil. The other pole of this section will be used when the receiver is made into a double conversion unit.

The shorting plates are necessary to avoid unwanted coupling between coils, with consequent "suckout" and degradation of performance. The shorting plate for the aerial coils is connected to earth, but the shorting plate for the oscillator coils must be left floating, otherwise the oscillator HT supply would be shorted to earth. The auxiliary switching in the signal grid circuit is needed because capacitors are introduced in series with the tuning capacitor, on the short-wave bands, to limit the coverage of each range.

Small capacitors of 3.3 and 4.7pF are used on all ranges except the highest frequency range. These capacitors are needed to give the right amount of oscillator injection into the mixer grid. There is sufficient injection on the



KIKUSUI

MODEL 539

- 5Hz to 1MHz • 3" 'SCOPE
- COMPACT • PORTABLE

SPECIFICATIONS

Y AMPLIFIER: Attenuator: Steps, .1 and .02 (Frequency Compensated)
Sensitivity: Better than 1 Volt p-p/cm.
Response: 5 c/s to 1 Mc/s within -3db.
Input Z: 1 Megohm shunted by 20pF max.
X AMPLIFIER: Sensitivity: Better than 3V p-p/cm.
Response: 1.5 c/s to 400 Kc/s within -3db.
Input Z: 2.2 Megohms approx. shunted by 60pF max.
TIME BASE: Freq.: 10-100 c/s; 100 c/s—1 Kc/s; 1 Kc/s-10 Kc/s;
10 c/s-10 Kc/s. Continuously Variable.
POWER SUPPLY: 240V: 50/60 c/s: 36VA approximately.
DIMENSIONS: 4 1/4 in x 7 1/4 in x 13 5/8 in.
WEIGHT: 11 pounds.

PRICE: \$110 plus 12 1/2% SALES TAX. FIS all State capital cities.



KEW

MODEL K-142 VT VM

- EASY-TO-READ 6" SCALE
- SIMPLE TO USE
- RELIABLE

SPECIFICATIONS

DC Volts: 0 to 1,500V FSD in 7 ranges (15KV or 30KV, using HV probe).
AC Volts: 0 to 1,500V FSD (sine-wave) in 7 ranges (Peak to Peak) 0 to 4000V in 7 ranges.
Resistance: 0-1000 Megohms in 7 ranges.
Input R: DCV 11 Megohms (1 Megohm in probe).
Accuracy: DCV 3 p.c. ACV 5 p.c., Ohms 3 p.c. FSD.
Decibels: -20 to +65dB.
Response: Zero Centre for adjusting FM detectors.
Plus or minus 3 p.c. 50Hz to 500KHz (AF/RF); Plus or minus 5 p.c. 30 Hz to 1.5MHz; 10 p.c. 15Hz to 10MHz.
Meter: 0 to 195uA DC.
Size: 7 1/2 in x 6 3/4 in x 4 1-8 in.
Weight: 4.5 pounds.

PRICE \$51 (Probes extra).



KEW

MODEL K-140 MULTITESTER

- 27 RANGE
- ELEGANT
- RUGGED

SPECIFICATIONS

DC Volts: 0 to 5000V in 8 ranges.
Input R: 20,000 Ohms. Load 50uA FSD.
Accuracy: Better than plus or minus 3 p.c. FSD.
DC Current: 0-10 Amps in 6 ranges.
Accuracy: Better than plus or minus 3 p.c.
AC Volts: 0 to 5000V in 8 ranges.
Input B: 5000 Ohms. Load 200uA FSD.
Resistance: 0 to 20 Megohms in 3 ranges.
Battery: 7.5 Volts.
Decibels: -20 to +50 in 4 ranges (Odb equals 1mW in 600 ohms).
Frequency: 10 Hz to 100 KHz (2.5V, 10V and 50V).
Response: Error plus or minus 0.5 db FSD.
Size: 7 1/2 in x 6 3/4 in x 4 1/2 in.
Weight: 3.3 pounds.

PRICE \$42.00



JACOBY, MITCHELL & Co. Pty. Ltd.
469-475 KENT STREET, SYDNEY (26-2651)



BRANCHES:

MELBOURNE:
15 ABBOTSFORD ST.,
NTN. MELBOURNE.
(30-2491-2)


ADELAIDE:
652 SOUTH ROAD,
GLANDORE. (53-6117)

BRISBANE:
56-74 EDWARD ST.
(20-535)

PERTH:
C. F. LIDDELOW & CO.,
252 WILLIAM ST.,
PERTH. (28-1102)

AGENTS:

TASMANIA:
K. W. McCULLOCH P./L.
P.O. BOX 606G,
LAUNCESTON. (2-3323)



This top view will serve to identify most of the major components. Note the vacant holes for future enlargement into a receiver with additional facilities and improved performance. These additions will be easy to make.

highest frequency range, via stray capacitance.

The pentode section of the 6BL8 is operated in a conventional manner as a mixer. It is a highly efficient mixer and is less noisy than the more conventional pentagrid mixers. This is important to us, as we are not using an RF stage, in the interests of economy.

The IF amplifier is relatively conventional. However, two points are worth noting. In common with the mixer, the cathode is connected directly to earth, obviating the need for both a resistor and bypass capacitor. In addition, by making a short, direct connection to earth, the likelihood of instability is reduced. Bias is obtained by another method and will be dealt with shortly. We have introduced a small amount of positive feedback, from plate to grid of the IF amplifier. This is strictly controlled and is not sufficient to make the stage oscillate. However, by introducing a judicious amount of feedback, it is possible to increase the gain and improve the selectivity—both important matters in such a simple receiver.

The feedback is shown as a dotted capacitor in the circuit diagram. The "capacitor" consists simply of a piece of hookup wire, about 14in long. One end of the wire is soldered to the plate lug of the socket. The wire is bent over the centre shield of the socket and "looks" at the grid lug. The wire is bent and moved close enough to the grid lug so that the requisite amount of feedback is obtained. This adjustment will be covered in the alignment details.

IF signal is taken from the plate of the IF amplifier and rectified for AGC. Taking the signal from the plate, rather than from the grid connection of the following IF transformer, gives a superior AGC characteristic. The AGC voltage developed is fed back into the control grid of both the IF amplifier and the mixer.

It will be noted that the AGC voltage to the mixer grid is "gated" through a BA100 silicon diode. This is necessary to prevent any negative voltage, which appears on the mixer grid, as a result of oscillator injection, from being fed back into the AGC line.

The AGC load resistor, instead of being returned to earth, is taken to the rotor of the IF gain control. One end of this control is taken to the -11 volts from the back-bias resistor in the power supply. The other end of the gain control is connected to earth, via a 2.7K resistor. At the junction of this resistor and the gain control, is about -2.2 volts. With the gain control at maximum and the rotor at this end of the potentiometer, this minimum voltage is fed into the AGC line and so acts as bias for the mixer and the IF amplifier. Moving the rotor of the IF gain control toward the other end progressively feeds a higher negative voltage into the AGC line and so acts as a manual gain control.

This type of manual gain control was used in the Deltahet receiver and it is a very effective method, particularly when an S-meter is used on the receiver. It is possible to introduce a certain amount of manual control on a signal, without affecting the S-meter reading. More will be said about this in a later article.

The power supply needs a certain amount of explanation. The transformer which we used is an A and R, type 2062. This is rated at 80mA and has secondary voltage taps at 115 and 105 volts. We used the 105 volt tap, which gives the voltages as shown on the circuit.

The two 50uF voltage doubler capacitors which we used are only rated at 150 volts working. Using the 105 volt tap on the transformer, these capacitors are run just inside their ratings and the rating is quite in order.

An alternative transformer which is

also suitable is the Ferguson type PVD100, also rated at 80mA. The secondary voltages on this transformer are 120, 110 and 100. Either the 100 volt or the 110 volt taps may be used. However, a word of caution is needed if you select the 110 volt tap. This will result in a voltage across the 50uF voltage doubler capacitors which exceeds 150 volts. In these circumstances, capacitors of a higher voltage rating, such as 200 volts working, will be required.

No doubt you will be wondering why a transformer rated at 80mA has been specified, when it is obvious that the drain is well below this figure. Firstly, 80mA is the lowest rating of voltage doubler transformer which is readily available. Secondly, when extra valves are added in the future, extra current drain will be imposed on the power supply.

The filter choke specified is also capable of a higher current than necessary. Again, this is a small unit and is readily available. Before leaving the power supply, we have brought the heater and HT supply to a miniature 4-pin socket on the rear skirt of the chassis. This may be used for ancillary equipment, such as a converter.

So much for the circuit details. Now we can turn our attention to the mechanical details. The photographs show clearly how the unit is constructed. The chassis measures 12in x 9in x 2in, with a front panel measuring 13in x 7in.

There are many vacant holes in the chassis, on this version of the receiver and we have deliberately left them that way. This highlights the space that has been provided for expansion into a larger version if and when required. On the other hand, we have filled up the holes on the front panel which are not being used at present. The holes referred to, are for the AM-SSB switch, BFO adjustment, S-Meter and S-Meter

CALLING ALL PROSPECTIVE AMATEURS

The Wireless Institute of Australia was established in 1922 to further the interest of Amateur Radio. With over 45 years experience, who could be more experienced in the teaching of this subject?

We are a non-profit making Organisation. Correspondence Courses are available at any time. Personal Classes commence in February of each year.

For further information write to:

**THE COURSE SUPERVISOR, W.I.A.,
14 Atchison Street,
CROWS NEST, N.S.W.**

LOTS OF EXTRA MONEY

How can you get it part or full time whether man or woman, between 18 and 58, in city or country. For Guaranteed Real Money Making information plus a Special **FREE PREMIUM**, send stamp **TODAY**. No obligation, no strings attached.

Dept. RH.37, Box 5076, G.P.O., SYDNEY

FERGUSON**MATSUNAGA****FERGUSON TRANSFORMERS***Proudly Present*

VARIABLE Voltage Transformers

By
MATSUNAGA



Portable Model

FEATURES INCLUDE:

- TROUBLE FREE BRUSH GEAR
- SMOOTH CONTROL, LINEAR THROUGHOUT 320 DEG. ROTATION
- TOROIDALLY WOUND
- ACCURATELY CALIBRATED DIRECT READING DIAL
- HIGH EFFICIENCY — LOW NO LOAD LOSS
- GOOD REGULATION
- RUGGED CONSTRUCTION
- INDIVIDUALLY TESTED AND PACKAGED

Also available from stock are types suitable for 415 volt 50 C.P.S. single or three phase operation — manual or motorised control.

SPECIAL TYPES MADE TO ORDER

TYPES LISTED BELOW ARE SUITABLE FOR 240 VOLT 50 C.P.S. INPUT: 0 - 280 VOLTS OUTPUT

STAND TYPE: Also available in panel mounting

MODEL	WATTS	AMPS.
SD280.8	200	0.8
SD281.25	300	1.25
SD282.1	500	2.1
SD285	1,000	5
SD288.2	2,000	8.2
SD2812.5	3,000	12.5
SD2816.6	4,000	16.6
SD2820.1	5,000	20.1
SD2825.06	6,000	25.06
SD2829.19	7,000	29.19
SD2833.36	8,000	33.36
SD2841.70	10,000	41.7

MINIATURE TYPE: PH—panel type; SD—stand type

MODEL	WATTS	AMPS.
PH280.5	50	0.25
PH281	100	0.5
PH281.5	150	0.72
SD280.5	50	0.25
SD281	100	0.5
SD281.5	150	0.72

PORTABLE TYPE: With fuse, voltmeter, etc.

MODEL	WATTS	AMPS.
C282.1	500	2.1
C285	1,000	5.0
C288.2	2,000	8.2

ADELAIDE: Wm T. Matthew: 23-6202

BRISBANE: Keith Percy and Co.: 51-5461

CANBERRA: Errol Nazer. 9-0325

MELBOURNE: A. H. Nicholls: 42-6897

PERTH: Athol M. Hill: 21-7861

HOBART: Associated Agencies 2-1843

LAUNCESTON: Associated Agencies: 2-1317

FERGUSON

TRANSFORMERS PTY. LTD.

331 HIGH STREET, CHATSWOOD, NSW 40-0261

FREE


CATALOGUE

PLEASE SEND A FERGUSON CATALOGUE TO:

NAME

ADDRESS

E.A. 8/67



The disposition of the coils, trimmers and switch can be seen with relation to each other. The aerial coils are nearest the front skirt, with the oscillator coils near the centre. The highest frequency coils are to the right of the switch, with the next range on the other side.

Zero. This has been done to give an idea of the appearance of the full-size receiver. Individual builders may leave the holes open at this stage.

The chassis and panel layouts have been worked out so that an efficient arrangement was achieved, together with a pleasing appearance and ease of operation. The most vital part of the layout concerns the coils and the switch, in relation to each other and to other closely associated components. Cramping has been avoided and there should be no difficulty in duplicating the original.

The wave-change switch is mounted on a special bracket and it is fixed to the chassis with the same two screws which fix the front foot of the tuning capacitor. With this arrangement, it will be noted that the hole in the bracket for the switch bush is off centre with respect to the bracket.


Following on from the coils and the 6BL8 mixer-oscillator, the IF strip is immediately behind. In the same line, is the detector and noise limiter wiring and this feeds across towards one back corner, to the audio amplifier and the output transformer. The power supply, both above and below chassis, occupies the rest of the space along the rear of the chassis.

Care has been taken with the three-valve version, so that all major components will stay in their present posi-

tions, even when all the extra facilities and stages have been added. Thus, the various switched coils of the front end, the audio circuits and the power supply, will remain in the same positions and substantially as they are at present.

The detector and noise limiter will not be changed. However, although the 6EH7 IF amplifier will also remain in its present position, it will become the second IF amplifier. At the present time, there is a relatively long lead from the plate of the 6BL8 mixer, to the IF transformer which couples into the IF amplifier. This lead, which is shielded for stability reasons, will be considerably shortened in later versions.

SHORT WAVE COIL TERMINATIONS VIEWED FROM ABOVE



This diagram of the coil terminations should be carefully followed, in relation to the circuit. This applies particularly to the oscillator coils.

One vital part of the "mechanics" has not been touched on so far. We refer to the dial. This is a never-ending problem but we were faced with the same sort of need when we developed the SSB Transmitter. The dial which we made up for that project turned out to be very satisfactory and so we were encouraged to adopt a similar approach for this receiver. The main difference between the two dials is that this one is somewhat larger.

The basic movement is the planetary dual-ratio unit, made by Jackson Bros., and distributed in Australia by Messrs Watkin Wynne. A backing plate, 6 5/16-in x 3 1/4-in, was made from 16-gauge aluminium sheet.

The dial scale is the same size as the backing plate and in our case, we used a piece of Formica board, which is about 1/16-in thick; one face is finished in matt white. All lines are drawn in, using drawing instruments and Indian ink. Photographic reproductions of the scale will be available through the Information Service, at 50c each. The alternative is to do the whole job yourself, along with the calibration, which will be discussed later.

An escutcheon adds an appropriate finishing touch to the assembly and we made one up from another piece of 16-gauge aluminium. The outside dimensions are the same as the backing plate. The inside dimensions are 5 11/16 x 3 1/8-in. These latter dimensions correspond with the cut-out in the front panel, with four mounting holes also corresponding with holes in the front panel and backing plate. The escutcheon was given a coat of glossy black enamel

ADCOLA

"M" SERIES PRECISION SOLDERING & DE-SOLDERING TOOLS

"The soldered joint is the link between components in the most scientifically designed and developed apparatus the world has ever known. One faulty joint can upset the functioning of the apparatus."


"The first important decision in Radio or Electronics is the careful selection of a Precision Soldering Tool."



M20 1 OZ. 1/8" DIA. TIP:

FOUR "TRICLAD" TIP SIZES


MICRO MINIATURE ELECTRONICS
6 volt, 12 volt, 24 volt, 32 volt, AC/DC



M64 3 1/2 OZS. 3/16" DIA. TIP:

FOUR "TRICLAD" TIP SIZES

RADIO AND TV ASSEMBLY AND
SERVICING
230-250 volt and all lower voltage
ranges AC/DC



M207 4 OZS. 1/4" DIA. TIP:

TWELVE "TRICLAD" TIP SIZES

RADIO AND TV SOLDERING AND DE-
SOLDERING
230-250 volt and all lower voltage
ranges AC/DC

PRECISION MADE
THOROUGHLY TESTED
ACCURATELY CALIBRATED
EASILY APPLIED
EFFICIENT AND RELIABLE
CORRECT TIP TEMPERATURE
RIGHT TIP SIZE AND SHAPE
LIGHT WEIGHT
FINE BALANCE
FINGERTIP GRIP
SLIM BARREL
CONSTANT OPERATION
MAINS VOLTAGE APPROVED
AVAILABLE ALL VOLT RANGES
NO TRANSFORMER NECESSARY
STANDARD IN R.A.N.
STANDARD IN ARMY
STANDARD IN R.A.A.F.
STANDARD IN P.M.G.
STANDARD IN COMPUTER FIRMS
STANDARD IN SPACE TRACKING
AUSTRALIAN MADE
SERVICE IN ALL STATES
QUALITY GUARANTEED

ADCOLA

Available from all Principal Radio and Electrical Components Suppliers

Further information is available from:

N.S.W.: H. Rowe & Co. Pty. Ltd., 512 Punchbowl Road, Lakemba. Tel.: 750-0333

S.A.: F. R. Mayfield Pty. Ltd., 11 Halifax Street, Adelaide. Tel.: 8-4131.

Qld.: T. H. Martin Pty. Ltd., 56-74 Edward Street, Brisbane. Tel.: 2-0555

W.A.: C. L. Sedunary & Co., 126 Brown Street, East Perth. Tel.: 23-2551

ADCOLA PRODUCTS PTY. LIMITED, 12 CHURCHILL STREET, MONT ALBERT,
MELBOURNE. Tel.: 88-4351.

and the results are very pleasing. Although we have not done it, a coat of black paint on the screw heads is another good finishing touch.

So much for the dial assembly, except for the pointer. We solved this one for the transmitter by using a meter pointer. However, these are not readily obtainable and in this case, it is doubtful if it would be possible to get one long enough. And so we got to work and made one out of a piece of 16-gauge copper wire. This is how we did it.

Take a piece of tinned copper wire, about 2½ in long. This is hammered flat, leaving about ¼ in still round at one end. This process calls for a little time and patience. A hammer with a good smooth face and a hard flat surface, such as part of a vyce, are the tools to begin with. Keep hammering, not too hard, until a reasonably flat surface is obtained on one side. Then turn the wire over and proceed to treat it in the same way. Do not worry overmuch, if the flattened wire assumes the shape of a banana. This can be straightened as the job proceeds.

Having done what could reasonably be considered as a good job up to this point, there will be undulations due to uneven hammering. These are removed by carefully filing both flat faces. As this proceeds, careful inspection will dictate what should be done to make the finishing touches. When you are satisfied and the pointer is straight once again, solder the round end to a small solder lug and then give the pointer a coat of black paint. The hole in the lug is used to fix the pointer to the movement, with one of the two screws supplied.

Although we did not fit a sheet of perspex over the dial, some builders may prefer to do so. A piece may be cut to the same outside dimensions as the escutcheon. The perspex may then be interposed between the escutcheon and the front panel.

Assembly of the dial unit is quite simple but it is desirable to do it in a logical sequence. The movement is fixed to the back plate with two screws through the holes adjacent to the 13/16 in hole. The lugs of the movement have to be spaced behind the back plate by about 9/16 in. Suitable brass spacers can be used but this is not really necessary. We simply used brass screws, ¼ in long. Six nuts are then used to give the right amount of spacing. This method has the advantage in that fine adjustments can be made to the spacing.

The backing plate is immediately behind the scale and the distance between the scale face and the back of the panel will need to be between 1/8 in and 3/16 in, according to space desired between the pointer and scale. One nut used as a spacer may be just insufficient and two nuts may give too much spacing. A combination of one nut and one or more washers will give the desired spacing.

Push the four screws through the corners of the escutcheon and include the perspex if used. The screws are then passed through the corresponding holes in the front panel. Run a nut (with the washers) on to each screw. The nuts should not be tightened at this stage. Offer the back plate assembly over the four screws and tighten the nuts. Four more nuts behind the back plate hold the complete dial in place. Screw the pointer to the movement.

PARTS LIST

- 1 Chassis, 12in x 9in x 2in.
- 1 Front Panel, 13in x 7in.
- 1 Cabinet to suit (if required).
- 1 Dual-ratio dial movement (see text for details).
- 1 Switch 2 wafers 2-pole 4-position with shorting plates, 1 wafer 2-pole 4-position.
- 1 Variable capacitor, 2-gang 10-415pF.
- 1 Power transformer, 105-110V 80mA, 6.3V 2.35A.
- 1 Speaker transformer 7K to voice coil.
- 1 Filter choke, 6H 100mA.
- 1 Coil, broadcast aerial.
- 1 Coil, broadcast oscillator.
- 1 Coil, 1.6-5MHz aerial (see text).
- 1 Coil, 1.6-5MHz oscillator (see text).
- 1 Coil 5-14MHz aerial (see text).
- 1 Coil, 5-14MHz oscillator (see text).
- 1 Coil, 14-30MHz aerial (see text).
- 1 Coil, 14-30MHz oscillator (see text).
- 2 IF transformers, 455KHz.
- 2 Valve sockets, 9-pin.
- 1 Valve socket, 7-pin.
- 1 Valve, 6BL8.
- 1 Valve, 6EH7.
- 1 Valve, 6GW8.
- 1 Socket, 2-pin miniature.
- 1 Socket, 4-pin miniature.
- 2 Terminals, one red, one black.
- 1 Potentiometer, 500K log.
- 1 Potentiometer, 10K lin.
- 2 Diodes, EM404-10, OA210, 1N3194.
- 2 Diodes, BA100.
- 1 Diode, OA91, 1N60A.
- 1 8-tag strip, with two mounting feet.
- 2 7-tag strips, with two mounting feet.

- 1 5-tag strip.
- 3 4-tag strips.
- 2 3-tag strips.
- 1 2-tag strip.
- 6 Knobs.

RESISTORS

(½W unless specified)

- | | |
|---------------|--------|
| 2 180 ohms 1W | 1 220K |
| 2 2.2K | 1 820K |
| 2 2.7K | 4 1M |
| 1 10K | 1 2.2M |
| 3 33K 1W | 2 270K |
| 4 47K | 1 470K |
| 1 100K | |

CAPACITORS

- | |
|--|
| 2 3.3pF NPO ceramic. |
| 1 4.7pF NPO, ceramic. |
| 5 100pF plastic. |
| 2 150pF plastic. |
| 1 425pF mica padder. |
| 1 470pF plastic. |
| 1 780pF plastic (two 390pF in parallel). |
| 1 .001uF 160V plastic. |
| 1 .0012uF 160V plastic. |
| 1 .0047uF 400V plastic. |
| 3 .01uF 160V plastic. |
| 1 .01uF 400V plastic. |
| 2 .01uF 400V ceramic. |
| 2 .047uF 160V plastic. |
| 2 .047uF 400V plastic. |
| 1 0.1uF 400V plastic. |
| 1 5uF 3VW electro. |
| 1 8uF 300VW electro. |
| 1 10uF 12VW electro. |
| 1 24uF 300VW electro. |
| 2 50uF 200VW electros. |

SUNDRIES

Power flex and plug, cable clamp, solder lugs, hookup wire, shielded cable, screws, nuts, solder, rubber grommets, etc.

The dial which results, is one which is capable of smooth and fine control over tuning. This can be even improved upon by the simple expedient of using a very large knob, which helps the vernier action. Note that this dial assembly information is placed out of the general assembly sequence, to keep the dial information together.

Before proceeding with the general assembly, it would be a good idea to get the short-wave aerial and oscillator coils ready. We will assume that you have two each of the Aegis types RFT2, RFT5 and RFT10. All the information needed is given in the coil table.

The process is quite easy but just a few pointers may be helpful. When removing turns, particularly with the fine wire, care should be taken to do it gently, to avoid breaking the wire. When the requisite number of turns have been removed, cut off the excess wire and terminate the end by soldering to the appropriate lug. In most cases, there will be sufficient sealing compound on the windings to hold the wire in place. In the case of the RFT10 coils, it is wise to put a dab of cellulose or other adhesive on the coil, to prevent unwinding and general movement of the turns. A diagram shows the terminations which are numbered and this correlates with the circuit diagram.

By tackling the assembly in some logical order, the job is made easier and

quicker. Fit three rubber grommets, one each for the power cord, the filter choke and speaker transformer. The valve sockets should be orientated with the gap pointing in the direction as shown on the underneath picture. A 4-tag strip is mounted under one of the screws for the 6BL8 valve socket. A 5-tag strip is fixed under one of the screws for the 6EH7 valve socket, with a 3-tag strip next to the 6GW8 valve socket.


Mount the tuning gang, together with the switch bracket and put a solder lug under each of the four nuts. Then follow the broadcast aerial and oscillator coils and the IF transformers. Fix a 2-tag strip adjacent to the oscillator coil. Fit the two sockets and two terminals to the back skirt of the chassis.

Mount the power transformer, output transformer and filter choke. Fix a 4-tag strip under one screw of the output transformer. Fix a cable clamp under the power transformer screw, nearest the rubber grommet. Diametrically opposite, fix a 4-tag strip under the power transformer screw. This strip should line up with the strip next to the IF valve socket.



Under each screw holding the filter choke, one foot of a 7-tag strip is fixed. Separate screws are needed for the other ends. An 8 tag strip is mounted between the second IF transformer and the audio amplifier. A 3-tag strip is also needed near the input of the first IF transformer.

The short-wave coils are about all that are left at this stage. They should

*AEGIS




**COILS
CANS
and
FORMERS**



PRE-WOUND SHORT WAVE COILS


covering from 1.5 to 30.0 MHz.



**455 KHz
TRANSISTOR
TYPE I. F.
TRANSFORMERS**

VALVE TYPE I. F. TRANSFORMERS

For the frequencies of
50.58, 455, 1600 KHz.
4 and 107 MHz.



VALVE AND TRANSISTOR TYPE TUNING COILS

For the broadcast
band (530 to 1620
KHz).

WRITE OR 'PHONE FOR PRICE LIST

Available
from all good
radio parts
stores

* Reg. Trade Mark



AEGIS PTY. LTD.

347 DAREBIN ROAD, THORNBURY

49-1017 49-6792

P.O. BOX 49, THORNBURY, VIC.

be carefully placed in the positions as indicated in the picture and with due regard to short leads. The coils are held to the chassis with spire clips; if the metal is too thick to take them, it may be necessary to countersink the holes slightly at the top of the chassis. The countersink should only be deep enough to allow the clip to spring into place.

The components should now be mounted on the front panel. The dial has been dealt with before and the other components need no comment, except that the gain controls are used to fix the panel to the chassis. If you do not fit the AM-SSB switch and the BFO control, it would be wise to fit at least one bush or a dummy control in either of the vacant holes, to stabilise the front panel at this end.

The job of wiring is tackled in the usual way. Terminate the flying leads from the transformers and the filter choke. This gets them out of the way and so makes the deck clear for the rest of the wiring. You will notice in the picture of the under-chassis wiring, that there is a "coil" underneath the power transformer. This is an unused tap on the transformer secondary. The bared end was cut off and the wire coiled up and placed so as not to allow any short circuit.

Run the heater wiring to the three valve sockets and the outlet socket on the back skirt of the chassis. We only earthed one side of the supply at one point, the earth connection being at the outlet socket. If you do not wire in this socket, the supply could be earthed at the 6GW8 valve socket.

Wire up the power supply, audio amplifier, detector and IF amplifier, in that order. The usual care should be taken to keep leads short and make the wiring generally neat. Be careful not to over-heat any of the components while soldering. Liberal use can be made of solder lugs, at strategic points for earth connections. They may also be used as clamps to hold down some of the wiring and so add to the neat appearance.

Before proceeding with the coil and switch wiring, finish off as much of the wiring around the 6BL8 socket as possible. The wiring around the switch should not be rushed. It should be carefully studied so that wires and components are placed in logical order. It can be most annoying to find that you have to remove some of your good work, to fit something that has been forgotten!

The plate lead from pin 6 of the 6BL8, to the first IF transformer, must be run in shielded lead, earthed only at the IF transformer end. Leads to and from the AF gain control are also run in the same type of shielded lead.

We provided earth points for the broadcast band components on lugs under the aerial and oscillator coil mounting screws. Earth points for the 1.6 5.0MHz components are to lugs under the 6BL8 socket screws. Lugs for the 5.0-14MHz components are those under the adjacent nuts for the tuning gang. Finally, the lugs under the other two nuts holding the tuning gang, are used for the earth points of the 14-30MHz range of components.

The trimmers for all the coils are of the Philips concentric type. These should be mounted as firmly as possible in all cases, especially those on the oscillator coils. We connected ours directly to the respective coils, running stout tinned

SHORT-WAVE COIL INFORMATION

1.6-5.0MHz. Use Aegis type No. RFT2.

Aerial: Prim. Remove 30 turns. This leaves 10 turns.
Sec. Remove 18 turns. This leaves 62 turns.
Osc.: Prim. Remove 32 turns. This leaves 8 turns.
Sec. Remove 25 turns. This leaves 55 turns.

5.0-14.0MHz. Use Aegis type No. RFT5.

Aerial: Prim. Remove 7 turns. This leaves 5 turns.
Sec. Remove 2 turns. This leaves 22 turns.
Osc.: Prim. Remove 8 turns. This leaves 4 turns.
Sec. Remove 5 turns. This leaves 19 turns.

14.0-30.0MHz. Use Aegis type No. RFT10.

Aerial: Prim. Remove 5 turns. This leaves 2 turns.
Sec. Remove 4 turns. This leaves 10 turns.
Osc.: Same as for aerial coil.


copper wire to the earth lug where necessary.

Having completed the wiring, make a thorough check and be sure that there are no errors. The usual check for short circuits on the HT line should also be made. Having satisfied yourself that all is in order, switch on and, assuming that there are no signs of distress, it is a good idea to make some voltage checks. The important voltages are given on the circuit diagram.

Assuming that all is well, we can proceed with the alignment. Close the tuning gang fully and set the dial pointer so that it is on the horizontal line of the dial. Set the Band switch to "broadcast." Inject 455KHz from a signal generator into the grid (pin 2) of the 6BL8. Keep

ever, when aligning at frequencies above, say, 5MHz. Care must be taken to ensure that you are on the correct frequency and not on the "image." This can be checked by tuning the signal generator higher in frequency by 910-KHz. If this signal is heard in the receiver, then you are on the correct frequency. If not, you are on the image and you must go back and reset the oscillator slug or trimmer to the correct frequency. This is a characteristic of single conversion receivers when tuned to the higher frequencies. It is avoided by the double conversion technique, which will be dealt with in a later article.

Having completed the alignment, we can improve the sensitivity and selectivity, by introducing a small amount of



This small picture of the prototype dial scale will indicate the coverage and frequency law to be expected.

the generator to the lowest level consistent with sufficient signal. Adjust the four slugs in the IF transformers for maximum audio level. This can be done by ear or more accurately if an output meter is available.

Now set the dial pointer to 600KHz and inject a signal from the generator into the aerial terminal, at this frequency. Adjust the slug in the oscillator coil for maximum response; then adjust the aerial coil slug for maximum. Remember to keep the output from the generator down to a reasonably low level. Now set the dial pointer to say, 1400KHz. Feed a signal in from the generator at this frequency. Adjust the oscillator coil trimmer for maximum response. Repeat for the aerial coil trimmer. Go over this procedure again at 600KHz and touch up the slugs. Then check the trimmers at 1400KHz and make any adjustment that may be needed.

Switch progressively to each of the short wave bands. Set the dial pointer toward the low and high frequency ends of the bands, corresponding approximately with those already used for the broadcast band. Align at these points, using the same techniques as before.

One point should be watched, how-

feedback to the IF amplifier. Take a piece of hookup wire about 14in long and solder one end to the plate, pin 7, of the 6EH7 valve. Now bend the free end over the top of the centre shield spigot of the valve socket, so that it comes within about 3/8in of the grid, pin 2. The amount of feedback can be closely controlled by moving the wire a little closer to, or further away from pin 2. It is possible to make the stage oscillate, but this is not the requirement. Just how close it is adjusted near to oscillation, depends upon personal choice.

You will notice that, as the feedback is increased, the sensitivity and selectivity will be noticeably improved. However, if set too close to oscillation, the performance may be erratic and this should be avoided.

After completing this adjustment, it is wise to check the alignment of the primary of the second IF transformer. At most, it will only need a touch. And so the project is complete as far as the three valve version is concerned. Whether you intend to add to it later on or not, you will have a lot of fun with this receiver. Next month, we hope to describe a four valve double-conversion unit.

KEEP THE RECORD STRAIGHT

Do you have a lot of information that has to be collected daily? — production statistics, library records, spare parts and inventory control, time sheets, etc.

Are you doing this economically and efficiently? Up to now perhaps you haven't been able to afford it at all. Have you thought of doing this job automatically?


We have a whole range of data acquisition equipment that will do this job for you — quickly, efficiently and economically. You can collect the data on your premises for as little as \$45 a week, and then have it processed at a Data Centre.

CONTROL DATA
AUSTRALIA PTY LIMITED

598 St. Kilda Road,
Melbourne
Telephone 51-1321

What's new


FISHER gives you the ultimate in HI-FI performance (everything from speakers to amplifiers!)



FISHER XP-7 SPEAKER

The new Fisher XP-7 at \$198 is ranked among the very finest bookshelf speaker systems by all the experts who have heard it and tested it. It offers the kind of performance that critical audiophiles demand of loudspeakers costing twice as much—and more. The highs are remarkably smooth, widely dispersed and peak-free, thanks to the unique Fisher soft-dome tweeter. Two specially designed 5-inch cone drivers carry more than three octaves of the mid-range, resulting in a much more natural sound than is possible with a narrow-band approach to mid-range design. The heavy 12-inch woofer goes all the way down to 30 cps without doubling.

Complete range of FISHER amplifiers from **\$240.00**
FISHER speakers from **\$86.00**



Fill out and mail this coupon for your free copies of RCA, Fisher and Elac literature, available to readers of this magazine without charge. Whether or not you know a great deal about high fidelity and stereo, you will find these invaluable in making buying decisions.

TO RCA OF AUSTRALIA PTY. LTD.
SYDNEY: 219 Elizabeth St. 61-8541
MELBOURNE: 2 Stephenson St.,
Richmond, 42-4586
BRISBANE: 173 Ann Street, 2-7884
ADELAIDE: 99 Currie St. 51-7870
PERTH: 280 Stirling Street, 28-5057

Return to
your nearest
RCA distributor

NAME.....
ADDRESS.....

Tick which required ☐ Fisher ☐ Elac. ☐ RCA

X-101-D 66-WATT STEREO CONTROL AMPLIFIER \$296

If you buy your speaker systems on looks . . . look at Fisher.

Sixty-six watts of music power (IHF), more than enough to drive the most inefficient of speaker systems to glorious volume.

Controls: Input Selector (Tape Head, Phone, Tuner, Auxiliary and Tape Play positions); Mode Selector (Mono, Stereo and Reverse positions); Left/Right Bass (concentric) Balance; Volume (including A.C. off).

Switches: Equalisation (Tape/Phone); High Filter (on/off); Speakers (on/off); Tape Monitor (on/off); Loudness Contour (on/off).

in HI-FI ?

New!




HIGH FIDELITY STEREOPHONIC MUSIC SYSTEM

RCA's new 'Stereo 10' has been completely designed in Australia for Australian Hi-Fi music lovers by craftsmen engineers experienced in professional equipment for Stereo and Mono reproduction. From the sound of a single note through to a full crescendo, this unit is virtually distortion-free, producing a magnificent, full-bodied tone through twin amplifiers.

The fully matched and integrated system provides the finest musical achievements with big sound reproduction from unobtrusive units. Each of the two bookshelf speakers has its own tweeter and powerful main speaker and will stand vertically or horizontally (even the famous RCA symbol is adjustable to suit either position). \$292.

- Music Power Output: 7.5 watts per channel at 5% distortion. 5.5 watts per channel at 0.5% distortion.
- RMS Power Output: 5 watts per channel at 5% distortion. 3.5 watts per channel at 0.5% distortion.
- Frequency Response—Amplifier: Within 1 db—35 cycles to 15 kc. Within 3 db—24 cycles to 20 kc.
- Hum and Noise (below rated output): —60 db.
- Amplifier Sensitivity: 0.55 volts RMS for full output.
- Treble Control: ± 15 db boost.
- Bass Control: ± 15 db boost.
- Amplifier Type: Fully solid state 14 transistors, 14 diodes.
- Output Stage: Quasi complementary pairs.
- Power: 230/250 Volt AC, 50 Cycles.
- Power Consumption: 40 watts.
- Speaker System: 2 separate oiled walnut cabinets, each with low frequency speaker mechanism and tweeter.
- Turntable: Four-speed, automatic and manual change, automatic cut-off and automatic repeat.
- Size: Unit—15" x 14" x 8". Speakers—14" x 8" x 8" each.
- Weight: Unit—18 lbs. Speakers—8 lb. each.
- Finish: Unit—Black matt finish with oiled walnut sides and smoke-grey perspex cover. Speakers—Oiled walnut.

ELAC MIRACORD 50H



The Elac Miracord 50H has a transcription turntable of the luxury class with versatile operating facilities, tracking control, anti-skating device and automatic changer mechanism. Price complete, \$148.

The finest automatic Turntable ever produced

- Four-speed turntable driven by synchronous hysteresis motor giving absolute speed accuracy.
- Universally balanced, high-precision tone arm with tracking control and anti-skating device for even tracking of record groove flanks.
- No records project over edge of massive 12" turntable of non-magnetic zinc casting.
- Record speed setting indicated in illuminated window with push-button control for luxury operating convenience.
- Special feature — the cueing device, an important aid which no record lover should be without.

RCA OF AUSTRALIA PTY. LTD.

An Associate Company of the Radio Corporation of America

SYDNEY • MELBOURNE • BRISBANE • ADELAIDE • PERTH
RCA31DPM

DESIGN PROCEDURE FOR AEGIS

In addition to providing a range of pre-wound short-wave coils, as featured in our "1967 All-Wave Three" receiver, Aegis Pty. Ltd. have set out simplified design procedures for correlating frequency coverage, tuning capacitance and numbers of turns for typical applications.

By L. R. Mitchell

A problem which is commonly met by those facing the construction of a short-wave receiver is the provision of the necessary tuning coils. In the constructional data, the emphasis is usually on the dimensions, the number of turns and the polarity of connection into circuit. In fact, the most trying problems are often the physical ones of procuring the necessary formers and winding wires, of laying the turns neatly in position, and the provision of means to terminate the windings and to mount the completed component on the chassis.

From time to time, in an effort to facilitate receiver construction, coil manufacturers have released sets of completed coils, intended for use with specific classes of valve (or transistor) and with particular tuning capacitors, to cover particular frequency ranges. While such coils have a place in the scheme of things, however, they cannot hope to meet all demands, because the requirements of individual projects and of individual constructors vary so widely.

As a practical alternative to these

ent single-hole mounting is provided by means of a spring clip.

Figure 1 indicates, in tabulated form, the turns and wire gauge on each of the three basic types of coil. The turns are retained in position by a special coating, which will nevertheless allow unwanted turns to be peeled off as necessary. By carefully noting the number of turns so removed and subtracting this from the figures in the table, the number of turns retained will be immediately apparent.

All wires are coated with an insulation which melts with heat so that tinning of the leads requires only the application of a soldering iron.

Figure 2 shows typical "Q" curves for the three types of coil. It will be apparent that maximum Q and maximum dynamic resistance for the complete tuned circuit, for any given frequency, will be achieved by retaining as nearly as possible the full number of turns provided for the tuned winding. In practice, the need to accommodate definite values of parallel capacitance and to

set down some fundamentals of tuned circuit design.

FIXED TUNED CIRCUITS: The basic circuit is given in figure 4a and the standard equation is:

$$f_r = \frac{1}{2\pi\sqrt{LC}} \dots\dots (1a)$$

where: f_r = resonant frequency in Hertz

L = inductance in Henries

C = capacitance in Farads

To obviate calculation this relationship has been plotted in columns 1, 2 and 3 of figure 3 using practical units. In operation it is only necessary to join two known quantities with a ruler when the unknown will appear at the point where the ruler cuts its scale. Practical coil details are indicated directly against the inductance scale and for convenience a wavelength scale has been added.

VARIABLE TUNED CIRCUITS:

Variable capacitors used in radio receivers are available in a limited number of sizes only and it is often necessary to modify the law in order to restrict coverage to a particular range. Two methods are commonly used.

The simple shunt method is shown in figure 4b. Given:—

$$\alpha = f_2/f_1 \dots\dots (2)$$

where f_2 and f_1 are the upper and lower frequency limits respectively, and

$$\Delta C_g = C_{gmax} - C_{gmin} \dots\dots (3)$$

where C_{gmin} and C_{gmax} are the tuning capacitor minimum and maximum values respectively. Then:—

$$C_s = \frac{\Delta C_g}{\alpha^2 - 1} - C_{gmin} \dots\dots (1b)$$

Once again this relationship has been plotted in figure 3 using scales 3, 4 and 5, it being first necessary to calculate values of ΔC_g and α .

It often occurs that the size of tuning capacitor used is dictated by requirements other than those of the frequency range in question, and the value of C_s may become excessively large. This has the following disadvantages:—

(i) The Q and dynamic resistance of the tuned circuit is considerably reduced.

TRANSFORMER TYPE No.	TURNS		SECONDARY WIRE GAUGE
	SECONDARY	PRIMARY	
RFT2	80	40	20/.002
RFT5	24	12	.0201
RFT10	14	7	.029

Figure 1: Set out above are the physical specifications of the double-wound short-wave coils, released by Aegis Pty. Ltd. and referred to quite correctly as "transformers". Unwanted turns can be stripped off easily to secure any desired secondary inductance and primary coupling.

familiar problems, the Aegis Company has produced a versatile series of short-wave coils which, with minor adjustments, may be adapted to a wide variety of applications at frequencies ranging from 1.5MHz to 30MHz. Based on a low-loss polystyrene former, these coils exhibit excellent electrical characteristics and are recommended for use in all small-signal applications where stable, high-Q tuned circuits are required.

A 1/4-inch former has been chosen as representing the best compromise between efficiency and compactness, and three different types of winding configuration have been produced to provide adequate coverage of the range. Each coil is, in effect, a radio frequency transformer complete with tuned and coupling windings. An adjustable screw core allows for easy alignment; conveni-

achieve certain figures of frequency coverage, will necessitate some modifications. Primary turns will also have to be adjusted to suit the particular application.


As supplied all coils carry primary and secondary windings with turns somewhat in excess of anticipated requirements, so that modification will normally require turns to be stripped off from both windings.

Tuned circuit calculations can be tedious, especially where it is required to tune a particular range of frequencies with an available variable capacitor. A chart such as in figure 3 can be very useful in all such circumstances, enabling component values to be predicted quickly and accurately with a minimum of calculation. Before proceeding to figure 3, however, it will be helpful to

Figure 3: The nomogram on the facing page allows capacitance, frequency, inductance and turns on a given coil to be read off directly from scales 1, 2 and 3. Scales 4 and 5 extend the possible use of the nomogram to take in problems involving frequency coverage for different values of tuning capacitor and the use of shunt and "padder" capacitors to hold the coverage to desired frequency limits.

PRE-WOUND SHORT-WAVE COILS

At first glance, this nomogram may appear to be upside down. However, it has been printed that way to simplify its use with the magazine turned on its side.



AGFA-GEVAERT




Tape yourself out of the amateur class...

record on  PE tapes

Agfa Recording Tapes have what any true tape enthusiast wants—greater clarity, sensitivity, uniformity, durability and greater range. Agfa PE (Polyester) Tapes are pre-stressed and stretch resistant to eliminate sound fluctuations, and abrasion and wear resistant to give you the longest, strongest tape life ever. Agfa Recording Tapes include Long Play, Double Play and Triple Play in a wide range of lengths and spool diameters. All three types of Agfa tapes are now available in various spool sizes in the new Novodur Cassettes. These plastic, almost-unbreakable cassettes are excellent for library storage.

WRITE FOR FREE LEAFLET ON AGFA RECORDING TAPES AND ACCESSORIES



To AGFA-GEVAERT LIMITED
P.O. Box 48, Nunawading, Victoria.

NAME

PLEASE PRINT

ADDRESS

The most sensitive tape for the finest in sound, **AGFA PE RECORDING TAPES.**

Registered trademark AGFA-GEVAERT Antwerp/Leverkusen.

AGFA-GEVAERT LIMITED • MELBOURNE • SYDNEY • BRISBANE • ADELAIDE • PERTH

(ii) Dial calibration tends to become exceedingly non-linear with frequency. These disadvantages may be overcome by incorporating a series capacitor (usually termed the padder capacitor) indicated as C_p in figure 4c. The value of C_s for this circuit will be modified by the addition of C_p . It can be shown that, for a particular size of tuning capacitor:—

$$C_s = \text{function} \left(\frac{C_1}{\alpha} \right) \dots (1c)$$

where C_1 = capacitance required to resonate with L at f_1 .

- (c) Select the nearest standard value of ganged capacitor C_g , say 10-300pF. (10-200pF would not provide sufficient capacitance. This may be verified by substituting that value in what follows.)
 (d) From (3) $\Delta C_g = 300 - 10 = 290\text{pF}$.
 (e) From (2) $\alpha = 4.5/1.5 = 3$.
 (f) From figure 3(1b) $C_s = 26\text{pF}$.
 (g) $C_1 = C_s + C_{g\max} = 326\text{pF}$.
 (h) From figure 3(1a) $L = 34.5\mu\text{H}$ (RFT2-62 turns, so that 18 must be stripped from the RFT2-80 inductor, as supplied).

EXAMPLE 3: It is required to tune the range 6-10MHz. Tuning capacitor, 10-415pF.

- (a) From figure 2 select a suitable inductor, RFT5-24 turns.
 (b) From (2) $\alpha = 10/6 = 1.67$.
 (c) From figure 3(1c) $C_1 = 180\text{pF}$, $C_s = 73\text{pF}$.
 (d) From (4) $C_c = 73 + 415 = 488$.
 (e) From (5) $C_p = \frac{488.180}{488-180} = 285\text{pF}$.




Figure 2: The three pre-wound coils provide potential coverage of the range from 1 to 30MHz considerable overlap. While the various factors are likely to affect the final L/C ratio, efforts should be directed to retaining as much "L" as practicable in the interest of high "Q" and dynamic resistance.

Values of C_s for four different sizes of tuning gang are given in the extreme right hand columns of figure 3 and the appropriate value may be selected simply by following the key.

The value of C_p may now be ascertained by calculation.

$$\text{given } C_c = C_s + C_{g\max} \dots (4)$$

$$\text{then } C_p = \frac{C_c \cdot C_1}{C_c - C_1} \dots (5)$$

In the following examples a complete design procedure is given for each of the circuits described above.

EXAMPLE 1: Assume that it is required to design a fixed tuned circuit to exhibit maximum available Q at a frequency of 15MHz. Determine values for L and C .

- (a) From figure 2 select a suitable inductor. In this case obviously RFT10-14 turns.
 (b) From figure 3(1a) we find that this corresponds to an inductance of $1.61\mu\text{H}$ and by aligning this value with 15 on the frequency scale, the required tuning capacity is found to be 70pF.

EXAMPLE 2: It is required to tune the range 1.5-4.5MHz. Determine values for L , C_g and C_s .

- (a) From figure 2 select a suitable inductor and preliminary value of L which may need to be modified. In this case RFT2-80 turns.
 (b) From figure 3(1a) the required resonating capacitance at f_1 is found to be 250pF.

SUPERHETERODYNE OSCILLATOR CIRCUITS: A basic problem in superheterodyne receivers is that of maintaining a constant frequency difference (equal to the intermediate frequency) between signal and oscillator circuits. This is not practicable using standard tuning capacitors having identical gang sections, but it is generally agreed that the error will be reduced to negligible proportions if precise tracking can be established at three points within the tuning range. Design equations are not simple and many experimenters prefer to select component values on a purely empirical basis.

It is comparatively simple, however, to establish tracking points at each end of the tuning range using the same



THE AUSTRALIAN POST OFFICE
HAS A VACANCY FOR AN

Instrument Maker

In its Research Laboratories.

SALARY

\$2538-\$2800

DUTIES

Interesting and varied work concerned with the construction, modification and repair of a wide range of scientific electrical and mechanical laboratory equipment.

LOCATION

The APO Research Laboratories are located in the Melbourne city area.

QUALIFICATIONS

Qualifications in Instrument Making are required together with some experience with laboratory type instruments.

LEAVE

Three weeks annual leave together with liberal sick leave and other benefits.

ENQUIRIES

Mr. R. Jepson (Telephone 630 7975. Business hours Mon.-Fri.)

APPLICATIONS


in writing, to — The Director-General, Posts & Telegraphs, Treasury Place, Melbourne, 3002, by 21st August, 1967.



MODEL – SA400

INTEGRATED STEREO AMPLIFIER

Sold only by selected Audio Centres throughout Australia



EXTRA-FINE SOUND AT BUDGET PRICE

TUBES

12Ax7x3; 6BM8x4

DIODES

SD-1Ax2; SE-05-01x2

MUSIC POWER OUTPUT

30 Watts total

POWER OUTPUT

11 Watts per channel (RMS)

HARMONIC DISTORTION

Less than 1% (at rated output)

FREQUENCY RESPONSE

± 1 DB from 30 to 20,000 CPS

SENSITIVITY

Magnetic Phono: 2.3MV

(For Rated Output)

Ceramic Phone: 38MV

Tape Head: 1.5MV, Tape Line Output

Playback (Monitor-in) 150MV

Auxiliary: 150MV

TONE CONTROLS

Bass: Boost 12DB, 14.5DB at 50 CPS

Treble: Boost 9DB, Cut 11DB at 10,000 CPS

Sole Australian Representative

ASTRONIC IMPORTS

(A division of Electronic Industries Limited)

622 NICHOLSON STREET, NORTH FITZROY, VIC. (489-1911)

also at

Sydney (31-6721), Brisbane (2-0271), Adelaide (23-4022), Perth (28-3111)
and Hobart (2-2711).

method as described in example 3. The third tracking point may then be adjusted during alignment. The following procedure may be applied equally to oscillator circuits operating below the signal frequency, but it should be observed that the signal circuit must be padded and that the roles of signal and oscillator circuits are reversed from the point of view of ascertaining component values.

EXAMPLE 4: Determine oscillator component values for the signal circuit described in example 3. The oscillator frequency is to be higher than the signal frequency and the selected intermediate frequency is 455KHz. For the notation oscillator components will be dashed.

- (a) $f1' = f1 + IF = 6 + .455 = 6.455\text{MHz.}$
- (b) $f2' = f2 + IF = 10 + .455 = 10.455\text{MHz.}$
- (c) $\alpha' = 10.455/6.455 = 1.62.$
- (d) From figure 2 select a suitable inductor, RFT5-24 turns.
- (e) From figure 3(c) $C1' = 156\text{pF,}$
 $Cs' = 69\text{pF.}$
- (f) From (4) $Cc' = 69 + 415 = 484.$
- (g) From (5) $Cp' = \frac{484.156}{484-156} = 230\text{pF.}$




Figure 4: The basis of discussion in the text—(a) is a simple tuned circuit, (b) a tuned circuit with shunt capacitance and (c) a tuned circuit with both shunt and series capacitance.

NOMENCLATURE

f1	lowest frequency required to be tuned.
f2	highest frequency required to be tuned.
alpha	tuning ratio= $f2/f1$.
Cgmin	tuning gang minimum capacitance.
Cgmax	tuning gang maximum capacitance.
L	tuned circuit inductance.
Cl	Capacitance required to resonate with L at f1.
Cs	shunt capacitance introduced across the tuned circuit.
Cp	capacitance introduced in series with the tuned circuit.

ALIGNMENT PROCEDURE

- (a) With the tuning capacitor fully closed, adjust all cores for maximum signal at f1 e.g. 6MHz.
- (b) With the tuning capacitor fully open adjust all trimmers for maximum signal at f2 e.g. 10MHz.
- (c) Repeat (a) and (b) until no further adjustment is required.
- (d) Set signal source to centre frequency e.g. 8MHz, and tune the receiver to this frequency.
- (e) Adjust aerial and/or RF trimmer for maximum output noting whether the capacitance must be increased or decreased.

If the trimmer has to be INCREASED then the oscillator padder must be INCREASED.

If the trimmer has to be DECREASED then the oscillator padder must be DECREASED.

(f) Make a small adjustment to the padder as described.

(g) Repeat this procedure starting again at (a) until no further adjustment is required.

Note that as these adjustments proceed it will usually be necessary to remove a few turns from the oscillator coil.

ADDITIONAL NOTES

(1) The practical coil details in figure 3 are plotted for the core in an approximate intermediate position.

(2) In practice, at least portion of Cs is made variable by means of a pre-set trimmer.

(3) Cp should be a fixed capacitor preferably within 2½ per cent of the calculated value.


(4) It is advisable to make preliminary adjustments to coupling windings before carrying out alignment. This applies particularly to the oscillator coil which should be adjusted for minimum excitation consistent with reliable operation. For valves check the manufacturer's data. Aerial primaries are usually

about one quarter of the secondary turns while RF coil requirements may be one third to one half, the primaries normally being interwound with, or adjacent to, the "earthy" end of the tuned winding.

(5) The basic principles outlined above apply equally to valve or transistor circuitry provided suitable matching arrangements are made where required.

TUNING LAW: In the case of padded signal circuits where a wide range tuning capacitor is used it is often practicable and indeed desirable to exercise some control over the rate with which tuning is accomplished, i.e. to arrange component values so that the dial calibration corresponds to a predetermined law, usually with the object of obtaining

GELOSO SIX BAND AMATEUR RECEIVER



G 4/216

TECHNICAL DETAILS:

Frequency Ranges: 10-meter band (28-30 MC); 15-meter band (21-21.5 MC); 20-meter band (14-14.5 MC); 40-meter band (7-7.5 MC); 80-meter band (3.5-4.0 MC) - 144-146 (26-28) MC for external VHF converter.

Tuning Control: By step-down ratio.

Accuracy of Frequency Calibration: ± 5 KC on the 80-, 40- and 20-meter bands; ± 10 KC on the 15 and 10-meter bands.

Frequency vs. Times Stability: ± 0.5 : 10,000 (i.e. ± 50 cycles/MC).

Intermediate Frequency: 467 KC.

Image Rejection: Better than 50 db on all frequency ranges.

Intermediate Frequency Rejection: Better than 70 db.

Sensitivity: Better than 1 µV for 1 watt a.f. output.

Signal-to-Noise Ratio: at 1 µV better than 6 db.

Selectivity: 5 positions: Normal - Xtal 1 - Xtal 2 - Xtal 3 - Xtal 4.

Reception of Amplitude Modulated Signals.

Reception of Single-Side-Band Signals (s.s.b.): amplifier and detector circuit for s.s.b. signals, with carrier re-insertion.

Noise Limiter: Effective with all type signals. Self-adjusting to various a.m. signal levels.

Signal-Strength Indicator: S-meter, calibrated in S-units from ((S-1)) to ((S-9)), ((S-9 + 20 db)) and ((S-9 + 40 db)).

Available ex stock \$269.31 inc. sales tax. Full information available from:

AUSTRALIAN AGENTS
R.H. Cunningham
PTY. LTD.


VIC.: 608 Collins St., Melbourne. 61-2464.

N.S.W.: 64 Alfred St., Milson's Pt. 929-8066.

QLD.: L. E. Boughen and Co., 85 Central Ave., Sherwood. 79-2207.

W.A.: H. J. MacQuillan Pty. Ltd., 1017 Wellington St., Perth. 21-4821.


AKAI'S NAME MEANS PERFECTION WHEN IT COMES TO STEREO



The Cross-Field Head It Revolutionized Stereo

People throughout the world have come to really enjoy this particular feature, because of the superb results. The Cross-Field System is actually composed of two heads facing one another and so mounted where by their centers are slightly off, as shown in the diagram. This combination of bias and signal heads makes possible clearer responses than the ordinary conventional head, even at slow tape speeds.

Model M-8: Cross-Field Head tape recording and playback superiority from Akai. The 4-track, 4-speed stereo/mono M-8 offers sound-on-sound recording—vertical center speakers—special bias for FM multiplex recording—automatic shutoff—instant stop—horizontal or vertical positioning—2 speed synchronous motor—30 to 25,000 cps frequency response—12 watts power output—operates on 100-240v AC at 50/60 cycles.



MODEL M-8

Be An Amateur

Enjoying professional Result...

This compact model is a 4-track stereo monaural record and playback tape recorder.

It is light in weight and even ladies can carry it gracefully with ease.

You get the same Akai quality at this surprisingly low price.

It has a frequency response of 40 to 18,000 cycles per second; 3-speed ($1\frac{1}{8}$, $3\frac{3}{4}$, and $7\frac{1}{2}$) and 15 ips optional two built-in speakers; automatic stop; simple changeover to AC power.

This Akai Model 1710 is selling exceptionally well in the United States under the brand name Roberts 1630. The matching stereo speaker Model SS-30 is also available.



MODEL 1710

AKAI

TAPE RECORDER

AKAI ELECTRIC CO., LTD.
HIGASHIKOJIYACHO OHTA-KU TOKYO JAPAN

N.S.W.: Magnecord Australasia Pty., Ltd. 210 Clarence St., Sydney Victoria: Magnecord Sales & Service, 3-Albury Rd., North Balwyn Queensland: Magnecord Sales & Service, 399 Montague Bd., West End; Brisbane S.A.: Magnecord Sales & Service, 8 Arthur St., Unley W.A.: Tedco Pty. Ltd., 579 Murray St., Perth




Figure 5: This second nomogram covers a particular case where tuning is to be accomplished by a 415pF ganged capacitor, of a type commonly used in this country for broadcast band receivers. Its use is explained in the text.

a linear or close to linear characteristic. This prevents crowding of frequencies at any particular section of the dial and results in considerably easier tuning over bandspread ranges.

The circuit is the same as that shown in figure 4c and the design problem consists of finding values of C_s , C_p and L so that simultaneously the desired scale calibration and frequency coverage is achieved. Care must also be taken to ensure that alterations to component values do not result in an appreciable reduction of Q .

As previously mentioned, use of a wide range capacitor is indicated and by restricting the application to one particular type of known characteristics it is possible to evolve a practical approach which is very simple to operate indeed. Accordingly the gang selected is of the modern miniature type having a maximum value in the vicinity of 415 pF and being fitted with symmetrically shaped plates. The Roblan RMG 10-415 is typical of this type but other

makes having similar characteristics may be substituted.

The design procedure now becomes quite easy and all calculations are eliminated by making use of figure 5. Simply align the two frequencies f_1 and f_2 with a straight-edge to locate a point on the reference line and by projecting horizontally across from this point the values of C_s , C_p and C_1 may be read off directly. The inductance value may then be determined by referring to figure 3(1a) of the previous section. It will be instructive to repeat the earlier example (ex. 3) using this method.

EXAMPLE 5. Required frequency range 6MHz to 10MHz.

Then $f_1 = 6\text{MHz}$ $f_2 = 10\text{MHz}$

From figure 5. $C_s = 76$ $C_p = 298$
 $C_1 = 188$

From figure 3(1a) $L = 3.7\mu\text{H}$ RFT5—23 turns.

Note that it has been necessary to

reduce the inductance value with a consequent loss of Q . This loss is unlikely to be serious, provided the turns on the tuned winding are not reduced by a factor of more than 20 per cent. It will be found that most likely ranges can be accommodated within this limitation.

For superheterodyne oscillator circuits simply add the intermediate frequency to f_1 and f_2 and substitute these values in the foregoing, viz:

EXAMPLE 6. Assume an I.F. of 455KHz

Then $f_1' = 6 + .455 = 6.455\text{MHz}$

$f_2' = 10 + .455 = 10.455\text{MHz}$

From figure 5 $C_s' = 78$ $C_p' = 264$
 $C_1' = 175$

From figure 3 (1a) $L' = 3.4\mu\text{H}$ RFT5—21 turns

Alignment follows standard procedures and alterations to the padder should not be necessary.

The utility of this system, particularly where a number of ranges are to be covered using a single tuning gang, will be immediately obvious. Close to optimum Q is achieved together with the advantage of a linear bandspread characteristic, while component values may be quickly and accurately evaluated without recourse to calculation. The only limitation imposed is in the choice of tuning capacitor and, where this conflicts with requirements, the general procedure in the first part of the article will provide the necessary solution.

In these discussions the aim has been to avoid complex mathematical analysis and to present the non-professional reader with a practical solution to a constantly recurring problem. No mention has been made of the effects of stray capacitance but some knowledge of practical layout on the part of the experimenter is assumed and these will be taken up during alignment. Nor has any attempt been made to define optimum tracking frequencies as, in most cases, only fairly narrow bands have been considered and the error is unlikely to be appreciable. Where wide coverages are required this should be checked during alignment and, if necessary, the error may be reduced by shifting either or both of the two extreme tracking points to a position slightly within the band limits.

All of the examples along with numerous others have been checked both by calculation and in a practical receiver situation. The author is indebted to Roger Harrison VK3ZRY for assistance in this regard.

WIRELESS INSTITUTE OF AUSTRALIA

(Victorian Division)


A.O.C.P. CLASS

commences


MONDAY, 21st AUGUST, 1967

Theory is held on Monday evenings and Morse and Regulations on Thursday evenings from 8 to 10 p.m.
Persons desirous of being enrolled should communicate with:

Secretary W.I.A., Victorian Division,
P.O. Box 36, East Melbourne.
(Phone: 41-3535, 10 a.m. to 3 p.m.),
or the Class Manager on either of the above evenings.



English Electric Valve's range of ceramic hydrogen thyratrons is unique. Because each is a tetrode with inherently low dynamic inductance the firing time may be made accurate to less than one nanosecond, and pulse rise times of less than 50 nanoseconds. The anode delay time drift is shorter and the trigger powers required are considerably less than with other types of thyatron.



For high speed switching applications ceramic thyratrons are better than the corresponding glass tubes wherever high-peak, high-mean characteristics have to be met. Higher hold-off voltages (40kV per gap) are possible by using specially designed thyratrons with deuterium filling. EEV will be glad to consider special development and manufacture for customers' own requirements.



AMALGAMATED WIRELESS VALVE COMPANY PTY. LTD.

SYDNEY • MELBOURNE • BRISBANE • ADELAIDE • PERTH

● DISTRIBUTORS FOR ENGLISH ELECTRIC VALVE COMPANY LTD. ●



Forum

Cold-cathode tubes — mostly harmless!

The letter in the June issue about radioactivity in cold cathode tubes seemed to take most readers by surprise, confirming our original impression that it was a subject to which few had given any thought. A couple of letters now to hand express quite different points of view.

Conducted by the Editor

Before quoting them, however, one correspondent takes us somewhat to task for our handling of the subject. He says:

"As a reader of your periodical for almost a decade, I believe other readers would agree that a topic for these columns, selected upon a statement unsupported by any acclaimed authoritative source, demands a more sophisticated editorial accompaniment than is implied by such references as 'a whip around our staff' and 'answers given off the cuff'."

This raises two points in relation to the conduct of a feature such as "Forum" which, in its present form, is an adaptation of the more usual "Letters to the Editor."

But, whether "Forum" or "Letters To The Editor," a certain amount of selection and editing is necessary, as anyone will know who has sat in any kind of an editorial chair. Some letters merely duplicate the sentiments expressed in others, which have already been selected on the basis of prior receipt or better composition. Other letters are rambling or deal with subjects which are not appropriate to the magazine; a pathetic few would appear to be the product of mental illness.

In selecting letters for publication and possible comment, an editor has to steer a course between freedom of expression and unduly narrow limits based on his own or "accepted" concepts. The letter in the June issue raised what appeared to be a major discrepancy between what is apparently being taught in our Armed Services and concepts in the amateur and commercial world outside those Forces.

Our purpose in seeking unrehearsed

reactions to the content of the letter was primarily to emphasise this point: The average commercial engineer, technician, hobbyist and textbook has not given the matter any attention. Further, let's highlight the discrepancy and see what comes out of it!

Something is coming out of it and this kind of "Forum" debate will probably focus more attention on the subject and de-fog more ideas in either direction than any single pronouncement, which many would miss, and with which others would politely disagree.

Be that as it may, we're not unhappy about the way we handled this particular letter, even though we quite appreciate our correspondent's point of view.

Well then, the first letter, which we quote below, is from a member of the Armed Forces who identifies himself but who requests complete anonymity:

Dear Sir,

"I am in a position to throw some light on the subject of radioactivity ('Forum,' June, 1967) since I was involved, to some extent, in propagating the precautions in my branch of the Services, in relation to this hazard.

"It is indeed a fact that many, if not all, cold-cathode tubes used in Service equipment contain radioactive materials and some of them have civilian equivalents. Even those that have no immediate civilian application may find their way into the hands of amateurs and others as a result of equipment disposal, though it is unlikely that bulk stocks of surplus radioactive tubes will ever reach the disposals market.

"The nature and quantity of radio-

active material in cold-cathode tubes varies widely. The types most likely to be found in civilian use (e.g. OA2, OB2) contain 0.0067 microcuries of Cobalt 60, considerably less than the activity of a luminous wristwatch. On the other hand, some more specialised types contain as much as 4 microcuries of Radium and some contain gaseous isotopes which become an inhalation hazard if the envelope is broken. One type (no known civilian equivalent) contains 60uC of Tritium gas, H3. Several types contain enough Uranium to be dangerous as a chemical poison, irrespective of associated radioactivity.

"The Service regulations I refer to cover such requirements as standards for packaging (usually in a lead foil box with a radioactivity warning symbol); for storage (limited quantities to be kept in any one box or store, according to the radioactivity content of each type); precautions for the disposal of broken valves; first-aid for cuts by broken glass from radioactive tubes.

"All this may seem pettifogging in relation to the degree of potential hazard for, after all, it is unlikely that any one individual would break more than one or two voltage regulator tubes in a lifetime. Nevertheless, the Forces, in common with other employers, have a responsibility to minimise any danger to which their members may find themselves exposed in the course of their duties.


"Other hazards which are covered by Service regulations include: X-ray emission from valves with high plate voltage; dangerously high RF energy fields; chemical poisoning from burnt out selenium rectifiers . . . etc.

"May I suggest, in conclusion, that there are enough health hazards in radio and electronics to justify a magazine article on the subject, if only to draw attention to the less obvious ones."

Before quoting the second major letter, I would acknowledge a brief note from R. H. of Alphinton, Victoria, who draws my attention to an item in "Radio Electronics" for October 1959, page 99. The wording of this item by E. H. Marriner is such that, on reading it, I couldn't escape the feeling that he was reacting in the same way and to the same kind of tuiotional material as quoted by our original correspondent in the June issue.

The item is headed: "DANGER! Some electron tubes are radioactive." It goes on:

"Some of the everyday tubes used in receivers and transmitters contain radioactive materials. The more common of these are regulator tubes—



CONNOISSEUR CLASSIC TURNTABLE

Incorporating two slow speed synchronous motors, the Classic features a lathe turned aluminium turntable. Speeds are 45 and 33-1/3 r.p.m. Spindles are high quality carbon steel, mirror finished—and soft rubber wheels disengage when not in use. **Encel price** **\$33.50**



CRAFTSMAN II TURNTABLE

Very popular overseas, the Craftsman II features two fixed speed and a full 12in. lathe-turned non-ferrous turntable. This precision instrument employs an hysteresis synchronous motor which is dynamically balanced—wow is 0.15%, flutter 0.1% and rumble—50 dB at RIAA characteristics when referred to 7 cm/sec. at 1 kHz. Ask for copies of reviews. **Encel price** **\$49**



CONNOISSEUR CRAFTSMAN III TURNTABLE

Perfection in a precision 3 speed transcription turntable is the only way to describe the Craftsman III. Fitted with a 12" non-ferrous lathe turned turntable and a hysteresis synchronous motor, and a built-in illuminated stroboscope. Speed variation of 8% may be made. See the reviews in "Gramophone" and "Hi-Fi News" or write for your own personal copy. **Encel price** **\$67.50**



FROM CONNOISSEUR ... THE NEW MODEL SAU-2 TONE ARM!

With a revolutionary type of gimbal mounting with axis at 45°, the SAU-2 tone arm is both unusual and remarkably effective. Bias adjustment is automatic—playing weight is controlled by a rear counterweight with a resilient backing to dampen the action. A lifting/lowering device is standard equipment—and the headshell accepts all standard 1" mounting cartridges. A small set of scales are provided to set stylus pressure—they are accurate to 0.1 gram. Height of the arm is adjustable from 1 1/4" to 1 3/4". This new Connoisseur arm will track down to 1/4 gram. Read the review of the SAU-2 tone arm and the Connoisseur Classic turntable in "Hi-Fi News", May, 1967, p. 133-5. Write for copies. **Encel price** **\$29.50**



CONNOISSEUR TONE ARMS— MODEL SAU-1

Pivoted on a single point to reduce friction and silicone grease damped, the SAU-1 tone arm is fitted with an effective lifting-lowering device. Height is adjustable, finish is nickel chrome and unbreakable black nylon plastic. Three counterweights are provided to give continuously variable stylus pressure. Ask for copies of the reviews. Price now is only **\$14.50**

SPECIAL CONNOISSEUR ARM/CARTRIDGE OFFER!


The popular Classic turntable will be supplied complete with the Model SAU-1 tone arm and the Model SCU-1 ceramic stereo cartridge (diamond stylus) for only (inc. sales tax) **\$54.50**

With the new Model SAU-2 arm in place of the SAU-1, price is only **\$69.50**

CONNOISSEUR STEREO CARTRIDGE MODEL SCU-1


Regarded as the finest ceramic stereo cartridge produced anywhere in the world, the Connoisseur SCU-1 will load any normal amplifier or tape recorder. Tip mass is 1 milligram, vertical compliance 8 x 10-6 cms-dyne, lateral compliance 12 x 10-6 cms-dyne. Sound qualities are exceptional—and include a pleasant musical transparency. Ask for copies of reviews in the "Gramophone" and "Records and Recording". **Encel price** **\$10.80**

STOP PRESS: Stocks of 78 styli are now available for the Connoisseur SCU-1 cartridge.



SOLID STATE STEREO AMPLIFIER OFFERS HIGH OUTPUT— AT LOW COST

The new Sound Model SAQ-501X is a well designed, high quality stereo amplifier, fully transistorised, with an output of 32.5 watts (I.H.F.M.) into an 8 ohm load in each channel and a frequency response of 20-20,000 Hz. plus or minus 1 dB. Magnetic pickup sens. is 3 mV, all controls are provided for flexible operation, tumble-type switches include loudness control, scratch filter, rumble filter, tape monitor, ON-OFF control. Keen purchasing enables us to sell this fine amplifier for only **\$109.50**



NEW PLANET MG-300 PUBLIC ADDRESS AND GUITAR AMPLIFIER

Power output is 35 watts R.M.S. with parallel push-pull 6BQ5's, frequency response is 30-15,000 Hz. plus or minus 2 dB. Three inputs—two crystal or dynamic microphones at 5 mV, and an auxiliary input for crystal or ceramic pick-ups, tape recorder or tuner at 300 mV. Output impedance includes 8, 16 and 250 ohms as well as a 70V line. Valve complement: 1 x 12AX7, 1 x 6AV6, 1 x 6AQ8, 4 x 6BQ5. **Encel price** is only **\$73.50**

DECCA KELLY

NEW KELLY 15" WOOFER SPEAKER (Mk. VII)

Rated at 50 watts, the frequency response of this new bass reproducer is 30-5000 Hz. Total flux is 350,000 maxwells. Recommended crossover frequency is 2500 Hz. (The Kelly Crossover costs \$11). The Mk. VII uses a laminated aluminium former with the voice coil embedded in polyester resin. Guitar models also available at the same price **\$59.50**

THE MK. II KELLY RIBBON TWEETER

Regarded as the most effective and advanced tweeter available for domestic speaker systems, the Kelly Mk. II is priced at only **\$39**

KELLY ACOUSTIC LENS

Designed for use with the Kelly Mk. II Ribbon Tweeter the Acoustic Lens effectively disperses H.F. radiation **\$12.50**

NEW MODEL 12" BASS REPRODUCER FROM

DECCA-KELLY . . . THE DK II!

This 12" woofer is the model used in the Kardiod enclosure; total flux is 250,000 maxwells due to use of a new ceramic ring magnet of "Magnadur 2". Frequency response is 30-5000 Hz. and the recommended crossover frequency is 2500 Hz. The voice coil is embedded in polyester resin—transient peaks of 100 watts will not damage the assembly. Normal power rating is 35 watts R.M.S. **Encel price** **\$48.50**



DECCA-KELLY KARDIOD KIT'S

In order to reduce prices the Kardiod is now available in component form. The Model DK1 bass reproducer, Mk. II Kelly Ribbon Tweeter, Acoustic Lens and Crossover Network are supplied. Detailed construction instructions and illustrations of the enclosure are provided. Total price: \$109. Cabinets are available if required — polished and unpainted. Ask for details. Components only **\$109**

NOW . . . A HIGH PERFORMANCE STEREO SYSTEM FOR SMALL LOUNGE ROOMS AND MODEST BUDGETS . . . THE ENCEL "COMPAX"!

Many music lovers have little space to spare—and require a small stereo system. The new Encel "Compax" consists of the Sound SAQ-202B solid state stereo amplifier with an output of 6 watts R.M.S. or 12 watts I.H.F.M. in each channel, a Connoisseur Classic turntable, the precision Nikka tone arm, a Micro ceramic stereo cartridge with diamond stylus, a teak base for the equipment and two hand finished multiple-speaker bookshelf enclosures. Stereo headphones may be added for only \$11 more. **Encel price** including sales tax is **\$156** only

A Mk. II "Compax" has just been introduced. The "Sound SAQ-202B" amplifier and speaker systems are the same; with this model the turntable supplied is the well known Labcraft 643, the tone arm has a lifting/lowering device, the cartridge is a high quality ceramic unit with a diamond stylus and the equipment is housed in an attractive base with a perspex dust-proof cover. This Mk. II "Compax" costs only **\$145**

Encel

ELECTRONICS PTY. LTD.

Head Office: 431 Bridge Rd., Richmond, Vic. Tel. 42 3762
Sydney Store: 257 Clarence St., Sydney. Tel. 29 4563, 29 4564
Australia's Greatest Hi-Fi Centre
* Wholesalers * Trade-Ins Accepted

the OA2 and OB2. Caution in handling cannot be overemphasised.

"The danger is similar to that experienced with early fluorescent lamps. When intact, bulb unbroken, there is no real hazard. The amount of radioactivity is below the level that is considered dangerous. But should the bulb be broken, the radioactive material (cobalt 60 and nickel 63) may be picked up and get into your body — through breathing, eating, drinking or wounds in the skin. These radioactive isotopes — they emit alpha, beta or gamma particles — can injure or destroy blood-forming organs and other tissue. Internal radiation of this type may show up in a few weeks or it may take a few years, because the material fixes itself in the tissue, and its removal from the body is very slow.

"If you should break one of these tubes, remember:

- Don't let any part of the broken tube touch the body. Use rubber gloves.

- Don't bring any food or drink into the contaminated area.

- Wash thoroughly.

"Also, since these tubes can be dangerous, don't let children play with old ones, or break them open to see what's inside.

"A detailed listing of all tubes that contain radioactive substances can be found in the 'Bureau of Ships' journal for December, 1957, published by the Department of the Navy. Aside from the regulator tubes — that section of the listing is presented here — only uncommon types are found (microwave, radar, special-purpose). However, some of these are extremely dangerous, containing much larger amounts of radioactive isotopes. Some have to be marked with a seal showing that they are radioactive, and special disposal precautions must be taken. But the only types you are likely to encounter are regulator tubes. The table shows a listing of these units as shown in the journal."

Type	Isotope	Amount (microcuries)
OA2	Cobalt 60	.0067
OA2-WA	Nickel 63	.01-.05
OA2-WA	Cobalt 60	.0067
OB2	Cobalt 60	.0067
OB2-WA	Nickel 63	.01-.05
OB2-WA	Cobalt 60	.0067

So much for Mr Marriner's item which, as I said, closely parallels the statement in our June issue. Much more positive is the thinking in the second major letter, referred to earlier. The letter is signed but, in deference to medical ethics, we again omit name or initials:

ACTIVITY EXPRESSED IN MICROCURIES

Substance	Max. quan. exempt from licensing and monitoring under S.A. Regulations.	Max. permissible burden in a body organ (International Commission of Radiological Protection-Publication 11 and Table 1).	Figures published in June edition of E.A. as "danger levels."
C14	1000	300	5
Cs137	10	30	1
Co60	10	10	1
Ni63	not included	200	1
Ra226	1.0	0.1	0.1

From a specialist:

Dear Sir,—

"If I may presume to comment upon the subject matter of the 'Forum' columns in your June issue, i.e. 'Cold-cathode tubes — radioactivity hazard,' I think that your correspondent, who has led you to introduce this subject, has either misinterpreted the information presented in his course of instruction or has received rather over-enthusiastic if well intentioned tuition concerning the hazards of ionizing radiation.

"As a medical specialist in diagnostic X-ray work, my partnership owns and operates several types of 'Irradiating apparatus' — as legislative authority prefers to term X-ray equipment.

"I can assure you that the Public Health authorities are very conscious of the matter of so-called 'radiation hazards' and each state of the Commonwealth has stringent and extensive regulations not only applying to 'irradiating apparatus' which must be registered and operated by licensed persons and is periodically inspected and monitored, but equally to all radioactive materials which are the source of ionizing radiation.

"To quote from the South Australian Health Act relating to Radioactive Substances and Irradiating Apparatus, the current regulations state in paragraph 11:

"No person shall import, manufacture, possess, store, use, handle, transport or dispose of any radioactive substance or irradiating apparatus except in accordance with the provisions of these regulations. The Act defines 'Radioactive Substance' as a substance which consists of or contains any radioactive element whether natural or artificial.

"Radioactive" is defined as 'undergoing spontaneous disintegration of an unstable nuclide with emission of particles or photons, to form a different nuclide.' You do not publish the source — other than your anonymous correspondent — of the figures which you quote as the 'Intensity' (the usual technical term is 'activity') in microcuries of the five elements which you list but, according to official publications, the data given is as set out in the accompanying table.


"The deliberate introduction of radioactive 'tracer' isotopes into the human body for medical diagnostic purposes by electronic scanning techniques is now established on such a scale that special departments are be-

WANTED

BY ALL
PRODUCTION ENGINEERS

ORYX

miniature
soldering instruments



ACTUAL
SIZE

- * RELIABLE
- * EFFICIENT
- * LONG LIFE
- * REPLACEABLE BITS
- * CONTINUOUSLY RATED
- * NO WARM UP DELAYS
- * NO SWITCH TROUBLES
- * NO OPERATOR FATIGUE
- * DOES WORK OF HEAVY IRONS


Weighs less than 1 oz. and compact handle enables girl operators to work quickly and accurately all day.

Write or phone to

MELBOURNE: AWA Ltd., 67 9161. HOBART: AWA Ltd., 3 3836. LAUNCESTON: AWA Ltd., 2 1804. ADELAIDE: Newton McLaren Ltd., 51 0111. BRISBANE: Chandlers Ltd., 31 0341. PERTH: AWA Ltd., 28 3425. SYDNEY: George Brown & Co. Pty. Ltd., 29 7031. Electronic Parts Pty. Ltd., 533 1277.

Australian Distributors
**MANUFACTURERS SPECIAL
PRODUCTS PTY. LTD.**

47 York Street, Sydney. 2 0233, Ext. 284



ANNOUNCING ...

attractive new rigid plastic shelf packs for instant 'roll-out' selection.

NEW CONVENIENCE — the plastic pack never leaves the shelf — simply open the swing back and 'roll-out' your tape.

NEW PROTECTION — now your collector tapes are double protected — plastic pack plus sturdy transparent container.

These attractive new shelf packs reflect the sound quality in every BASF recording tape. The tape that recorder manufacturers recommend; the tape with the Mirror Finish surface that gives 5 times longer life to your recording heads; the tape that belongs in your sound library.



SPECIAL ECONOMY PACK



For working tapes and day-to-day use the new BASF economy pack is ideal. See it now at your tape recorder dealer — you get the same quality tape for less cost!



BASF

RECORDING TAPE

reflects your sound taste

Distributed throughout Australia by:

MAURICE CHAPMAN & CO. PTY. LTD.

ing established in the major hospitals to conduct these investigations.

"As radioactive materials utilised for medical and industrial purposes are nowadays almost invariably synthesised, their precise atomic structure is known, their 'half-life' and decay rate are accurately calculated and range from 1622 years in the case of the element radium to 0.3×10^{-10} seconds for one of the polonium isotopes.

"The precise proportions of alpha particles (two protons and two neutrons bound together) ejected at 10 cm/sec, beta particles (positrons) travelling at a rate from zero to that of electromagnetic radiation and of gamma radiation emitted is known and able to be calculated and monitored in its effects by scientists working in this field.

"Physicists, expert in monitoring radiation, operate in departments lavishly equipped with an extensive array of electronic test gear, as part of the Radiotherapy Division of practically every major metropolitan hospital.

"The Commonwealth X-Ray and Radium Laboratory in Melbourne conducts a monitoring service for recording the radiation received by personnel associated with radioactive substances or irradiating apparatus in all states and your readers may rest assured that the Public Health authorities supported with the scientific skill of nuclear physicists in the Universities and Technical Colleges are not lacking in expertise or energy in monitoring, inspecting and regulating all possible sources of ionizing radiation which might conceivably be classified as a human hazard"

COMMENT: The first thing that emerges out of the discussion is that, except for Radium 226, there is a wide discrepancy between the "danger level" figures quoted from the Service literature and those from the International Commission of Radiological Protection. The discrepancy is heightened by the fact that the Service literature refers to a quantity of radioactive material present in a radio valve as a mere potential hazard; the other figure refers to the "burden" actually present in an organ of the body. In view of the fact that the latter figures come from an International Commission, concerned among other things with the use of radioactive tracers, it is difficult to regard their figures as other than authoritative.

It would appear that the Australian Service figures are based, at least in part, on British "CV" specifications which are — or have been — "classified" or "restricted" and which are probably of rather venerable age. They would also appear to be conservative in the extreme.

However, even by such conservative standards, few cold-cathode tubes would contain enough radioactivity to cause any apprehension as individual tubes. One list I was able to look at covered about 450 types. Of these about 36, containing mainly Co60 and Ni63, would have been at or above permissible Service limits but well below both the International Commission and South Australian figures listed on the previous page. Another 23 types contained Ra226 at or above the 0.1uCi level.

To discover whether or not these figures were typical of other lists from other sources would involve a far greater effort than we can even contemplate at


the moment. I imagine, however, that they would be fairly representative.

On this assumption, about 5 p.c. of cold-cathode tube types contain enough radioactivity to pose a theoretical hazard in a "one-off" handling situation. Another 8 per cent would qualify as a hazard on Service figures, but are far below hazard level according to other listed data. The remainder of the tubes are well below even the most conservative danger levels.

Included among the "harmless" types are the popular cold-cathode types mentioned by E. H. Marriner, and one must therefore discount the inference of his item, and perhaps of our June correspondent in these columns, that cold-cathode tubes as a class pose a radioactivity hazard. In fact, the great majority of such tubes, and particularly of those likely to reach commercial and amateur circles, are quite harmless in terms of radioactivity. It is not surprising, therefore, that engineers, technicians and sales representatives in commercial circles seem not to have given the matter a second thought.

Are the "dangerous" tubes marked? The specifications for CV tubes, mentioned earlier, do nominate levels of radioactivity, above which tubes must carry a distinguishing mark, and I imagine that this would be fairly typical practice.

CAUTION




Originally, British-made radioactive tubes carried a warning in the form of an orange band 4-inch wide. Though this has been superseded, individual, old tubes may be encountered in service situations which still carry the marking.

Later practice is much more positive and I paraphrase from a clipping supplied by a reader, with access to CV specifications:

1. The word "CAUTION" in positive lettering, i.e. printed in the imprinting colour in the ordinary sense. (This is opposite to the American practice where the imprinting colour is used as a large surround and the cautionary word appears by absence of imprinting ink in the background colour).
2. A three-bladed radioactivity symbol, as illustrated.
3. The chemical symbol(s) for the radioactive substance(s) within the valve. As an example, the illustration shows the chemical symbol "Co 60" for Cobalt 60.
4. Imprinting colour—dark violet or magenta.
5. Background colour — not specified for valves but the violet or magenta must be clearly visible against the background.
6. Diameter of symbol must be not less than half the diameter of the bulb or envelope.

So much for the British specification. Other readers who may have access to specifications or details from other countries may be able to add to these remarks.

Learn what makes the giant computers tick!



... with this

NEW MINI-MODEL

"DIGITAL COMPUTER"

Stimulating Educational Fun!

- SOLVE PROBLEMS ● PLAY GAMES
- TELL FORTUNES ● SOLVE RIDDLES

with this fascinating miniature version of a giant electronic brain

Teaches Computer Fundamentals, Solves Real Problems, Adds, Subtracts, Multiplies, Complements, Shifts, Carries, Memorises, Compares, Sequences ... Does Everything (Mechanically) The Giant Electronic Brains Do.

Easily Assembled Kit Includes 28-Page Manual Covering Operation, Computer Language (Binary System), Programming, Problems, PLUS Dozens More Exciting Experiments In The Big NEW FREE 50-Page Detailed Programming Book ... ALL for Only \$12.95 post paid.

EDUCATIONAL

FUN

INCREASE YOUR I.Q. with

Games FOR Thinkers

WFF'N PROOF: The Game of Modern Logic
 ● **EQUATIONS:** The Game of Creative Mathematics
 ● **WFF:** The Beginners Game of Modern Logic
 ● **ON-SETS:** The Game of Set Theory
 ● **THE REAL NUMBERS GAME:** The Pen-clip kit for the Number Buffs
 ● **TAC-TICKLE:** A Challenging Game of Pure Strategy.



MAKE YOUR OWN GENUINE COPPER PLAQUES

for pleasure or profit

Now you can create professional looking **COPPER PLAQUES**, with dozens of interesting subjects to choose from. Ever so easy to make, the 4" x 4", 5" x 5" or 6" x 8" kit comes complete with everything needed to make beautiful copper pictures.

Priced from Only 90 cents to 2 dollars. Send 4c stamp for **FREE COLOUR BROCHURE!**

Send cheque/m.-order to: **Dept. E8**

MODERN SCIENCE SUPPLIES

Box 3702, G.P.O., Sydney.
 Or 85 William St., Sydney. Telephone 31-3922

WARBURTON FRANKI



AFTER-STOCKTAKING SPECIALS

KNOBS Attractive white knurled edge. Black face with gold moulded pointer. 1½" diameter, 9/16" deep. Standard ¼" bore in brass bush.

20c ea. or \$2.25 doz.
Inc. pack. and post.

MICROPHONE CABLE, TWIN

½" diameter. Black P.V.C. covered. 100 yard rolls.

\$15.75 ea.
inc. pack. and post.

PANEL METERS

MR2-P SIZE—1½" Square
0-500 Microamps ... **\$3.25**
0-1 Milliamp ... **\$3.10**
0-300 Volts A.C. ... **\$3.10**
P25 SIZE—2½" Square
0-1 Milliamp ... **\$5.00**
CR3-P SIZE—3" x 3½"
0-300 Volts AC ... **\$4.85**
P60 SIZE—6" x 4½"
0-1 Milliamp ... **\$8.60**

MOVING IRON AC/DC METERS

SIZE—1½" Square—
\$3.50 each.
0-1, 0-5, 0-10, 0-20 amps.
0-10, 0-20, 0-40, 0-50 Volts
ANY OF ABOVE—POST FREE.

HIGH STABILITY RESISTORS

1 Watt $\pm 1\%$, 15 ohms to 8.2 megohms
1 Watt $\pm 2\%$, 11 megohms to 30 megohms
Famous Rosenthal Brand Made in West Germany.

Write or Call for List of Values
Available **25c each. Post Free**

SAPPHIRE STYLII ALL TYPES

STEREO L.P. OR STANDARD
Any single Tip **75c each**
Any double Tip **\$1.25 each**

DIAMOND STYLII ALL TYPES

STEREO L.P. OR STANDARD
Any Single Tip **\$3.25 each**
Any Double Tip **\$4.50 each**
(One Diamond)
(One Sapphire)

Post Free.

VALVES

American Sylvania Type 807.
\$1.75 each
Post Free

MINIATURE LOW VOLTAGE ELECTROLYTIC CONDENSERS

2 to 100 mfd in 6, 12, 25 and 50 V.W. Bags of 25 assorted.

\$3.50
including pack. and post.

AUDIO AMPLIFIER MODULES

4 transistor—1 watt output. High Impedance Input—100,000 ohms. Low Impedance Input—1,000 ohms. Output—4, 8 or 16 ohms. Power Source—6 Volts. Gain—70DB. Size of board, 4½" x 2" approx. Weight: 6 ozs. Supplied with circuit and wiring instructions.

\$8.50
inc. postage.

WORLD FAMOUS POLYPACS

- No. 1—30 carbon resistors, asst. ½ watt and 1 watt, presets too. **\$1.**
- No. 2—20 asst. capacitors, 5 each paper, plastic, mica, ceramic. **\$1.**
- No. 3—20 silver mica capacitors, inc. 5 per cent values. **\$1.**
- No. 5—100 assorted rubber grommets. **\$1.**
- No. 6—35 assorted ½ watt resistors (English Erie). **\$1.**
- No. 7—25 assorted 1 watt resistors (English Erie). **\$1.**
- No. 8—50 assorted components, including resistors, mica condensers, tubular condensers, styrosea^l condensers, grommets, transistor transformer and potentiometer. **\$1.**

Guaranteed A1 quality. Popular brands. 1 pack postage, 4c. 3 packs, post free.



MONDO 6 TRANSISTOR TAPE RECORDERS MODEL MH-6A

Featuring—Automatic Level Control and simple Push Button Operation. Will take up to 5" reels. 2 speeds 3½ and 1½ I.P.S. Capstan Drive. Microphone has remote control switch. Twin track.

\$55.00
Freight Free.

NEW POWER SUPPLY BASIC KIT


Consists of:
One Transformer tapped for 9V and 12V at 500 m.a.
One full wave contact cooled Rectifier.
One 1000mfd 15 V.W. Capacitor. Make your own 9 or 12 Volt power pack to supply transistor radios, record players, slot cars, toys, etc. . . . Supplied with wiring diagram.

\$3.00
Inc. postage.




WARBURTON FRANKI

220 PARK ST., STH. MELB., VIC. Ph. 69-0151 (30 lines)



• PLEASE INCLUDE POSTAGE OR FREIGHT WITH ALL ORDERS. • OPEN SAT. MORNINGS.

Basic Radio Course



CHAPTER 26: Sound transmission. The TV channel. Receiver functions. The tuner. IF amplifiers. Video detector. Intercarrier sound. Sound IF. Video amplifier. Sync separator. Differentiation and integration. Vertical oscillator. Horizontal oscillator. Flywheel circuits. Vertical output circuit. Horizontal output circuit, EHT, boosted HT, AGC. Power supply.

In the previous chapter we discussed the basic principles of television, the manner in which a television signal is generated, and the final form it takes when ready for transmission. Briefly, this consists of a complex waveform comprising the video information on a line by line basis, interrupted at the end of each line by a line synchronising pulse, and at the end of each field by a block of field synchronising pulses. In this chapter we plan to discuss how the signal is received and processed by the receiver.

First, however, a brief mention of one aspect of the transmission which we had insufficient room to discuss in the previous chapter—the sound (or audio) signal. Because sound transmission is something with which we are relatively familiar, there is a tendency to take it for granted in association with TV. In fact, it must be treated as a part of the overall system if good results are to be obtained.

Early TV systems—including the British 405 line system which is still in operation—used AM sound transmitted on an adjacent frequency. Later systems switched to FM sound, both to take an advantage of the superior noise rejection properties of this system and to simplify some aspects of sound and picture separation in the receiver.

Australian TV uses an FM sound system, with a deviation of plus and minus 50KHz, an audio response to 15KHz, and treble pre-emphasis amounting to approximately 13dB at 15KHz, relative to 1KHz. Treble pre-emphasis is a fairly standard procedure for FM program transmissions to provide as much protection as possible against noise. Complementary de-emphasis is provided in the receiver to produce a level response from the audio system. The sound transmitter is normally located higher in frequency than the picture- or video-transmitter and, in the Australian system, always exactly 5.5MHz away from it. The reason for this precise spacing will be evident later.

In greater detail, the distribution of signals within an Australian TV channel is as follows: The picture carrier is located at 1.25MHz above the lower limit of the 7MHz channel, the sound carrier is 5.5MHz above this, and the upper limit of the channel is .25MHz

above this again. Vestigial sideband transmission is used for the picture carrier, which means that most of one set of sidebands (usually the lower) is suppressed. Australian practice is to suppress all but 1.25MHz of the lower sidebands adjacent to the carrier, and this is the reason for the picture carrier position 1.25MHz above the lower limit. Australian TV channel frequencies range from 45MHz at the lower limit of channel 0 to 222MHz for the upper limit of channel 11.


A brief comparison may be worthwhile here. Whereas one TV channel occupies 7MHz, the entire broadcast

constitute the complete TV transmission. It has to separate the sound from the video, the video from the sync pulses, the horizontal pulses from the vertical pulses, and then process each according to its requirements.

A logical place to start is the tuner. Physically, this is a self-contained unit, which may be mounted either directly on the chassis, or separate from it, where the cabinet layout dictates such an arrangement. Heater and HT power are derived from the main chassis, as is AGC (AUTOMATIC GAIN CONTROL) voltage. Signal from the tuner is fed to the chassis via coaxial cable.

Among other things, the tuner has to tune over a wide range of frequencies—approximately 50 to 200MHz to cover the 13 channels of the Australian system. Fairly obviously, such a requirement is beyond the scope of a simple variable capacitor tuning system as employed in a broadcast or short-wave receiver. Instead, a system of coil switching is employed with a set of coils being switched into circuit for each channel. A small variable capacitor is provided as a FINE TUNING CONTROL, to compensate for drift due to temperature, valve aging, etc.

How signals are distributed within a TV channel. Note the 5MHz space for picture information and the 5.5MHz spacing between picture and sound carriers.



band occupies about 1MHz. And into this we can put 100 sound transmissions each nominally 10KHz wide. (In fact, by means of channel sharing, the band is currently accommodating over 180 transmitters.) Thus, on a straight channel for channel basis, the total TV signal occupies 700 times as much spectrum space as a sound transmitter!

From all the foregoing it is quite obvious that the TV receiver has to handle a much more complex signal than a simple sound receiver. For one thing, it has to handle the 7MHz bandwidth of the transmitted signals, at the same time providing compensation for the vestigial sideband transmission and correct levels for sound and video signals to ensure minimum interference between them. And, having done that, it has to sort out the complex of signals which

There are two popular methods of selecting coils: (1) by means of more or less conventional rotary switch wafers, or (2) by means of a turret. In the switching system the switch contacts engage connections which are, in reality,appings on what amounts to one continuous coil. For the highest frequency channel only a small portion of the coil would be in circuit while, for the lowest frequency channel, the whole coil would be employed. This arrangement is called an INCREMENTAL TUNER.

The alternative arrangement provides a set of completely self-contained coils for each channel. These are mounted on plastic bases equipped with suitable contacts and, by reason of their shape and colour, are popularly referred to as "BISCUITS." They are supported between discs mounted on a central shaft,



University

GENERAL PURPOSE VACUUM TUBE VOLTMETER MODEL MVA 6

The UNIVERSITY High Impedance Vacuum Tube Voltmeter model MVA6 has been designed for utmost versatility and high stability coupled with minimum of controls and simplicity of operation.

The large "Easy to See" meter with clearly marked scales make University model MVA6 a pleasure to use.

All University instruments are backed by a comprehensive Sales and Service department thus assuring complete satisfaction.

PRICE \$42.00 PLUS TAX. PACKING & POST \$1.00

SPECIFICATIONS:

DC Volts:— (negative or positive)
0 - 1.5 - 5 - 15 - 50 - 150 - 500 - 1500 V DC
input resistance 10 Megohm.
H.V. Probe (HV.20) up to 30KV.

AC Volts:—
0 - 1.5 - 5 - 15 - 50 - 150 - 500 - 1500 V RMS
Frequency range 30 cps to 100 kcs.

Peak to Peak:—
0 - 4 - 14 - 40 - 140 - 400 - 1400 - 4000 V P. P.

Ohms:—
R x 10 - 100 - 1k - 10k - 100k - 1M - 10M
(0.2Ω—1000MΩ)

DB:— Ref. level 1mW in 600Ω line.
- 10db to plus 65db (7 Ranges)

Accuracy:—± 3% for DC Ranges
± 5% for AC Ranges

Power Supply:— 220 - 240 V AC 50 cps.

Battery:— 950 Cell 1.5 Volt

Tube Compliment:— 12AU7 - 6AL5

Dimensions:— 5.5" x 9.5" x 6" (140 x 215 x 152mm)

Weight:— 5.5 lbs (2.5 kg.)

FEATURES:

Large, 3 colour, Easy to read scale
Engraved Aluminium Front Label
Unbreakable front cover on meter
Printed Circuit
Rugged Steel Case finished in 2 tone grey Baked Enamel.
Complete with — Test Leads, Instruction Book and Battery.

ACCESSORIES:

HV.20 Probe:—To Measure D.C. Voltage up to 30KV
Dimensions 9½" (250mm) Weight 5oz. (140 gr.)
Trade Price — \$8.00 plus Sales Tax

RF-22 Probe:—Crystal RF probe 20V Max. up to 60 mcs.
Dimensions 6½" (160mm) Weight 3oz. (85gr.)
Trade Price—\$6.00 plus Sales Tax

Leather Carrying Case:—
Trade Price—\$6.00 plus Sales Tax.

UNIVERSITY GRAHAM INSTRUMENTS Pty. Ltd.,
106 BELMORE ROAD, RIVERWOOD, N.S.W.
Telephones: 53-8758, 53-0644 (5 lines)
Telegrams and Cables: Raquip, Sydney.

VICTORIA: EASTERN INSTRUMENT SERVICE Pty. Ltd.,
38 MILTON PARADE, MALVERN,
VICTORIA. Ph. 20-1156

W.A.: Atkins (W.A.) Ltd.,
894 Hay Street, Perth, W.A.
S.A.: Jason Trading Co., Pty. Ltd.
33 Market Street,
Adelaide. Ph. 51-6263.

Representatives:

QLD.: Keith Percy and Co. Pty. Ltd.,
Waterloo St., Newstead, Bris.,
Qld.

TAS.: W. P. Martin and Company,
202 Argyle Street, Hobart,
And 150 Wellington Street,
Launceston.

AUSTRALIA'S LEADING MANUFACTURER OF ELECTRICAL INSTRUMENTS

in such a way that the contacts face outwards. As the central shaft is rotated, the coil assemblies rotate with it, each set making contact in turn with a set of fixed, wiping contacts. A mechanical indexing system on the central shaft ensures that each set of coils are moved into exactly the right position to correctly engage the contacts. Such an arrangement is known as a **TURRET TUNER**.

Electrically, tuners consist normally of two stages, an RF amplifier and local oscillator/mixer. The RF amplifier is usually a twin triode in a **CASCADE** configuration, a very popular arrangement which provides a useful order of gain with low inherent background noise.

The mixer/oscillator stage usually employs a triode/pentode valve, with the triode in the oscillator circuit and the pentode functioning as the mixer. The tuner is designed to have a bandpass wide enough to encompass the full bandwidth of the TV channel—7MHz—and the “Q” and coupling of the tuned circuits are selected with this in view. As with normal superheterodyne practice, the local oscillator runs at a higher frequency than the incoming signal and this transposes the relative positions of the video and sound carriers. Whereas the sound carrier is transmitted as the higher frequency it appears as the lower intermediate frequency.

The Australian system has used two intermediate frequency standards. The first specified 36MHz as the picture IF and 30.5MHz as the sound IF. More recently, alternative values of 36.75 and 31.25 have been adopted by some manufacturers in an effort to minimise spurious patterns which can occur in some circumstances. Note particularly that, regardless of the IF, the 5.5MHz difference between sound and picture is retained.

From the tuner, the signal goes to the IF channel. As well as amplifying the signal, the IF channel has the job of “shaping” the receiver’s response to the various frequencies within the passband, an important function which can have a marked bearing on the quality of the picture and sound.

In short, the IF channel, like the tuner, must accommodate the full 7MHz bandwidth of the channel, but with the difference that it is not required to respond to all frequencies equally. To achieve adequate bandwidth several stages are employed—from two to four typically—with several tuned circuits. These latter may be loaded with resistors to reduce their “Q” and broaden their response, while the coupling between them is arranged also to produce the same effect. In addition, the various circuits are stagger-tuned, that is, tuned to different frequencies within the required passband.

It is usual to refer to the IF channel response characteristic as the **SHAPE**. This is a convenient concept because the method of adjustment employs a **SWEEP GENERATOR** and a cathode ray oscilloscope, the latter portraying the response of the channel in graph form. Thus we tend to think of, and discuss, the response in terms of the graph’s shape.


One major requirement of the IF channel is to compensate for the vestigial sideband transmission system. As we explained in the previous chapter, all but about 1.25MHz of one picture sideband is suppressed at the transmitter, this being the maximum amount of suppres-

sion which is practical at the present state of the art. This means that, for the first 1.25MHz on either side of the picture carrier, the system is essentially a double sideband system, and transmits twice as much sideband power as it does for higher frequencies, where the system is essentially single sideband.

To compensate for this the IF channel must be adjusted so that its response to the 1.25MHz double sideband signals is less than its response to the remaining

designed to ensure—for quite complex reasons—that picture signals do not appear at more than minimal strength in the sound system.

From the IF channel the signal goes to the picture—or video—detector. This functions in exactly the same fashion as the detector in a conventional sound receiver and is normally a diode—either valve or solid state. From the detector we get our video signal and, to ensure that the full video bandwidth is obtain-



Although a little dated, this exploded drawing of a turret tuner gives an excellent idea of the mechanical principle involved. Ease of coil adjustment or replacement is a major feature of the turret system.


single sideband signal, and by the correct amount at each frequency. Thus the response is “down” at the picture IF (say 36MHz) but increases steadily to 34.75MHz after which it levels off for the remainder of the picture response channel. This extends, in theory, for 5MHz, to 31MHz, although individual IF systems will vary in their ability to reach this value.

Beyond the 31MHz point the response is required to drop sharply before reaching the sound carrier IF at 30.5MHz. Here the response must form a plateau as wide as the deviation of the FM system (100kHz) and approximately 10 p.c. of the height of the maximum picture signal response. The height of the plateau is moderately critical and is

ed, extreme care is taken to reduce stray capacitance to a minimum, and to boost the high video frequencies where necessary to offset any losses. The video signals then pass to the video amplifier.

However, another type of signal is present in the detector circuit and the manner in which this is used is one of the cunning tricks employed by TV engineers. The signal is a 5.5MHz beat, caused by the difference between the sound and picture carriers. This beat contains both FM sound modulation and AM picture modulation but, by employing suitable limiting circuits, the AM content can be eliminated, leaving the FM sound signal only.

So, connected to the video detector we have an auxiliary IF amplifier, the



A block diagram showing the main sections of a TV receiver. Refer to it as each section of the receiver is discussed.

SONY TC-105



only recorder on the Australian market that gives all these features for \$199.50 list

Features ■ Four-track monophonic — 12 hours of recording and playback ■ Reliable all-transistor circuit using Silicon transistors ■ 3 speeds ■ Automatic recording volume control "SONY-O-MATIC" ■ Wide, smooth frequency response and rich output ■ Easy and quick tape loading with "retractomatic" pinch roller and self-threading "SONY-O-MATIC" reel ■ Speaker monitoring and public address facilities ■ Automatic shut-off, instant stop lever with locking facility, digital tape index counter, speaker on/off switch, tone control, voltage selector, professional level meter, etc.

Model TC-105 SONY's new model TC-105 is a versatile four-track monophonic portable tape recorder with truly dependable all-transistor circuit. Designed to meet everyone's purpose and requirements, it also contains professional facilities: 3 speeds, tone control, digital tape index counter, VU meter, lockable instant-stop lever, speaker on/off switch, voltage selector, 7-inch reel capacity, etc. Its extremely narrow gap head assures precise recording in wide frequency range and reproduction of high fidelity with rich 4 W. output from a large, oval dynamic speaker.

SPECIFICATIONS

Power requirement: 100, 110, 117, 125, 220 or 240 V., 50/60 c.p.s. 45 W.
Tape speeds: Instantaneous selection $7\frac{1}{2}$, $3\frac{3}{4}$ or $1\frac{1}{8}$ i.p.s. (19, 9.5 or 4.75 cm/s.)
Tracks: 4 tracks, monophonic
Recording Time: 45 minutes per track, 3 hours in total at $7\frac{1}{2}$ i.p.s.
(With 1800'/550 m. tape) 1.5 hours per track, 6 hours in total at $3\frac{3}{4}$ i.p.s.
3 hours per track, 12 hours in total at $1\frac{1}{8}$ i.p.s.
Reels: 7" (18 cm.) or smaller
Frequency response: 40-18,000 c.p.s. at $7\frac{1}{2}$ i.p.s.
40-13,000 c.p.s. at $3\frac{3}{4}$ i.p.s.
50-6,000 c.p.s. at $1\frac{1}{8}$ i.p.s.
Flutter and wow: Less than 0.17% at $7\frac{1}{2}$ i.p.s.
Less than 0.3% at $3\frac{3}{4}$ i.p.s.
Less than 0.4% at $1\frac{1}{8}$ i.p.s.
Record/Playback head: In-line quarter track
Erase head: In-line quarter track
Inputs: Low impedance microphone (1)
High impedance auxiliary input (1)

Outputs: 8 ohm external speaker output (1)
High impedance monitor jack (1)
Integrated record/playback connector: 1
Speaker: 4 x 6" (10 x 15 cm.) PM dynamic
Power output: Max. 4 W.
Transistors: 2SC402 (4), 2SB381 (1), 2SB383 (1), 2SD28 (2)
Diodes: FRIU (1) IT22 (1) 5G-D (2)
Dimensions: $14\frac{3}{4}$ (w.) x $7\frac{1}{4}$ (h.) x $13\frac{3}{8}$ (d.) (37.5 x 18.5 x 34.0 cm.)
Weight: 21 lbs. (9.5 kgs.)
Accessories: SONY dynamic microphone
5' self-threading reel
Pre-recorded 5" reel demonstration tape
Earphone
Connection cord
Head cleaning ribbon
Splicing tape
Optional accessories: Telephone pick-up, TP-4S Microphone mixer, MX-600

SONY

Distributors: Jacoby, Mitchell & Co. Pty. Ltd., Sydney & Melbourne.

To: Jacoby Mitchell & Co. Pty. Ltd. 469-475 Kent St., Sydney.
Send me information on Sony Tape Recorders & name of nearest Sony retailer.

NAME

ADDRESS

EA

sound IF amplifier, operating at 5.5MHz. It incorporates the necessary limiting stage and is followed by some form of FM detector which extracts the audio component and feeds it to a conventional audio amplifier. De-emphasis of the high audio frequencies normally takes place within this amplifier.

The main advantage of this form of sound system, called the INTER-CARRIER system, is that it provides a high order of sound stability. The 5.5-MHz IF is determined by the two transmitter carriers and thus remains absolutely constant, regardless of any drift in the receiver tuner. In older receiver designs (never used in Australia) the sound IF was as delivered by the tuner, and so would vary as the fine tuning control was adjusted. Careful adjustment of the fine tuning control was necessary to produce undistorted sound, while small orders of local oscillator drift in the tuners, having negligible effect on the picture, could seriously distort the sound.

To ensure that the inter-carrier system functions correctly, it is essential that the video carrier never be allowed to drop to zero. Should this happen, there would be no carrier against which the sound carrier could beat to produce a 5.5MHz IF, and there would be a momentary loss of sound. For this reason the transmission standards specify that peak white should never cause the carrier level to fall below a specified value (about 10 p.c.) instead of to near zero, which would be the natural assumption.

The intercarrier system is the reason that the sound channel is so trouble-free in modern TV receivers. No matter how the set is tuned—or mistuned—the sound remains substantially undisturbed. This is a vast improvement on early designs, which were quite critical in this respect.


Reverting to the video signal as it comes from the detector, this is then passed to the video amplifier. This is usually a single stage, although some designs may use two stages. The major requirement is a suitable order of amplification together with an adequate bandwidth, the latter requiring, nominally, to cover from below 50Hz to 5MHz. Careful design is required to achieve this, in regard to both the circuit and the physical layout. Stray capacitance must be reduced to a minimum and high frequency compensation used to offset losses which cannot be avoided. In addition, a 5.5MHz trap circuit is employed to reject the inter-carrier sound IF signal and preventing it from appearing as an interference pattern in the picture.

Somewhere in the video amplifier there is usually a variable gain control, which becomes the CONTRAST control on the front of the set. This may be regarded as analogous to the volume control on a sound receiver. However, some designers prefer to associate the contrast control with other sections, such as the IF amplifier.

The output of the video amplifier is an amplified version of the composite video signal, i.e., the actual video information plus the vertical and horizontal sync pulses. This signal is fed to the grid/cathode circuit of the picture tube, often via the cathode rather than the grid, for reasons of convenience. The fact that the sync pulses are included is of no consequence, since they are "blacker than black" as already explained.

However, the sync pulses have not yet performed any useful function. Before they can be employed they have to be separated from the video information and the stage which performs this is called a SYNC SEPARATOR. The sync separator is normally fed from the output of the video amplifier, thereby taking advantage of the amplification which this provides.

Separation of the sync pulses from the video information is based on the difference in amplitude between the two.



The "shape" of a TV IF amplifier as displayed on a CRO. It is a practical curve which comes very close to the theoretical ideal. Check the frequencies shown against the text.

The sync separator might best be described as an amplifier stage deliberately biased well beyond cut-off. Imagine a valve operating under conditions of low plate voltage and high negative grid bias. Such a stage would not function at all for signals of only moderate amplitude, but would function during part of the positive cycle if we applied a signal of sufficient amplitude.

In practice, we arrange that the video signal fed to such a stage will have positive going sync pulses. We also arrange the operating conditions of the valve so that the amplitude of the video information is just insufficient to overcome the bias. Only the higher amplitude positive-going sync pulses can do that, and so they appear as amplified pulses, minus the video information, in the plate circuit of the stage.

Since the amplitude of the video signal will vary widely according to the strength of the incoming signal, it is obviously not possible to use a fixed operating condition for the sync separator. Rather must it be able to adjust itself to any likely signal amplitude. This is achieved by using the video signal itself to generate the bias for the stage. Each positive sync pulse drives the grid positive, causes grid current to flow and generates a voltage across a resistor in the grid circuit. This voltage is stored as a charge in a capacitor and is of such polarity and amplitude that it drives the grid beyond cut-off when the sync pulse finishes, and holds it there until the next sync pulse occurs.

With the sync pulses effectively separated from the video, it is now necessary to separate the vertical and horizontal pulses from each other in order that they may be directed to their respective deflection oscillators. The main difference between these pulses is their duration. The horizontal pulses are relatively short and occur 15,625 times a second. The vertical pulses are, individually, several times longer and, in addition, are presented in a block of five. This block occurs 50 times a second.


The two circuits used to separate

these pulses are called the DIFFERENTIATING circuit and the INTEGRATING circuit. The differentiating circuit selects the horizontal pulses and the integrating circuit the vertical pulses. The differentiating circuit may be likened to a high pass filter, or one which does not respond to low frequencies. With associated circuitry it is made to respond to the leading edge only of all the pulses—vertical and horizontal.

The integrating circuit has opposite characteristics, and may be likened to a low pass filter, or one which does not respond to high frequencies. It ignores the horizontal pulses, but responds to the longer, individual, vertical pulses. These it adds together, or integrates, to make one large pulse.

The reason for using five separate pulses, which must be added together to form one large pulse, rather than simply presenting one large pulse, is to enable the horizontal pulses to be retained during this period. It will be remembered that we said that the differentiating circuit responded to the leading edge of all pulses and this fact makes it possible to continue to transmit horizontal pulses, in the form of serrations in the vertical pulse, while the latter is being transmitted. If this were not done, the horizontal oscillator would drift out of sync during each vertical pulse period, and might not be restored in time for the first lines of the new frame.

From the integrating and differentiating circuits the sync pulses are directed to their respective oscillators. The simpler of these two is the vertical oscillator, to which the pulses from the integrating circuit are directed, so we will consider it first.




A differentiating circuit (a) and a normal input waveform (b). At (c), (d), and (e) are the output waveforms as the capacitor is made progressively smaller. The (e) waveform is as required in a TV receiver.



NEW VERSATILITY VARIPAK II

PRINTED CIRCUIT CARD ENCLOSURE




VARIPAK II is our improved printed circuit or matrix board card enclosure designed to provide maximum density coupled with complete flexibility. It has, in addition, the following features:

1. Simplicity of Card Guide design offers greater strength.
2. Guides can be easily inserted into Guide Plate and also quickly removed from any position without damage to either the Guide or the Guide Plate.
3. Card Guides have sufficient float to allow for any tolerance accumulation between the Card Guide and connectors.
4. Guide Plate fabrication from extruded aluminium provides a much stronger unit.
5. Connector Panel is assembled with machine screws and nuts rather than self-tapping sheet metal screws.
6. Sixteen standard sizes covering a wide range of printed circuit card sizes are available.
7. Special sizes can be provided with little or no tooling charges.

DUAL PURPOSE MODULE ENCLOSURE PRINTED CIRCUIT OR MATRIX CARD

The Elco 5002/4 Series Printed Circuit Connectors shown with a printed circuit board is unique in its design and flexibility. The actual connection is made by a male contact attached to the P.C. board by a simple staking operation. This ensures a degree of reliability which cannot be obtained by the old method of connection. This method relied on the foil of the P.C. board for the actual male contact and unlike the ELCO contact, did not provide the gold surface now considered almost essential by experienced circuit engineers. The connector itself is made from individual modules and can be readily altered if this becomes necessary at some later date.



An ELCO 5023 Series Printed Circuit Connector with a Vector-Board Type 837BWE epoxy glass matrix board is an ideal combination for prototypes. The strong board will withstand even the most rugged handling and can be drilled or punched for mounting components with no danger of cracking or breaking. Elco contacts may be quickly staked to the board, if required and by using the special MINI-KLIP terminals for component mounting, the board may be wired in the same actual layout which will be used when a printed or etched circuit module is made. This means that even in the very early prototype stage the circuit can have all the advantages of plug-in facilities.

POST TODAY for information

- ☐ Varipak card enclosure ☐ Vector matrix boards
☐ Elco plugs and sockets

NAME

ADDRESS

Elco (Australasia) Pty. Limited
(A subsidiary of International Resistance Holdings Limited)
The Crescent, Kingsgrove, N.S.W.
Telephone: 50 0111

This oscillator can take a variety of forms, but they all have one requirement in common—ability to be readily triggered by a synchronising pulse. Also, they invariably employ the same basic circuit, a resistor and capacitor in series connected across a supply voltage. Such a circuit will develop a steadily rising voltage across the capacitor, commencing at zero at the instant the supply voltage is applied and rising towards the supply voltage at a finite—and predictable—rate. The actual rate will depend on the values of the capacitor, the resistor, and the supply voltage, all of which may be made substantially constant.

This rising voltage, or a current derived from it, is used to move the scanning beam down the face of the picture tube, thus providing the vertical portion of the scan. When it reaches the bottom of the screen, means must be provided to return it quickly to the top and commence another downwards trace. This is done by rapidly discharging the capacitor, then leaving it to complete another charging cycle, and so on in a regular pattern. This pattern, when portrayed graphically, looks like the teeth of a saw and, in fact, is called a SAWTOOTH waveform.

To discharge the capacitor we might envisage an ordinary mechanical switch which is closed just long enough for this purpose, then opened again to allow the next charging cycle to commence. Fairly obviously, a mechanical switch would be impractical in such a role, but we can use various forms of electronic switch. Typical examples are the thyatron, or gas triode, conventional "hard" valves, or transistors. Only the last two are employed in modern TV sets.

A popular arrangement uses the **BLOCKING OSCILLATOR**. A blocking oscillator is one which is designed to alternately oscillate and "block" itself off by reason of its own oscillation. As with other types of oscillator, this type generates its own bias by reason of grid current, the voltage being developed across the grid resistor and stored as a charge in the grid capacitor. If these two components are made large enough a burst of oscillation will not only generate enough bias to cut the valve off but this condition will be retained for a relatively long period until the capacitor can discharge through the grid resistor. When it has discharged sufficiently the circuit will again oscillate, and the blocking process will be repeated.


These short bursts of oscillation, separated by relatively long periods of inactivity, can be used to perform the switching function needed to discharge the capacitor in our sawtooth network. The blocking oscillator valve is, in effect, connected in parallel with the sawtooth capacitor, and discharges the latter when it conducts during the brief oscillatory cycle. The time between bursts of oscillation is made approximately equal to the vertical scanning period.

More precisely, it is made slightly longer. Then vertical sync pulses, of positive polarity, are fed to the grid of the valve. These over-ride the negative charge left on the grid, causing the stage to oscillate (and subsequently block) earlier than it otherwise would, and precisely in step with the signals radiated from the transmitter. Thus the vertical deflection circuits are exactly synchronised with the transmitter.

Another popular vertical oscillator circuit is the **MULTIVIBRATOR**. This requires two amplifying devices and typi-

cal circuits usually employ a twin triode valve. Although the oscillator functions in a somewhat different manner, it also depends on the rate of discharge of a capacitor to allow a valve grid to rise sufficiently above cut-off to function, and therefore can be triggered by a positive sync pulse if the natural frequency of oscillation is made slightly slower than is required.

As a matter of interest, the natural rate of these oscillators is normally controlled by the vertical hold control on



An integrating circuit. Compare it with the differentiating circuit on the previous page.

the front panel of the TV set. The user has to set it so that the oscillator stage is running slow and, although he may not appreciate what he is doing, he manages this quite easily by simply adjusting it until the picture locks. The amount by which the stage runs slow is not critical within reasonable limits.

The horizontal oscillator could use similar circuitry to that just described for the vertical stage, assuming that the values of the frequency determining components were changed to suit the line frequency (15,625Hz) rather than the frame frequency. In fact, such arrangements were used in early commercial receivers and may still be used in simple experimental sets. Modern sets use a


able inertia. While they are synchronised by the station sync pulses, they will not respond to short-term changes—i.e., from line to line—which may occur, or appear to occur, in the line pulses.

Since, in fact, such changes do not (or should not) occur in properly controlled transmissions, it is quite in order to employ a circuit which is incapable of responding to them. Should they seem to occur they must really be spurious signals and should be ignored.

Such flywheel circuits take a number of forms, but many are based on the use of an oscillator of a type which can be readily controlled by the application of a DC control voltage. This voltage is produced by comparing the phase of a sample pulse taken from the output of the line oscillator, and the sync pulse from the transmitter. While ever these are in agreement, no correction signal is applied to the oscillator but, should an error occur, a correction signal is generated which changes the frequency of the line oscillator by the required amount and direction. However, capacitor networks associated with the control voltage give it a suitably long time constant.

In a discussion of this nature it is impossible to discuss all these circuits in detail. The best we can do is to give a broad outline. One popular arrangement, called the **Synchro-Guide**, uses a blocking oscillator similar to that already described for vertical oscillators. However, instead of feeding positive sync pulses to the grid of the valve to trigger oscillation at a precise moment, it is fed with the steady positive voltage derived from the phase comparator circuit. This opposes the valve's self-generated negative bias, more or less according to the value of positive voltage, and so varies the time between bursts of oscillation, or the rate at which the oscillator functions.

Basic sawtooth generator circuit, and typical waveform. In practice, "S" is replaced by an electronic switch of some kind.



more refined system which has a number of advantages.

The main disadvantage of the simple system is its tendency to trigger prematurely, due to random noise pulses present with the signal. Unless the signal is very strong, giving a high signal-to-noise ratio, noise pulses can be strong enough to be mistaken for a sync pulse, at the moment the oscillator is primed for triggering by either. The result is a degree of random sideways misplacement by successive lines which, though small, gives the picture a shimmering effect and renders it less acceptable than it should be.

The circuits which have replaced it are generally known under the broad title of **FLYWHEEL** circuits, though sometimes also referred to as **AUTOMATIC FREQUENCY CONTROL (AFC)** circuits. (Do not confuse the term "flywheel" used in this context with the same term sometimes used to explain the behaviour of tuned circuits.) The flywheel circuits, as their name implies, behave as if they have consider-

Another popular system uses a multivibrator oscillator in conjunction with a discriminator circuit. In this arrangement two sets of sync pulses, of equal amplitude and opposite polarity, are applied to a discriminator circuit consisting of a pair of diodes. To this network is also fed a sample pulse from the line oscillator and the comparison of these pulses results in an output which is either positive or negative according to whether the oscillator is running too slow or too fast. Applied to the grid of the multivibrator stage it will either speed up or slow down the repetition rate as required.

As distinct from the circuits just discussed, in which a DC voltage is used to control an oscillator directly, there is also a scheme which employs a more conventional type of Hartley or Colpitts oscillator controlled indirectly by means of a reactance valve. Since oscillators of this type cannot be controlled directly by DC voltages, the DC voltage derived from the phase comparing network is fed to the grid of a reactance



A smug TV Serviceman

He can afford to be smug... he knows Thomas can supply him with both new and replacement TV picture tubes of any SIZE or TYPE, test tubes too! AND Thomas give him same day speedy delivery service.


Thomas guarantee both new and replacement picture tubes against all manufacturing defects for 12 months. Replacement tubes are made from ALL

new materials — only the glass bulb is used again.

Country servicemen please note:-

You may phone your orders to Thomas and reverse the charges, and we will pay the first \$1 of freight charges. Daily delivery to country areas by passenger train or road transport.

So get smug — call Thomas!




THOMAS ELECTRONICS

SALES INQUIRIES AND TECHNICAL DATA AVAILABLE FROM: **N.S.W.:** THOMAS ELECTRONICS OF AUST. PTY. LTD. 12 Larkin St., Riverwood — Telephone 53 0721. **R. W. WINNING PTY. LTD.** (Selling Agents) 225 Clarence St., Sydney — Telephone 29 2111. **VIC.:** THOMAS ELECTRONICS OF AUST. PTY. LTD. 131 Burwood Rd., Hawthorn, E.2. Vic. — Telephone 81 0294. **QLD.:** GRADWELL & CO. PTY. LTD. 42 Grenier St., Valley, Brisbane — Telephone 5 4881. **S.A.:** RADIO & ELECTRIC WHOLESALERS LIMITED. 10-12 Orsmond St., Hindmarsh — Telephone 46 4041. **W.A.:** SIMON HOLMAN & CO. 184 Roe St., Perth — Telephone 28 1666. **TAS.:** W. & G. GENDERS PTY. LTD. HOBART 2 7201 — LAUNCESTON 31 2511. ALSO DEVONPORT AND BURNIE.

The final anode of a TV picture tube requires a voltage of around 15,000, more or less according to the size and type of tube. Generating voltages of this order presented a problem in early designs, since it meant large and expensive power transformers and associated filter components. Later it was realised that, by using frequencies substantially higher than the mains, much simpler equipment could be used. Not only could the transformer be reduced to a fraction of its original size, but the higher frequency greatly simplified the filter circuits and reduced the capaci-

The boosted HT supply is really a natural by-product of an essential part of the deflection system: the DAMPER DIODE. The damper diode is used to suppress unwanted oscillations in the output circuit, generated by the abrupt nature of the waveforms involved. By the addition of a few extra components it is easy to add from 150 to 300 volts to the main HT line, providing a boosted HT supply of up to 600V and capable of supplying several milliamps. This is most useful for the de-

The amplitude of horizontal signals generated in the output stage is quite



The Synchro-Guide. The right hand triode and associated circuitry is a conventional blocking oscillator. The other triode compares the synchro pulses with the line output pulses, and generates a cathode voltage which is applied to the blocking oscillator grid for frequency correction.







While it is possible to provide a simple AGC system which uses the entire video signal, such an arrangement has limited use in commercial sets. What is needed is a system which will respond to the true signal strength of the transmitter, rather than one which is confused by the varying video content. The only constant level transmitted by a TV station is the sync pulse

Throughout this discussion, explanations have been based on the use of valves for all the functions in a TV receiver. This is logical, since TV sets evolved around these devices, and they are still predominant in locally produced sets. However, all these valves (with the exception of the picture tube) can be replaced by solid state devices (transistors, diodes, etc.) and which will perform as well or, in some respects, better. A number of manufacturers, both locally and overseas, are producing all solid state TV receivers, both portable and full-size. Doubtless it is only a matter of time and economics before they replace valves completely in this role. ■

CHOOSE THE BEST

A LOUDSPEAKER UNIT

GOODMANS FULL RANGE SINGLE UNIT HIGH FIDELITY LOUDSPEAKERS

-  **AXIETTE 8** (8 inch—6 watt—15 ohm)
The smallest full range High Fidelity loudspeaker unit produced.
-  **AXIOM 10** (10 inch—10 watt—15 ohm)
The very popular and economical "medium size" High Fidelity loudspeaker.
-  **AXIOM 80** (9½ inch—6 watt—15 ohm)
The hand-built twin cone transducer featuring exclusive "free edged" suspension giving very high quality sound reproduction for the connoisseur.
-  **AXIOM 201** (12 inch—15 watt—15 ohm)
The remarkable 12" twin-cone High Fidelity Speaker for the enthusiast who does not require the higher power handling of the Axiom 301.
-  **AXIOM 301** (12 inch—20 watt—15 ohm)
The world's most advanced 12" High Fidelity twin cone loudspeaker.
-  **TRIAXIOM 1220c** (12 inch—20 watt—15 ohm)
Triple element 12" loudspeaker, spanning over 9 octaves giving professional standard High Fidelity. Complete with adjustable Treble control.

—BUILD UP A SYSTEM

GOODMANS MULTIPLE SPEAKER HIGH FIDELITY SYSTEMS

consist of an Audiom Bass unit and pressure-driven horn-loaded mid-range and high frequency units, with crossover networks and attenuators. The result—very low distortion, high sensitivity 3-way loudspeaker systems.

BASS UNITS

(12 inch—15 watt—15 ohm) **AUDIOM 51 BASS**
Rugged 12" single diaphragm speaker, specially designed as Bass unit in a 3 way system.

(12 inch—20 watt—15 ohm) **AUDIOM 61 BASS**
Powerful, extra high efficiency 12" unit, giving exceptional performance and control—ideal as Bass unit in 3 way systems.

(15 inch—25 watt—15 ohm) **AUDIOM 81 BASS**
Capable of handling high power with very low distortion. Ideal in high powered 3 way High Fidelity systems.

(18 inch—50 watt—15 ohm) **AUDIOM 91 BASS**
Exceptionally robust, heavy duty 18" loudspeaker for very high power systems.

N.B. Multiple Speaker Systems can also be "stage-built" using Axiom 201 or 301 as the first stage unit. Full details in the High Fidelity Manual.

Standard Versions of all Audiom speakers are available for Public Address work and Musical Instrument amplification (Electric guitars etc.)




CHOOSE GOODMAN'S

A COMPLETE SYSTEM IN MINIATURE

GOODMANS MAXIM

Only 10½" x 5½" x 7¼" deep. Fantastic! but true—the smallest true High Fidelity loudspeaker system made. No bigger than a stout book, but with a really outstanding performance. Up to 8 watts of power.



COMPONENTS FOR MULTIPLE SPEAKER HIGH FIDELITY SYSTEMS

TREBAX HIGH FREQUENCY PRESSURE UNITS

TREBAX 100 Range 2,500-20,000 c/s, covering the treble register smoothly with very low distortion. Crossover frequency: 5,000 c/s. System power handling: 25 watts.

TREBAX 5K/20XL As Trebax 100 but handling 20 watts of power in systems. Complete with built-in crossover network and attenuator.

MIDAX MID-RANGE PRESSURE DRIVEN HORN UNIT

Range 650-8,000 c/s, covers the middle register with high efficiency and realism. Crossover frequencies: 950 and 5,000 c/s. System power handling: 25 watts.

CROSSOVER NETWORKS


XO/950/5000 Crossover frequencies 950 and 5,000 c/s. For use with Audiom Bass unit, Midax and Trebax 100.

XO/950 Crossover frequency: 950 c/s. For use when adding Midax to Axiom and Trebax.

XO/5000 Crossover frequency: 5,000 c/s. For use when adding Trebax 100 to Axiom unit.

ATTENUATOR

For use with Trebax 100 and Midax. 8-step, 0db-12db and "off".



STILL UNDECIDED?

Call at your Goodmans Dealer for a demonstration or send for Goodmans High Fidelity Manual, giving full specifications and information.

Made in England by Goodmans Industries Ltd.

Sole Australian Agent:

BRITISH MERCHANDISING PTY. LTD.

Shaw House, 49-51 York St., Sydney. Telephone 29-1571

FREE

Please send me details of Goodmans loudspeakers listed below.

Models required.....

Name.....

Address.....

State.....

A FUZZ-BOX for ELECTRIC GUITARS

By Anthony Leo



By popular request we are presenting a small but relatively useful adjunct to our series of guitar amplifiers. This "electronic fuzz-tone generator" may be interposed between guitar and associated amplifier to produce a guitar sound which is known commonly as "fuzz".

The completed fuzz-box, styled to rest on the floor near the guitarist's foot. The fuzz/normal switch is on the sloping panel, while the combined fuzz control pot, and off/on switch is on the horizontal panel.

From the many requests we have had for such a unit, it is a foregone conclusion that guitar enthusiasts will say: "Thanks; it's just what we've wanted."

It is equally likely that guitar non-enthusiasts will ask: "What the heck is a fuzz-box?" Perhaps we owe such readers an explanation.

Bluntly, a fuzz-box is a piece of circuitry which is introduced into the amplifier chain of an electric guitar, deliberately to distort the waveform. It produces a sound which is "buzzy" by nature, not unlike that from a heavily overloaded amplifier or from a loudspeaker whose voice coil is fouling in the magnet gap. In fact, the similarity of fuzz to overload is no accident, because a fuzz-box deliberately simulates or introduces an overload condition.

By nature, the waveform from an electric guitar ranges from the reasonably sinoidal to one carrying mainly consonant harmonics — depending on playing technique and the position of the pickup coils in use. A fuzz-box squares off, or clips or otherwise distorts the waveform envelope, adding multiple harmonics as it does so, and also adding further dissonant frequencies by intermodulation of those actually being fed in from the pickup coil. The naturally "round" tone of a guitar therefore takes on a strident quality, sometimes considered desirable for its sonic effect.

Just how a fuzz-box treats the wave envelope passing through it depends largely on the circuitry involved. Straight clipping circuits, for example, tend to square off the tops of the waveform, so that predominantly sinoidal waves begin to look quite square on a CRO. As might be expected, the sharper the corners, the wider is the spectrum of the harmonics so generated.


In actual fact, the current generation of guitarists tends to regard squared waves as too conservative in terms of fuzz, particularly when generated from substantially pure waveforms. This arises from the fact that a squared sine wave has a rather pleasant "woodwind" quality and is anything but strident. Again, while a broad spectrum of harmonics may be generated in the first instance by simple clipping, those above about 4KHz don't count for much in the average guitar situation.

The kind of guitar fuzz which is likely to have greater sonic impact is that in which there is a concentration of spurious harmonics within the normal musical range of a guitar system — that is, up to about 3KHz. Aurally, the requirement seems to be met best by circuitry which tends not just to clip waveforms, but to generate waves with generous overshoot at either or both ends of the plateau.

In the face of all this, it is natural to wonder what has happened to all the traditional concepts of minimising distortion in amplifiers. Why has something that has been so wrong for decades suddenly become so right for guitarists?

In part, the answer is that guitarists are creating music, not just reproducing it. If the presentation demands a sound which is strident, the guitarist is at perfect liberty to use an overload condition in the amplifier, if it gives him the effect that he wants.

However, old-fashioned rules still apply. A guitarist may



FUZZ BOX

The fuzz-box contains a two-stage direct-coupled transistor amplifier which operates at well under a milliamp of current drain from a small 9-volt battery. If the circuit configuration seems odd, it is basically because the device is designed deliberately to introduce a very large order of distortion.

use deliberate distortion to "roughen up" the output from a single string, on the basis that the number of frequencies initially present will not create a higher proportion of intermodulation and other non-musical components than is acceptable for the desired purpose. He may even find it practical to use fuzz for the same purpose with certain simple chords. But, for complex chords or rapid scale progressions, the number of spurious components will usually multiply to such an order that even the most way-out guitarist must stop calling the result "fuzz" and admit it to be old-fashioned and thoroughly unpleasant distortion.

In short, fuzz is a gimmick intended primarily to add stridency to single tones or, at most, simple chords. It cannot be used with complex chords and must be switched out of circuit before such chords are attempted. For the same reason, it has no place in amplifiers generally, or even in electronic organs, where playing techniques seldom call for single tones.

There are several methods for obtaining "fuzz," probably the simplest being to place two "back-to-back" semiconductor diodes across the speaker connection of the amplifier's output transformer. By connecting the diodes "back-to-back," both positive and negative peaks of the signal excursion are clipped.

Unfortunately there are certain disadvantages with this very simple method:

- (1) Having the fuzz circuitry applied to the amplifier rather than to the individual guitar means that the amplifier can only be used by one guitarist.

- (2) Because the diodes are virtually a short circuit across the output transformer, when conducting at the peaks

ORTOFON

WORLD LEADERS IN TONE ARM AND CARTRIDGE TECHNOLOGY!

* Over 90% of Australian radio and television stations (and recording studios) have standardised on ORTOFON moving coil pick-ups. Audio engineers with facilities for precise measurement specify ORTOFON; the ORTOFON moving coil system has been proven reliable, predictable and consistent . . . as well as being *inherently more linear*. Only ORTOFON cartridges satisfy professional demands for *stable, distortion-free pick-ups*.



The audio enthusiast seeking the ultimate in high-fidelity reproduction can purchase ORTOFON arms and cartridge with complete confidence for the **most realistic high-fidelity sound originates with ORTOFON**. The new ORTOFON S-15 series cartridge has been acclaimed by critics all over the world. Tracking angle is precisely 15° and the most complex wave form may be traced at 1½ grams stylus pressure; the superbly polished elliptical diamond stylus is fully protected should the cartridge be accidentally dropped to the record surface.

Specifications —

Frequency response: 20-20,000 Hz. ± 2 dB.


Static compliance: 20×10^{-4} cm/dyne.

Channel separation: 20-30 dB.

Stylus: 0.0007 x 0.0003 elliptical diamond.

Equivalent mass: 0.9 mg.

The ORTOFON elliptical diamond stylus closely approximates the shape of the original cutting stylus, and will track without distortion due to pinch effect . . . this freedom from distortion being obvious towards the label where pinch effect is always a problem. Illustrated is the popular SMG-212 tone arm fitted with the "G" shell. ORTOFON tone arms are available in nine models. When the open-front metal "G" shell is used any cartridge may be fitted. *We invite you to listen to ORTOFON today at your favourite hi-fi supplier; listen to the astounding difference!*



Australian National Distributors:

Simon Gray Pty. Ltd.

INTERSTATE REPRESENTATIVES:

S.A.: Eilco Sales Pty. Ltd., 7-9 Osmond Terrace, Norwood, S.A. Tel. 63 4844
Q'land: Sydney G. Hughes, 154-158 Arthur St., New Farm, Brisbane. Tel. 58 1014
W.A.: Athol M. Hill, 613-615 Wellington Street, Perth. Tel. 21 7861

Head Office:

28 Elizabeth Street, Melbourne, Vic.
Tel. 63 8101*

Sydney Office:


22 Ridge Street, North Sydney, N.S.W.
Tel. 92 3890

Tas.: K. W. McCulloch Pty. Ltd., 109 York Street, Launceston. Tel. 2 5322
A.C.T.: Australian Physical Laboratories, P.O. Box 225, Canberra City.
Tel. 4 3010 (Mr. J. E. Howe)
N.T.: Pfizner's Music House, Smith Street, Darwin. Tel. 3801

of the signal excursion, severe stress may be imposed on the output stage.


(3) Being a virtual short circuit at signal peaks, the diodes restrict the available output power and so cause an appreciable decrease of volume and power when "fuzz" is applied.

A rather neater method of using diodes is to introduce them across one of the voltage amplifying stages of the amplifier, the point being carefully chosen in relation to signal level and the position of other circuit functions such as volume control, tone control and vibrato. The method avoids waste of power output and stress on the output-stage but it still causes a change in level and still imposes the limitation that the amplifier can serve only one guitar at a time. We had a close look at the idea during the early stages of this present project but rejected it, for the stated reasons. As well, we could foresee difficulties in providing foot-switch control, without becoming involved in a relay or inconveniently long shielded cables.



At this point, it is appropriate to mention that there is a fundamental problem in the use of diodes for clipping, intrinsic to the semiconductor diode itself. Basically, such a diode is comprised of a junction of P and N-type semiconductor, the P-type semiconductor having a deficiency of mobile electrons, while the N-type has an excess of mobile electrons. When the two types of semiconductor are brought together to form a junction, there is a migration of the free electrons which tends to form a potential difference across the junction somewhat akin to "contact potential" of a thermionic diode.

This means that, for the diode to conduct in the forward direction, the applied voltage must be larger than the intrinsic "contact potential" of the junction. For this reason the diodes must



The diagram above and the photograph at left should make it possible for readers with only very limited experience to construct the fuzz-box for themselves. Some kind of clip or strap will need to be provided to hold the battery in position, while still allowing for replacement at infrequent intervals.

be placed in the circuit at a position where the peak signal swing greatly exceeds the diode potential, or as it is more commonly stated "the forward biased diode voltage drop." For reasonable clipping, the signal swing should be at least one volt peak.

Since the output signal from an electric guitar is typically less than 30mV peak, it is not practicable to achieve any useful order of clipping by introducing diodes directly across the guitar signal line. Thus, if fuzz circuitry is to operate in the signal line of individual guitars and ahead of the main amplifier, something other than diode clipping is called for.

The method which is preferred, and the one we have used, is to pass the guitar signal through a small transistor amplifier whose operating conditions can be modified to operate in overload mode from direct guitar signals. By building this kind of circuitry into a small box, complete with switch, each player can have his own independent fuzz box and players can share common amplifiers if they so desire.

A further advantage is that, with suitable provision, the relative loudness of the signal, with and without fuzz, can be made much the same, obviating any need to readjust the volume simultaneously with a switch from fuzz to non-fuzz.

The characteristics of our own unit may be summed up as follows:

(1) Completely self-contained, connecting between an individual guitar and its normal input jack to the main amplifier. While designed primarily to go with our current Playmaster 116 and 117 amplifiers, it will operate equally well with any normal guitar system.

(2) Output on "normal" and "fuzz" is at substantially the same level and, in both modes, the unit contributes a small amount of gain.

(3) In addition to the normal fuzz footswitch, a control allows the degree of fuzz to be varied as required.

As can be seen from the circuit diagram, the device consists of, basically, two DC coupled transistors operating as an amplifier in the guitar line. With the switch in the "fuzz" position, as shown, the load seen by the first transistor is the sum of 15K and 680K ohms and

Tape Recorder Enthusiasts Check Your Head Alignment & Frequency Response

TEST TAPES

REEL

NOW AVAILABLE

- No. 1. Pure tones 40-10,000 C/S with voice identification of each band at 7½ I.P.S. Track 2 continuous 7,500 C/S tone.
- No. 2. Pure tones 40-7500 C/S with voice identification at 3¾ I.P.S.
- No. 3. White noise one third octave bands 40-10,000 C/S track to full range unfiltered white noise at 7½ I.P.S.
- No. 4. White noise one octave bands 100-6400 C/S track two full range unfiltered white noise at 7½ I.P.S.
- No. 5. Azimuth and vertical head alignment tape can be used without test equipment at all tape speeds and 2 or 4 track heads.

EACH TAPE IDENTIFIED ON 3" REEL IN CARTON
PRICE \$7.20 EACH.

Also available: 40ft length of tape with white noise and 2-1" length of rubber magnetic strip on card with full instructions. Price \$1.20.

FULL DETAILS SENT ON RECEIPT OF STAMPED AND ADDRESSED ENVELOPE AVAILABLE FROM

J. H. McGrath Pty. Ltd.,
208 Lt. Lonsdale Street, MELBOURNE, VIC.

Electronic Developments Pty. Ltd.,
232 Flinders Lane, MELBOURNE, VIC.

DISTRIBUTORS:

COMTEL International (Vic.) Pty. Ltd.,
17 Rokeby Street, COLLINGWOOD, VIC.

ADELAIDE:
551437

SYDNEY:
564292

PERTH:
214621



LOW PRICED SOLID STATE STEREO AMPLIFIER

With 6 watts R.M.S. per channel, the Sound Model SAQ-202B must be regarded as exceptional value at this price. Separate bass and treble controls, input sens. is 100 mV. for pick-up, tuner and auxiliary. In attractive metal case. Frequency response is 20-20,000 Hz. plus or minus **\$49**
3 dB. 12 transistors

INTERCOMMUNICATION SYSTEMS


Look at these prices—and the variety! Gem 2 station—\$9.50. Gem 3 station—\$11.50. Eden 4 station—\$27.50. Eden 7 station—\$35.50. Fountain 2 station—\$14.10. Fountain 4 station—\$27.10. Fountain 7 station—\$44. All models are suitable for office, school and home and are fully transistorised.

IMPROVE STANDARDS WHEN RECORDING—DEMAGNETISE!

Two new tape head demagnetisers are now available . . . the single probe is Encel priced at \$3.50 and the double probe only \$3.00. Recording heads may be demagnetised in a few seconds and quality of recordings improved considerably. Essential for all tape enthusiasts.

SHORT OF SPACE? BUY A WHARFEDALE "LINTON"

Only 19" x 10" x 10" but a proven performer as a compact speaker system. Ask for an EMQ or a trade-in valuation.



COMPARE THE QUALITY OF THE NEW "SOUND" SAT-200X STEREO TUNER/AMPLIFIER

Here is an effective combination stereo tuner/amplifier with plenty of power for realistic stereophonic listening. Frequency response from 20-20,000 Hz. plus or minus 1 dB., output is 12 watts R.M.S. per channel (36 watts total music power). PP 6GW8's are used in both channels. The stereo AM tuner pulls in distant stations . . . and an FM stereo Multiplex tuner may be added. Switches are provided for scratch suppression, loudness control, rumble filter and tape monitor. Stereo 'phones plug into the front panel. All normal mode and tone controls are standard. Beautifully finished, this versatile amplifier has been designed for use with magnetic or ceramic/crystal pick-ups. Ask for detailed specifications **\$148**

SEE YOUR NEAREST ENCEL STEREO CENTRE FOR REDUCED PRICES ON THE FAMOUS LEAK SANDWICH SPEAKER SYSTEM!

The new reduced price applies at all Encel Stereo Centres . . . and stocks are also available of the new Leak Mini Sandwich. Both systems provide excellent audio, the smaller unit differing only in the lowest octave. Write for an EMQ or a trade-in valuation.

WHAT IS AN EMQ?

Because of trade agreements many prices cannot be advertised so we advise you to write to us for an EMQ . . . an Encel Mail Quote. Please print your name and address in BLOCK LETTERS . . . and, if you're writing for amplifier or tape recorder information, please be reasonably specific as our stock of these items is extremely wide. Help us to help you! Ask for copies of reviews.

ENCCEL SERVICE DIVISIONS

Modern and efficient service centres operate in Sydney and Melbourne. Up to the minute servicing equipment is provided and skilled technicians who have been specially trained actually save you money when service is necessary as time expended is kept to a minimum. Encel service does not cost—it pays.

MICRO/ORTOFON EXCLUSIVE OFFER!

A new model MA-77 or MA-77S tone arm complete with an Ortofon S-15 T stereo cartridge (diamond stylus, naturally) will be supplied for **\$79.50**
Ask for an EMQ on the S-15 cartridge only.

SPECIAL OFFER ON ALL-BALANCE ARMS!

We now have limited stock of the well-known and popular All-Balance tone arms—brand new and fully guaranteed. 12 in. model, for professional use. **\$13.50**
Encel price

DUAL MODEL 1010 A TURNTABLES REDUCED!

List price is \$69.80 for this popular Dual automatic record changer. **\$49.50**
Encel price is now

ASK FOR AKAI PRICES!


ALL AKAI models are in stock . . . M8, X4, 355, X1000D and 1710. Encel trade-in prices and end-user EMQ's are more than just attractive, too!

LOW PRICED CERAMIC CARTRIDGE FOR BUDGET CONSCIOUS MUSIC LOVERS!

Now the well known Micro Model SC301 Ceramic Stereo Cartridge with diamond stylus is available for only **\$6.90**. Frequency response is 20-15,000 Hz. Tracking angle is 15°. This popular stereo cartridge is A1 value at

TANDBERG "SERIES 12" RECORDERS AVAILABLE FOR IMMEDIATE DELIVERY!

This professional stereo recorder has proved to be a best-seller and stocks have been in one door and out the other . . . but now delivery is immediate. Write for trade-in valuations or an EMQ. Your great leap forward to Tandberg could cost less than you imagined at Encel Stereo Centres . . .



NEW UNOBTRUSIVE DYNAMIC MICROPHONE

The robust, pint sized dynamic microphone, the Piezo Model DX75, is supplied with a desk stand. Dual impedance is 50 k-ohms and 50 ohms. Ideal for tape recorder applications. Exceptional value at **\$6.90**

GET THE ENCEL FACTS

Pamphlets and technical specifications are usually available for most Encel merchandise. Write or call for further information.

THE NEW ORTOFON S-15 STEREO CARTRIDGE AVAILABLE AT ALL ENCEL STEREO CENTRES!

World wide acclaim provides significant testimony to the outstanding performance of the new S-15. Ask for an EMQ or a trade-in valuation.




HIGH FIDELITY STEREO 'PHONES COST LESS AT ENCEL ELECTRONICS!

Several wide range stereo headsets are now available — all are fitted with comfort-plus earpads which also reduce external noise. The Sonics costs only \$11.50; the popular Elegia is fitted with separate volume controls on each earpiece and is priced at only \$13. Connections are made with standard PMG type jacks. If your amplifier is not fitted with a headphone socket, we will supply an easily fitted junction box for only \$3. Stereo playback becomes more realistic than ever with hi-fi phones. **\$11.50**
From



SAVE YOUR RECORDS . . . USE THE UNIVERSAL "LUSTRE" TONE ARM LIFT!

This beautifully finished universal lift will fit all tone arms — the lowering action is hydraulically dampened and extremely smooth. The risk of record damage may now be eliminated **\$8.50**



NEW ZENZA BRONICA CAMERAS

The most famous 2 1/2 squ. reflex cameras in the world would be the Hasselblad and the Zenza Bronica — but only the latter has incomparable Nikkor lens equipment and a focal plane shutter. In consequence supplementary lenses are much lower in price. . . . The new model S2 Bronica has a detachable film back enabling change of film type in a few seconds and is attractively priced at \$299 complete with f2.8 75 mm. lens. The model C2 sells at only \$245. Both prices include sales tax. Encel Electronics Pty. Ltd. is the Australian Agent for Zenza Bronica. Ask for prices on the multitude of supplementary lenses and accessories. Encel prices are less than 1/3 U.K. prices and less than 3/4 U.S. prices for identical cameras.

Model S2—\$299

Model C2—\$245

NEW SYDNEY ENCEL STEREO CENTRE A MUSIC LOVER'S MECCA!

Although only just over one year old, the Sydney branch of Encel Electronics is a very healthy infant. Situated on the Ground Floor of the 2SM Building at 257 Clarence Street, the store incorporates a complete Service Centre. Harbor City music lovers are always welcome . . .

Encel

**ELECTRONICS
PTY. LTD.**

Head Office: 431 Bridge Rd., Richmond, Vic. Tel. 42 3762
Sydney Store: 257 Clarence St., Sydney. Tel. 29 4563, 29 4564
Australia's Greatest Hi-Fi Centre
* Wholesalers * Trade-Ins Accepted

PARTS LIST

- 1 small black box (see text).
- 1 double-pole double-throw switch (see text).
- 2 shorting type jack sockets.
- 1 small 9V battery and connector.
- 1 12-lug length of miniature resistor panel.
- 1 knob for fuzz control.
- 1 50K lin. taper potentiometer, with switch.
- 2 transistors, type 2N3565, BC108 or similar.

RESISTORS

(All $\frac{1}{4}$ -watt types)

- 1 x 4.7M, 1 x 680K, 1 x 68K, 1 x 47K, 1 x 15K, 1 x 10K, 1 x 6.8K, 1 x 470 ohms.

CAPACITORS

- 1 .047uF 25VW ceramic.
- 1 .027uF 25VW ceramic.
- 1 .001uF LV plastic.

this, with the forward bias applied, is sufficient to bring the stage near to current saturation. Because the second transistor base is DC coupled to the first collector, the second transistor will simultaneously be held to near cut-off.

When a sinoidal signal, which has positive and negative peaks, is applied to the first transistor base it will be driven alternately positive and negative. On the positive swing of the input signal the transistor will be driven into complete saturation, so limiting the collector's voltage swing and resulting in a clipped signal peak at the collector.

On the other hand, however, the quiescent voltage across the load is sufficient to allow a full and unclipped collector voltage swing on the other half-cycle of the signal. The resulting waveform at the first collector is therefore a sinusoid with a clipped negative peak.

Now for the other transistor. The unaffected signal peak at the first collector will drive the second transistor into complete cut-off, thereby delivering a signal at the output which has both peaks clipped. This statement rests on the assumption that the output from the guitar will be sufficient to overdrive the transistors, but this will normally be the case provided that the guitar is operated with its own volume control fairly well advanced.

ERRATA and NOTES

Playmaster 116 Guitar Amplifier, June, 1967. Correction to parts list: Three 1M resistors were omitted.

Playmaster 117 Guitar Amplifier, July, 1967. Correction to parts list: Three 1M and one 68K resistors were omitted.

Playmaster 116, 117 Guitar Amplifiers: A power diode, type 1N3193, should be included in both the 40 and 60 watt guitar amplifier designs. The diode is connected across the 100uF screen supply electro, with its anode earthed, such that it is normally not conducting. It was pointed out and confirmed in our own workshop that, in the original design, a small negative potential would be developed across the abovementioned electro when on standby. In the interests of a completely valid design, the particular diode is considered necessary so as to completely safeguard the electrolytic capacitor.

Thyristor Train Controller, March, 1967. The parts list shows three 0.47uF capacitors. This should be two, to agree with the circuit diagram.

DC Supply for Transistors, April, 1966. The 10K wire wound potentiometer shown in the parts list should be 2K as in the circuit diagram.

The actual gain through the fuzz unit is largely a function of the output divider, the 10K and 68K resistors being chosen to give a small amount of gain in both modes, actually about 1.5 times.

However, as we have already pointed out, waves which are merely squared have a rather modest sound, in terms of fuzz, and further elaboration of the distortion circuitry is called for, at least for the more extreme effects.

Looking again at the circuit, a distorted signal appears also at the emitter of the second transistor and, by adding the higher frequency components from this distorted and out-of-phase wave-

form to the output from the collector circuit, the end result is a large spike above the trailing edge of the initial, squared output waveform.

By using a potentiometer as the emitter load for the second transistor, it is possible to vary the basic fuzz shape to one with the superimposed spike, as already mentioned.

When the "box" is switched to normal operation two things happen. Firstly, the operating condition of the transistors is changed so that they give linear amplification; this is done by switching the collector loads of the transistors. The second step is to disconnect the harmonic adding circuit, involving the .001uF capacitor from the "fuzz control" potentiometer.

Constructionally, the most important aspects of the device are that it should be small and robust. Our own prototype was built into a small steel box which is readily available from R. Moody and Co., of 126 Bombay St, Lidcombe, N.S.W. Similar boxes will doubtless be made available in due course by other suppliers. The main body of the box measures 6 $\frac{1}{2}$ x 3 inches, being 1 $\frac{1}{2}$ inches high at one end and $\frac{1}{2}$ in at the other. A bottom plate with turned-up flange, and carrying four rubber feet attaches to the underside by self-tapping screws.

The switch, mounted on the sloping

CSIRO

DIVISION OF ANIMAL PHYSIOLOGY

Technical Officer

(MALE)

Electronics Technician

SALARY: Technical Officer Grade 1, \$3,448-\$3,864 p.a. or Technical Officer Grade 2, \$3,969-\$4,281 p.a.

LOCATION: Pastoral Research Laboratory, Armidale, N.S.W.

GENERAL: The Pastoral Research Laboratory is part of the Division of Animal Physiology and is concerned with the investigation of factors affecting the productivity of grazing sheep in pastoral systems. The Laboratory has a staff of 25 professional scientists working in various plant and animal disciplines together with some 60 supporting staff.

DUTIES: To assist in a telemetry programme to aid studies of some aspects of the interaction of grazing sheep with their environment. His duties will include the development of circuitry which will provide measurements of microclimatic and physiological parameters associated with grazing sheep, and the development of circuitry associated with the tracking of sheep. He will also be expected to supervise the installation and maintenance of field equipment.

QUALIFICATIONS: Considerable training and experience in semiconductor electronics. A knowledge of physiological transducers, computing or digital data handling techniques, and some interest in the problems of biological measurements, would be an advantage.

Applications quoting reference number 246/223 and stating full personal particulars and details of qualifications and experience, should reach:

Officer-in-Charge
Pastoral Research Laboratory,
CSIRO, Private Bag,
ARMIDALE, N.S.W.

by 8th September, 1967.



NKK switches

(The best the World can offer)

"A selected few from the large range available"

TYPE	MODEL	CIRCUIT	CAPACITY	CIRCUIT ARRANGEMENT
Toggle Switch	S-211	SP. ST	1.5A 250V. A.C.	ON-OFF
	S-114	DP. ST	2A 250V. A.C.	ON-OFF
	S-116	DP. DT	2A 250V. A.C.	ON-ON
	S-2B	SP. DT	5A 250V. A.C.	ON-ON
	S-6A	DP. DT	10A 250V. A.C.	ON-ON
	S-7A	DP. DT	10A 250V. A.C.	ON-OFF-ON
	S-533	DP. DT	15A 250V. A.C.	ON-OFF-ON
Push Button Switch	SB265	SP. ST	3A 250V. A.C.	ON-OFF
	SB61A	DP. DT	5A 250V. A.C.	ON-Mom. ON
See-Saw Switch	SW-3511	SP. ST	1.5A 250V. A.C.	ON-OFF
	SW-3006	DP. DT	10A 250V. A.C.	ON-ON
Lamp Lighted Switch	NB-SL	SP. DT	15A 250V. A.C.	ON-Mom. ON
	SLB-D-25	DP. DT	9A 250V. A.C.	ON-ON
Micro Switch	NZ-2R	SP. DT	15A 250V. A.C.	Full range of activators available
	ND-2R	DP. DT	10A 250V. A.C.	
Rotary Switch	HS-5	SP	2A 250V. A.C.	3 position-OFF

INTERNATIONAL RESISTANCE CO. (A'SIA) PTY. LTD.

(A subsidiary of International Resistance Holdings Ltd.)

THE CRESCENT, KINGSGROVE, N.S.W. TELEPHONE 50 0111

POST TODAY

Please supply
Sub-Miniature and Standard switch catalogue







NAME

ADDRESS

front panel, must be of the double-pole double-throw variety and sufficiently robust to withstand operation by a none-too-gentle foot. Suitable switches may be available from a number of sources but the one on the prototype came from A. E. Ackland of 321 Prince's Highway, St. Peters, N.S.W.

The outside of the box is finished in black-crackle baked enamel with the contrasting chrome finish of the push-on push-off switch. The knob used was one of the black instrument style knobs, featured in our recent guitar amplifiers, with a white-line pointer to indicate the off and on positions.


The wiring of the device is quite straight forward and, in our case, was



Shown above are typical wave-forms from the unit. As can be seen, the "fuzz" at minimum is amplitude dependent but at higher levels of distortion the wave-form is determined mainly by the "fuzz-control" setting

accommodated on a strip of miniature resistor panel. The panel contained 12 solder lugs down each side, and was secured in the box by two 4in Whitworth screws on two 4in spacers. The box which we used was cadmium plated and earth connections could be soldered directly to the inside which had been left unpainted.

Users will need to remember to switch the unit off at the end of each performance, to obviate unnecessary drain from the battery. Fortunately, the penalty for occasionally forgetting to do so is not very great since, as already mentioned, the current drain is less than a milliamp and, overall, the battery should last for about its natural shelf life.



The "Answer Man" Explains

Schematic, Block and Equivalent Circuits

Electronic circuits are common enough things but one of our younger readers has discovered that there are other things called "block schematic circuits" and "equivalent circuits."

What is the difference between a circuit, a block schematic circuit and an equivalent circuit? I have seen all three terms used at various times.

In the ordinary sense of the term, a "circuit" is what we publish each month for projects. It uses a more or less formalised set of symbols to represent resistors, inductors, capacitors, transformers, etc., each marked with the appropriate values and ratings. These are interconnected by lines representing the actual electrical interconnection within the equipment. With such a circuit—often called a "schematic circuit"—it is possible to analyse the operation of a proposed piece of equipment in detail, or build it from the requisite parts, or work out what may have gone wrong when the said equipment fails. We use schematic circuits when working out a design and publish them for the guidance of intending constructors. Similarly, manufacturers make them available for use by people who may have to service their equipment in the field.

In contrast with an ordinary schematic circuit, a "block schematic" circuit, or a "block diagram," contains much less detail. In fact, it may contain virtually no detail of either components or wiring, its normal function being to convey to the reader no more than a broad impression of what a particular piece of equipment does—or how it goes about doing it.

Mostly it uses rectangles, suitably branded to represent whole stages or groups of stages, with interconnecting lines which represent the path followed by the signal being handled plus, in some cases, an indication of power supply or other arrangements.

To take a typical case, the full schematic circuit of a superheterodyne receiver would show all the valves or transistors, all the coils, IF transformers, resistors, capacitors, etc., and the entire interconnection network from aerial input terminal to the loudspeaker voice coil wiring.

A block schematic, on the other hand, may have a rectangle marked "Frequency Changer," with a single line running to another rectangle marked "IF Amplifier," thence "Detector," "Audio Amplifier" and, at the end, "Loud-

speaker." Another rectangle, somewhat separated from the rest, might be marked "Power Supply."

In the context of an elementary textbook, this diagram might serve to illustrate paragraphs reading like this:

"The incoming signal passes first to a Frequency Changer stage, where it is changed to another, usually lower, frequency called the Intermediate Frequency or just IF. At this new frequency, the signal is amplified in an IF Amplifier stage. Thence it passes to a Detector..." and so on.

While block schematic diagrams have their uses in elementary textbooks on radio, they find equal application at a much higher technical level. For example, anyone faced with the full schematic circuit diagram of a computer—if such a thing has ever been drawn—one would find it quite impossible to gain any real

value from it; it would be just a huge, bewildering maze of symbols and lines.

In complex equipment like this, it is quite normal to rely heavily on block schematics to convey information as to the general mode of operation. Even the engineers who work on such things are tending more and more to think in terms of "black boxes" designed to perform certain functions, leaving it to others to work out the details of what goes inside the various basic units.

And that's about the only level at which schematic circuits of computers and similar items can exist—in the factories which, perhaps quite independently, produce the basic building blocks from which a complete computer or other system is assembled.

An "equivalent circuit" is the absolute converse of a block schematic. Whereas the latter tends to lump a lot of components together into a suitably branded rectangle or "black box," an equivalent circuit tends to break up individual components into their basic qualities. A mono magnetic pickup, for example, may be represented in an ordinary circuit diagram as a circle, with two leads running from it, and with an arrow drawn through it to represent a stylus.


But the equivalent circuit for a magnetic pickup might show it as an AC generator, an inductor and a resistor all in series, indicating that it can be regarded as a basic voltage or current generator whose output is modified by the inductance and resistance of its own internal coils. To be still more exact, a capacitor could be added to represent any distributed capacitance of the electrical system.

By allotting quantities to the internal L, C and R, it becomes possible to forecast, for example, what effect external loading may have on the performance of the particular cartridge.


At the other end of the amplifier chain, equivalent circuits are used quite a lot to analyse the operation of loud-speaker systems. In this case, the equivalent circuit is arranged to include additional electrical quantities—inductance, capacitance and resistance—which are equivalent in their effect to mechanical properties of the loudspeaker and its baffle system: Mass, inertia, springiness, damping, air volume, and so on. In fact, a detailed equivalent circuit for a loud-speaker system is a quite imposing array of circuitry, the working out of which represents a major engineering exercise.

An equivalent circuit which contains a preponderance of electrical quantities, substituting for mechanical quantities


EQUIVALENT CIRCUIT OF LF SYSTEM



EQUIVALENT CIRCUIT OF HF SYSTEM



We borrowed these two diagrams from an article in "Hi-Fi News" by B. Weingartner. They are equivalent circuits illustrating the behaviour of acoustic elements in an AKG microphone, relative to low frequency and high frequency sounds. Pressure \times area is likened to voltage, velocity to current, friction to resistance, mass to inductance, and spring to capacitance.



Sansui lays it on the line



Look at that distortion curve.

It, better than pages of exaggerated advertising claims, tells the serious stereo fan something about the kind of engineering that has gone into building a receiver.

While this curve belongs to Sansui's Model 3000, it is the result of the same engineering, the same careful component selection, and the same precision fabrication that goes into every product carrying the Sansui name.

Sansui's line of audio equipment

includes more than a dozen quality receivers at all power outputs — solid-states, tube types, single or multiple band tuners, amplifiers, amplifier-tuners—as well as matching speaker systems and stereo headphone sets.

Pick up specifications for any Sansui product and you'll find performance and distortion characteristics laid on the line as few stereo equipment manufacturers would dare.

Then listen to a Sansui at your

dealer for a frank personal appraisal.

Sansui model 3000: Solid-State AM/FM Multiplex Stereo Receiver. Total output power: 130 watts. RMS power: 48/48 watts. Stereo RMS power: 45 watts x 2. Bandwidth: 20 to 20,000 Hz. Harmonic Distortion: less than 1% at all power levels.

Sansui®

SANSUI ELECTRIC COMPANY, LIMITED: 14-1, 2-chome, Izumi, Suginami-ku, Tokyo, Japan Tel: 328-0111

for purpose of analysis, is sometimes referred to as an "analog," a term which might seem less strange if we were to remark that a particular electrical circuit is "analogous" to a certain mechanical assembly or component.

★ ★ ★

I heard an artist recently who was playing what I think he called a transistorised accordion. Sometimes it sounded more like an organ than accordion. What gives?

Unless we miss our guess, the artist you heard was one of the Palermo Brothers, whose LP we reviewed on page 113 of the May issue. We didn't hear the instrument "in the flesh" but we did hear it on the record. From the tonal qualities, we'd say that it contained reeds for the basic accordion sound; either that or the electronic circuitry was remarkably well contrived to imitate them!

Equally, however, we felt that it probably contained a set of oscillators and multipliers, along with contacts under the keys for the organ sound. Either that or, once again, the electronic amplification had included some very effective filters to modify the sound of reed generators to tones more commonly associated with a conventional electronic organ.

However, the job of adapting an accordion to produce "organ" facilities would be simple compared with the latest creation of the Thomas Organ Company, in America. Showing remarkable ingenuity, they have built an organ-type transistor generator into the body of a guitar and adapted the string and fret system so that it will produce ordinary guitar sounds, when played in the conventional manner, but it will also key the transistor generator to produce electronically generated signals to a related pitch! The following description is by courtesy of "Electronics World."

"It is a combination of a six-string guitar and a miniaturised electronic organ that will operate with any amplifier with at least two inputs. It can also be used as a stereo unit, if it has the guitar portion plugged into one amplifier and the organ portion plugged into another.

"The instrument can be played as an ordinary electronic guitar, and the usual volume and tone controls are provided. An on-off side control brings in or cuts out the organ section. The organ can be played by depressing a string or strings, using one or both hands. It is not necessary to use the right hand unless it is desired to add some guitar melody or background. The organ sound is created when a string touches a fret (which acts as a contact) and sends the signal down the neck to the components inside the guitar body.

"The guitar-organ has two sets of tuning slots located on the back. One set is composed of six potentiometers which may be adjusted for fine tuning of the instrument. The other set of pots is used to fine tune the octaves.

"The guitar portion has three controls which are for volume, bass, and treble. The organ portion has fifteen controls which are for volume, repeat, percussion, sustain, basic flute, and octaves, including six open-string buttons. These open-string buttons do three things. They can tune the organ

to the guitar, supply a simple bass line, and sound the notes of the open strings. The guitar portion is powered by two six-pole magnetic pickups located between the neck and bridge.

"The guitar-organ can duplicate such tones and sounds as a church organ, rock-and-roll organ, baritone saxophone, low and high clarinets, bagpipes, flute, banjo, chimes, harpsichord, zither, and an oriental effect. The instrument requires no special technique except for the operation of some additional controls."

★ ★ ★

Is it possible to work out the proper connections for the reaction winding in a regenerative receiver, rather than having to change leads over?

Fortunately, yes. The basic requirement is that energy from the plate circuit must be coupled back to the grid circuit 180 degrees out of phase.

Let's start by assuming that the two windings (grid and plate/reaction) are wound on to the former in the same direction. In other words, holding the former upright, the wire should spiral upwards from the bottom of each winding in the same direction. This should hold, irrespective of the relative positions of the two windings.

If, now, the "top" of the main winding is to connect to grid, the "bottom" of the reaction winding will have to go to plate — and vice versa.

The most common way of winding a small coil for a regenerative receiver is to wind the larger or "grid" winding nearer the bottom of the former, with the smaller "reaction" winding spaced about 1/8 inch above it and continuing in the same direction. From the bottom, the connections would then run: Earth, Grid, Plate, Reaction Capacitor (or B-plus).


If, for any reason, the reaction winding were put on in the reverse direction, the connections would become: Earth, Grid, Capacitor, Plate. In this case, the necessary change in phase would have been effected, not by connecting the active valve elements to opposite ends of the relevant windings, but by reversing the directions of the windings themselves.

When reaction (or feedback) is derived from the cathode rather than the plate circuit, it is important that the cathode and grid signals be in phase. This being so, if the grid goes to the top of the main winding, the cathode should equally go to the top of the feedback winding. More commonly, the cathode is simply taken to a tapping on the grid winding, a turn or so from the earthy end. This is usually more convenient physically and it satisfies the stated requirement that the cathode and grid signals be in phase.

These rules hold, irrespective of whether the detector valve is a triode or a pentode.

They also hold for transistors in the normal common emitter configuration. Thus, where reaction involves a separate feedback winding in the collector circuit, the base and collector must connect to opposite ends of their respective windings, assuming the windings to be in the same direction.

Similarly, emitter and base signals must be in phase for regeneration to take place.



COMPONENT

REFERENCES ON TAPES
YOU JUST PRESS DOWN
for circuit drawings, printed circuits, engineering drawings, chassis and panel marking.

A comprehensive range of component references is now available on Letratapes. The range is in two letter sizes — 1.8" and 3.16". The 1.8" size is designed for same-size work; the 3.16" size is ideal for 2:1 photographic reduction and will provide clear, easy-to-read reference codes even at 3:1 reduction. The range of 61 different tapes in each size contains individual tapes of every letter in the alphabet, and numerals 0-9. Also included are a range of pre-set component references (MR, ebc, PL, SKT etc.), consecutive numeral sequences (1-99, R1-R60 etc.) and commonly used pre-set words.

LETRASET (VIC) PTY LTD.
447 COLLINS ST, MELB.
PHONE 62 1154.

Available from all good Hi-Fi stores, the latest

SHURE

SME precision pick-up arm

This model is now fitted with an improved dynamic damping system. The tracking error is lower which is an advantage especially when using an elliptical stylus.



Now supplied complete with 4 feet of miniature coaxial connecting lead with a capacity of less than 27 pf per foot, terminated with shielded output socket and SME precision Phono Plugs. Also features S2 ultra lightweight shell, finger lift and light alloy mounting hardware.

Model 3009/S2 suggested list price .. \$107

Model 3012/S2 suggested list price .. \$113

ACCESSORIES

S2 ultra lightweight shell \$10.95

Decca D3 Adapter \$1.38

Lifting Handle \$1.00

SME Phono Plug \$1.00

SHURE

High "Trackability" Cartridges Make Perfect Companions

SHURE V-15 TYPE II

Trackability at $\frac{1}{2}$ gram tracking force using a Shure/SME Arm:

17.9 CM/SEC at 400 Hz (cps):

26 CM/SEC at 1,000 Hz (cps)

26 CM/SEC at 5,000 Hz (cps):


18 CM/SEC at 10,000 Hz (cps).

Frequency Response: 20 to 25,000 Hz (cps).

Output Voltage: 3.5 mv per channel at 1,000 Hz (cps) at 5 CM/SEC.

Channel Separation: Over 25 db at 1,000 Hz (cps);
Over 17 db from 500 to 10,000 Hz (cps).

Suggested list price \$118.75.



SHURE

M75E Hi-Track

This cartridge is truly from the new generation of cartridges that deliver high trackability at light tracking forces . . . yet, it is surprisingly modest in cost. Also includes retractile stylus to prevent record damage, Bi-Radial Elliptical Stylus configuration and 15 degree tracking features! Manufactured and tested under Shure's standard quality control program. Maximum tracking force is $\frac{1}{2}$ grams.

Suggested list price \$69.

Also suitable are models M75G and M75-6.

Suggested list price \$38.

Distributed by:

Audio Engineers Pty. Ltd.
342 KENT STREET, SYDNEY — 29-6731

Queensland readers please note: Our new distributors in Queensland are:

MESSRS RON JONES PTY. LTD.

7 Merton Rd., South Brisbane, 91-1915

MAGNETIC PICKUP PREAMP

FOR THE PLAYMASTER 118

When we presented the Playmaster 118 amplifier, last month, we indicated our intention of describing the addition of an in-built preamplifier, to allow it to operate from a high-quality magnetic pickup. We show how it can be done but, in so doing, revive some of the problems which can attend the construction of high-gain single-unit amplifiers.

Superficially, the job of adding a solid-state preamplifier to the 118 looked to be a matter of pure routine and we initially approached it as such.

Because we knew that 7 volts or more DC would be available from the cathode circuits of the output valves, it seemed logical to settle for the silicon transistor preamplifier originally featured in the October 1965 issue. The preamplifier is capable of operating from a voltage of this order, at low current drain, and can provide a suitably high input impedance (with series input resistor) ample gain and the requisite RIAA compensation.

In addition, it has the advantage over our more recent preamplifier using field effect transistors that no adjustment or setting-up is required. Last but not least, the twin board, carrying both channels, seemed tailor-made for the space which had been reserved for it on the 118 chassis.

It did not take long to wire up and install the preamplifier and we would very much like to say that it worked fine from the outset; unfortunately such was not the case. As the gain was advanced towards a usable level with a typical magnetic pick-up, the amplifier exhibited instability at high frequency, motorboating at low frequency and more than its fair share of hum. Our first problem was to discover whether the effects were interdependent or merely occurring simultaneously! By operating the unit from a supplementary power supply, experimenting with the connecting leads and terminals, and lifting the board away from the chassis, we were able to determine that the effects were, in fact, quite unrelated and that we were faced with the need to find three separate cures for three separate problems.

Not surprisingly, the motorboating turned out to be a feedback loop from the output valve cathodes to the preamplifier supply line. With the volume and bass-boost controls turned full on, the gain at low frequencies is so high that a scheme which is neat and convenient in other circumstances turned out to be just too touchy with the augmented 118. With sufficient decoupling, it was, in fact, possible to stabilise the system but, at such a cost and with such a loss of voltage, that it became more logical to go over to a zener stabilised supply, fed from the main HT line.

In so doing, some of the argument in

favour of the silicon preamplifier was weakened but only in part; low voltage zeners are cheaper than high voltage zeners, and the commitment for resistors would likewise be less to regulate a lower order of current. The further advantage of not having to adjust the operating conditions also remains.

So point number 1 emerged; The way to supply such a preamplifier is by means of a dropping resistor and zener from the HT line, with an extra resistor and by-pass capacitor to complete the low voltage supply.


The high frequency instability turned out to be due to proximity of the pickup input connectors to the wiring of the output stages and, in particular, to two components on the rear end of one tag-board — a 4.7K resistor and a 100pF capacitor. In the original version of the 118, with about 100mV sensitivity for a ceramic pick-up, the juxtaposition of the input and low impedance output wiring posed no hazard but it is a different matter when the input sensitivity gets down to below 5mV.

In fact, we found it possible to stabilise the amplifier simply by mounting the


100pF capacitor on the same pair of lugs as the 4.7K resistor and bridging the lugs formerly allotted to the capacitor with an earthed busbar. However, rather than rely on a half-measure, we decided to install a small shield plate to isolate the pickup connectors from adjacent wiring. Two methods suggest themselves: One is to cut a small shield from a scrap of tinfoil and solder it to the two lugs just mentioned, earthing the assembly with a short busbar; alternatively, the end of the tagstrip can be cut off and a shield plate bolted to the chassis.

Point number 2, therefore, is that the input wiring and connectors must be fully shielded from the pickup cartridge through to the input connectors of the preamplifier board. Once again what is "near enough" for a 100mV sensitivity is not good enough for less than 5mV.

If the hum problem could have been as easily solved as the first two, we would have been very happy, but such was not to be. Basically the problem was found to stem from stray fields from the power transformer—to some extent conducted through the steel chassis but



This picture taken over the front of the panel shows the preamplifier, attached to its support and shield plate. Note that the input, output and supply connections are mounted uppermost and away from the basic chassis.




Circuit details of the preamplifier. The section picked out in blue represents connections and components mounted on the printed wiring board. Other wiring has to be added, as described in the text.

EVERYTHING FOR THE HOBBYIST & SERVICEMAN

INSTROL LABELS

High quality anodised labels to suit all Playmaster projects:



(A) 115-117 Amps.

(B) 111-114 Tuners.

(C) 105-107 Amp/Tuners.

(D) Unit 3 and 4 Amps.

(E) Guitar Amps.

Nos. 115-117 Labels are smart silver, white background with dark-brown lettering. The label illustrated covers the complete front panel. A smaller one is available to suit 112 and also 115 and 117. All the other labels illustrated are fine gold background with black lettering.

PRICES: Large 115 and 117 and Guitar **\$2.80**
Small 112, 115 and 117 **\$2.00**
111, 106 and 107 **\$2.80**
Add Postage, 20c per label.

INSTROL PRINTED CIRCUIT BOARDS FOR 115 AMPLIFIER

To make component assembly easy, Instrol pre-fluxed printed circuit boards are clearly printed on the reverse side with a coded component code sheet. No guesswork, every component must fall correctly into place. For the crystal/ceramic version 3 boards are required (2 amplifiers, 1 pre-amp). The Magnetic version requires one additional magnetic pre-amp board.



PRICE:
Crystal Pre-Amp **\$2.00** (plus postage 10c).
Main Amplifier, ea. **\$1.60** (plus postage 10c).
Magnetic Pre-Amp **\$1.60** (plus postage 10c).
Set of 4 **\$5.80** Post Free.

HI-FI KITSET CATALOGUE

Yes, a free catalogue is available, giving prices and details of all "Playmaster" designs, including the latest 115, 116, 117 and 118. Send stamp for your free copy.

INSTROL & OXFORD METALWORK

We carry a complete range in stock for all "Electronics Australia" projects. Detailed price list available upon request.



MICROPHONE CATALOGUE

Just printed—our new free microphone catalogue and price list, detailing a wide range of various makes and models. The range includes types suitable for P.A. work, tape recording, stage work, etc. Send for your free copy.




CANNON CONNECTORS

Full range of these high quality audio connectors always available ex-stock. Detailed price list available.



TRANSISTORISED IGNITION

Fully described "R.T.V. & H." March, 1964. ROFO 12v or 6v Coils only available at **\$10.70** or Complete Kit, including coil for **\$34.65**. Postage 50c.



2 AMAZING "UNIVERSITY" INSTRUMENTS

MODEL MVA-4-General Purpose 20,000 ohms per Volt Multimeter

Brief Specifications:

D.C.V.: 2.5/10/50/250/1,000 (20KΩV)
A.C.V.: 2.5/10/50/250/1,000 (8KΩV)
D.C.A.: 50uA, 2.5mA, 25mA, 250mA
Ohm: 10K, 100K, 1M, 10M
db: -20, +22, +20, +36

Accuracy: $\pm 3\%$ for D.C. range
 $\pm 4\%$ for A.C. range
Size: 6" x 4 3/16" x 2 1/4"



MODEL MVA-6-VACUUM TUBE VOLTMETER

All "University" instruments are backed by full service facilities.

Brief Specifications:

A.C. Volts RMS—0—1,500 (in 7 steps)
Volts P—P—0—4,000 (in 7 steps)
D.C. Volts+and—0—1,500 (in 7 steps)
Ext' to 30KV with ext' Probe
Input res' 10 meg.
Ohms—.2ohms—1,000mcg (in 7 steps)
DB—(ref' 1mW in 600Ω)
—20 to +65 (in 7 ranges)
Accuracy: $\pm 3\%$ for D.C. ranges
 $\pm 5\%$ for A.C. ranges
Size: 5 1/2" x 9 1/2" x 6"

PRICES

MVA4 **\$16.31**
MVA6 **\$47.25**
R.F. Probe **\$6.75**
H.V. Probe **\$9.00**

Above prices include Sales Tax. (Regd. Postage \$1 extra).

BROADWAY ELECTRONICS PTY. LTD.

E.S. & A. BANK BUILDING, CNR. BROADWAY & CITY RD. SYDNEY
(Opp. Grace Bros.)

Phone: 211-4224, 211-4244, 211-4213

otherwise in the free space surrounding the transformer.

Fortunately, the position selected for the preamplifier—mounted vertically in the opposite corner of the chassis—is about the optimum and, by proper arrangement of shielding and earth returns, it is possible to get the amplifier virtually hum-free.

But herein lies the rub. Before the amplifier can be of any use, pickup leads have to be brought to it and the approach can only be through the fields from the power transformer. Ordinary shielding offers little protection against magnetic hum fields and the hum level is likely to rise with connection of the input leads.

Unfortunately, the effect is likely to be rather random, depending on the particular transformer used and the length and routing of the input leads.

We pulled all the tricks we know in trying to solve this one, while still retaining the original power transformer—but with only very limited success. One such trick was to isolate the runs of shielded wire to the two halves of the cartridge, eliminating the link at the cartridge which is often used to join the two earth pins. This precaution obviated what can be an earth loop remotely bridging the inputs to the two channels.

Under these conditions we were able to get the hum down to where it was barely audible at ordinary listening distances, with the amplifier set up for fairly loud volume and partial bass boost, with a typical "5 millivolt" magnetic cartridge. For some, this might be good enough, but it would not meet the situation where the loudspeakers had a peak at 50Hz, or where the listener was fond of bass boost or given to listening critically for hum.

So to lesson number 3: You don't try to mix on the one chassis a high-gain preamplifier, full bass compensation and a power transformer with unrestricted leakage field!

If you have already built the 118 Playmaster and want to add a magnetic pickup preamplifier, we suggest that you mount the preamplifier up under the motor board and close to the base of the pickup. For good measure, it can be partially enclosed in an earthed coverplate bent up from tinplate or aluminium. Take the leads from pickup to input and run shielded leads from the output lugs of the preamplifier to the input connectors already on the amplifier and wired for a ceramic pickup. The positive supply line can be run from the amplifier supplying the requisite few volts from the zener and filter to the preamplifier. Since the signal approaches the amplifier at more like 200mV than 5mV, hum injection into the leads from the power transformer is no longer significant.

The ultimate answer to the problem, however, is in the use of a power transformer fitted with a copper strap to short the stray field. Very fortunately, Ferguson Transformers were able to supply us with their type PVD111FT, the "T" indicating shorting strap. Electrically it has the same specifications as the PF1555 or PVD111F, etc., used in the original amplifier. Most likely, other manufacturers will make available their own version with shorting strap and we are going to suggest to suppliers that this modified line of transformers be supplied for the appropriate units in

the Playmaster range, whether or not they are intended for ultimate use with a magnetic pickup. The difference in cost is not all that much.



In this case, the drop in hum level was little short of sensational. With the wiring otherwise undisturbed and the pickup connected, the hum level dropped to the point where it was below the prevailing noise level of the preamplifier, with volume and bass controls at full on and a sensitivity of better than 2mV

for full output! With the tone controls at level and the volume control set for loud listening level, the hum and noise was quite inaudible.


To our great relief, an amplifier, which had started out as just about as unsatisfactory as it could be, had ended up with a performance which was quite outstanding.

So much for the story behind the amplifier, which we have told in detail for the sake of the lessons which it con-

At right is the wiring diagram for the preamplifier, as originally described in the October 1965 issue and constructed on the 65/p10 wiring board. This design calls for the addition of two lugs to accommodate the 47K input series resistors.



The supply components for the silicon preamplifier can conveniently be mounted on a short length of tagstrip and held under the same bolt, behind the control switches, which currently supports one of the existing tagboards. Alternatively, a longer tagboard can be installed in the first place.



Here is the bracket which we bent up to support the preamplifier. We suggest that it be made from 18 or 20 gauge steel, as used for the chassis, to help side-track any stray field in the plane of the board.

tains. Now for a few paragraphs about the actual construction of the preamplifier.

As mentioned earlier, the preamp was originally featured in the October 1965 issue. This article described in full the operation of the preamp., which could also be adapted as a preamp for tape heads.


Assembly can begin with the wiring of the printed board. When mounting components on the board, do not bend the pigtailed too close to the component body or bend them too sharply, since this encourages fracture. Care should be taken, also, not to overheat the components, and particularly the transistors, during soldering. Since the original preamp board did not have provision for mounting the 47K input resistors, we mounted an extra two solder lugs on the board, one on each side of the 9-volt supply terminal, as shown in the diagram. Do not overlook these two resistors, since they ensure suitable loading for the cartridge.

Initially, we used several low voltage ceramic capacitors in the prototype preamp but we do not recommend their use as they turned out to be a potential source of microphony. Low voltage polyester capacitors do not suffer from this trouble and are a better choice in very low level stages such as these.

The printed board is mounted on a steel plate with dimensions as in the diagram and bent up from 20-gauge steel. We had to drill two extra 1/8in diameter holes in the chassis to mount the plate which is set back 2inches from the front panel. The board is secured to the plate with 1/8in screws and spacers or spacing nuts to provide adequate clearance between board and plate. Make sure that these rear nuts or spacers do not foul the copper pattern near the corners.

Referring to the photograph of the




(Continued on page 174)



PRECISION OSCILLATORS

As designers and as users of oscillators, Marconi set an exceptionally high standard in accurate frequency control. Years of experience give Marconi authority in the production of crystals, crystals with ovens, and complete oscillators.

The new Marconi range of packaged, transistorised, highly stable, pre-tested, quartz crystal oscillators, using conservatively rated silicon transistors, is available within the frequency range 1 kHz to 75 MHz



Marconi specialised components are designed and manufactured only when the precision and high performance required is otherwise unobtainable.

Marconi specialised components



Engineering Products Division

422 LANE COVE ROAD NORTH RYDE NSW 88 6666

AMALGAMATED WIRELESS (AUSTRALASIA) LTD

MELBOURNE
67 9161

BRISBANE
4 1631

ADELAIDE
51 0111

PERTH
28 3425

LAUNCESTON
2 1804



The Serviceman



NED KELLY — TV SERVICEMAN!

My two main stories this month are, I am sorry to say, classic examples of service tactics which, at the very least, must be regarded as highly suspect. Coming, as they do, hard on last month's experience along similar lines, they force me to wonder just how widespread are such malpractices, and whether there is some kind of resurgence.

My first story concerns a complaint about a TV set suffering from low sound output. The history of the fault, as I finally pieced it together, was quite enlightening, in view of what I subsequently discovered.

It seemed that, about two years previously, the set's sound had failed completely. The people had called in a serviceman, who, after examining the set, had diagnosed a condition which, according to the owner, would have been quite expensive to repair. Exactly what this condition was supposed to be, or whether it was ever precisely described, I was unable to determine after such a long time. Neither was I able to determine whether the serviceman simply described it as expensive, or quoted a figure but, either way, he succeeded in frightening the customer off having the job done.

Then the serviceman suggested that, if they didn't want to pay for an expensive repair right then, he could make a temporary repair which might serve them until they were ready to have the job done properly, assuming they were prepared to accept a reduced performance. So this was agreed to. The serviceman made his temporary repair, collected his fee, and went on his way.

As it turned out, the reduced performance was a marked drop in available sound level in a set which was not renowned for its reserve in this regard, even in the best circumstances. More precisely, the level now available was just about sufficient under ideal conditions, i.e., a reasonable level from the transmitter and with everybody watching the program maintaining a strict silence. Even then it was sometimes a strain.

But the owner and his family tolerated this for two years, so effectively had they been frightened off by the "expensive repair." Finally, he could stand it no longer. As far as he was concerned the TV set had long since ceased to be a source of entertainment and had become simply one of irritation and annoyance. He made up his mind to have it fixed, no matter what it cost. And so he sought my aid.

I was rather intrigued by the story. I couldn't imagine what kind of sound fault could involve such a high level of expense, but was prepared to learn if it really was something unusual. On inspection, the set behaved very much as the owner had described it, although

what sound there was was perfectly clean.

The set was a fairly old model, and a little unusual in regard to the sound channel. Instead of the more conventional triode pentode valve as a complete output stage, it employed a 6AU6 and a 6AQ5. On the other hand, it used only one stage in the sound IF system.

As far as the video section was concerned, everything seemed to be working fine. There was plenty of signal, a good reserve in the contrast control, and no sign of snow. I formed the opinion that, whatever the trouble was, it was unlikely to be in the common sound and video stages, but was much more likely to be in the sound IF or audio system. Well, at least that narrowed the field considerably.

First I tried new valves throughout, but this made no difference. I withdrew the chassis to the point where I could reach the sound section and went right over all stages with a multimeter. All voltages came up within a few per cent of the figures on the circuit; no future there.

Then I probed the grid of the 6AU6 with my finger via the blade of screwdriver. The speaker blurred obligingly, but I sensed that it wasn't as loud as it should have been for a pair of

pentodes. So it looked as though the trouble was in the audio section. Thus encouraged, I went over the stage again with the voltmeter. I found nothing new as far as voltages were concerned, but I did notice that the 6AU6 screen resistor looked a bit dark on it, as though it had been overloaded at some time.

This didn't seem very relevant, because the screen voltage was normal, but it did suggest that this was the area where the previous serviceman had worked. And if the screen resistor had been overloaded it almost certainly meant that the screen bypass had broken down. So, for want of a better approach at that moment, I took a closer look at the screen bypass.

And then I spotted it. The pigtail from the bypass came close to, but did not touch, the terminal on the socket. What was more, it had clearly been left this way, rather than simply come adrift. Unfortunately, the placement of it and other components was such that the break was not readily visible until I started probing. Naturally, it didn't take a Sherlock Holmes to deduce that the capacitor would turn out to be shorted. So, in fact, it proved to be.


After that, it was plain sailing. It took only a few minutes to select and fit a new capacitor, whereupon the sound came through at full bore; something the owner hadn't heard for so long that he had forgotten how a proper set sounded. It wouldn't have taken much talking on my part to convince him that it was "better than ever."

But what was the story behind this story? Why had the previous serviceman acted as he did? The most generous suggestion I can put forward was that he just didn't have a suitable capacitor in his kit at that moment, and concocted the "expensive repair" story to cover up. But such a theory leaves a lot of things unexplained. For example, if the real problem was a shortage of a suitable part, he could have made almost any excuse—or even told the truth—to explain the need for delay and second trip. I doubt if the owner would have minded so long as his set was repaired at a reasonable cost.



Frankly, I just can't buy such a story. As far as I'm concerned, it was a straight attempt to "take" the customer. The "expensive repair" was a try-on; a feeler to see how the customer reacted. Had he shrugged his shoulders and said, "Do what's necessary," the serviceman would have taken it as a go-ahead to load the job for as much as he felt it would bear. Doubtless, he would have taken the chassis away "to make it look good," and kept it for a suitable period for the same reason.

But when the owner flinched he had another trick up his sleeve. No doubt to discourage the owner from calling in another serviceman, he made a good fellow of himself with a "generous" offer to effect a temporary repair, most likely reasoning that the owner would weaken after a week or two of indifferent sound, and call him back to finish the job.

Unfortunately—for him—he overplayed his hand. So effectively did he paint the picture of an expensive repair that the owner not only waited much longer than he would have thought possible but, when he did decide to do something about it, he elected to call in someone else.



"People think us TV servicemen have it soft! Why, I've already been to two homes today where they didn't even offer me coffee or cake." ("PF Reporter").



The New Empire Royal Grenadier Divergent Lens Speaker System—Model 9000M

Years ahead in design and engineering the Grenadier projects a majestic sound unlike any you've heard before. Its cylindrical shape creates a system relatively free from room standing waves and approaches acoustically flat frequency response. Sound level and tone remain constant virtually anywhere in the room. Its three divergent acoustic lenses achieve unparalleled stereo separation. With the Empire Grenadier . . . speaker placement becomes non-critical.

Model 9000M outstanding features:

1. 15" mass loaded woofer with floating suspension and 4" voice coil.
2. Sound absorbent rear loading.
3. Die-cast mid frequency-high frequency full dispersion acoustic lens.
4. Hand rubbed satin walnut finish.
5. Imported Italian Perlata marble.
6. Ultra-sonic domed tweeter.
7. Full presence mid range direct radiator.
8. Exclusive non-resonant rigidised heptagonal sonic column.
9. World's largest (18lbs) speaker ceramic magnet structure.
10. Front loaded Horn — 360 deg. aperture throat.
11. Complete symmetry of design with terminals concealed underneath.
12. Dimensions: height 29" — diameter 22".

TECHNICAL SPECIFICATIONS MODEL 808

Frequency Response
10—20,000 cps.*
Output Voltage
8.0 mv. per channel
Channel Separation
more than 30 DB
Compliance
 8×10^{-6} cm/dyne
Tracking Force
1 to 6 grams
Stylus
7 mil. radius diamond
Terminating Impedance
47,000 ohms
Stylus Replacement
S 808/7RD Black

*Dynamic capability to 40,000 cps.

TECHNICAL SPECIFICATIONS

MODEL	808	808E	808P	808PE	808SE
Frequency Response	10-24,000† cps.	10-30,000† cps.	8-28,000† cps.	6-30,000† cps.	6-32,000† cps.
Output Voltage	8.0 mv. per channel	8.0 mv. per channel	8.0 mv. per channel	8.0 mv. per channel	8.0 mv. per channel
Channel Separation	more than 30 DB	more than 30 DB	more than 30 DB	more than 30 DB	more than 30 DB
Compliance	10×10^{-6} cm/dyne	12×10^{-6} cm/dyne	15×10^{-6} cm/dyne	20×10^{-6} cm/dyne	25×10^{-6} cm/dyne
Tracking Force	$\frac{3}{4}$ to 6 grams	$\frac{3}{4}$ to 5 grams	$\frac{1}{2}$ to 4 grams	$\frac{1}{2}$ to 3 grams	$\frac{1}{2}$ to 3 grams
Stylus	.7 mil radius diamond	.4 x .9 mil bi-radial elliptical hand polished diamond	.6 mil radius hand polished diamond	.2 x .9 mil bi-radial elliptical hand polished diamond	.3 x .7 mil bi-radial elliptical hand polished diamond
Terminating Impedance	47,000 ohms	47,000 ohms	47,000 ohms	47,000 ohms	47,000 ohms
Stylus Replacement	S888/7RD Brown	S888E/ERD Green	S888P/6RD Orange	S888PE/ERD Yellow	S888SE/ERD Blue

†Dynamic capability to 40,000 cps.

SPECIAL FEATURES

15 Degree Vertical Tracking Angle ● Exclusive Induced Field Moving Magnetic Cone Stylus ● Fully compatible for stereo or mono ● Complete freedom from hum pickup ● Replaceable Stylus assembly. ● Lowest dynamic mass. Outstanding stereo channel separation. ● Very low tracking force required. ● No magnetic attraction to steel turntables. ● Low needle talk ● Highest stylus compliance.

EMPIRE—WORLD'S MOST PERFECT MONO-STEREO CARTRIDGE

Manufactured in U.S.A. Sole Agents for Australia — TRUE FIDELITY

WEIGHTLESSNESS

"NEW EMPIRE 999VE PROFESSIONAL STEREO CARTRIDGE WILL TRACK 30cm/sec AT LESS THAN 1 GRAM!"

The 999VE PROFESSIONAL is the world's only cartridge based on a patented* 4 pole, 4 coil, 3 magnet design, resulting in the most efficient magnetic system available today.

* U.S. Patent 2875282 — Other patents pending.

Sole agents for Australia


TRUE FIDELITY

For a complete colour brochure and further information write to.

C. PINCZEWSKI

RECORDED MUSIC SALON, 23 Collins Street, Melbourne. Telephone 63-6257

Wholesale and Trade enquiries welcome



LIGHTEST MOVING MECHANISM YET DEVELOPED DYNAMIC MASS LESS THAN $.5 \times 10^{-10}$ GRAMS

But, compared with this "one that got away," I wonder how many people he has caught with the same racket? Ordinary people, people on wages, with a couple of kids to raise! People who, if faced with too many such demands, might well ask themselves whether they can afford to run a TV set. Small wonder there are people who regard servicemen as a bunch of crooks; who will put up with almost any kind of set performance rather than call one; who attempt to make their own repairs, no matter how ill equipped they are to do so; and who dig their heels in in protest whenever a serviceman wants to take the set out of the house, no matter how legitimate the suggestion may be.

The next story started late one Saturday morning, just as I was about to shut up shop. The customer, whom I had not seen before, explained that he was having trouble with his TV set. The story as he told it was somewhat garbled but, as nearly as I could make out, it had all started when his wife was dusting the set.

"I think she must have disturbed something," he went on, "because when I switched it on the next time the picture was all leaning sideways with black bars across it."

"Sounds like loss of horizontal hold," I replied. "Probably caused by your wife accidentally disturbing the horizontal hold control. In fact, it shouldn't be hard for you to reset it yourself."

I went on to explain that, in the model set which he had described, the horizontal hold control was one of those located on the rear of the chassis. It shouldn't be hard, by adjusting it carefully, to bring the picture back into lock. The only snag was that it seemed that he had already tried this or, as he put it, he had "... tried all the knobs on the back, but this didn't fix it." He also intimated that he was anxious to get the set going that afternoon, as he wanted to watch the football.

This presented a problem. I was already committed for a couple of out-of-hours calls that afternoon, which I was undertaking as a special favour, and I didn't feel disposed to obligate myself any further. And even if I did, there was little chance that I could even look at the set before the football was over.

I explained this situation to the customer and suggested that, in view of the urgent nature of the situation, it might be better if he tried to find somebody else, better able to tackle the job immediately. I certainly wouldn't mind if he did. So he thanked me for what advice I had given him and we left it at that.

I was rather surprised, therefore, when I found him waiting for me when I opened the shop on Monday morning. But the real surprises were yet to come, and the first was contained in his opening remarks.

"I tried to watch the football on Saturday afternoon, but I got a bit jack of holding my head at forty-five degrees all the time, so I called in another serviceman."

Suddenly the penny dropped. My original diagnosis had obviously been quite wrong, though possibly justified by the garbled story I had been told. I had to clarify the situation before he went any further.

"Do you mean," I said, "that your set was delivering a recognisable picture?

IT IS LATER THAN YOU THINK!

The following story has been reprinted from the British "Electronics Weekly" 7/7/67, where it appeared in their "Talk-back" column, conducted by one "Janus". It appealed to me because, like Janus, I too regard Joseph Roizen as one of my favourite speakers. (At a local I.R.E.E. meeting on one occasion his humorous anecdotes reduced at least one member of the audience to tears.) This story is well up to standard.

Joseph Roizen, of Ampex, one of my favourite electronic raconteurs, seldom misses an opportunity to enliven his talks with a seemingly inexhaustible supply of anecdotes — as from time to time I have noted.

At Montreux (International TV Symposium and Exhibition at Montreux, Switzerland), I gather, his description of the new Ampex slow and stop motion video disc recording unit (viewers are in for some shocks when they see some of the effects possible on this remarkable equipment) was subject to pretty severe cuts by the firm's legal department due to possible patent disclosures.

But this gave him more opportunity to slip in a few stories, one of which I abridge below.

This was about the electronics engineer working, a few years hence, on a gigantic new computer which if successful might result in electronics taking over the work of many millions of humans.

Although fascinated by the challenge of the computer, this prospect put the engineer into a quandary. Should he go ahead and so possibly deliver mankind to the machines, or should he throw over the whole project?

Worried, he returned home one evening to be met by a distracted wife who told him that the refrigerator was not working, and all the food was being spoiled. Dutifully, he checked all the fuses, the leads, the sockets, the connections. But everything seemed in order—yet the fridge remained warm.

Finally, he resorted to that mark of electronics desperation and gave it a hard kick. Sure enough, the fridge responded, and jumped into action.

The incident came as a great relief. No diagnostic computer, he felt, would ever have come up with this solution. Man was clearly destined to remain boss. He could go ahead with the huge computer project without qualms.

So light in heart, he set off next morning for his office. The lift was of the latest voice-controlled type. "Eighth floor," he commanded.

The lift ascended; stopped at the eighth; but then gently slid up to 8½ and firmly came to a halt; the engineer was stuck.

In surprise, he snapped at the control unit: "I said eighth floor."

"I know," replied the lift, "but this will teach you not to kick a fridge."

That the whole picture was simply tilted on its side?"

"Yes, that's right. And it had these black bars across the corner."

I will never understand why "black bars" seem to have such a morbid attraction for TV viewers. Yet it is a fact that any malfunction which reveals the edge of the picture is invariably described with all the emphasis on this fact. And it was the undue emphasis which this customer had put on the black bars which had deceived me in the first place. It was now obvious that all that was wrong was that the yoke had become tilted (a feather duster caught in one of the yoke leads?) and the appearance of the border across each corner was such an obvious thing — to me — that I wouldn't have expected anybody to mention it. The fact that it was mentioned, in a garbled way, led me to believe that the horizontal circuit had lost hold.

But the real surprise was yet to come.

"So I rang up another bloke, like you suggested, and he said he would come around straight away. And he did, too. He looked at the picture, then reached inside the back of the set and did something. The picture started to straighten up and I called out, 'That's better.' But it went back again immediately and the serviceman took his hand out and shook his head. 'Too big a job to fix here,' he said. 'It'll have to go back to the shop to do it properly.'

"Well, I wasn't going to let him take

the set away without knowing what I was up for, so I asked him what it was going to cost. He rocked me a bit when he said, 'Oh, about \$20.' I mean, I don't mind a fair thing, but a tenner seemed a bit steep for what you reckoned would only take a few minutes. So I told him I'd think it over, thanks very much, and let him know later. He seemed a bit put out, but he didn't say much. What do you think?"

"I think," I replied. "that you acted with commendable caution. Come in here." And I led the way into the workshop. There was a set on the floor, with the back off and the yoke still to be tightened, and I switched it on. When the picture appeared I reached inside and gave the yoke a quarter turn.

"That the trouble?" I asked.

"Yeah! It was just like that."

"Well, all you do to fix it is this." And I demonstrated how the yoke was rotated to straighten the picture. I also showed him how to tighten the yoke clamp so that the trouble wouldn't happen again.

For several seconds he said nothing. Then, with considerable feeling, he muttered, half to himself, "And that — wanted to sting me a tenner, just for that."

As we walked back into the shop, he put his hand in his pocket. "What do I owe you for the advice?"

"Forget it," I replied. "This one's on me."

In other circumstances I might have

**NOW
IS
THE
TIME**



**TO
COMPLETE
YOUR
HI-FI
SYSTEM!**

... ADD A SONY TAPEDECK!



TC350—Perfection Plus!


4 Track—2 channel—3 heads.
30-20000 cps.—2 speeds.
S/N ratio:—55 db.—Facilities for
sound on sound, multiplay, etc.

ONLY \$208—after trade-in

TC250A—The Perfect Playmate!

4 Track—2 channel—2 heads
30-18000 cps.—2 speeds—7½" and 3¼" ips.
S/N ratio:—50 db.—2 VU Meters.

ONLY \$160—after trade-in



BUY ON EASY TERMS

**ARE
YOU
GETTING
ONLY
HALF
THE
SOUND!**



**Hear it all with
the NEW**

DECCA

MK. 4 PICK-UP CARTRIDGE
WITH ELLIPTICAL STYLUS

NOW WITH STANDARD ½" MOUNT

DECCA C4/E \$55.50

Outstanding Value!

The excellent DUAL
1009/SK fitted with the
SHURE M55/E MAGNETIC
CARTRIDGE **\$105.00**

Special

Pioneer SE-1 Headphones
complete with 2-way
junction box.

only \$18.00

MASTERSOUND SALES PTY. LTD.,
400 KENT STREET,
SYDNEY—29-1527

OPEN SAT. MORNINGS
9-12 NOON

accepted a nominal sum for advice in lieu of a call, but I reasoned that a little free advice was the least I could do to try to restore some of the lost image which servicemen in general must have suffered.

In this case, I'm afraid, I can't even offer the benefit of a doubt. It was a straight out, calculated attempt to play the customer for a "sucker." And, had it not been for the perfectly innocent discussion which the customer had had with me before he called the other serviceman, this character might well have pulled it off. As it was, the customer had been conditioned to the idea that the fault was slight and the cure simple.

Later, when passing the customer's home, I took the opportunity to drop in and make sure that all had gone well with the repairs. They had, as it turned out, but the thing that struck me most was the unmistakable atmosphere of a couple of "battlers"; an atmosphere which must have been just as apparent to the other serviceman as it was to me. A young couple, obviously not long married, they were renting a "flat" — actually half an old house—while saving everything they could for a deposit on

WARNING

"There is a story going around Queensland that an electrician was electrocuted attempting to push in a contactor with a packet of — cigarettes.

"I have examined one of these packets and it appears to be coated with some kind of metallic film; at any rate, it is an excellent conductor. I think there may be other packets similarly coated.

"Even cigarettes using ordinary cardboard packets are usually wrapped in metal foil inside the packet. Not quite as dangerous as having the metal on the outside, I agree, but I feel that 'ELECTRONICS' Australia' could serve the public interest by publishing the points outlined above."

—W.R.S. (Bundaberg, Q.).

their own home. So our smart friend did not have even the well-worn excuse that "the customer's got more money than I have."

These two stories, plus the one I told last month, are typical of many others which have forced me to the conclusion that there is an increasing amount of malpractice occurring in the service industry. What I was once inclined to write off as exceptions, caused by the odd "black sheep" which plagues every organisation, I am now forced to regard as an increasing and accepted trend in the industry.

As I commented in last month's article, I wonder how these types can sleep at nights. But morals aside — though I make no apologies for quoting moral values—surely this dishonest approach can only be a self-destructive one. And, unfortunately, destructive for the industry as a whole, rather than merely for those who employ such tactics. For this reason, it becomes the responsibility of all who believe in honest trading not only to follow this principle themselves but also to do everything they can to stamp out the dishonest practices of the unscrupulous get-rich-quick characters.

FREQUENCY AND WAVELENGTH

When one starts to work with radio, frequency and wavelength are among the first concepts to be encountered.

by John Schroeder*

To begin with, radio waves are a wave motion, in principle much like the waves caused by the wind on lakes and seas. We shall use the latter kind of wave motion in order to explain what is meant by wavelength and frequency.

Imagine that you are sitting in a boat and you hear the splashing sound of small water waves as they hit the side of the boat. You know from experience that small waves hit the boat at a faster rate than larger ones. Suppose that you (with the help of a watch) determine how many splashes there are per second. That number is, then, the frequency of the waves, or the number of wave crests passing a fixed point — in this case the side of the boat — in one second. The distance between two crests is the wavelength (figure 1). Your experience tells you that big waves have larger wavelengths than small waves. A little thinking will reveal that waves with long wavelengths have a lower frequency (splash at a slower rate against the boat) than waves with shorter wavelength.

For example, think of ocean waves having a wavelength of some 40 or 50 meters from crest to crest rolling toward the shore. There may be only one such wave every ten seconds, and the frequency may therefore be said to be one tenth crest per second. Then think of small waves on the surface of a lake having wavelengths of one tenth of a meter. They hit a fixed point at a rate of 5 every second, in which case the frequency is 5 crests per second.

In broadcasting the radio waves are often compared to the circles of ripples on the surface of the water caused when a stone or similar heavy object is dropped (figure 2).

There is apparently a relationship between the wavelength and the frequency of the water waves. In broad terms, the relationship may be expressed as follows: **the greater the wavelength, the lower the frequency, and the smaller the wavelength, the higher the frequency.**

The same is true for radio waves, although they travel with far higher speeds than water waves. The speed of radio waves is the same as that of light waves, about 186,000 miles per second. The frequency of radio waves is not counted in a few waves per second passing a fixed point (for example, a radio antenna, figure 3), but in thousands or millions of waves per second. Furthermore, the frequency is not given in terms of the number of waves per second, but is expressed in the number of thousands or millions of cycles per second.

In ordinary circumstances, there is a fixed relationship between the wavelength of radio waves and their frequency. A given wavelength corresponds to a definite frequency, and vice versa.




Figure 1: Normally, wavelength is considered to be the distance between the crests of the waves. Their frequency is the number of wavelengths that pass a point in 1 second.



Figure 2: Radio-wave transmission has often been compared with dropping a stone into a pool of liquid. The waves go out in all directions, in concentric circles, like ripples on the water.




Figure 3: With longer wavelengths (a) the frequency is lower. As wavelength diminishes (b) and (c) frequency increases in a fixed relationship.




Figure 4: Radio waves leaving a transmitter antenna travel at more than 186,000 miles per second to the receiver antenna. This definite speed of propagation establishes the relationship between wavelength and frequency.

Radio waves may be identified either by their wavelength or by their frequency, both ways being equally valid.

What makes it possible to separate radio stations from one another in the receiver is that they transmit on different wavelengths, or at different frequencies. In the infancy of radio the wavelength concept was predominantly used to describe the radio waves transmitted. Today, the concept of frequency is being used more.

A significant factor in bringing about this change in custom is the fact that frequency is a natural term to use in connection with audio (or sound) circuits and it is rather cumbersome to think of transmitters operating on a certain wavelength but transmitting sidebands displaced from the carrier by certain frequencies. Equally, it is cumbersome to think of receivers processing a signal of a certain wavelength and recovering frequencies in the audio spectrum to operate the loudspeaker. It is much easier to think in terms of frequency right through the process — though, in fact, there was considerable resistance to the practice in the early days from those who had grown accustomed to wavelength terminology.

It is interesting to note, however, that wavelength terminology is often used in connection with transmitting and special purpose receiving antennas, because there is a basic relationship between the physical dimensions of an antenna and the wavelength of the radio frequency energy it may be designed to handle. For a somewhat similar reason, expressions of wavelength are frequently heard in the context of the very high frequency signals involved in radar, satellite and point-to-point communications. As often as not, these are referred to as "microwave" systems operating on a wavelength of so many centimetres.

Figure 6 shows at a glance the relationship between frequency and wavelength for waves used in communications.

The wavelength of radio waves is ordinarily expressed in metres. The frequency is expressed in cycles per second




Figure 5: Passing the receiver antenna, the waves cause a signal to be generated in the wire. This signal is selected and amplified by the receiver circuits to make it strong enough to operate an earphone or a speaker.

* Adapted by arrangement from an original text by the author.

MAGRATH'S

"SCOPE" THE FASTEST HEATING IRON MONEY CAN BUY!

SCOPE DELUXE

Complete with pouch pack. Stainless barrel. Only 6 seconds INITIAL heat-up time from cold. Exclusive "switch-ring" — no metal to metal contact to burn out. **\$5.95**

SCOPE STANDARD

6 second INITIAL warm up from cold. Performs work of irons requiring up to 150 watts. **\$5.50**

VIBROSCOPE

Protects your property by etching on any metal, ferrous or non-ferrous or annealed, dull or polished. Produces deep penetration—lasting results **\$3.50**

MINISCOPE

Light, only 1½ozs. FIVE seconds heat-up time from cold. Ideal for reaching inaccessible spots. **\$5.28**

Matching "Scope" 3.3V transformer designed for these "Scope" products \$6.58

POST FREE
Anywhere in Aust.

STENTORIAN SPEAKERS

Model H.F. 1016 STENTORIAN
10in P.M. Unit and 16,000 gauss magnet. Universal impedance speech coil at 3, 7.5 and 15 ohms. Capacity 10 watts. Frequency response 30 c.p.s. to 15,000 c.p.s. Bass resonance 35 c.p.s. **\$21.00** (including sales tax).

Model H.F. 1012 STENTORIAN
10in Unit 12,000 gauss magnet. Universal impedance speech coil at 3, 7.5 and 15 ohms. Capacity 10 watts. Frequency response 30 c.p.s. to 14,000 c.p.s. Bass resonance, 35 c.p.s. **\$14.00** (including Sales Tax).

Model T.10 STENTORIAN TWEETER

Speech coil is aluminium wire wound on an aluminium former rigidly fixed to an aluminium diaphragm. Giving high standard of reproduction when used with Stentorian H.F.1012 and H.F.1016 speakers. Speech coil impedance: 15 ohms. Response: 200/15,000 c.p.s. Flux density: 14,000 gauss. Capacity: 5 watts. **\$16.00** (including Sales Tax).

CROSSOVER NETWORK

W/B Crossover is of the filter type and is fitted to all the Duplex Loudspeakers. It is available for use separately, the 3,000 c/s type is half section series connected having an attenuation of 12 dB per octave. C.X. 3000. **\$6.50** (including Sales Tax).

POST FREE Anywhere in Australia.

Panbrake Bench Mounting METAL FOLDER

Invaluable for design prototypes, model shops and hobbyists in every field where light sheet metal is used.

FOLDS Angles from 175 deg. to 85 deg. 18in long. **FORMS** Pans (chassis) from ½in x 3/8in to 18in x 16½in. Maximum depth of pan—1 1/8in. **MAKES** Channels from ½in upward by 18in long. Z section, decorative trims, etc.

CAPACITY: Aluminium to 13-gauge. Mild steel to 21-gauge. ½in bed plate adjustable by cams—multiple slots permit a range of 14 pan sizes from 3/8in to approx. 16½in **SIZE:** 20in x 4in x 4in. **WEIGHT:** 17lb. Mounts with 4-5 1/16 bolts.

\$19.50 **PLUS 12% SALES TAX**

POSTAGE EXTRA.

Within Victoria **\$1.25**
Within N.S.W., Tas. and S.A. **\$1.80**
Elsewhere in Aust. **\$2.60**

Coilmaster

For all types of hand-made coils

This hand-operated, coil-winding machine will produce self-supporting universal and honeycomb coils, also solenoid, single-layer, etc. Three cams, ½in, 3/16in and ¼in throw are included with each. Using these in various combinations with four gears supplied and using different sizes of wire from No. 22 to No. 40, many types and sizes of coils can be made.

\$13.95

Including Sales Tax and postage, anywhere in Australia.

FOUR CHANNEL AUDIO MIXER PROJECT KIT

Especially for Amateur Tape Recordists, Movie makers and Public Address men. This mixing unit has been designed to blend together signals from up to four sources—two dynamic microphones and two crystal-ceramic pick-ups. Fully transistorised, it offers outstanding performance, compactness and economy of operation.

\$25.00

COMPLETE.
Post free. Anywhere in Aust.

CHASSIS Punch Kits

TOOL SETS

Comprises — Wooden Carrying Case . . . Reamer . . . Tommy Bar . . . 1 1/8in Die . . . plus 5 combination Die-Cutters to suit 5/8in, ¾in, 7/8in, 1in, 1 1/8in standard valve sockets.

\$7.00

Hand Operated Nibbling Tool

"Adel" cuts round, square or irregular holes and shapes to any size over 7/16in and notches and trims undersized holes to fit points. Capacity — Steel to 18-gauge. Aluminium or Copper to 16-gauge, punching Bakelite, Plastics, etc.

\$7.50

Replacement Cutting Punch, \$3.75

POST FREE! Anywhere in Australia and territories

VARI-TACH Motor speed control project kit

Further details—Page 43, March '66 "ELECTRONICS AUSTRALIA"

Using this easily constructed, low-cost unit the speed of a "universal" or commutator-type AC motor may be adjusted over a wide range while still maintaining fairly constant torque. Ideal for controlling speed of electric drills, saws, food mixers, projectors, etc.

\$21.75

COMPLETE AND POST FREE

Anywhere in Australia and territories.

Model Train control kit with SIMULATED INERTIA

Further details—Page 80, March '67 "ELECTRONICS AUSTRALIA"

\$14.75


SALES TAX AND POSTAGE PAID

It offers all the advantages of the simple thyristor controller, together with circuitry which makes the model perform just like a real train.

J. H. MAGRATH & CO. PTY. LTD.

208 LT. LONSDALE STREET, MELBOURNE, VICTORIA, PHONE 32 3731

Figure 6: Depicted here is the terminology normally used to describe the major sections of the radio frequency spectrum between 30KHz and 300MHz. Most countries use an AM broadcast band and allocate TV channels in the VHF spectrum. Long - wave broadcasting is used in some countries, also FM broadcasting. There is a good deal of variation in the use of other frequencies.



Because the frequency of radio waves is so high, the unit kilocycles per second is also used, or popularly kilocycles. One kilocycle per second equals 1,000 cycles per second. (Compare the units kilogram = 1,000 grams; kilometre = 1,000 metres.)

EXAMPLE: 1.45 kilocycles per second = 1450 cycles per second; 0.15 kilocycles per second = 150 cycles per second; 174 kilocycles per second = 174,000 cycles per second, etc.

For still higher frequencies the unit megacycles per second is used, or popularly megacycles. One megacycle per second = 1,000 kilocycles per second = 1,000,000 cycles per second. Therefore, 15 megacycles per second = 15,000 kilocycles per second = 15,000,000 cycles per second.

Rules for converting wavelength to frequency and vice versa are set out below:

Frequency in Kcps = 300,000 ÷ wavelength in metres

Frequency in Mcps = 300 ÷ wavelength in metres.

Wavelength in metres = 300,000 ÷ frequency in Kcps

Wavelength in metres = 300 ÷ frequency in Mcps

Frequency	Wavelength
30 Kcps	10,000 metres
100 "	3,000 "
300 "	1,000 "
1 Mcps	300 "
3 "	100 "
10 "	30 "
30 "	10 "
100 "	3 "
300 "	1 "

Kilocycles per second and Megacycles per second are abbreviated as kc/s (or kcps) and Mc/s (or Mcps) respectively. The following units refer to frequency.

1 cycle per second = 1 c/s (cps)
1,000 cycles per second = 1,000 c/s = 1 kc/s (kcps)

1,000 kilocycles per second = 1,000 kc/s = 1,000,000 c/s (cps)

1,000,000 cycles per second = 1Mc/s (Mcps)

Sometimes the letter "s" is arbitrarily omitted from the abbreviation. Thus in the same sentence we might have a reference to 60 cps and 10 Kc or 20 Mc, instead of 10kc/s or 20Mc/s.

In fact, the cumbersome nature of the basic terms "cycles per second," "kilocycles per second" and so on, and the confusion that can arise over their contractions and abbreviations has been largely responsible for the recent widespread adoption of "Hertz," meaning "cycles per second." Metric expansions of the term become kilohertz and megahertz, and the abbreviations Hz, KHz and MHz.

The term cycles per second and its derivations are still legitimate because they express basic quantities. Use of Hertz simply achieves an economy of expression—though its ultimate adoption is being attended by the same pangs which years ago were apparent in the

changeover from wavelength to frequency. In order to accustom readers to the term, Hertz is used throughout the remainder of this article.


Long, medium and short waves: Employing a suitable radio receiver one can tune in transmitters operating in the long-wave and medium-wave bands. The long-wave band covers radio waves having wavelengths between 2,000 and 670 metres (150 to 450KHz), the medium-wave band covers those between 600 and 190 metres (500-1,600 KHz). Many short-wave receivers can also be tuned to certain portions of the short-wave band, which covers waves between 100 and 10 metres (3-30MHz). The range between the long—and the medium-wave bands, 670-600 metres (450-500KHz), and the range between the medium- and short-wave bands, 190-100 metres (1,600-3,000 KHz) are reserved for other uses, such as radio-communication between ships on the sea.

In many ways the short-wave range is particularly interesting to the experimenter. Not only are there a large number of broadcast transmitters operating in the short-wave bands, but one may listen to various types of communication. For example, in the so-called amateur bands (see figure 7) one can follow the conversations and experiments carried on by amateurs. In addition, there are bands reserved for telegraph and telephony between ships, aircraft, etc.

Particular charm is given to the short-waves by their special propagation characteristics. Transmitters very far away may be received, even when using very primitive and inexpensive equipment. This naturally appeals to the amateur, who seldom has any surplus money.

Ultra-short waves (VHF): In later years, the ultra-short waves have attracted more and more interest. Ultra-short waves are radio waves with wavelengths shorter than about 1-metre i.e. with frequencies higher than 300MHz. Broadcasting is taking place today in this range from frequency - modulated transmitters, as well as television transmissions. The FM broadcast transmitters in many countries are assigned wavelengths between 2.7 and 3.4 metres (88-108 MHz), while television transmitters are allocated to "channels" distributed between about 6.7 metres (45MHz) and 1.35 metres (222MHz).

CIRCUIT BOARDS



20c. per transistor, diodes, etc., free. Not necessary as illustrated. Minimum order \$2.00. Technical details with order.

W.I.A. TASMANIAN DIVISION
Box 851-J G.P.O., HOBART

PALACE 8-WATT STEREO AMPLIFIER




SPECIFICATIONS:

● Output Power: 8 Watts, 4 Watts per channel. ● Frequency Response: 60 to 15,000 cps \pm 1db. ● Harmonic Distortion: Less than 3 per cent. ● Hum and Noise: 52 db below rated output. ● Sensitivity: Phono (Crystal) 100mV 250K ohm Tuner 100mV. ● Tube Complements: 12AX7 x 1, 30A5 x 2, 1S315 x 1 (Silicon Rectifier). ● Dimensions: 9 $\frac{1}{2}$ in x 6 $\frac{1}{2}$ in x 3in. ● Weight: 5.1lb.

Price \$32.50

MODEL M6 FOUR CHANNEL TRANSISTORISED MICROPHONE MIXER




All four inputs accept standard two circuit Phone Plugs, while the output jack accepts a standard circuit Phone Pin Plug.

SPECIFICATIONS:

● Input Impedance: "Hi" Impedance for Crystal Microphone, etc. ● Gain: Approximately 6 db. ● Maximum Input Signal: 1.5 volts. ● Maximum Output Signal: 2.5 volts. ● Output for Minimum Distortion: 2 volts. ● Hum: 0. ● Battery: 9 volts.

Price \$6.75

BELPHONE HOUSE TELEPHONE



Complete with batteries and 50ft connecting wire. May be used further apart if desired by using heavier connecting wire.

Colors Available—Ivory, Red and Black
\$13.50 Set of two

Please Note: Clarence St., city, and Liverpool Stores are open Saturday mornings.

KALTRO SVC TV-RADIO REMOTE CONTROL LISTENER



This TV-Radio Remote Control Listener is a combination of an extension speaker and a remote control station to regulate the sound of both the TV, Radio, Phono, or Hi-Fi set and the speaker incorporated in the Listener itself. In addition, up to two earphones can be attached for listening to the sound of the TV, Radio, Phono, or Hi-Fi set without disturbing others around you. Unwanted commercials can be easily cut off by merely turning down the control of the TV-Radio Remote control Listener. A modern designed plastic cabinet with easily adjustable fingertip controls ideal for use in home, office and business. Complete with earphone, 20ft of lead wire and installation instructions.

Price \$8.75

CHEST OF DRAWERS


Three types of Galvanised Chests measuring 17 $\frac{1}{2}$ in x 6 $\frac{3}{4}$ in x 11 $\frac{1}{2}$ in, containing 16 drawers, each measuring 6 $\frac{1}{2}$ x 3 $\frac{3}{4}$ in x 2 $\frac{1}{2}$ in.

● TYPE C.D.1. With 16 undivided drawers. \$7.00.

● TYPE C.D.2. With 16 triple compartment drawers. \$8.00.


● TYPE C.D.3. With 8 triple compartment drawers, and 8 undivided drawers. \$8.00.

The Chests are finished in blue hammertone stoving enamel, are complete with identification cards and packed in strong corrugated cartons. Provision is made for all units to be bolted together in tiers.



CHEST OF DRAWERS TYPE C.D.4.

A 17 $\frac{1}{2}$ in x 6 $\frac{3}{4}$ in x 11 $\frac{1}{2}$ in Galvanised Chest containing 4 full-length drawers each measuring 15 $\frac{1}{2}$ in x 6 $\frac{3}{4}$ in x 2 $\frac{1}{2}$ in. Finished in blue hammertone stoving enamel. \$7.00.



WRITE FOR FREE CATALOGUE AND
PRICE LIST OF TOOL BOXES AND CHEST
OF DRAWERS



"PIPGRAS" HOLE PUNCHES

"PIPGRAS" Hole Punches are made from Alloy Tool Steel, and cut clean and accurate holes in sheet metal. They make a smooth, perfect hole without reaming or filing.

SCREW TYPE, ROUND

Supplied with "UNBRAKO" High Tensile Socket Screws and Wrenches. Cut holes in sheet metal up to 18 gauge.

Type No.	Nominal Size	Actual Water Pipe Size (I.D.)	Pilot Drill Size	Price Each
32.S	$\frac{1}{2}$ in	0.507in	—	$\frac{1}{4}$ in \$2.17
40.S	$\frac{3}{8}$ in	0.618in	$\frac{1}{4}$ in	5/16in \$2.17
48.S	$\frac{1}{2}$ in	0.742in	$\frac{3}{8}$ in	5/16in \$2.80
56.S	$\frac{3}{4}$ in	0.884in	$\frac{1}{2}$ in	$\frac{3}{4}$ in \$3.80
64.S	1in	1.008in	—	$\frac{3}{4}$ in \$4.10
72.S	1 $\frac{1}{4}$ in	1.133in	$\frac{3}{4}$ in	$\frac{3}{4}$ in \$4.53
76.S	1 $\frac{3}{8}$ in	1.172in	—	$\frac{3}{4}$ in \$4.53
80.S	1 $\frac{1}{2}$ in	1.258in	—	$\frac{3}{4}$ in \$4.97
88.S	1 $\frac{3}{4}$ in	1.382in	1in	7/16in \$8.97

With Heat Treated, High Tensile Steel Hex. Head Bolt and Nut.

Cut holes in sheet metal up to	16 gauge.
96.S	1 $\frac{1}{2}$ in 1.512in — 9/16in \$6.60
112.S	1 $\frac{3}{4}$ in 1.762in 1 $\frac{1}{4}$ in 9/16in \$7.60
128.S	2in 2.014in 1 $\frac{3}{8}$ in 9/16in \$8.33

MANUALS

Radio Servicing No. 1	\$1.00
Radio Servicing No. 2	\$1.75
Radio Servicing No. 3	\$1.50
Fault Finding No. 4	\$0.88
Television Servicing No. 1	\$1.50
Television Servicing No. 2	\$1.50
Television Servicing No. 3	\$1.00
Television Servicing No. 4	\$1.25
Philips valve data Book New Issue	\$3.00.

25c postage.

TRANSISTOR MEGAPHONE



Miniature and handy. Can be used anywhere by anybody. Megapet PM-77 Transistor Megaphone . . . Transistors: 3 pcs. Battery: Dry Cell (UM-3) 8 pcs. Acoustic Range: 100 metres. Height: 98 mm. Width 68mm. Overall length: 170 mm. Weight: 550 g. (with batteries).

Price \$18.90



MODEL SB-401 PLASTIC CABINET

Complete with 4in speaker.

Price \$4.00

GENERAL ACCESSORIES

Trade Enquiries Invited

116-118 Clarence St., city, (Clarence St. City and Rhodes Stores are Open on Saturday mornings)

443 Concord Road, Rhodes. 73-0211

7 Pirie Street, Fyshwick, A.C.T. 90035



A READER BUILT IT!

Circuits and devices which we have not actually tested in our laboratory but published for the general interest of beginners and experimenters.

POWER SUPPLY FOR CAR RADIOS ETC.

"Here is a description of a high current low voltage power supply intended for use as a bench supply in the workshop. It is suitable for driving the older vibrator type car radios, of which there are still a number in use.

"I decided to build this because I was sick of continually charging a battery under the bench, which was usually flat after each use. No doubt other technicians have experienced this trouble.

"Since building it I have found other uses for it, such as battery charging, for testing small car refrigerators which are now readily available on the Australian market, and small transistor radios. In these and other general workshop uses it has proved itself after nearly a year of operation, in use almost every day.

"Construction and operation is as follows:

volt' design. The new winding should supply 12V centre tapped.

"Current rating is about 8A and this determines the gauge of wire required. One authority suggests 1200 circular mils of cross sectional area per amp or, for 8A, about 10,000 circular mils. This would correspond to approximately 10 B & S or 12 SWG. This figure probably errs on the conservative side. In any case, the largest gauge that can be used will depend on the available 'window' space inside the core.


"This transformer feeds a bridge type rectifier consisting of four heavy duty diodes, type BYX20/200, mounted two each to two Mullard type 40 P4CB heat sinks. These provide sufficient cooling under maximum load.

"The filter capacitors must be at least 4200uF each to permit testing hybrid and all-transistor type car radios.

EDITOR'S NOTE: There are some points to be considered by anyone likely to build a unit of this kind, but who may not be able to copy the published design exactly.

One concerns possible overload of and damage to the rectifiers in the event of a short circuit across the output — as from a faulty vibrator in a car radio. In the circuit as published the resistance of the choke is probably sufficient to protect the diodes, but this may be lost if one attempts to fit a bigger and better choke.

Secondly, while it is natural to fit as much "C" as possible in the filter circuit, in the interest of better filtering, there is a definite limit to what may be used for the first filter, directly after the rectifier. In its discharged state this represents a short circuit, leaving only the impedance of the transformer to limit



HEAVY DUTY POWER SUPPLY

The supply is designed to deliver up to 8A at 6V or 12V and should operate any type of car radio, as well as other automotive appliances.

"Power passes via an ON-OFF switch to power transformer T1. This came from an old radio, and has taps from 110V to 250V. It is used as a Variac to supply T2. A 6.3V winding in the same transformer is used to supply a panel indicator lamp.

"Transformer T2 was wound for the job, using the core and primary winding of an old TV transformer. All windings other than the primary should be removed, the number of turns of the lower voltage secondaries being checked in the process to arrive at the 'turns per volt' design figure for the transformer. Thus, a 6.3V winding which consisted of about 33 turns would suggest a '5 turns per

The choke which I used was a K type Rola speaker transformer with a 15 ohm/3.5 ohm secondary, the whole secondary winding being used. Anything smaller will not handle a heavy load without overheating.

"An oscilloscope test with the supply delivering 6A showed it to be near enough to pure DC. Only a slight ripple was apparent. This supply could, of course, be regulated but I have found this unnecessary as the voltage remains fairly stable even under considerable drain. Metering of the supply is optional.


"The cost of this supply could be kept under \$20 and for the serviceman it's a time saver."

(From Mr R. A. Bayley, 27 George St., Thirroul, N.S.W.)

the rectifier current to a safe value. Again, it is probable that the transformer used in the original has a high enough value to limit the current to a safe value, but this may not be automatically so for other units. Unless the situation is known precisely, additional "C" should be added to the second filter only.


Finally, an RF by-pass in parallel with the second filter may prove beneficial, particularly when the electrolytic begins to age a little. This should be a non-electrolytic capacitor of about .1uF, or larger if this can be provided economically. The need for such a capacitor would be indicated by any tendency to RF instability in a receiver, particularly if this was absent on battery operation.

A SCIENTIFIC BREAK-THROUGH IN DESIGN




The new ADC-10E/II Cartridge

Stylus mass could not be further reduced, as, thanks to the INDUCED MAGNET ARRANGEMENT, the Mark I has a moving mass dramatically lower than that of its closest competitors. Equally, it would have been pointless to increase an already fantastically high compliance of 35 c.u. It was not easy to further improve such an advanced design, BUT IT HAS BEEN DONE BY INCORPORATING A SIGNIFICANT, PATENTED REFINEMENT OF THE ARMATURE SUSPENSION. This new version traces the most complex and difficult passages so superbly that the mind can only grope clumsily for words of sufficient praise. You simply have to experience such unparalleled tracing ability and listening quality for yourself. There is no doubt, that the new ADC.10E Mark II represents the state of the art in high fidelity cartridges and its genuine, effortless reproduction is a new experience in sound quality. The performance is, indeed, second to none.




The CRESTA

The response to our June and July advertisements was outstanding. Very soon, these world-famous speakers and speaker-systems will be available on the Australian market. Our waiting lists are long, but the supply position will dramatically improve in the near future.



The CONCORD, reviewed in Hi-Fi News, March 1967.



The no-compromise, professional CARLTON

We sincerely suggest that you audition **KEF SPEAKERS** before buying any other brand and if you are not in a particular hurry your patience will be well rewarded. To say that these superb and truly remarkable speakers are well worth waiting for would be an understatement. Watch for further announcements!


J. H. REPRODUCERS PTY. LTD.

293 HUNTINGDALE ROAD, CHADSTONE, VICTORIA. 3148

TELEPHONE 277-3066

Exclusive Australian Representatives of ADC, U.S.A. and KEF, U.K. and Makers of the J.H. Synchronous Turntable.

AUDIO TOPICS



LESS NOISE, MORE DYNAMIC RANGE

In terms of background noise, modern discs and tapes are a far cry from those of the immediate post-war era but engineers — and critical buyers — are not yet satisfied. The battle against background noise still goes on, as evidenced by recent developments.

By Neville Williams

Noise problems begin at the original recording site. Particularly with large orchestras and large organs, the recording equipment has to be taken to the performance, rather than vice versa. Microphones have to be placed so that they will "hear" the performance as a whole, involving something of the acoustic environment. All too readily does this mean that the microphones will pick up extraneous acoustic noise at sufficient level to be heard through the quieter musical passages. Largely, this is a problem of time, site and microphone placement and the problem is being eased by new auditoriums which have been designed with an eye to their likely use for recording and broadcasting.

However, this is only the beginning of the problem. In practical recording systems, the amplitude at which the strongest signals which can be recorded is limited by the onset of distortion in the medium — non-linearity in the magnetic or optical pattern, loss of tracing ability in a stylus system, etc. The weakest signals have to compete against the inherent noise in the system — grain structure in the film or tape, surface characteristics of discs, hiss and hum in the associated amplifiers etc. In practice, the ratio of the strongest to the weakest signals which can be successfully (and commercially) recorded, referred to as the "dynamic range" of the system, is smaller than is called for by many musical performances. As a result, either the musical performance itself has to be modified to the restrictions imposed by the recording system, or else the dynamic range of the signals actually recorded has to be compressed by manual or automatic manipulation of the recording amplifier gain.

In considering the problem, it is insufficient to think just in terms of the original process of committing the performance to a master recording. In practice, the signal on the master recording has to be transferred several times before it reaches the copy which a customer will actually buy. Each copying or "dubbing" process is likely to apply further restriction to the dynamic

range, notably by adding a quota of noise to compromise signals which are at too low a level. The master recording, therefore, has to be engineered not as an end in itself but as the first link in a fairly long chain.

Many techniques have been employed in an effort to reconcile the naturally wide dynamic range of musical performances to the limitations of practical commercial recording systems. Typically:

(1) Setting the gain of the system to cope well with low level passages and manually lowering the gain in anticipation of loud passages.

(2) Setting the gain to cope well with loud passages but advancing it in anticipation of low level passages.

(3) Using automatic compression techniques, normally to restrict the amplitude of large waveform peaks.

(4) Use of multiple microphones and complex console techniques to pick up total or individual sounds from suitable distances.

(5) Use of highly sophisticated amplifiers and recording medium (e.g. magnetically coated 35mm film stock) to preserve the highest possible dynamic range during the early stages of recording.

Apart from the limitations of human operators, methods (1) and (2) in particular call attention to themselves in the final reproduction by their effect on the total noise and reverberation ambient of the particular performance. Anyone who has listened at all critically to reproduced sound will, many times, have noticed changes in background as some unseen and perhaps otherwise forgotten operator has turned a fader up or down.

Automatic compression or peak limiting (3) minimises this latter problem but all too easily introduces a distortion component in the waveforms upon which it operates. Nor is the process readily reversible; it is not easy to restore accurately the waveshape or to recover the original dynamic range, particularly for large orders of compression. This complicates any idea of using a compressed

signal for the early recordings and transfers, and of restoring it, at least in part, on the final customer recording.

By using and especially combining techniques (4) and (5) records can be made having very low noise and a dynamic range with peaks of such amplitude that they are likely to exceed the tracking abilities of even high quality magnetic pickup cartridges. However, it is not always practical to use these techniques and the recording industry still has to face two rather harsh realities:

(1) Neglecting pops caused by surface effects, many discs are still quieter in terms of "white" noise than the master tapes from which they were taken, and

(2) While pre-recorded tapes on the market are free from clicks and pops and have better stereo separation than the equivalent discs, their signal/white noise ratio is markedly poorer under similar playing conditions.

While commercial tapes and discs are both well able to meet the standards required by the present-day mass market, engineers and hi-fi conscious listeners alike are aware of these limitations and there is a constant challenge to overcome them. The aims may be expressed in three ways, all of which are really variations on the one basic theme:

(1) To achieve wider dynamic range from the ultimate consumer recording, minimising the problems of peak amplitude on the one hand and background noise on the other.

(2) To do so with less expensive recording and copying facilities.

(3) To increase the tolerance of the recording chain as a whole to signals of all amplitudes, so that the final result will depend less on critical setting up of gain and levels.


In the face of this situation, audio engineers and hi-fi enthusiasts alike are likely to show ready interest in any system claiming to increase the dynamic range and/or reduce background noise, particularly if it is applicable to existing equipment. But, equally, they are likely to be dubious of any claim to have solved the problem in any easy way.

And they have certainly been dubious about the "Dolby Audio Noise Reduction System" which was announced some time ago. Until proved otherwise, "The Dolby" was fated to be treated as just another black box, surrounded by just another set of extravagant and unlikely claims. Gradually, however, the impression has grown that the Dolby unit may be worth a second look, even if

Some plain talk from Kodak about tape:

SIGNAL-TO-NOISE RATIOS, SATURATION OUTPUT AND UNIFORMITY


Modulation noise, jocularly referred to as "mud", is the most discriminating test of sound tape. A close look at the "mud" that forms the lower limit of the dynamic range reveals that the recorder's electronic and transport systems are responsible for the lion's share of noise. By noise spectrum analysis we can examine noise level (in db's) at every frequency. Look at the graph below.



Note that there is a much higher level of modulation noise at 1,000 cycles than at 15,000 cycles. This indicates — to us, anyway — that a single-frequency modulation noise test is not the most meaningful in terms of a noise spectrum. We use two frequency bands: 0-1000 cps and 1000-15,000 cps to provide us with a low-frequency s/n ratio and a high-frequency s/n ratio.

This is a much tougher test than using a single frequency or integrating the entire spectrum. The following chart shows the effect.

Notice how taking a modulation noise average for the entire spectrum results in a figure that is lower than the L.F. figure and



higher than the H.F. figure. How is this important? Here's how. If we use the modulation noise level from the low-frequency range (A) we get a poor dynamic range and signal-to-noise ratio. We get a moderate one from the average (B) and a great one from the H.F. figure (C). There are those who would measure from C and publish this as the performance of their tape. Let them. We measure low-frequency and high-frequency mud and still come up with a dynamic range that is often as much as 6.5 db better than conventional tapes in the L.F. area. 1.5 db better in the H.F. range — even when they use their lowest figure. We are pretty proud of our silence. Shhhhhh is the word at Kodak.

Here's how we test for saturation output. We increase the input and monitor the output. When we reach a point where the output no longer increases with the input, we know that we have reached saturation, which is the point where every available oxide particle in the layer has been polarized.

As a test it does not have earth-shaking implications, but it does tell us about how many oxide particles

are present, which is actually a measure of the thickness and particle density of the oxide layer. We get a figure in db and can use it to accomplish some pretty tight quality-control over oxide coatings.

We're pretty proud of that control, too . . . and with good reason. We make our tape so that we are well within the rigid specifications we publish. At Kodak, uniformity is a way of life. When we say sensitivity varies no more than $\pm \frac{1}{4}$ db within a roll and $\pm \frac{1}{2}$ db from roll to roll, we *really mean it!* This is only the uniformity of the low-frequency signal. We check high-frequency uniformity as well. In that way we can keep close tabs on the uniformity of the oxide thickness and the uniformity of the oxide surface.

But uniformity is more — much more — than just a word. It has plenty of practical significance. For instance, uniformity within a roll assures constant frequency response, balanced output for all recording tracks, and freedom from "drop-outs". Reel-to-Reel uniformity permits inter-reel splicing without obvious changes in the level of the recorded signal. And for the professional, it means that he can find one optimum bias level for all rolls of tape.

You can do all these things with Kodak tape. In fact, we're so proud of the uniformity of our product we put our name on it . . . right there on the back of the tape!

only because it manages the job of compression and decompression far more effectively than earlier circuitry. Writing in "Hi-Fi Stereo Review" for July, '67, John Milder reflects some of this recent enthusiasm. What follows is a condensation of his article.

Over the past few months, recording engineers and executives have been talking enthusiastically about "the Dolby," a device whose purpose is to reduce the background noise of master tape recordings. According to reports from the recording industry, the new device has important implications not only for professional applications, but for the ultimate quality of records to be played in the home. And from the evidence now supplied by the first


halves (input and output) of the Dolby's operational cycle, and that all tapes and recorders using the Dolby system are completely interchangeable. In the process, it assures that the print-through noise that often accumulates during the storage of tape will be greatly diminished when the tape is put through the second (or playback) half of the cycle.

As far as the recording industry is concerned, the big advantages of the system are, first, the tremendous basic gain in signal-to-noise ratio (10 to 15dB, depending on the frequency range) and, second, the ability to re-record ("dub") tapes for processing with virtually no discernible increase in noise from copy to copy.

I came within a foot or two of a loudspeaker. In a direct comparison with the best record I know of, derived from a 30ips master tape recording on half-inch tape, instead of the usual 15ips recording on quarter-inch, the difference in favour of the new records was very audible. And after several hours of listening and cross-checking, I became convinced that virtually all of the "material noise" that I—and you—have been hearing from recent discs is actually the result of tape hiss in the master recording. (This is not to say that there can't be a bad pressing made from a Dolbyised master tape.)

The absence of tape hiss is not nearly as important for most listeners

Figure 1: A system developed by Pye transforms the audio envelope temporarily into a pulse train. In this form the signal can be modified by varying pulse width.



two "Dolbyised" records produced in this country (one from Vanguard, one from Nonesuch), the reports seem to be justified.

I feel these two records represent one of the most clearly audible breakthroughs in sound quality in many years. That is not the kind of statement I thought I would be making when given these recordings to evaluate, but the more I have listened to them, the more I have become convinced that the new Dolby system will become a sine qua non for recordings of serious musical material until some entirely new recording medium arrives.

The Dolby A-301 Audio Noise Reduction System is a simple-looking "black box" designed for connection to the inputs of a tape recorder during recording and the outputs during playback. The invention of Ray M. Dolby, an American audio engineer now living in England, it is designed to combat not only the high-frequency tape hiss added to any original signal during tape recording, but also many other kinds of background disturbances (including print-through echo, crosstalk, and scrape noise) that inevitably appear during the tape-recording process.

The new Dolby system does nothing at all to loud signals. Instead, working in four separate segments of the frequency range, it begins by boosting the level of all signals below a certain strength just before they are recorded. Then, during playback, it cuts these boosted signal areas back to their original level, and, in the process, reduces to the same degree any noise that has been added to the signal during the recording process.

This "backward" process has been attempted before, but the Dolby system succeeds where previous gadgets have not, and for two reasons. Firstly, by handling four separate frequency bands and secondly because its operation is perfectly symmetrical in its boosting and cutting of signal strength.

It means that a tape can be stored for months or years between the two




Figure 2: Illustrating the performance characteristics of the Pye unit operating in linear mode, with three orders of compression or as a peak limiter with a 20:1 compression ratio above the limit threshold.

Can you hear a 10 or 15dB reduction in noise? Yes, you can, and the results are far more dramatic than you would guess. The outstanding characteristic both of Vanguard's and Nonesuch's first Dolbyised records is clarity—to an almost incredible degree. It is not simply the absence of tape hiss or other noises during a quiet passage heard in a quiet room, but the absence of all sorts of effects, unidentifiable in themselves, that add a slight haze to the reproduction of musical instruments. The effects of print-through, crosstalk, and other kinds of middle- or low-frequency noise are unquestionably subtle individually or in combination, but there is nothing subtle about their absence.

Aside from clarity there is also a definite decrease in the amount of distortion perceptible in loud passages. This is a function of the engineer's ability, with the Dolby, to set peak recording levels a bit lower without having to worry about noise in quiet passages. And it is highly noticeable in the undistorted burr of the trombone in Vanguard's L'Histoire du Soldat and the unfuzzed fortissimo of the piano on the Nonesuch recording.

As for tape hiss as such, for all practical purposes it simply isn't there. Late at night, in a quiet room, at a listening level louder than my neighbours will freely tolerate, I couldn't hear the slightest sound of hiss until

as the question of overall clarity. But it does become important to those who own very-wide-range loudspeakers.

Finally, it is worth emphasising that the Dolby system appears to add no distortion of its own worthy of the name. No spurious effects of any kind appear to be added. Aside from Mr Dolby's thoroughgoing engineering, this seems to be a function of the system's doctoring of only the lowest signal levels.

The two recordings referred to by John Milder are:

RACHMANINOFF Sonata in C Minor for Cello and Piano, Op. 19. **KODALY** Sonata for Cello and Piano, Op. 4. Harvey Shapiro (cello); Earl Wild (piano). **NONESUCH** H 71155.

STRAVINSKY L'Histoire du Soldat, Madeleine Milhaud, Narrator; Jean-Pierre Aumont, the Soldier; Martial Singher, the Devil. Gerald Tarack (violin); Charles Russo (clarinet); Theodore Weis (trumpet); Julius Levine double bass; Lorin Glickman (bassoon); John Swallow (trombone); Raymond Desroches (percussion); Leopold Stokowski cond. Vanguard VSD 71165/66 two discs.

Whether John Milder's enthusiasm for the Dolby system is justified, only time will tell. It could be that some of the advantage in the records reviewed is stemming from improvements in other directions, or from special attention which detail often receives when

something new is afoot. Again, Dolby may not have a mortgage on the ideas behind his unit and other engineers and companies may well have their own developing answers to the whole problem.

As a matter of interest, in this connection, the May 1967 issue of "Industrial Electronics" refers to a system which the Pye Company in England has developed to compress audio signals fed to sound transmitters, to obviate the effects of inadvertent overmodulation on peaks.

The article refers to the known limitations of the type of compressor in current use, using non-linear elements to re-

duce gain on unduly large peaks of signal:

(1) Distortion tends to be excessive if the system operates at too high a signal level, especially with large orders of compression.

(2) If signal levels are restricted to minimise distortion, signal/noise ratio becomes a problem.

(3) It is difficult to define precisely the characteristics of non-linear circuit elements and to provide their converse where required.

(4) Distortion components introduced by normal compression methods can themselves become modulation compon-

ents, so that an attack on one problem introduces another.

In the new Pye system, the audio envelope is interrupted at a frequency much greater than the highest audio frequency being handled. This interrupted waveform, as illustrated in figure 1, is subsequently passed through a low-pass filter, which removes the pulse component and reconstitutes the original envelope, with minimal distortion. If no other circumstances intervene, the system is quite linear in its operation and output very closely approximates input.

However, at the point in the chain where the signal is in the form of discrete pulses, it is possible to modify their energy content in terms of pulse width and according to a predetermined mode governed by signal amplitude or pulse height. Any such modification of pulse width appears as a modification of output waveform relative to input waveform.

Figure 2 indicates the claimed performance parameters. Unlike the Dolby unit which leaves the peaks unaltered and elevates the low level signals above the noise, the Pye unit achieves a similar end result by elevating the entire recording level and operating to compress the louder signals. Alternatively, it can operate in a "peak limiting" mode, similar to existing peak limiters used by broadcast stations.

In compression mode, the unit operates above a defined pivot or threshold point with selectable conditions ranging from linear (no compression) to ratios of 2:1, 3:1, 5:1.

As a peak limiter, the threshold is raised by 8dB but the compression ratio is increased to 20:1.

While the whole of the discussion is in the context of compression and/or peak limiting for broadcast transmitters, its relevance to the recording situation is evident. Again, only time will tell whether the new generation of records and tapes on the market will be "Dolbied" or "Pyed." ■

When accuracy counts (and that's ALWAYS) choose **selectest** TESTERS

The SALFORD SELECTEST makes no compromise with accuracy. In either position (vertical or horizontal) legible markings and a knife edge needle give you quick easy-to-see readings that are ACCURATE.



Consider these important features that only SELECTEST can offer:

- Large dial gives 25 % greater scale
- Mirror positioned for minimum parallax error
- Continuous rotation switches and multiplier switch give excellent range of readings
- Convenient terminals location for horizontal or vertical operation
- Automatic overload cut-out
- Sturdy 'Melamine' case for long life
- Strong, convenient longlasting handle

For full details of this superb instrument contact:



Electronics & Communications Division,
G. E. C. (AUSTRALIA) PTY. LTD.
Cnr. Bibby St. and Burns Cres., Chiswick, N.S.W. 83 4011

**MAIL
THIS
COUPON
TODAY!**

Please send me further details on the Selectest Tester.

Name.....

Address.....

GE2133

CARTRIDGE REPLACEMENT GUIDE LISTS 6,600 TYPES

The job of selecting a replacement cartridge for a difficult to get type has been made easier for audiophiles in U.S.A. The Singer Products Company, of New York, has produced a cartridge replacement guide which lists 6,600 cartridges for which its Sonotone range of cartridges can be used as replacements. All data has been printed out of the company's computer. The cross references are held in the computer's memory bank, and are up-dated monthly.

The guide is divided into two main sections. Section 1 shows all data for the use of Sonotone cartridges to replace competitive cartridges, with the latter alphabetically. Section 2 gives compiled data for using Sonotone cartridges as original equipment and as replacement equipment for radiograms and players. Other information included is a comprehensive index to enable the user to quickly locate the page on which a cartridge is listed; a cartridge specification guide for performance comparison; and photographs of all Sonotone cartridges to simplify identification when the type number is not known. ■

KNOW YOUR GRAMOPHONE*

A plain man's guide to records and reproducers

By JOHN BORWICK, B.Sc.

PART ELEVEN — LOUDSPEAKERS

The subject of loudspeakers is rambling and at a designer's level, complex. However at our, mainly practical level, it will be enough to look at just a few of the construction aspects. Ultimately, a loudspeaker is a source of sound waves and, since we hope that these will be "musical" sounds, it is natural to compare the loudspeaker with musical instruments.

String, wind and percussion instruments all vibrate—when they are bowed, plucked, blown or struck—and their vibrations set the air into a sympathetic to and fro motion which spreads outwards at about 760 miles per hour. Each type of musical instrument has a limited band of frequencies to cover and is carefully built to impart a traditional tone colour to the sounds it emits.

A loudspeaker is meant to reproduce the sounds of all musical instruments. It should therefore be capable of vibrating and radiating at all frequencies. It should also be equally efficient at all frequencies and, even more difficult, it should introduce no characteristic tonal quality of its own.

How loudspeakers work: Moving coil (electromagnetic) loudspeakers are so much in the majority, that I shall follow the usual practice of describing this type first and treat other types—including the important electrostatic loudspeakers—in a brief coda.

Figure 1 shows the outline of a typical drive unit. The voltage appearing across the amplifier output terminals is applied to the ends of the coil. In the absence of any signal, the front and back suspensions hold the coil accurately in the annular gap between the magnet pole pieces. When current flows, the coil is subjected to the well-known electromagnetic force and will tend to swing back and forth in step with the half cycles of the alternating current signal. We have therefore achieved the first part of our electro-acoustic conversion and produced a vibratory movement corresponding to the signal to be reproduced.

It is now necessary, however, to cause this vibration to set a substantial amount of air in motion. This is the function of the cone. It is large enough to couple the oscillations of the coil, which is mounted at the cone apex, to the air—producing a train of alternating compressions and rarefactions. The cone should be light enough to be easily driven, other important characteristics being its stiffness and the flexibility and damping properties of the periphery surround.

The need for a baffle: Setting aside

for the moment the problems of making the loudspeaker equally responsive to all frequencies, we can examine the way sounds will be radiated. Assuming that the cone is completely stiff and that the surround is 100 per cent compliant, the system will move backwards and forwards like a piston (see figure 2a).

Notice that the cone is actually a double radiator. At the same time as one train of alternating pressures is pushed out by the front of the cone, a similar train is emitted by the back. There is the important difference too that the front and back radiations are




Figure 1: Moving coil loudspeaker, showing the most important construction features.




Figure 2: Need for a baffle: (a) without a baffle, back radiation can bend round to the front; (b) a baffle can prevent this interference except at the lowest frequencies.




Figure 3: Infinite baffles: (a) mounting in a solid wall; (b) a totally closed box.

always half a cycle out of step (180 deg. out of phase). Therefore, we must expect serious cancellation effects due to interference between the two waves.

At the sides, this cancellation will be more or less complete: at the front, due to the screening effect of the cone itself, the cancellation will be very much less at middle and high frequencies. But the low frequency (long wavelength) sounds can bend round the cone and so even here we get serious interference—at all frequencies below that for which the wavelength is roughly equal to the cone diameter. It is possible to extend this screening effect to lower frequencies by fitting a baffle (see 2b). Excellent results can be obtained down to say 120Hz, with a baffle about 36in across. Lower frequencies than this need impossibly large baffles.


Infinite baffles: One solution, attractive in its theoretical simplicity, is to mount the loudspeaker in an infinitely large baffle. This will keep the two waves apart and allow the low frequency performance, as heard by a listener at the front, to extend as far down the musical scale as the mechanical system can go. The back radiation is lost, of course, though it is possible to visualise a loudspeaker built into the wall dividing two rooms (see figure 3a). The music could then be enjoyed in two rooms at the same time. Using the wall or even the door, of a large cupboard has also been tried successfully. The door should be fairly well sealed, of course, and the cupboard must be large (and preferably contain hanging clothes, etc., to break up and absorb any internal resonances).

Talking about the true infinite baffle now takes us to the class of, often quite small, cabinets which are euphemistically referred to as "infinite baffle" enclosures. An example is shown in figure 3b and it will be seen that the baffle is indeed infinite in that the box is totally enclosed so that none of the back radiation from the cone can escape. Unfortunately, a closed box will always act as a resonator—like the body of a violin or 'cello—and specific frequencies will be emphasised out of all proportion. (There will be resonant modes associated with each dimension of the enclosure and its total volume.) It is to cut down these resonances that, as figure 3b shows, infinite baffle enclosures must be heavily lagged with sound absorbent materials. In fact, it is quite usual to fill the enclosure completely with absorbent. This has the effect of reducing the sound velocity and so increasing the apparent box volume.

Another aspect, which I have not so far touched upon, is that the loudspeaker coil/cone assembly will itself have an inherent resonant frequency. This is determined by the mass of the system and the stiffness of the suspension and is the familiar base resonance frequency quoted in loudspeaker specifications. Now, clearly, in an airtight box the stiffness of the enclosed air will add to the effective stiffness of the speaker drive unit and the effect of this is to push up the overall resonance by an octave or more.

This is a severe drawback and, to counteract the bass loss which this entails, infinite baffle loudspeakers are generally fitted with unique new types of drive unit. These have very compliant, floppy surrounds, to give extra low initial resonant frequencies—of about 25Hz instead of the usual 35-65Hz—and ingenious coil centring devices to allow extra


Reproduced by arrangement with "Gramophone" magazine.



More of the music and less of the distortion!

The processing and production of discs produce a waveform in which distortion rises extremely rapidly as the upper frequency limit is approached. To obtain the best quality under such conditions the very high harmonics must be attenuated at a rate which is a function of the rate of rise of distortion.

The QUAD filters provide both switched adjustment for frequency and continuously variable adjustment for rate of attenuation. The degree of attenuation need, therefore, never be greater than necessary to clean up the programme but is always adequate even for very bad cases.




For the closest approach to the original sound

Our slogan for fifteen years and our design objective for twice that long. Ask your retailer for details of the QUAD range of high fidelity units or write to your State Distributor (below) or to the sole Australian Agent:

British Merchandising Pty. Ltd.
SHAW HOUSE 49-51 York St., Sydney, N.S.W.

Telephones 29.1571 (3 lines)



Interstate Representatives—VIC.: D. G. Lockwood & Co. Pty. Ltd., 810 Glenferrie Rd., Hawthorn. QLD.: A. E. Harrold Pty. Ltd., 23 Charlotte St., Brisbane. SOUTH AUST.: Stephen & Company, 53 Wyatt St., Adelaide. WEST AUST.: O. F. Gamble Pty. Ltd., 888 Hay St., Perth.

"long-throw" vibrations and so restore some of the bass efficiency. Not surprisingly, these special units tend to be expensive, but the growing demand for ultra-compact loudspeakers to give stereo in a reasonably small space has led to their adoption by most manufacturers.

Bass reflex enclosures: Before the advent of stereo, when it was necessary to accommodate just one loudspeaker, the bass reflex system was in vogue—and is still preferred by many people whose rooms can take two decent sized cabinets.

Figure 4 shows the basic construction of a reflex enclosure. Instead of being suppressed, the back radiation is folded back and allowed to radiate from a carefully dimensioned port. The cabinet and port dimensions are worked out together so as to produce a resonating enclosure tuned to the resonant frequency of the drive unit. (Well, it is the enclosed volume of air that really matters: any reasonable combination of length, breadth and height to give the required volume will do.) When this is done properly, the effect is to give just the right phase shift within the box so that the sound radiated from the port, instead of being in reverse phase with the cone frontal wave, is in phase and so reinforces the bass.

An impressive way of illustrating the effect of a bass reflex enclosure is to show the graph of a loudspeaker's impedance (see figure 5). Curve A is for the drive unit alone, and the impedance is seen to leap upwards at the resonant frequency and then rapidly die away. Curve B shows that the cabinet produces a much smaller double hump, with at least the promise of a smoother bass response. In passing, it will be seen that the 15-ohms nominal impedance of this particular unit applies only at around 400Hz, and is quite different elsewhere in the frequency band.




Figure 4: Bass reflex cabinet: the internal dimensions are tuned to the unit resonance and so in-phase radiation takes place from the port.

Other types of enclosure: Column loudspeakers had a spell of popularity when stereo first came on the scene but have now been largely superseded by the compact, infinite baffle units. The column has the distinct advantage that, while taking up only a limited amount of floor space—about 1 ft square—it can nevertheless have a decently large internal volume and the sound is radiated at a useful height to clear furniture, etc.

Instead of making the drive unit forward-facing at the top of the column, which might mean distortion due to strong reflections from the back and sides, it is usual to mount the unit on

its back. Then, to give a useful diffusion of high frequencies over the listening area, a conical reflector can be placed above the drive unit.

The column may be designed on any of the normal cabinet principles—infinite baffle, bass reflex—perhaps with a “distributed port” consisting of a number of holes or slots instead of a single opening—or two types not so far discussed, the folded horn and labyrinth.

Horn loading, that is the placing of a flared tunnel in front of a loudspeaker drive unit, gives a very worthwhile increase in overall efficiency. This leads to very low distortion, because the cone excursions can be so much smaller, and




Figure 5: A properly tuned reflex enclosure changes the peak A in the unit's impedance curve to two smaller peaks B.

a clean, crisp response to transient sounds. Unfortunately, the sound output falls off rapidly below a critical frequency which depends on the size of the horn. Therefore, to cope with very low frequencies, horns of 10 or 20ft length are necessary with flare openings measuring several square feet. Except for a few amateur under-floor constructions, the only way that such dimensions can be accommodated is to fold the horn back on itself at least once. The construction of horn-loaded speakers is therefore complicated and relatively costly.

Much the same applies to labyrinth enclosures. Here the principle is that the back radiation enters a very long, lagged pipe which absorbs it completely—only the forward radiation normally being sent.

Other types of drive unit: So far we have dealt only with the moving coil type of drive unit (figure 1). A number of other types are in use, however, and deserve brief mention.

First, the **ribbon loudspeaker**: this also is a powerful magnet but the coil/cone combination is replaced by a single corrugated ribbon of aluminium. This is 3in long by about 1/4in wide and acts as coil and diaphragm simultaneously.

Naturally the radiating surface is small and so, to increase the efficiency, ribbon speakers normally use horn loading. This applies, for instance, to the Altec Ribbon tweeter which has a 9in horn and handles frequencies from about 1000Hz upwards. A steep cut filter is necessary to protect the ribbon from low frequency currents but, on the credit side, the high frequency and transient performances can be excellent.

The **electrostatic loudspeaker** depends on the force of attraction which exists between electrically charged bodies. In simplest form, used in a number of high frequency designs, it consists of a flat plate over which is stretched a

plastic film. The outer face of this film has a conductive coating and applying a voltage between plate and coating will cause an inward movement against the resilience of the film. If a DC bias of, say, 300 volts is applied, an alternating signal (not exceeding 300 volts peak) will produce the required vibrations. Special steps are necessary to overcome the distortions inherent in this simple arrangement, but the push-pull system obtained by having two fixed plates, with the diaphragm in between, virtually eliminates the distortion altogether.

The best known example of this latter system is the Quad Electrostatic loudspeaker. This covers the full frequency spectrum by using a central treble section operating from 200-300Hz upwards. On either side of this is a bass section having a greater plate spacing to permit the larger diaphragm displacements necessary at low frequencies. Special delay networks avoid too directional radiation at high frequencies, the result being a fairly even distribution over front and back angles of about 70 degrees. Since no cabinet is used, the Quad ESL avoids the problems associated with cabinet resonances, but against this must be weighted its greater dependence on room positioning and the fact that, though delayed, there must eventually be front/back cancellation effects at the extreme bass frequencies.

The **ionic loudspeaker** has no moving parts. A small volume of air in a quartz cell is subjected to a high voltage at a supersonic frequency. The effect is for the air to be ionised (formed into particles carrying positive or negative electric charges). If the high frequency voltage is modulated by the audio signal, the ionised air will tend to expand and contract and so generate sound waves. As with the ribbon speaker, the ionophone cell is situated at the throat of an expanding horn to give efficient radiation. This principle is used in the Fane Ionofane high frequency unit, operating at frequencies above about 3,500Hz.

Most of these special drive units are designed to handle only high frequencies and therefore must be used in conjunction with a conventional moving coil bass unit. The questions of multi-speaker systems, amplifier matching, room positioning, etc., will be covered in the next instalment.

SPRAGUE

THE MARK OF RELIABILITY

BLUE JACKET

VITREOUS ENAMEL RESISTORS

ACRASIL

SILICON WIREWOUND RESISTORS

HYREL EXTENDED RANGE MATCHED NETWORKS

METAL FILM RESISTORS.

Sole Australian Representative

D. R. Johnston and Co. Pty. Ltd.

Suite 14, "Stanhill 33",

Queens Road, Melbourne.

TELEPHONE 26-1381—TELEGRAMS & CABLES "VIATON", MELBOURNE

printed circuits

Specialist in Printed Circuits, Coding, Artwork to Order, Prototype Service.

HOTRONIC

67 Howard Ave. Dee Why N.S.W. 9822056

JABEL



MAKE YOUR OWN PRINTED CIRCUITS

NEW LOW PRICES HANDY SIZES

XXXX SINTHANE PANELS

6" x 3", 25c	12" x 3", 45c
6" x 6", 45c	9" x 6", 60c
	12" x 12", . . . \$1.55

ETCHING KITS—

comprising Bituminous Paint, Artist's Brush, Resin, Ferric Chloride and full instructions 75c.

SPECIAL

\$2.00 PACKAGE OFFER

One 6" x 3", one 6" x 6" or one 12" x 3", one 9" x 6" and etching kit. All prices include Sales Tax, packaging, postage.

FROM RADIO SUPPLY STORES EVERYWHERE

or Sole Distributor:

WATKIN WYNNE PTY. LTD. 32 Falcon Street, Crows Nest. 43-2107, 43-1912. P.O. Box 318.



Classical reviews

By JULIAN RUSSELL

Nielsen's 3rd Symphony—"finest work"

NIELSEN — Symphony No. 3 ("Sinfonia Espansiva"), Royal Danish Orchestra conducted by Leonard Bernstein, CBS Stereo SBR235210.

The music of Danish composer Carl Nielsen (1865-1931) had to wait till the early 1950s to win a brief few years of popularity in England. In Australia it still remains for the most part unknown and I can recall no more than a couple of performances of his symphonies at Sydney orchestral concerts. Those who wish to learn more about this unusual man can find everything set down lucidly and perceptively by Dr Robert Simpson in his biography, "Carl Nielsen, Symphonist" published in England by Dent.

Perhaps the most immediately noticeable characteristic of Nielsen's music is a constant struggle to reconcile a complex key scheme that employs constantly moving tonalities with orthodox sonata form, and it is this which gives his music its strong individual flavour. Another feature is the condensation of the material, often to the point of terseness. I am aware that these few words will give you little ideal of what the music sounds like. It is just as impossible to describe the sound of music works as it is to describe a scent.

For that reason the few words I have written about Nielsen's music must suffice. But if you wish to hear an example of a work that is characteristically

Nielsenian I can recommend this Third Symphony. It is considered by Danes to be his finest work, and Bernstein's performance of it in Copenhagen in 1965 was hailed by them as masterly. It was composed in 1911 when Nielsen was 46 and the sleeve notes make an interesting point when they list other works which were roughly contemporaneous—Stravinsky's "Petrouchka," Mahler's "Das Lied von der Erde" and Schoenberg's "Pierrot Lunaire," were three.

At a first run through, the work may sound to you quite simple. But one repetition should reveal just how complex it really is, and these complexities increase with familiarity with the score. And appreciation is likely to grow with each repetition. But don't expect to be either shocked or bewitched. The music will remain healthily normal however well you come to know it — perhaps a little too normal for many contemporary tastes.

Bernstein is in one of his unbuttoned moods as he builds climax on climax and handles his orchestra in a manner that brings out all that is tuneful in the melodious score. And in the second movement Bernstein is deliciously lyrical in music that is essentially pastoral and features a wordless vocalise, sung by a soprano and baritone at a distance, that is given real perspective by the recording engineer. Bernstein caresses the music with true affection. And however much forceful vitality he displays elsewhere there is never a bar that might be properly labelled gauche.

★ ★ ★

NIELSEN — Symphony No. 6 ("Sinfonia Semplice"). Prelude to Act 2 of "Masquerade." Overture to "Masquerade." Philadelphia Orchestra conducted by Eugene Ormandy, CBS Stereo SBR235216.

If you are a stranger to Nielsen's music, and if what I have written above has kindled some curiosity to hear it, I recommend, as a starter, the Third Symphony, reviewed above rather than the Sixth, which, despite its title, is by no means simple. It is, in fact, enormously complex, even after several repetitions. Dr Simpson, Nielsen's biographer, thinks it inferior to the composer's other five symphonies and I am inclined to agree with him. But that is not to say that there are not some splendid pages (I know of nothing better in the Nielsen oeuvre than the first movement) side by side with some of decidedly lower quality.

In the latter class must be put the movement labelled "Humoresque" which has all the anticlimatic features of a joke that needs explaining. Not even the eloquent advocacy of Ormandy and his orchestra can make it gel. But elsewhere they are so persuasive, that you may finish up by liking it more than I do.

I cannot, however, imagine anyone being disappointed with the two fills, the enchantingly pastoral Prelude to Act 2 of "Masquerade" and the brilliant overture to the same work. The recording is good, though I did miss the golden quality of the Philadelphia strings; here they tend to harden in loud passages.

★ ★ ★

MAHLER—Das Lied von der Erde. James King (tenor); Dietrich Fischer-Dieskau (baritone). Vienna Philharmonic Orchestra conducted by Leonard Bernstein, Decca Stereo SET331.

Leonard Bernstein has been lavishly represented in recent recordings, and in none to greater advantage than in this outstanding Mahler performance. But I do not expect it to receive the unqualified acclamation of Mahler purists, and by these I mean the disciples of the Bruno Walter school of Mahlerian interpretation. This is not to be taken as disparagement of Walter's superb conducting of the works of a master whom he loved as much as he respected. His understanding of Mahler's aims was deep and wide ranging. But I think his readings much more likely to cloy than Bernstein's.

For Bernstein brings to "Das Lied von der Erde" a freshness and vitality that to me, gave new life to a work that I have perhaps heard too often in the past few years. And he achieves this in two ways, tempos that at first might sound inordinately fast—the opening Drinking Song is one example—and a degree of passion that stops only just this side of delirium. But stop it does, and I find its emotional impact irresistible. And as if to contradict what I have just written, Bernstein takes the final "Farewell" movement slower than I have ever heard it played before. But he still manages to keep the emotional message unimpaired.

And even in his fastest passage Bernstein seems always to have enough in hand to press on with even more intensity during the many climaxes. The extreme delicacy and clarity of Mahler scoring, despite the large orchestra always used, has by now become legendary, and Bernstein's ear is fully appreciative of this aspect of the performance as is the recording engineer, who has reproduced it so admirably. And the Vienna Philharmonic are at the top of their form, a standard hard to beat even to match by any other orchestra.

We come now to the vexed question of baritone versus contralto in one of the vocal parts. Mahler himself approved the alternative, but the many who insist on hearing a female voice claim that the baritone arrangement is only an experiment. That is as it may be, but, if the voice is to be a male one, I can imagine none better than Fischer-Dieskau's in the eloquent part. He, too, is at the very peak of his form, if one excepts a tendency to slightly overdo emphasis in the fourth movement.

The tenor part, with its high tessitura, is immensely difficult to deliver satisfactorily throughout, but James King's virile and expressive account of the part leaves little to be desired. One has dismissed a tendency to strain on the very highest notes. In my review of this performance for the Sydney "Star" I went out on a limb by forecasting so early in the year, that this would be one of 1967's best productions. I have played it several times since then and see no reason to change my opinion.

RADIO HOUSE PTY. LTD.

308 Pitt Street, Sydney.

STOCKTAKING SPECIALS

\$1.00 EACH.

HEAVY DUTY SIDECUTTING PLIERS.

2 CELL (UM.1) TORCH AND CIG. LIGHTER.

RUBBER GRIP HAMMERS.

2 CELL (UM.1) WATERPROOF TORCHES.

POSTED ANYWHERE.

ACOS CHANGER DUST BUG



PRICE: \$5.50

Essential to all who value their records, the Changer Dust Bug clips easily over most changer arms and sweeps the record both before and behind the stylus, at the same time depositing a very fine antistatic film which prevents dust attraction through static changes. Record and stylus life can be increased by up to five times with a Changer Dust Bug. Spare fluid, bristles and plush pad are available in complete spares kit.

AMPLION (A/SIA) Pty. Ltd.,
29 Major's Bay Rd., Concord, N.S.W.

DEBUSSY—Rhapsody for Saxophone and Orchestra. Sigurd Rascher (saxophone). Rhapsody No. 1 for Clarinet and Orchestra. Stanley Drucker (clarinet).

HONEGGER—Rugby; Pastorale d'Ete; Pacific 231. New York Philharmonic Orchestra conducted by Leonard Bernstein. CBS stereo SBR235206.

Still another Bernstein recording, and if it isn't quite in the same class as the two previously noticed in this column, it is nevertheless highly enjoyable. Debussy fiddled around with the Saxophone Rhapsody for years. It was a commissioned work for an instrument which he disliked intensely. On its reluctant completion he lacked enough interest in it to orchestrate it, a task he handed over to his fellow-composer Roger-Ducasse.

However, since the Rhapsody is one of the very few serious works written for the saxophone it retains its place in current repertoires, and has been played by Sigurd Rascher for at least a generation. I remember hearing him play it in the Sydney Town Hall before World War II. But however often he may have played it since, he still makes it sound nice and fresh, and his technique is, of course, impeccable.

The Clarinet Rhapsody, on the other hand, was a work of which Debussy himself was extremely fond. It is in every way a better composition than the other. Its melodies are shapely and original, its harmonies subtle, its scoring deliciously fragile. Stanley Drucker, using a beguilingly reedy tone, overcomes its many formidable technical difficulties with almost ridiculous ease and Bernstein's orchestra provides an exemplary accompaniment.

Two of the three Honegger pieces sound very trite and contrived nowadays, however daring they might have seemed back in the early 1920s when the composer was a member of the then way-out French group known as "Les Six." "Rugby" is utterly poverty stricken in its thematic material despite the composer's efforts to disguise the fact by abrasive harmonies and coarse orchestration. And "Pacific 231"—the title is taken from the serial number of an American locomotive—sounds just as much like a train as ever, despite the composer's denial that it is onomatopaeic program music. But that is all.

The only piece to wear well is the "Pastoral d'Ete," which, as the title suggests, is pleasingly pastoral, and responsively treated as such by Bernstein. The sound throughout is good.

★ ★ ★

MOZART—Piano Concerto No. 8 in C Major (K.246). Piano Concerto No. 9 in E Flat Major (K.271). Rondo in A Major (K.386). Vladimir Ashkenazy (piano) and the London Symphony Orchestra conducted by Istvan Kertesz. Decca Stereo SXL-6259.

As Ashkenazy's list of recordings grows, so does his stature as a pianist. have not heard him play in public but in the strength of his recordings he is well on the way to becoming one of the world's finest. This month he makes his first appearance in Mozart and, as you will discover later in this column, Schubert. In both he is impressive—and immensely enjoyable.

Less than a year separated the composition of these two concertos, but

* 2-State Service for Hi-Fi Enthusiasts

SYDNEY

asdic
STEREO HI-FI

Address: 166D Glebe Pt. Rd., Glebe
Phone 68-1453

Specialising in quality Cabinets to any design . . . Complete systems including Radford, Quad Fisher and Leak. Installations in the home . . . all good brands supplied and guaranteed.
Management & Sales: W. Bardsley-Smith.

ENGINEERING: H. BEN WILSON, S.M.I.R.E.E., M.S.I.T.A.
Phone 68-4283. Authorised Service Centre for Quad, Goodman's, Ferrograph, Rogers, Roland, Trio, Beocord, B. & O., Labcraft, Radford, K.E.F., Wharfedale.

BRISBANE

BRISBANE AGENCIES
STEREO HI-FI


Address: 78 Wickham St., Valley, Qld.
Phone 2-6931

Steve Eklund, Proprietor. Specialised installations for homes, halls and institutions. Cabinets to any design. Complete Systems including Radford, Quad, Fisher and all good brands. Agents for ADC, Labcraft, J.H., Radford, K.E.F., Roland. All work guaranteed.

ENGINEERING:

No job too small or too big in Hi-Fi. Qualified engineers for all major service.

* **FREE 16 PAGE BOOK!**



DESCRIBES
THE FAMOUS
GRAMDECK
TAPE RECORDER

\$49.00

ASDIC STEREO SPECIALISTS


166D Glebe Rd., Glebe, N.S.W. Phone 68-1453

Please forward, free and post free, your 16 page book on this unique Tape Recorder.


Name

Address

State



REASONS WHY...



- 1** Brand 5 is your best buy irrespective of price. It is the fifth oldest brand of recording tape in the world and it is now better than ever under the guidance of the Ferrodyamics chemists and engineers.
- 2** Brand 5 has a better frequency response to give you sharper, brighter high fidelity mono and stereo recordings to the most professional standards. Brand 5 has the lowest background noise of all.
- 3** Brand 5 tape offers increased output with reduced distortion at the same recording level. The high remanence iron oxide emulsion is coated onto the best quality acetate or polyester base and it is splice free with green start/red stop leaders.
- 4** Brand 5 is permanently lubricated with a special dry synthetic lubricant. There is no squeal and no gumming of heads. The non-abrasive character of Brand 5 will reduce head wear and protect your valuable recording equipment.
- 5** Brand 5 gives you twice as much tape for the same money . . . and a better tape into the bargain. Compare the price of Brand 5 with other quality tapes and you will see that you save 50% off normal list price . . . and Brand 5 is fully imported from America in sealed boxes.

Type No.	Description	Other Tapes	Our Price	Type No.	Description	Other Tapes	Our Price
ON 7" REELS				ON 5½" REELS			
15D7	1200' 1.5 Mil Acetate	\$5.00	\$2.50	15D57	800' 1.5 Mil Acetate	\$4.66	\$2.33
10D7	1800' 1.0 Mil Acetate	5.98	2.99	10D57	1200' 1.0 Mil Acetate	5.10	2.55
10D7M	1800' 1.0 Mil Polyester	7.70	3.85	10D57M	1200' 1.0 Mil Polyester	6.66	3.33
5D7M	2400' .5 Mil Polyester	9.30	4.65	5D57M	1800' .5 Mil Polyester	7.98	3.99
5D7MT	2400' .5 Mil Tensil. Poly.	10.50	5.25	CORRESPONDENCE TAPE ON 3" REELS			
5D7MS	3600' .48 Mil Polyester	15.90	7.95	15D3	150' 1.5 Mil Acetate	\$1.00	\$0.50
5D7MTS	3600' .48 Mil Tensil. Poly.	17.90	8.95	15C3*	150' 1.5 Mil Acetate	1.32	0.66
ON 5" REELS				10D3	225' 1.0 Mil Acetate	1.30	0.65
15D5	600' 1.5 Mil Acetate	\$3.60	\$1.80	10C3*	225' 1.0 Mil Acetate	1.54	0.77
10D5	900' 1.0 Mil Acetate	3.96	1.98	10C3M*	225' 1.0 Mil Polyester	1.76	0.88
10D5M	900' 1.0 Mil Polyester	5.32	2.66	5C3M*	300' .5 Mil Polyester	1.98	0.99
5D5M	1200' .5 Mil Polyester	5.70	2.85	CORRESPONDENCE TAPE ON 3½" REELS			
5D5MTS	1800' .48 Mil Tensil. Poly.	9.96	4.98	5C32M*	600' .5 Mil Polyester	\$3.54	\$1.77

*Plastic re-usable mailing carton.



GREEN CORPORATION LTD. 88 KING STREET, SYDNEY. PHONE 25-1989

**AVAILABLE AT ALL
GOOD RADIO, TAPE
& RECORD STORES**

**GREEN CORPORATION LTD.
88 KING STREET, SYDNEY, N.S.W.**

Please send me FREE Booklet on "brand 5" Tape.

Name

Address

GN18

Mozart took a vast stride in the direction of maturity in the second of them. The C Major calls for little more than a performance that can alternate effervescence with tenderness, both of which Ashkenazy awards it in generous measure. Yet he manages to fill his reading with a subtlety of phrasing and richness in tonal variety that makes one hope this disc will only be first of a series of Mozart concerto recordings. He is careful to keep his dynamic range well within permissible 18th Century limits without, however, producing the effect of a deliberate curtailment.

But the C Major, despite the surprises Mozart has in store for those who expect a conventional formal development and the superb polish of Ashkenazy's performance, is only small stuff compared to the E Flat, which is generally recognised as the first of the "great" Mozart piano concertos. This calls for much deeper emotional involvement on the part of the performers and a much greater variety of colour from the soloist. And again both are generously awarded, though, at the risk of appearing ungenerous myself in assessing the value of a performance that gave me so much pleasure, I must point out that in a couple of sequences a fraction more intensity would have been welcome.

The orchestra's contribution under Kertesz is in every way admirable, give or take an occasionally heavy string passage, and the engineering splendid. And for a fill, the A Major Rondo offers a small but welcome bonus.

★ ★ ★
MOZART — String Quartet in D Major (K.575) "Prussian" No. 1 String Quartet in F Major (K.590) "Prussian" No. 3. Weller String Quartet. Decca Stereo SXL6258.

This recording of two of the "Prussian" quartets will be welcomed by all Mozart lovers since I can trace no previous coupling in any catalogue of two of the set. Moreover they are seldom heard in the concert hall. (Since writing this I have learned that a version was put out by Vox, played by the Barchet Quartet some years ago and has long been deleted from local catalogues.) The Weller is a Viennese quartet whose members take their Mozart as they take life —urbanelly, sensitive to nuance, and without apparent effort. The result is a performance that will, I predict, remain unchallenged in excellence for many years.

To those who insist on sharper accenting and a slightly less mellifluous style I put the question: "Where are they likely to hear playing that breathes more naturally and to which the listener can surrender himself with more sense of security?" The performers give the impression of playing entirely for their own enjoyment, and the listener feels privileged to be in on the treat. The tempos are sensible, and if the minuet in the F Major sounds a little more suave than it might in other hands, bear in mind that it was the precursor of the Viennese waltz.

There is, too, a tendency to linger over the delights of the Andante in the D Major, but since the slow movement of the F Major is an allegretto you don't run into the same problem there. The sound is generally speaking good without being outstanding and I could have put up with a little more weight in the cello part. No matter how I juggled my equipment I couldn't bring his out without destroying the balance

elsewhere. But these are only minor shortcomings in a disc that is otherwise made for relaxed listening.

★ ★ ★
MOZART — Church Sonatas for Organ and Orchestra, Nos. 1-17. Marie-Claire Alain (organ) and the Jean-Francois Paillard Chamber Orchestra conducted by J. F. Paillard Andante in F Major for Organ. Fantasia No. 1 in F Minor for Organ (K.594). Fantasia No. 2 in F Minor for Organ (K.608). Marie-Claire Alain. World Record Club Stereos T4147/8.

I consider these much better performances than those by E. Power Biggs that I reviewed about nine months ago. Importantly Marie-Claire Alain's organ part is much less intrusive than Biggs. Indeed Madame (or Monsieur — the name is no clue?) Alain's playing is, for the most part, exactly what Mozart had in mind, for it must be remembered that these pieces were written for performance as short instrumental interludes during the Mass and in many of them the organ was called on to do no more than supply harmonies from a figured bass.

That this is not primarily organ music is made clear by the balance and the soloist's choice of a sweet, light-toned baroque instrument for her performances. These are by no means even. In some she is satisfied with a very matter-of-fact reading. Others — especially K.224 in F — are full of grace and charm. Taking them all round they may not be the best that might become available from time to time, but until something better turns up they will do very nicely.

The organ solos are also well played and though I have heard the Allegro in the K.594 sound a little sprightlier, the introductory adagio is fine. Similarly the K.608 starts impressively with a fine broad tempo but the next section grows a trifle confused in some bars. Throughout, the choice of stops provides plenty of variations in the sonorities and the sound is consistently first rate. Excellent value at the club price.

★ ★ ★
MOZART — Complete Dances and Marches Vols. 6 and 7. Vienna Mozart Ensemble conducted by Willi Boskovsky. Decca Stereo SXLA6199 and SXLA6246 (two discs).

There seems to be no end to these usually charming little pieces, most of them written as part of daily work for a patron. They were used as dances for a dance-mad population and as occasional pieces, dashed off at a moment's notice. But such was the nature of Mozart's genius that you seldom find one, however trivial, without some testimony to the inexhaustible ingenuity of its creator. The standard of performance is again irreproachable and the engineering tip-top.

★ ★ ★
BARTOK — Concerto No. 2 (1938) for Violin and Orchestra. Yehudi Menuhin (violin) and the New Philharmonia Orchestra conducted by Antal Dorati. Six Duos for Two Violins. Yehudi Menuhin and Nell Gotkovsky. HMV Stereo OASD-2281.

If I remember rightly, Menuhin was the first to record this Bartok concerto on 78s, back in the early days of the

If you want STEREO EQUIPMENT

You'll deal better with
H. B. RADIO SALES

AUGUST SPECIALS

PIONEER SA400 amplifier (11w RMS Per channel) and **2 GOODMAN'S** Twin Axiom 10 Speakers in 3cf cabinet **\$208.00.**
With TRM40 Peak Amp. . . **\$222.00**
D.P. SLIMLINE enclosure to suit 10in and 12in speakers, **\$18.50**
Cabinet Kit only **\$10.50**
MAGNAVOX or **ROLA** design slimline cabinet with 8 W.R. (V.C. 15, 8 or 3 ohms) or 8 CMX speaker fitted **\$26.50**
Cabinet Kit only **\$10.50**
MAGNAVOX 12 W.R. and 3 T.C. Tweeter with Crossover network in 3 C.F. cabinet; 2 material **\$41.00**

PLAYER PLATFORMS

With mitred corners and raised, veneered edges. Size 16in x 14in x 3 3/8. **\$7.50.** Maple or Walnut Veneer, Teak Veneer, **\$4.00.** Cut free. Perspex Covers to match, 5in high, **\$8.20.** Postage **\$2.00.** WRITE FOR PLAYER PRICE LIST AND GUIDE.

GOODMANS design 3 CF Cabinet and Twin-axiom 10 speaker, 2in material **\$54**
Cabinet Kit and Speaker . . **\$44.20**
WHARFEDALE design, 3 CF cabinet (R3) 2in material and Golden 10 speaker **\$57.00**
Cabinet Kit and Golden 10 Speaker **\$47.00**

Special quotes for other Wharfedale or Goodman speakers.

Available in Maple, Walnut or Rosewood colours. Teak veneer \$1 extra for Slimline and Bookshelf models. \$3.00 extra for others.

PLAYMASTER Bookshelf Speaker System. Complete, **\$30.**
Cabinet kit only **\$7.**

All other parts, including speakers, inner bond, etc., **\$15.40.**
MULLARD Mini BS Unit.
Kit of parts, including Cabinet, made and polished, speakers, inner-bond and condenser, **\$21.50.** Unit complete, **\$25.**

Postage, N.S.W. \$1.00; Qld., Vic., Tas., \$1.40; other States, \$2.00.

SPECIAL QUOTES

For Complete Sets Based On
LEAK — MAXAMP — PEAK
— PIONEER — QUAD —
ROLAND — SANSUI —
STAR — TRIO.

Write for Stereo Catalogue

H. B. RADIO SALES

Manufacturers of Quality Radio and Radio Furniture for 36 years

**103-105 Catherine Street,
LEICHHARDT, SYDNEY**

Telephone 56-5580

ARROW

presents

SOLID STATE

PERFECTION IN SOUND

WITH THE NEW SONY TA-1120 STEREO AMPLIFIER



Guaranteed incomparable high-performance to satisfy the most exacting audio listeners. An amplifier you must hear to believe. All silicon with incredibly low distortion. Total harmonic distortion: Less than .1 p.c. at 50 WATTS throughout 30 C/S—20,000 C/S. High damping factor of more than 70. A smaller power version the MODEL 1080 is also available. Call for a demonstration or phone/write for specification sheets. You must hear these top-class units to appreciate them. **PRICES**, model 1120 \$592, model 1080 \$432. WELL WORTH EVERY PENNY.

We have many other transistorised amplifiers for you to choose from as low in price as \$96.00!

AFTER STOCKTAKING BARGAINS

- 1** Peak KST200 transistorised amplifier, 5 watts per channel — Garrard SP25 player—Shure M44-C cartridge 2 Trio bookshelf 2-way speaker systems.

\$263.90

- 2** New model peak TRM20 transistorised amplifier 7½ watts per channel — dual 1009SK Player — Shure M44 — or G cartridge—2 Wharfedale Golden 10RSDD speakers in 2 cubic foot Teak enclosures.

\$331.00

- 3** Peak TRM20 amplifiers 7½ watts per channel — peak STP-7 Hifi player in case with magnetic cartridge—2 Wharfedale Golden 10RSDD speakers in 2 cubic foot enclosures.

\$326.00

or without player case \$297.00

- 4 FEW ONLY**

Wharfedale bronze 8RSDD Loudspeakers in 1 cubic foot Teak enclosures. While they last.

\$40.00

ARROW ELECTRONICS PTY. LTD.

the original home of Hi-Fi

432 Kent Street, Sydney. Telephone 29-8580

war. My pressing has long since gone the way of all 78s so that I cannot compare that one with this, which was recorded late last year. Menuhin and the orchestra are both in fine fettle and handle the work's many intricacies with almost contemptuous ease. There is, however, no objectionable top-dressing of dash either in the solo or orchestral part. Indeed Menuhin seems intent on keeping his tone within strictly musical bounds when a slightly more forceful treatment seems to have been in the composer's mind.

Yet it cannot be said that the reading lacks fire. It glows most persuasively, even if it seldom bursts into flames. And I, for one, prefer this disciplined intensity to a more unrestrained exhibition of emotion. As to the engineering, some may find the solo part recorded a little too distantly for their taste, but in a work where the orchestral part has so much significance, I think this a fault on the right side. Moreover it gives one a chance to hear the quite marvellous score played with a perfection seldom met in a concert hall performance.

The deliberate hardening of tone some violinists use in the concerto, but which Menuhin deliberately eschews here, can be enjoyed in his playing of the Six Duos for Two Violins. This however, may be due, not so much to the difference in Menuhin's playing, but to the fact that in these he is recorded closer to the mike. At any rate if you find his version of the concerto over-refined, these admirable, and exciting, duos will supply just the right contrast. In these the sound has much more presence than in the concerto. And his partner, Nell Gotkovsky, contributes nobly to the success of the enterprise.

★ ★ ★

SCHUBERT—Piano Sonata in A Major (D.664). Piano Sonata in A Minor (D.784). Hungarian Melody (D.817). 12 Waltzes (D.145). Vladimir Ashkenazy. Decca Stereo SXL6260.

This A Major Sonata has acquired the nickname of the "little one." Dimensionally it may be smaller than most works of this kind. And the fact that it is sweetly tuneful—and often given to learners to practise — may encourage some to think that, interpretatively, it is child's play. Nothing could be more untrue. If you happen to be a pianist yourself, try it, then listen to how it sounds played by Ashkenazy. I should be surprised if the maturity of his interpretation doesn't quickly make you change your mind.

This is the only disc that couples the two major works you hear Ashkenazy play here and it is unlikely that a better will be put out in the foreseeable future. His reading of both works is warm, virile, and always aware of the many opportunities Schubert provides for a discriminating exponent to contrast the varying sonorities of the instrument. And the proportions of both works will deter even the most churlish critics of Schubert's prolixity from making their usual charges.

Nor are the fills without their own particular interest. The Hungarian Melody is unlikely to be familiar to any one but a Schubert scholar. It was published for the first time as recently as 1928. And the tiny waltzes are full of graceful ideas, modestly but resourcefully treated. For Schubert-lovers, it must. For others—well, you'll certainly not find anything to complain about in the playing—or recording. **E**

DOCUMENTARY RECORDS

Reviewed by Glen Menzies

"JULIUS CAESAR" Dramatic Highlights from the Sound Track of the M-G-M film. James Mason. John Gielgud, Marlon Brando, Louis Calhern and Company. Encore mono MGM-VO2 9307.

Back in the early 1950s, M-G-M made a movie of epic proportions of one of the timeless, and at the same time, most controversial of Shakespeare's plays. John Houseman, who produced the film, also selected the material which makes up this album; he also serves as the excellent narrator who fills in the story where necessary. In a personal note on the film he says, "... we had one dominant artistic aim; to bring to a contemporary audience, in all their energy and beauty, the sustained dramatic impact of Shakespeare's words." In this respect, John Gielgud more than succeeds and James Mason and Marlon Brando acquit themselves very well indeed, but Louis Calhern with his slightly twanging American accent fails to make much of Caesar (in words alone that is); perhaps it was a more dominating presence on the screen.

This is, of necessity, a much truncated version of the complete Julius Caesar; nevertheless, there is sufficient left for us to grasp the broad outlines, to be able to see Brutus as the central figure and the tragic hero, influenced by Cassius, who as his associate and friend, helps to sow the seeds of doubt which lead to Caesar's assassination. John Gielgud gives a truly remarkable performance as Cassius. In a wonderfully vibrant, perfectly poised piece of acting, his articulation is phenomenal and each word is precisely focused in such a way that it helps to build tension in a cumulative, rather than immediately emotional way.

Though a little overshadowed by Gielgud, James Mason misses few opportunities in his role as the young idealist, who, instead of benefiting his country, brings it into ruin and civil war. In verbal exchanges between these two side one, as Cassius uses all his powers of persuasion to finally convince Brutus, we can only marvel at Shakespeare's genius for dialogue.

Brando is something of a surprise. His voice is better than I was prepared to expect, remembering some of his earlier roles of a few years ago, in which he seemed forever condemned to be inarticulate. He is no Shakespearean actor as we might find at Stratford-on-Avon, but nevertheless he makes a wonderful sounding Mark Antony, a little less at times but still able to raise a multitude to a frenzy of revenge. It is that the sound of an angry man always sounds even more ominous in film sound track? Irrespective of our familiarity with the "Friends, Romans and Countrymen, Lend me your ears" soliloquy, this is a great piece of oratorical writing which also reveals Mark Antony as a quite remarkable political opportunist.

Even in this drastically shortened

form I have found this album a stimulating experience with much to think about with regard to the rights and wrongs of Caesar's death and the fate of the republic over which he ruled. This is a generous disc which runs for just over the hour, and apart from a little hardness in places, the sound is clear and the dramatic impact considerable. With the exception of some "typical" film music at the start, Miklos Roszas score is subdued. The chosen excerpts dovetail together very well with the help of Mr Houseman's linking narrative. As a primer, for a closer look at a great Shakespearean play, this Encore reissue can be wholeheartedly recommended.

★ ★ ★

TALES OF EARLY AUSTRALIA: Read by Wilfrid Thomas. Festival, Mono FL-32,138.

This album makes an interesting follow up to my review last month of the poems of Banjo Paterson and Henry Lawson, but this time the material comes from many sources with quite a few anonymous Australian poets represented. Wilfrid Thomas remains one of the best known of Australian broadcasters despite the fact that he has resided in London for many years. Familiarity with the reader's very singular voice made me wonder whether the recital would capture and hold my attention right throughout both sides. I can say after several hearings that it makes an outstanding addition to the spoken word field, and Mr Thomas emerges with flying colours.

He takes an unorthodox view of the poems, looking first for the hard core of the narrative to give the impression of a story-teller at work, rather than just a mere reciter. This is not to say that he is insensitive to the rhymes and rhythms themselves, but he knows just when to throw away a word whilst keeping the story line flowing freely. His use of light and shade is excellent and the changes of pace are extremely well-judged.

Much of the material has been culled from the two volumes, "Australian Bush Ballads" and "Old Bush Songs," compiled by Douglas Stewart and Nancy Keesing, and are well contrasted, some

humorous, some dramatic, some protesting and others touched with sadness or tragedy. "The Convict in Chains," "Female Transport" and "10,000 Miles Away" are all concerned with horrors of being transported to Van Diemen's Land. But "Dick Briggs From Australia" is from the opposite view altogether — a well brought up Englishman returns back home to England and to polite society after a spell in the Australian Outback, his language having undergone radical changes. This is read in a racy fashion with sharp awareness of the peculiarities of the Australian idiom. There are a number of Bush-ranger poems including one by Edward Harrington which dwells not so much on Ned Kelly the folk hero, but the tragedy of his death; in contrast, an anonymous poem simply called "The Kellys," emphasises his dashing heroism.

It was an interesting exercise to be able to play Banjo Paterson's, "The Travelling Post Office," which I noted in last month's review of "The Best of Banjo" read by John Clements. There is a quite different approach in the readings, with Wilfrid Thomas emerging as the more unorthodox reader who places greater emphasis on the poem's inner contrasts and changes of pace.

The recording is technically very good, it is so clear in fact that any fault in Wilfrid Thomas's microphone technique would have been glaringly revealed. For those with wide range equipment, I recommend the use of a top cut filter to reduce the tendency towards a slight hardening of tone at this end of the range.

REVISED PRICES for G.E. TRIACS

SC40D	6 amp	400V	now \$5.46
SC45D	10 amp	400V	now \$7.04
SC50D	15 amp	400V	now \$10.47

Other G.E. devices generally available from stock,

C20D S.C.R.	\$4.28
CI06Y1 S.C.R.	30V	\$1.49
ST2 Trigger Diode	\$1.47
2N2160 U.J.T.	\$2.02
2N2646 U.J.T.	\$1.52

Quoted prices include Sales Tax and postage within Australia.

From Radio Supply Stores everywhere.


WATKIN WYNNE PTY. LTD.

32 Falcon Street, Crows Nest.

P.O. Box 318, Crows Nest.

Phone: 43 2107, 43 1912

CHOOSE THE BEST—IT COSTS NO MORE



O. T. LEMPRIERE & CO. LIMITED. Head Office: 27-41 Bowden Street, Alexandria, N.S.W. and at Melbourne, Brisbane, Adelaide, Perth, Newcastle.

Simon Gray Pty. Ltd. and H. J. Leak (Aust.) Pty. Ltd. are happy to announce a new marketing policy for the benefit of our customers. In our mutual endeavors to bring you the finest equipment at realistic prices it has been decided to separate the professional and consumer distribution. Coupled with local production this enables us to bring our prices in line with those applicable in other countries.

LEAK

The first name in high fidelity!

FIRST

with a very low distortion amplifier

In 1945 LEAK released a revolutionary high fidelity amplifier—the famous "Point One" series. For the first time power amplifiers were marketed with a distortion content of less than 0.1%. This has become the accepted world-wide standard.

FIRST

with a piston action loudspeaker system

Another breakthrough was the release of the LEAK Sandwich Loudspeaker System with its fantastically rigid Sandwich cone. For the first time in audio history a direct radiator diaphragm is able to reproduce a signal free from mechanical break-up.

FIRST

internationally famous audio equipment company to manufacture in Australia

The continued world-wide success of LEAK High Fidelity Equipment produced a 38% increased demand last year. The demand in Australia warranted the opening of a factory in Sydney where Sandwich and Mini Sandwich Loudspeaker Systems are now being produced.

FIRST

Australian company to export Hi-Fi components to the United States


When opening H. J. Leak (Aust.) Pty. Ltd., in March, 1966, Harold J. Leak, Chairman of both the English and Australian companies, invited us to compete for export markets. In response, firm orders have been obtained from California, and the first two shipments of Australian made Sandwich Loudspeaker Systems have already been delivered in San Francisco

AND NOW

FIRST WITH A STREAMLINED SALES POLICY DIRECT FROM

MANUFACTURER TO RETAILER MAKING LEAK EQUIPMENT


NOT ONLY THE FINEST, BUT ALSO THE BEST VALUE.



\$139.00

Leak Sandwich Mk. II Speaker system


The Sandwich cones comprise stiff aluminium skins for the outer surfaces where stresses are greatest, bonded to a thick core of featherweight, expanded plastic where stresses are lowest. Use of this material provides immense stiffness and rigid piston action over more than six octaves and results in a remarkably smooth response free from violent peaks and troughs over a very wide frequency range. Available in mahogany, teak and walnut, this beautifully finished enclosure is still the only compact speaker system offering substantially linear frequency response. Size: 26" x 15" x 12".



\$99.00

Leak Mini Sandwich Speaker system

For music lovers who cannot spare space for a full-size LEAK Sandwich, the new Mini-Sandwich provides almost identical performance, with the exception of the very lowest octave. This superlative small speaker system is designed and made exactly as its larger companion. Size: 18½" x 11" x 7". Available in mahogany, teak and walnut.



\$198.30

Leak 'Stereo 30' amplifier

The "Stereo 30" solid state amplifier offers the discriminating music lover, studio — quality sound reproduction, advanced audio engineering and pleasing aesthetic design. The performance of the LEAK "Stereo 30" represents the highest standards available.

Each LEAK instrument is individually crafted and has the same high quality performance as LEAK instruments supplied to broadcasting and television companies throughout the world.

* See and hear LEAK Equipment today at leading Hi Fi Stores and sound centres.
For leaflets & information write to:

H. J. LEAK (AUST.) PTY. LTD.

P.O. BOX 14, FRENCH'S FOREST, N.S.W. 2086.
FACTORY: 1 CAMPBELL PARADE. MANLY VALE.
N.S.W. TELEPHONE: 94 4902.
CABLES: LECTRON. SYDNEY.

Professional equipment enquiries to
Simon Gray offices or Representatives
in all states



RESEARCH • ENGINEERING • MANUFACTURING


LK. 703.DPS

NOW THE EXTRA REALISM OF HARMAN-KARDON EXTRA-WIDEBAND SOUND CAN BE YOURS

with **harman kardon**
NOCTURNE

ALL-TRANSISTOR STEREO RECEIVERS

New Nocturne receivers bring the incredible realism of Harman-Kardon's exclusive ultra-wide frequency response within reach of every music lover. The new all-transistor design assures absolutely cool operation with no deterioration of sound quality over years of constant use. The luxurious ebony-and-gold styling enhances the decor of any room. And Nocturne receivers — even the lowest priced — deliver clear power sufficient to drive stereo speakers in one or two rooms, separately or simultaneously.



NOCTURNE 210—FM stereo plus AM radio. All the quality performance and styling of the Model 200 above, with the added convenience of AM radio played through your high-fidelity music system. Walnut enclosure optional.

How to enjoy
the ultimate in
Listening Pleasure
with your new



EMPIRE

MADE IN U.S.A.

888
CARTRIDGE


Series



U.S. Patent No. 3,153,332



SCHAUB-LORENZ



MUSIC CENTRE 5005


Is world's most brilliantly designed recording and playback system for 46 hours programming of your favourite music. This versatile instrument with a large storage capacity is ideally suited for playing back any section of your program in a flick of a second without using any tapes or other media of conventional recordings.



**SPECIALISTS IN HIGH QUALITY
SOUND REPRODUCTION**

The best stereo record playing equipment MUST have an ARMSTRONG

**JORDAN WATTS
HIGH-FIDELITY LOUDSPEAKER
SYSTEMS AND DRIVING UNITS**



SECTION DRAWING OF LOUDSPEAKER

TRUE FIDELITY C. PINCZEWSKI

For complete brochures on the Armstrong and Empire Equipment and further information, write to:

RECORDED MUSIC SALON, 23 COLLINS ST., MELBOURNE. PHONE: 63-6257

VARIETY FARE

★ ★ ★
"ELECTRONICS Australia"

Staff Review Panel

Devotional

STORIES WITH A MESSAGE. Rev Roger Bush. Mono, ATA (Festival) ATAL-32,259.

Interest: Stories for children.

Performance: Sincere.

Quality: Well recorded.

Roger Bush, one-time member of the R.A.A.F., university student, public servant and industrial worker, is now the Rev. Roger Bush, minister of the Crows Nest Methodist church, on Sydney's north side. He also broadcasts regularly over the ABC and conducts a "Helping Hand Mission" column in the Sydney "Sunday Mirror."

On side 1 of this album, he recounts the story of the Passion, Crucifixion and Resurrection, in terms which closely parallel the Bible account. The telling could be shared by all ages, particularly at the Easter season.

The remainder of the album is devoted to seven stories for children, in the manner of legends or fairy tales, but each with a scriptural moral — hence the title.

The narration is straightforward and sincere and I imagine that, in a sympathetic home situation, the children could well come to regard this as "their record." (W.N.W.)

★ ★ ★

ROOM AT THE CROSS. Al Garr, Tenor, with Paul Mickelson Orchestra and Choir. Stereo, Supreme SS-2001. Also available in mono SM1001. (Supreme Productions S.E. Asia Ltd.).

Interest: Gifted Gospel tenor.

Performance: Very smooth.

Quality: Good.

Stereo: Modest.

Al Garr, son of an itinerant evangelist, showed an early preference for show biz, over his father's calling to such good effect that he later starred as a tenor soloist for three years on a CBS coast-to-coast radio show and was associated with John Nesbitt on his famous "Passing Parade" series. But, on the eve of bigger things, he cancelled his radio and film contracts and took up theological studies; these were interrupted by war service, which took him through the Normandy landing as a Lieut. Colonel.

Since then, he has become deeply involved in various aspects of evangelism but with a continuing interest in singing. His sense of pitch, smooth production and excellent diction are all evidence of thorough training and the only reservation one might have would be in terms of a general preference for other than a tenor voice.

In a well varied program, the track titles are: Count Your Blessings—Blessed Be The Glorious Things—Moment By Moment—Someday, Sometime—The

Lord Is My Shepherd—Ye People Rend Your Hearts and If All Your Hearts (from "Elijah")—I Won't Have To Cross Jordan Alone—The Hem Of His Garment—When I Found Jesus—I Have Found A Hiding Place—Onward With Christ—Room At The Cross.

With orchestra, choir, piano and organ providing varied accompaniment under the hand of Paul Mickelson, this is a pleasant, sincere and well-produced album. (W.N.W.)

★ ★ ★

MORE SOUTHLAND FAVOURITES. George Beverly Shea. Arranged by Anita Kerr; produced by David Rice. Stereo, RCA LSP-3634. Also in mono LPM-3634.

Interest: Best known Gospel soloist.

Performance: Typical.

Quality: Good.

Stereo: Used effectively.

Those charged with the responsibility of meeting the seemingly insatiable demand for Bev. Shea recordings must be as hard put to it to think up new presentation ideas, as this reviewer is to think up something different to say about them. The theme here is "Southland favourites" and the jacket notes which, for other artists, would have been emphasising the Anita Kerr Singers and the Nashville sound, are content to refer to "the gentle rhythm so characteristic of the Bible Belt."

The "gentle rhythm" and Anita Kerr's arrangements are evident almost exclusively in the instrumental and vocal accompaniment. Bev. Shea sings on in much the same fashion as in any one of his other albums. The track titles: Kneel At The Cross—The Wonder Of It All—Adoration — The Stranger Of Galilee—I Shall Not Be Moved—Beautiful Isle—Ten Thousand Angels — The Night Watch — Sometime — God Is Still On The Throne — Oh Gentle Shepherd—Jesus Will Give You Rest.

For those with a place in their collection for yet another Bev. Shea album, this one features a modest up-tempo treatment. Quality and stereo are well up to standard. (W.N.W.)

★ ★ ★

ELLA FITZGERALD'S BRIGHTEN THE CORNER. With the Ralph Carmichael Choir and Orchestra. Stereo, Capitol ST-2685. Also in mono T-2685.

Interest: Ella's first Gospel album.

Performance: Appealing.

Quality: Excellent.

Stereo: Modest but effective.

Only those with a rigid dislike for Negro style Gospel should fail to enjoy this, the first devotional album by that most accomplished singer, Ella Fitzgerald. The elements of the Negro style are all there but in moderation — the vocal improvisation, the emotional intensity and, in other numbers, the joyous rhythm. And what excellent support is

given by the Ralph Carmichael Choir and Orchestra. They're on the job all the time and while, frequently, one is aware of their deft touches, they never exceed their basic task of complementing the soloist.

In a generous and well varied program, occupying more than 40 minutes, Ella sings no less than 14 well known hymns: Abide With Me—Just A Closer Walk—The Old Rugged Cross—Brighten The Corner—I Need Thee Every Hour—In The Garden—God Be With You Till We Meet Again—God Will Take Care Of You—Throw Out The Lifeline—I Shall Not Be Moved—Let The Lower Lights Be Burning—What A Friend We Have In Jesus—Rock Of Ages, Cleft For Me.

While I have sometimes voiced reservation about Gospel songs — presented Negro style or by singers with a purely "entertainment" background—this album I thoroughly enjoyed. Well worth a hearing. (W.N.W.)

WE SPECIALISE IN

TAPE RECORDERS

EXPERT REPAIRS

To all brands by German technicians in modern equipped workshop.

Contact

REKLA

KLAPP ELECTRONICS PTY. LTD.,
224 CHAPEL STREET, PRAHRAN, VICTORIA.
TELEPHONE: 51-4653.

EKCO - STYLUS RADIOGRAM NEEDLES DIAMOND OR SAPPHIRE


- You See! NEEDLES are OUR "business"!
- EKCO-STYLUS are craftsman-built — not mass produced!
- EKCO-STYLUS are products unsurpassed!
- EKCO-STYLUS have a long history of success!
- Also after-sales service and advice assured.

Obtainable all good Music Houses

Enquiries:

ERNEST KUENZLI
PTY. LIMITED
60 HUNTER ST., SYDNEY
N.S.W. PHONE: 28-6991

Technically Tested and Proven Circuitry



**SOLID STATE
INTEGRATED STEREO AMPLIFIER
Model TK-400E**



**MW-MW-SW STEREO TUNER AMPLIFIER
Model W-26**

the sound approach to quality

TRIO

SPECIAL TK-400E FEATURES: ● Completely transistorized pre-amplifier and main amplifier all on a single chassis. (Total 21 transistors.) ● New AUTOMATIC circuit breaker protects transistors for added long life. (U.S. Pat. No. 3,277,386)


● **OUTPUT POWER:** 80 watts total music power (IHF Standard) or 40 watts per channel. 32 watts RMS power per channel.

● **DAMPING FACTOR:** 20. ● **FREQUENCY RESPONSE:** 20-50,000 cps ± 1 db.

● **SWITCHES:** Input selector, Mode selector, Low Filter, High Filter, Loudness, Speakers and Phones, Phase, Tape Monitor. ● **DIMENSIONS:** Width 15 $\frac{1}{4}$ ", Height 5 $\frac{1}{4}$ ", Depth 12 $\frac{1}{4}$ ".

SPECIAL W-26 FEATURES: ● Built-in MW Stereo circuit is provided for MW stereo broadcast. ● A new, two professional type tuning meters are illuminated to make pinpoint tuning possible.

● **OUTPUT POWER:** 24 watts total music power (IHF Standard) ● **FREQUENCY RESPONSE:** 20-20,000 cps (± 1 db) ● **SENSITIVITY:** MW; 10 microvolts 1,000 KC, SW; 30 microvolts 17 MC (Input required for S/N 10 db) ● **SPECIAL CIRCUITS:** Loudness Control, High Filter, Tape Monitor. ● **DIMENSIONS:** Width 17 $\frac{1}{8}$ ", Height 5 $\frac{1}{8}$ ", Depth 14".



Manufactured By **TRIO CORPORATION** 6-5, 1-chome, Shibuya, Shibuya-ku, Tokyo, Japan

SOLE AGENT: Jacoby, Mitchell & Co., Pty., Ltd. **HEAD OFFICE:** 469-475 Kent Street, Sydney Tel: 26-2651
MELBOURNE: 15 Abbotsford Street Tel: 30-2491 **BRISBANE:** 56 Edward Street, Tel: 2-6467
ADELAIDE: Truscott Electronics, 64 Hindmarsh Square Tel: 23-3024

Instrumental, Vocal & Humour

IOLANTHE by Gilbert and Sullivan.
World Record Club, two record set,
stereo. Available in mono.
Interest: Gilbert and Sullivan.
Performance: First class.
Quality: Excellent.
Stereo: Good spread.

"Iolanthe" was the first work to be presented at the Savoy Theatre built by Mr D'Oyly Carte especially for the purpose of presenting Gilbert and Sullivan operas. It may thus be regarded as the first of the Savoy operas, although the earlier operas can justifiably be included in the Savoy category through subsequent performances there. Many G. and S. devotees regard the music as Sullivan's finest score, including no less an authority than Thomas Dunhill (Sullivan's most vociferous champion). Moreover, the satire, with its sly digs at the anachronistic House of Lords, wears very well. The present day popularity of the work is therefore not surprising.

The cast here is mostly the same as that featured in the other World Record Club presentations of G. and S., with veteran "Savoyard" George Baker playing the demanding part of the Lord Chancellor—surely the most difficult in all the Savoy operas. Those fine singers Elsie Morison and John Cameron take the parts of Phyllis and Strepson, while Marjorie Thomas is in the title role of Iolanthe. The other performers are: Monica Sinclair as Queen of the Fairies; Ian Wallace as Earl of Mountararat; Alexander Young as Earl Tolloller; Owen Brannigan as Private Willis; April Cantelo and Heather Harper as fairies. The Pro Arte Orchestra and Glyndebourne Festival Chorus are conducted by Sir Malcolm Sargent (who also has a reputation as a champion of Sullivan's music.)

As one would expect, this distinguished cast present an eminently satisfactory performance of this tuneful score. The excellent quality sound and low surface noise allow one to follow the plot without the aid of a libretto, although here and there sections are recorded at rather low level, so that one has to strain the ears a little. (H.A.T.)

★ ★ ★

BLOOD AND SAND. Music from the film composed and performed by Vicente Gomez, with Graciela Parraga (vocalist) and supporting instrumentalists, Universal Record Club stereo U-753. Available in mono.

Interest: Spanish style film music.
Performance: Exciting.
Quality: Excellent.
Stereo: Normal.

The music written by Vicente Gomez for the Hollywood epic "Blood And Sand" is unusual in that it gains considerably in stature out of its film context. I saw the film on two occasions, and was impressed by the music both times, but I did not realise how good it is until I had the opportunity to hear it away from the visual distractions of the cinema.

The sleeve note refers to Senor Gomez as "performer, composer, musician extraordinary." I would not quarrel with this description, since his skill as a composer and performer are amply demonstrated here. However, I thought the

outstanding talent on this disc is exhibited by Graciela Parraga, singing most expressively and with great versatility. She is at her best in the beautiful ballad "Verde Luna," singing with a voice as dark and warm as black velvet but, when the livelier tempos demand it, with a hint of mischievous laughter, or flamenco fire. She appears in six of the eight tracks and is impressive in every one.

The eight tracks are entitled: Blood And Sand — Torero Serenade — The Price of Glory — Fiesta Torera — Chi Qui Qui — Green Moon (Verde Luna) — Love And Sorrow — Cafe Pirate. All these have vocal except "The Price Of Glory" which is an arrangement of "Verde Luna" for guitars and flute; and "Love And Sorrow" which is a grave little tiento for solo guitars. I recommend this disc to those who have a liking for Spanish music with a little more freedom than the purely flamenco style. (H.A.T.)

★ ★ ★

BROADWAY STEREO SPECTACULAR. Nobuo Hara and his Sharps and Flats, with the SDS Choir. Stereo, Universal Record Club SU-833.

Interest: Broadway favourites.
Performance: Tuneful.
Quality: Excellent.
Stereo: Likewise excellent.

I tend to be a trifle wary about "spectaculars." As often as not, the term provides the excuse—or the explanation—for a noisy display by musicians and stereo technicians alike, and which I personally find rather wearing after a few tracks. However, this album, from an original recording by King Records, Japan, is not lacking in variety, but it does retain the mood of the original scores and it is pleasantly listenable. A novel feature is the complete replacement of strings by a vocal chorus, yet without one spoken syllable. The numbers are surefire favourites:

Maria — Tonight — Hernando's Hideaway—Bali Ha'i—C'est Magnifique — If I Loved You—On The Street Where You Live—Get Me To The Church On Time—I Could Have Danced All Night —Oh, What A Beautiful Morning — They Say It Is Wonderful—Hello, Young Lovers.

A good one. (W.N.W.)

★ ★ ★

CINEMA. The Knightsbridge Strings. Monument (Festival) stereo S(PL)-932,182. Available in mono.

Interest: Film favourites.
Performance: Lush.
Quality: Good.
Stereo: Good spread.

Film tunes which have remained firm favourites long after the screen epics themselves disappeared from the scene are featured in the ten tracks presented here. Those who have already heard The Knightsbridge Strings will know what to expect—lush arrangements with the emphasis on the melodies right through. Every member of the orchestra puts his art at the service of the melody, with individual virtuosity rigidly excluded, so that one is carried along by the tune without being particularly aware of the vehicle. Incidentally, don't let the name

We have a large range of pre-recorded tapes and records always in stock.

P. CARTER RADIO & TV SERVICE

79 NEW ILLAWARRA ROAD,
BEXLEY NORTH, N.S.W.
PHONE: 50-3150

PLAYER CABINETS




New Player Cabinet model 186 is 9in high, 17in wide, 16½in deep and 5½in above shelf. Finished with attractive hinged, tinted perspex top.
Price: \$20.00 for maple or walnut.
Kit of parts: \$13.50.
Teak: \$1.00 extra.

New Player Platform model 175 is 16in x 14in x 3½in. Price \$7.00 for maple or walnut. Kit of parts \$3.50. Teak 50c extra. Perspex cover, 5in high, \$8.20 and \$1.50 extra if required hinged.

Please specify cutout required.

NEW EQUIPMENT CABINET



MODEL 154

With lift-up lid over player. Sliding door in front of amplifier compartment. Large storage space. Size: 36in wide, 17½in deep, 31in high.

Price:
Made and polished \$53.00
Packing \$2.20
Kit of Parts \$33.50
Packing \$1.40
Teak Extra \$7.00
Free on rail.

Write for Catalogue and Player Guide

H.B. RADIO SALES

Manufacturers of Quality Radio and Radio Furniture for 36 years.

103-105 Catherine Street,
LEICHHARDT, SYDNEY

Telephone 56-5580



Price is the only difference between a \$70 plus precision changer and a \$47 BSR UA70/Macdonald 500.

For \$70 you can get a very good precision changer. No doubt it would have all the goodies to back up the price tag: a low-mass precision vernier counter-balanced pickup arm, a 4-pole dynamically balanced shielded motor. But, so does ours.


And we would hope, for that kind of money, that it would also have a feathertouch cueing device, "Dialomatic" precision stylus-pressure control, an 11" deep-rim turntable, vibration-free 4-point corner suspension, interchangeable manual and automatic spindles, plus the ability to play 7,"10"and 12" records at 4 speeds.

The BSR UA70/Macdonald 500 can give you all this. For \$47.00.

It has everything for the most fastidious listener, including the famous C1 ceramic stereo cartridge and diamond stylus. Optional extras include a Flexi-glass lid, teak base, and the fabulous Pickering magnetic cartridge.

So you see, the \$47 BSR UA70/Macdonald 500 from Goldring has everything a \$70 precision changer has.

Except a big price-tag.



**BSR UA70
MACDONALD 500
FROM**

GOLDRING

N.S.W.: 443 Kent Street, Sydney. 29-1275. VIC.: 368 Little Bourke Street, Melbourne. 67.1197. QLD.: 235 Edward Street, Brisbane. 2-7010. W.A.: 91 Hay Street, Subiaco, Perth. 8.4988, 8.4989. S.A.: 77 Wright Street, Adelaide. 51.5117.

ENGINEERING (A'ASIA) PTY. LTD.

GE:P385

fool you—this is not just a string orchestra, but a comprehensive ensemble with woodwinds, brass and percussion sections. It does, however, have an unusually large string section which gives the characteristic lush sound.

Tune titles are: Temptation — My Melancholy Baby—As Time Goes By—Moonlight Becomes You—You'll Never Know — You Made Me Love You — Tangerine—Over The Rainbow—Laura —That Old Feeling. Sound quality and stereo separation are up to standard. (H.A.T.)

★ ★ ★

HANDEL: Concertos for Lute and Harp, Op. 4, No. 5 in F major and No. 6 in B-flat major. Desmond Dupre, lute, and Osian Ellis, harp. Concerto Grosso in C major ("Alexander's Feast"), the Philomusica of London conducted by Granville Jones; organ and harpsichord continuo by Thurston Dart. World Record Club 12in stereo, S/T4219.

Interest: Handelian concerti.
Performance: Fresh, lively.
Recording: Excellent.
Stereo: Widespread.

A little gem for Handel lovers, this one. Originally from the catalogue of L'Oiseau-Lyre, it features the "Alexander's Feast" Concerto Grosso together with Thurston Dart's reconstruction of the supposed original form of the fifth and sixth opus 4 concerti. It may be remembered that these are usually regarded and played as part of the remaining opus 4 organ concerti, although there is strong evidence that neither were composed for organ.

It makes delightful listening, indeed. As chamber works with the solo parts featured on lute and harp, the two opus

4 concerti really sound fresh and lively as compared with most organ performances. The balance which has been set between soloists and continuo is quite superb, and could hardly be bettered. The same high standard is maintained in the concerto grosso, too—what a pity this lovely little work is usually omitted from performances of "Alexander's Feast"!

The technical side of the recording is quite the equal of the performance. There is negligible noise and distortion, and the stereo is widely spread yet quite smooth. For lovers of Handel, then, a disc that can be warmly commended. (J.R.)

★ ★ ★

AN ORCHESTRA OF ORGANS. Buddy Bonds. Stereo, 20th Century Fox STL-932,156. Also in Mono TL-32,156.

Interest: Three organs.
Performance: Good.
Quality: Good.
Stereo: Normal.

Buddy Bonds, well known in the U.S. club circuit as a duo-organist, comes to light here with an organ trio—plus: Buddy Bonds, Baldwin organ; Ray Jenkins, Hammond organ; Darrell Stuckey, Wurliitzer organ; Bobby Haggart, bass; Sol Gubin, drums.

On stage, I imagine the group could be quite a hit but, without the visual, the involvement of the five players, three organs, bass and drums is largely lost. One is liable to feel that, in terms of sound, Reginald Dixon and his Blackpool Wurliitzer could do at least as well on his own. Mind you, he doesn't carry his instrument round from club to club!

Still, if electronic organ sounds intrigue and you want to try your hand at picking them, listen to side 2, which

rare, good band recording, here's one you should hear. What there is of the band is superb and, if it occupies the sound stage for only part of the total time, I imagine that anyone interested in band music will be interested also in the traditions which gave it birth.

Technically, the quality, definition and stereo separation are excellent. Recommended. (W.N.W.)

has a lot more get-up-and-go than side 1. The titles: Have You Heard The One About — I Want to be Happy — Little Girl Blue — How About You — Don't Take Your Love From Me — Let's Fall In Love — Teenage Polka — Anema E Core — This Can't Be Love — I Wish You Love — The Boy Next Door — Olay. (W.N.W.)

★ ★ ★

ITS A GUITAR WORLD. Chet Atkins. RCA Dynagroove stereo LSP-3728. Available in mono.

Interest: Popular guitarist.
Performance: First class.
Quality: Excellent.
Stereo: Good.

If you like the Nashville style of guitar playing, you are hardly likely to hear a more skilful exponent than Chet Atkins. In fact, I would go so far as to say that I have never heard better such playing than is to be found on this disc. Chet Atkins turns out a splendid performance with some first class support from some of the competent (but un-named) Nashville musicians, playing the following: What's I Say — Cast Your Fate to the Wind — Lara's Theme — A Taste of Honey — For No One — Pickin' Nashville — January in Bombay — Ranjana — What Now My

Band and its traditions

SOLDIERS. The Band Of The Grenadier Guards conducted by Captain Rodney Bashford. Stereo, Decca SKLA-4750. Also in mono LKA-4750.

Interest: Sound documentary.
Performance: Very good.
Quality: First rate.
Stereo: Outstanding.

This record reminded me very strongly of that other very early and very successful Decca release "A Journey Into Stereo Sound." It has the same careful planning, the same ring of authenticity and the same technical finesse.

As the title would suggest, it is a sound picture of a soldier's life. Beginning with Reveille, and a training sequence, it highlights the ceremonial with a representation of the changing of the guard. Commands echo from here and from there; marching feet cross the parade ground in front of the stereo microphones and, punctuating it all are marching tunes from the Band Of The Grenadier Guards.

On side 2 is a sound montage of war—first a war of foot soldiers, cavalry and old-world muskets and cannon. Then the scene changes to pom-poms, ack-ack, aircraft and tanks. The music changes likewise from simulated seventeenth-century sound to a modern military band, marching by and then fading into the distance.

To those readers who wait for the

For virtually PERFECT REPRODUCTION

build your own
world-famous Dynaco
Hi-Fi Amplifier,
with an easy-to-assemble

DYNAKIT

Contact us for all
models of fully assembled
(240V 50 c/s)

DYNACO

HI-FI AMPLIFIERS

Write for free brochures to

Danish Hi-Fi


66 Mayston St., Camberwell,
Victoria. 82 4839

ACOS

REPLACEMENT CRYSTAL CARTRIDGES

Acos 90 Series — a brand new family of four pick-up cartridges, covering all the main types needed to-day, each fitted with Diamond Stylus at no extra cost.

GP91-1 Replaces GP67-1G MONO CRYSTAL	\$5.95
GP91-2 Replaces GP67-2G HIGH OUTPUT MONO CRYSTAL	\$5.95
GP92 MONO CERAMIC	\$6.55
GP93 Replaces GP73-2A STEREO CRYSTAL	\$7.55
GP94-1 Replaces GP81 STEREO CERAMIC	\$7.95
GP94-5 STEREO CERAMIC FOR TRANSISTOR AMPLIFIERS	\$8.95



fitted with
DIAMOND
Stylus at no extra cost.

TECHNICAL DATA SHEETS SENT FREE ON REQUEST

Sole Australian Agents:

AMPLION (A'SIA) PTY. LTD.

29 Majors Bay Rd., Concord,
Sydney, N.S.W. Phone 73 1227

NEW Releases!

IN HI-FI STEREO EQUIPMENT BY CLASSIC



Based on the R. & H. Playmaster 106 and 101 Amplifiers with these added features:-

- Loudness control giving bass boost at low volume.
- Sensitivity switch — normal or wide band.
- Provision for tape recorder with separate record-play switch.
- Calibrated dial available for all States showing main stations in larger type.
- Fully guaranteed.

SPECIFICATIONS COMMON TO BOTH UNITS

• Inbuilt high gain tuner with a frequency coverage of 530 to 1,600 K.C. • EM84 tuning indicator giving accurate tunings with ease. • Two channel tone control stage with separate bass and treble controls. • Input facilities with switching for pick-up and stereo or mono tape recorder for record of play back. • Chassis is plated and mounted in attractive and durable metal case finished in grey with control panel in black and silver with matching knobs. • Valves used:—4 6GW8, 12AX7 or 12AU7, 6AN7, 6N8, EM84 and 2.210 diodes. Dimensions 15½" x 5¼" x 11".

106 UNIT WITH TUNER

- Output 8 watts per channel (16 watts).
- Incorporating Ferguson type O.P. 412 grain orientated output transformers giving a frequency response of 20 to 30,000 cycles.

\$115.50 (£57/15/-)

106 AMPLIFIER WITH GARRARD CHANGER AND HI-FI SPEAKERS

Type 3000 changer fitted with 9th Sonatone ceramic cartridge and diamond stylus and two Magnavox 8WR or Rola 8CM. 8in Hi-Fi speakers.

\$160.00 (£80)

101 UNIT WITH TUNER

- Output 11 watts per channel (22 watts).
- Incorporating Ferguson type O.P. 387 grain orientated output transformers giving a frequency response of 20 to 30,000 cycles.


\$119.50 (£59/15/-)

101 AMPLIFIER WITH GARRARD CHANGER AND HI-FI SPEAKERS

Type AT6 changer fitted with Sonatone 9TA ceramic cartridge and diamond stylus and two Rola 12PX 12in speakers or two Philips 9710 dual cone Hi-Fi 8in speakers.

\$190.00 (£95/-/-)

FREIGHT EXTRA



PLAYMASTER BOOKSHELF LOUD SPEAKER SYSTEM

Complete unit, built, wired and polished in walnut, teak or maple.

\$30 (£15.0.0)

Post and packing:

N.S.W. \$2.00, Interstate \$3.00.

Complete kit of parts less Cabinet but including Speakers, Inductance, Condenser, Resistor, Innabond and Speaker Silk.

\$17.50 each Post and packing \$1.25 extra.

Available 7½ or 15 ohm impedance.

CABINET DIMENSIONS
18" x 12" x 7"

THE NEW MULLARD BOOKSHELF MINI SPEAKER UNITS


As featured in "Mullard Outlook," April, 1966, issue.

These units designed by Mullard and Magnavox engineers compare favourably with imported B/S Speakers costing more than twice the amount and are ideal where space is limited. Incorporates the Magnavox 6WR 6in Speaker and the new 3TC Mk 11 tweeter frequency response, 50 to 18,000 cycles. Power rating max. 8 watts. Polished in rosewood, teak, maple or walnut.

Available in 7½ or 15 ohm impedance.

\$27 (£13/10/-) each

Post and packing: N.S.W. \$1.30, Interstate \$2.50.



CABINET DIMENSIONS
14in x 8in x 8in


NEW SUPER BOOKSHELF SPEAKERS as featured in December '66 "Electronics Australia." Finished in Teak, Walnut or Maple **\$39.00 each, postage \$2.00.**

NEW AMPLIFIERS AND TUNERS BASED ON THE PLAYMASTER 106 AND 107

107 AMPLIFIER AND TUNER

\$79.50 (£39/15/-)

FREIGHT EXTRA



106 AMPLIFIER AND TUNER

\$104.00 (£52)

FREIGHT EXTRA

107 AMPLIFIER

• Output 5 watts per channel (10 watts). Ferguson output transformers with a response of 30 to 20,000 cycles.

• Valves used: 6AN7, 6N8, 2—12AT7, 2—6BQ5, and 6CA4 rectifier.

SPECIFICATIONS COMMON TO BOTH UNITS

- Inbuilt high-gain tuner with a frequency coverage of 530 to 1,600KC.
- Two-channel tone control stage with separate bass and treble controls.
- Switching facilities for pick-up and stereo or mono tape recorder for record or play-back.
- Loudness control giving bass boost at low volume.
- Chassis plated and mounted in attractive metal case finished in grey with control panel in silver and black with matching knobs and switches.
- Dimensions: 13½in x 5¼in x 11in.
- Fully guaranteed.

106 AMPLIFIER

• Output 8 watts per channel (16 watts). Ferguson orientated grain output transformers with a response of 20 to 30,000 cycles.

• EM84 tuning indicator. • Valves used 6AN7 6N8, 12AU7 or 12AX7, 4—6GW8 and 2—0A210 rectifiers.

THE ABOVE AMPLIFIERS SUPPLIED WITH THE NEW GARRARD 1,000 CHANGER WITH RONETTE CARTRIDGE AND TWO MAGNAVOK 8WR OR ROLA 8CMX HI-FI SPEAKERS

107—\$116.75 (£58/7/6)

FREIGHT EXTRA

106—\$141.25 (£70/12/6)

CLASSIC RADIO

245 PARRAMATTA ROAD, HABERFIELD, N.S.W. PHONE 71-2145

Love — 'Na Voce, 'Na Chitarre 'E Poco 'E Luna — Star Time — Sempre.

In "January in Bombay" and "Ranjana," Chet joins forces with one of India's outstanding sitar players to play rather weird duets with the plangent quarter tones of the oriental instrument imitating the guitar, and the guitar doing its best to sound oriental. A welcome touch of variety with considerable interest. (H.A.T.)

★ ★ ★

BANDSTAND No. 10 G.U.S. (FOOTWEAR BAND) Conducted by Stanley H. Boddington L.R.A.M., A.C.R.M. Stereo, Columbia SCXO-6050. Also in mono 330SX-6050.

Interest: Small but proficient band.
Performance: Some good playing.
Quality: Clean but "dry."
Stereo: Pronounced separation.

This band is just about as different as it could be from The Band Of The Grenadier Guards, mentioned elsewhere. Whereas the Grenadier Guards gain a weight and a richness from the very size of the band, this, by contrast, is a much smaller group. The difference is emphasised by the very "dry" or non-reverberant environment in which this particular recording has been made. Significantly, the program was recorded while the band was on tour in Switzerland and exactly the same criticism has been levelled at other Swiss recordings which have reached Australia on another label.

The end result is that where the band tries for a big sound, as in "Anchors Aweigh," it just isn't forthcoming. The players work hard, especially the drummer, and that's exactly the way it sounds!

On the other hand, some very excellent instrumental work is revealed by the combination of a non-reverberant studio and highly perceptive stereo and those inclined to analyse performances and techniques within a band will find plenty to listen to. In fact, herein lies its major appeal.

The track titles: March Of The Swiss Alpine Club—Una Voce Poco Fa—Symphony Of Marches—Lisbon Carnival—Eternal Father, Strong To Save—Anchors Aweigh—The Lost Chord—The Shipbuilders—Slavonic Rhapsody No. 1—King Of Glory, King Of Peace. An album that will appeal strongly to some, very little to others. (W.N.W.)

★ ★ ★

MUSIC FOR WIVES AND LOVERS. Nelson Riddle and orchestra. United Artists (Festival). Stereo SUAL-932,296. Also available in mono, UAL-932,296.

Interest: The Nelson Riddle style.
Performance: Smooth.
Quality: Very good.
Stereo: Well exploited.

This record features a selection of movie themes and popular "show-tunes" some of which are identified with well-known vocalists, although the recording is strictly instrumental. The tracks are: Side 1: Cabinet—Born Free—What Now My Love?—Yesterday—The Shadow Of Your Smile—Somewhere My Love. Side 2: Winchester Cathedral — Wives And Lovers—A Man And A Woman—Spanish Eyes—Music To Watch Girls By—Strangers In The Night.

The arrangements are distinctly those of Nelson Riddle with his smooth up-tempo style. Very effective use is made of a jazz organ, played somewhat after the style of Jimmy Smith, together with

the rather dominating sound of a harmon-mute trumpet. Despite the competition between the organ in one channel and muted trumpet in the other, the arrangements will set a swinging mood for many besides just "wives and lovers." (A.J.L.)

★ ★ ★

THE BEST ORIGINAL SOUND TRACKS And Great Themes From The Motion Pictures. United Artists (Festival) stereo SUAL-932,293. Also available mono UAL-932,393.

Interest: As per title.
Performance: Excellent.
Quality: Very good.

To the movie fan this record will have special appeal, as it contains a selection of themes and other instrumentals from the motion pictures, including "Dr Zhivago," "A Funny Thing Happened On The Way To The Forum" and "The Russians Are Coming." The tracks are; Side 1: Hawaii—Return Of The Seven—The Fortune Cookie—After The Fox—Duel At Diablo—Khartoum. Side 2: A Man And A Woman — Cast A Giant Shadow — Viva Maria — Somewhere My Love—Escorts Away—Comedy Tonight. (A.J.L.)

★ ★ ★

PERCUSSIVE MARIACHI, arranged and conducted by Ted Sommers. United Artists stereo SUAL-932,295. Available in mono.

Interest: Varied percussion.
Performance: Stimulating.
Quality: First class.
Stereo: Excellent.

The sleeve note lists no fewer than 38 percussive devices as being used in this recording, from the familiar drums, tympani, vibraphone and tambourine to the exotic Chinese bell tree, cold grass drums, and jawbone. With this astonishing range of instruments, Ted Sommers and his band of collaborators produce their versions of some of the familiar tunes one hears so frequently nowadays in Mariachi arrangements: Feelin' Good — The Apple Tree—Never on Sunday—If I Were A Rich Man—Watermelon Man—La Bamba—Samba de Orfeu—Carnival—Brasilia—Dark Eyes—Work Song—Tequila.

The amount of enjoyment you are likely to get from this disc will depend on your liking for percussion generally. Some folk, including myself, thought it rather overdone; others thought it quite perfect. It is definitely not music for relaxation—it is too stimulating for that. Probably the best thing to do if you are interested is to try to hear a few sample tracks at your record dealers—I suggest "Never on Sunday" and "If I Were a Rich Man" as two of the best on the disc. (H.A.T.)

★ ★ ★

THE DREAM PIANO. Aldo Ciccolini plays music of dreams and dreamers, Capitol (E.M.I.) stereo SP 8651. Available in mono.

Interest: Classical snippets for piano.
Performance: Tasteful.
Quality: Excellent.
Stereo: Not significant.

If the contents of this disc had anything in common with the tasteless cover design, depicting a piano adorned with flowers and cute little birds, with cherubs peering coyly from all angles, it would be a painful experience for any self-

respecting music lover. Fortunately, Signor Ciccolini proves himself to be a musician of sensibility and refinement, so that he is able to overcome the difficulties inherent in a program consisting entirely of the easier type of light classic piece, to make them sound like the masterpieces in miniature they are.

Signor Ciccolini has a finely controlled touch and a fluid keyboard technique which even the most critical listener should find without blemish. If his dynamic range seems rather limited, this could be due to the prevailing restful mood of the pieces: Nocturne in E Flat Op. 9, No. 2 (Chopin) — Liebestraum No. 3 (Liszt) — Adagio from "Moonlight" Sonata (Beethoven)—Study In E major, Op. 10, No. 3 (Chopin) — Spring Song (Mendelssohn) — Fur Elise (Beethoven) — Prelude in C sharp minor (Rachmaninoff) — Clair de Lune (Debussy)—Idylle (Chabrier) — La Plus que Lente (Debussy)—To Spring (Grieg). These pieces are all so familiar that it is hardly necessary to enlarge on the above. However, those who cannot remember opus numbers may care to know that the Nocturne is the famous one which seems always to appear in recitals of this kind, and the study is the one known as "Tristesse." The Liebestraum is also the most famous of the set.

It is only necessary to add that the

"INNERBOND" (Regd.)

BONDED ACETATE FIBRES

For packing in

SPEAKER ENCLOSURES

A new resilient Bonded Wadding made from ultra fine Cellulose Acetate Fibres that gives high efficiency for Sound Absorption.

"INNERBOND" is light, clean dust free and easy to handle. Because all the fibres are bonded "INNERBOND" will hang as a "curtain" and will not fracture or break down due to vibration.

"INNERBOND" is odourless, highly resistant to attack by bacteria or fungus and is vermin repellent: "INNERBOND" at 16oz sq. yd. has a nominal thickness of 1" and at this density is recommended as a packing in Speaker Enclosures for Sound Absorption.

STOCKISTS

SYDNEY—Arrow Electronics Pty. Ltd., 432 Kent St.; Broadway Electronics Pty. Ltd., Broadway and City Rd.
MELBOURNE—J. H. Magrath and Co. Pty. Ltd., 208 Little Lonsdale St.
BRISBANE—A. E. Harrold Pty. Ltd., 123 Charlotte St.
ADELAIDE—Duncan Agencies, 57 Woodville Rd., Woodville; General Accessories, 81 Flinders St.
PERTH—General Accessories, 46 Milligan St.

If unobtainable

For 1 sq. yd. as above send \$2.00
For 2 sq. yds. as above send \$3.75
For 4 sq. yds. as above send \$6.50

Postage paid in Australia and Territories.

to the manufacturers

WONDER WOOL
PTY. LIMITED.

87 James Street, Leichhardt, N.S.W.
BOX 548 — G.P.O., SYDNEY.
Phone: 56-2780.

BREAKTHROUGH IN PICK-UP PERFORMANCE

INCORPORATING THE
U-15 MINICONIC SEMI-
CONDUCTOR CARTRIDGE

THE REVOLUTIONARY EUPHONIC MINICONIC
SEMI-CONDUCTOR TRANSDUCER SMASHES
THROUGH THE PERFORMANCE LIMIT-
ATIONS OF ALL EXISTING PICK-UPS

PHENOMENAL RANGE


20 to 20,000 cps \pm 2db. Smoothest, distortion-free sound, to give TOTAL MUSIC RESPONSE.

LOWEST EFFECTIVE TIP MASS

Tracks 40 kcps 2nd harmonic pinch effects of 20 kcps fundamental; thus stylus tip stays in groove at all frequencies with only .5 gram needle force. No shock or modulation noise from loss of groove contact—gives clean highs on loudest passages—on outer or inner grooves.

ALL THE COMPLIANCE YOUR SYSTEM CAN USE—25 MICRO CM/DYNE


Unequalled tracking ability at low frequencies. More important, for perfect tracking of the upper register—is the fantastically high stylus-groove resonance of 47 kcps—more than one full octave out of the pass band! THIS MAKES A PERFECT MARRIAGE OF STYLUS TIP TO GROOVE—GIVES MUSIC PURITY AN ENTIRE ORDER OF MAGNITUDE BETTER THAN EVER BEFORE!



**MINICONIC
PHONO
SYSTEM—
LOW-MASS
TONE ARM
WITH PLUG-IN
SEMI-CONDUCTOR
CARTRIDGE**

SILICON SEMI-CONDUCTOR ELEMENTS

First cartridge to employ silicon semi-conductor elements. Delivers fabulous output—10,000 times the power of magnetic cartridges. Ideal for transistor circuits. World's most efficient, stable, rugged, hum-free cartridge, with indefinitely long life.




ELLIPTICAL BIRADIAL DIAMOND STYLUS

Precision-ground, polished, individually inspected and tested for perfect symmetry. Elliptical shape assists styles in reducing pinch effect on inner grooves.

VIRTUALLY NO PLAYBACK LOSS FROM OUTSIDE TO INSIDE GROOVES—ALL THE RECORD SOUNDS GOOD.

ENERGY DERIVED FROM EXTERNAL POWER SOURCE

—thus saving the delicate record grooves. The U-15 cartridge is essentially a modulating device, not a reciprocal generator. Miniature-type P-15 power source (left) has all cables to plug into any high-fidelity amplifier. Includes switch to feed low-level magnetic inputs or high-level auxiliary inputs. Works from 240 volts A.C. supply. \$37.60.



PS-15 power source

**CARTRIDGES WITH POWER SOURCE AVAILABLE IN
SEPARATE FORM TO FIT MAJORITY OF HIGH-
QUALITY TONE ARMS.**

BRIEF SPECIFICATIONS AND PRICES

Model U-15-LS miniconic laboratory standard stereo cartridge, consisting of U-15 semi-conductor modulator assembly and N-15-BR biradial diamond stylus; fits all standard heads. \$39.20

Model U-15-LS (P1). Same as U-15-LS above, but plug-in; for TA-15 low-mass tone arms. \$39.20

Model U-15-P miniconic professional stereo cartridge, consisting of U-15 semi-conductor modulator assembly and low-mass, .5 mil tip N-15-LM conical diamond stylus; fits all standard heads. \$21.60

Model U-15-P (P1). Same as U-15-P above, but plug-in; for TA-15 low-mass tone arms. \$21.60

Note: All the above cartridges require a power source.

Model TA-15 professional low-mass tone arm for 12" turntables; accepts U-15-LS (P1) and U-15-P (P1) heads. \$36.80

TEST REPORT BY HIRSCH-HOUCK LABORATORIES in "ELECTRONICS WORLD" July—1965

FREQUENCY RESPONSE RANGE: "The frequency response was unusually flat and peak-free over the entire audio range—we would confirm Euphonics' claim of \pm 2db. response from 20 to 20,000 cps."

TRACKING: "The cartridge tracked our high-level Cook and Fairchild records at only 1 gram of stylus force, matching or surpassing any other cartridge we have tested in this respect."

HUM: "If it is correctly installed, the Euphonics Miniconic is perhaps the most basically hum-free cartridge on the market."

HOW MINICONIC SOUNDS: "In its sound, the Euphonics CK-15-LS is as good as its measurements suggest. It is clean, sweet and uncoloured, its sound is very full with no portions of the spectrum apparently emphasised or diminished."

"With top-quality auxiliary equipment, the Euphonics cartridge is capable of fidelity of response that rivals anything we have heard."

RCA OF AUSTRALIA PTY. LTD.

An Associate Company of the Radio Corporation of America

SYDNEY: 219 Elizabeth Street. 61-8541. **MELBOURNE:** 2 Stephenson Street, Richmond. 42-4586.
PERTH: 280 Stirling St. 28-5057. **ADELAIDE:** 99 Currie St. 51-7870. **BRISBANE:** 173 Ann St. 2-7884.

RCA32X.FPM

sound quality is of excellent standard, and it will be obvious that this is a record which those with a taste for classical snippets can buy with confidence. The stereo does not add anything to the listening qualities. (H.A.T.)

★ ★ ★

LATIN AMERICAN HITS. Los Campaneros with the Frank Raye Singers, conducted by Sebastian Mure. Universal Record Club, stereo U741. Available on mono.

Interest: See title.

Performance: Typically slick.

Quality: Very good, but . . .

Stereo: Normal spread.

Recordings of Latin American music are so numerous that the potential buyer is posed a considerable problem. The choice at the moment seems to lie largely between the "bullring" sound now so much in vogue, the nightclub orchestra and the traditional vocal group with orchestral backing. It is to the latter category that this disc belongs, and I have no hesitation in giving it a high rating, as far as the contents and performance are concerned. The titles include some of the best-known Latin American tunes, mainly oldies which show no signs of diminishing in popularity as the years go by: Amor—Me Lo Dijo Adele—Mambo Jambo—Frenesi—No Puede Quererte—Adios—Besame Mucho—El Cumbanchero—Te Quiere Dijiste—Aquellos Ojos Verdes—Patricia—Solamente Una Vez.

The band and the Frank Raye Singers make the most of the catchy rhythms of the rumba, samba, cha cha, etc., etc., and perform in the typically slick style of Latin American groups. They sing mainly in Spanish, although a few verses are repeated in English. Sound quality is good in the main, but deteriorates slightly toward the end of each side. The stereo is widely spread, but is rather weak in the middle, owing to the singers having been grouped at the sides (H.A.T.).

★ ★ ★

CLASSICAL ARIAS. Maria Callas with the Paris Conservatoire Orchestra conducted by Nicola Rescigno. World Record Club stereo S/T 4218.

Interest: Soprano arias.

Performance: Could be better.

Quality: Very good.

Stereo: Normal.

Madame Callas does not often move into the realms of German opera, but here the whole recital is devoted to the works of Mozart, Beethoven and Weber. The single Beethoven work is his dramatic aria for soprano and orchestra, intended for concert performances—"Ah, Perfido." Weber also is represented by a single work, the popular aria "Ocean Thou Mighty Monster" from the opera "Oberon." The dramatic nature of these suits Madame Callas' declamatory style, and she sounds quite at home here.

It is a different story in the Mozart. Here she sings three arias from "Don Giovanni"—Oh! Crudele (Non Mi Dir), In Quali Eccessi (Mi Tradi Quell'alma Ingrata) and Or Sai Chi L'Onore—and the beautiful "Porgi Amor" from "The Marriage Of Figaro." While Madame Callas' style is undoubtedly well suited to the bel canto singing of Italian opera, her rather hard tone and wide vibrato sound quite unconvincing in these Mozart works, which

require a higher degree of characterisation than she seems able to provide. In the "Porgi Amor" she just does not convey the image of a gentle, grieving woman, and in the "Non Mi Dir" she runs up against the intricacies of Mozart coloratura writing, with which she seems quite unable to cope—I can only describe her handling of this as inept (H.A.T.).

★ ★ ★

CELESTE AIDA. Richard Tucker. CBS stereo SBR 235218. Available in mono.

Interest: Opera favourites.

Performance: Excellent.

Quality: Excellent.

Stereo: Normal.

Although CBS could be buying an argument in suggesting that the world's favourite tenor arias all come from Italian and French operas (mainly the former) without so much as a glance at the German and Russian composers, few would quarrel with their choice of Richard Tucker to sing them. Considered by many to be the best operatic tenor singing today, he is always a pleasure to listen to. In addition to the more common attributes of the top-ranking opera star, he has the virtues of bright clear tone with none of the pain-laden inflections which so many tenors acquire; and his high notes are entirely unforced.

There are 14 tracks (excellent value for money) entitled: Celeste Aida from "Aida" (Verdi)—Che Gelida Manina from "La Boheme" (Puccini)—Recondita Armonia from "Tosca" (Puccini)—E Lucevan le Stelle from "Tosca" (Puccini)—Ah Si, Ben Mio from "Il Trovatore" (Verdi)—Di Quella Pira from "Il Trovatore" (Verdi)—Flower Song from "Carmen" (Bizet)—La Donna e Mobile from "Rigoletto" (Verdi)—Questa o Quella from "Rigoletto" (Verdi)—Ah Fuyez, Douce Image from "Faust" (Gounod)—Mama, Quel Vino e Generoso from "Cavalleria Rusticana" (Mascagni)—Salut Demeure from "Faust" (Gounod)—Nessun Dorma from "Turandot" (Puccini).

Perhaps my critical faculties were somewhat dimmed by the pure enjoyment of listening to such a collection of excellent tunes, but at the end of the second side I was not conscious of a single defect in Mr Tucker's performance—not one instance likely to bring a frown to the reviewer's face. In retrospect, I should say that the orchestral support is a little weak, but this does have the virtue of keeping the spotlight on the principal performer. Excellent sound and stereo make this a record which the opera lover will find hard to resist. (H.A.T.)

★ ★ ★

SERENADE. Robert Tasman, baritone, accompanied by John Champ, piano and guitar. CBS mono only, BP 233393.

Interest: Varied song recital.


Performance: Excellent standard.

Quality: Very good.

It is always pleasing to see talented young Australian artists afforded the opportunity to make records and, when they come up with a record as pleasant to listen to as this one, it is to be hoped that sales will justify the confidence of the recording company. Robert Tasman is fairly well known in Sydney musical circles for his appearances in opera and

SPECIAL !!

6 Transistor Radio Kit, complete. Incl. instruction manual — \$16.50 Incl. Tax.
Wired and Tested \$19.



60 SIMPLE ELECTRONIC PROJECTS YOU CAN BUILD NOW!

How would you like to make a 4-Band Short-Wave converter, a Screaming Siren, Boat Hailer, Telephone amplifier, Electronic Organ, Electric Fence—Battery operated 15-mile range, or any one of 60 exciting, easy-to-build projects? IT'S EASY THE S.E.W. KIT WAY. * All Kits Transistorised and use special printed Circuit Boards.

Palace 8-Watt Stereo Amplifier

Frequency Response 50 to 15,000 cps. \$32.50.




TRANSISTOR MODULES



Unit 2. 10 Watt Amplifier 1.5 Ohms 20/20 kc/s 12V supply, \$15, plus Tax OR 3W to 50W from \$9. Plus Tax

Unit 13. 10 Watt RMS. Continuous 15 Ohms, 40V Supply \$21 plus tax. Also 25W, 35W, 75W, RMS Amplifiers, 8 Ohms from \$44 plus tax. Also 7W with tone control stage. P.A. AMPLIFIERS 12V Transistorised from 3W to 50W from \$9.50 plus tax. Also 50 Watt Guitar Boost Amplifier.



Unit 10A TRANSISTORISED.

Tuners: Bandwidth 8 Kc/s With Power Supply \$23 plus 25% Tax. With RF Stage \$33 plus 25% Tax.

TAPE RECORDER KITS

Unit 14. TAPE PRE-AMPLIFIER, Unit 15. 60/90 Kc/s Push/Pull Transistorised Bias. Erase Oscillator Module. Unit 16. Transistor Tape Recording Amplifier Module. Used with Unit 14.

NEW RELEASE ROLAND AM/FM STEREO RECEIVER Plus 14 WATT STEREO AMPLIFIER. Suitable Magnetic Pick-Up. Limited Stocks.



Full Price \$150.00 (£75)

TRANSISTORS AND DIODES AT SPECIAL PRICES, including

BC107, \$1; AF114, 95c; AC125, 90c; BC108, 90c; AF1115, 95c; 2N301, \$2.50; BC109, \$1.30; AF116, 90c; OC74, 95c.

Also Components, Tape, Films, etc. Send S.A.E. for Details and List.

S. E. WILLIS TRADING CO.

38 RIVERSDALE RD., CAMBERWELL, E.6., VICTORIA. 82-5787.


LUX SETS NEW PERFORMANCE STANDARDS

New vistas in electronics have been opened by the research division of the Lux Corporation, Japan's leading manufacturer of high quality amplifiers and associated equipment. Engineering and wiring are most meticulous as detailed examination discloses. The NHK Broadcasting Network use Lux amplifiers—and the Olympic Stadium in Tokyo was equipped with Lux public address systems. Much Lux electronic circuitry carries world wide patents and is exclusive to Lux amplifiers. As Australian agents, Encel Electronics Pty. Ltd. has selected a number of Lux models; in every case the unit offers remarkable value and is fully guaranteed.




LUX MODEL FL-15 CHANNEL CONTROL

The FL-15 is a frequency divider network designed for multiple amplifier systems, with crossover points at 100, 200, 400 and 800 Hz. Three terminals are also provided for 3-D sound systems. In every way the FL-15 is superior to normal conventional crossover networks; speakers with differing efficiency and impedance may be matched, amplifier stability is improved, triode amplifiers are used for medium and high frequencies and more powerful amplification is used for the low registers. Contact us for full details, specification and price.



NEW LUX AMPLIFIER SOON TO BE RELEASED

An all new model, the SQ 1220, will soon be available. This solid state stereo unit is rated at 56 watts R.M.S. into a 16 ohm load in each channel. Production of this superlative amplifier will be restricted so enquire now! Full specifications on request. Price is expected to be very close to \$300.



THE LUX SQ 65—30 WATTS R.M.S. PER CHANNEL


With a wide frequency response of 20-20,000 Hz. plus or minus 1½ dB. at full output, the circuitry of the SQ 65 incorporates silicon diodes and P.P. 7868's, output being 30 watts R.M.S. in each channel. Input sensitivity is 4 mV. for magnetic p.u. Tone compensation circuits include a U.S. patented M.F.B. system and new Lux NF electronics. Substantial grain oriented output transformers of unique design are responsible for the outstanding performance of the SQ 65. Features include tape monitoring circuit, phase switch, blend control, speaker switch, headphone jack, scratch filter and rumble filter. The MFB circuitry is effective on normal speaker systems. Write for complete specifications

\$199




THE LUX SQ-101 SOLID STATE STEREO AMPLIFIER — \$189

This fine silicon transistor stereo amplifier is rated at 80 watts peak power output and distortion is negligible at normal lounge room listening levels. Frequency response is 15-50,000 Hz. plus or minus 2 dB. Magnetic sensitivity is 3.5 mV, tape head input 1.8 mV and additional features include unique bass and treble control circuitry permitting changeable crossover frequencies for both high and low ranges. High cut (scratch filter), low boost (loudness control), tape monitor, speaker switch, headphone jack and normal treble/bass controls are standard. Used with 16 ohm speaker systems power output is 15 watts R.M.S. per channel. The audio excellence of the SQ-101 is obvious even to the untrained ear. Earlier substantial shipments sold out in a few days! **\$189**



PRICE OF LUX STEREO CONTROL UNIT SLASHED TO \$55!

The completely transistorised printed circuit control unit Model P212 will match the majority of stereo power amplifiers. Built-in power supply (240 V AC) and input sens. as low as 3.5 mV. Performance is exceptionally good, low noise 2SB345 and 2SB347 transistors (12 altogether) being used for complete stability. Inputs for magnetic pickup and two auxiliaries . . . controls for bass, treble, balance and ON/OFF volume. (May be operated from batteries.) **\$55.**



NEW MOVING MAGNET STEREO CARTRIDGE

The Lux T-15-M has been acclaimed as a brilliant performer by discriminating audio enthusiasts—frequency response is conservatively quoted at 20-20,000 Hz. and stylus pressure is from 1 to 2½ grams. Tracking angle is 15°, output is 5 mV. at 1 kHz. Stylus sizes available are 0.7 and 0.5 mil. conical diamonds. From a musical appreciation point of view the Lux T-15-M compares favourably with cartridges twice the Encel price. **\$24.50**
JUST RELEASED! The Model T15M with an elliptical diamond stylus! **\$29.50.**

Encel
ELECTRONICS
PTY. LTD.

Head Office: 431 Bridge Rd., Richmond, Vic. Tel. 42 3762
Sydney Store: 257 Clarence St., Sydney. Tel. 29 4563, 29 4564
Australia's Greatest Hi-Fi Centre
* Wholesalers * Trade-Ins Accepted

recitals, and has also sung in a number of European countries. John Champ often appears on ABC radio and television, and may be remembered as the compere of "Sunday Concert" during part of its run on TV. He has had extensive experience as an accompanist. The work of both artists is of excellent standard.

The recital here is a real pot-pourri of many different song styles in a variety of languages, comprising as it does folk songs, Lieder, art songs, musical comedy numbers and songs of the classical composer: Spanish Popular Song—Mens Je Venter—Jeg Elsker Deg—A Page's Road Song—Water Boy—Santa Lucia—Jamaican Song (Wata Come A Me Y'eye)—O Waly, Waly—Du, Du Liegst Mir in Herzen—Jabbin, Jabbin (Aboriginal Song)—Love Makes The World Go Round—Foggy, Foggy Dew—Edelweiss—Two Finnish Folk Songs (One Lovely Summer Evening and Far Away My Lover Has Gone)—Now Sleeps the Crimson Petal—The Plough Boy—Les Cloches—Die Nacht—Serenade.

Mr Tasman demonstrates his linguistic prowess by singing all songs in the original language. While this is no doubt very clever, it is a definite drawback as far as the listener is concerned, particularly as no texts with translation are provided. I believe the average listener likes to know what the song is about, however pleasant the tune. (H.A.T.).

BRIEFLY...

OVERTURE. The Hollywood Bowl Symphony Orchestra, conducted by Felix Slatkin. Encore, stereo SENC 9242 (or mono). Routine performances of four popular light classics: 1812 Overture (Tchaikovsky)—Light Cavalry Overture (Von Suppe)—William Tell Overture (Rossini)—Poet and Peasant Overture (Von Suppe). The orchestra plays with plenty of vigour, and their instrumental work is polished enough, but the performances are rather lacking in warmth. Sound quality and stereo are adequate. (H.A.T.).



**Graeme
Bell
Says...**

BRASS IMPACT. Command (Festival) stereo, SNDL-932-237.
Interest: Swinging brass.
Performance: Most impressive.
Quality: Full sound spectrum.
Stereo: Startling effect.

This brass choir consists of four flugel-horns, three trumpets, and four trombones. Added to this is one woodwind, three girl singers and a four-piece rhythm section plus two percussionists. The arranger is Jack Andrews and the whole thing is conducted by Warren Kime who was responsible for the idea. This is a most compelling album con-

HITS OF OUR TIME. Dot (Festival) stereo SZL-932,226. Music for dancing, but excellent for just listening as well. Polished playing by the Lawrence Welk Orchestra combined with interesting variations in arrangements make for pleasant listening indeed. The technical quality is excellent, and there is good stereo spread. Ten tracks (playing time 25 minutes), including Somewhere My Love—Georgy Girl—Strangers in the Night. (H.A.T.).

FLAMENCO FEVER. Sabicas. Ampar (Festival) stereo SML-932,228 (or mono). Strictly for the dedicated flamenco lover, this one, since it is severely classical flamenco. Master guitarist Sabicas proves again that he has mastered every aspect of the art in this recital which covers most of the main flamenco rhythms, including Alegrias, Soleares, Bulerias, Seguidilla, Fandango, etc. Eight tracks in all, playing time about 40 minutes. Excellent sound. (H.A.T.).

IN A LITTLE SPANISH TOWN. Living Brass, RCA Camden Stereo CAS-2114 and mono CAL-2114. Under the hand of Ray Martin, the boys in "Living Brass" have a musical night out in a Spanish town, ranging from brief, languid interludes to Mexican mariachi, snatches of American jazz, rock and roll, swing and calypso. Spanish Town—Tequila—Guantanamo—El Paso—La Bamba—Work Song—Cielito Lindo—Amor, Por Favor—El Mariachi Mexicano—Gotham City Swing Band. They enjoyed making it; you'll enjoy listening, when it fits your mood. Quality is O.K., stereo normal. Playing time, about 25 minutes total.

CINDERELLA. Camden (RCA) mono CAL-1085. This version of the classic children's tale has received the full American treatment, and is presented with a host of supporting characters, including talking animals and birds, and numerous songs. The best recommendation is that an eight-year-old, who was given this record for her own, has spent many happy hours playing it. Sound quality could be better but, for this type of record, this hardly matters. (H.A.T.).

taining a varied assortment of compositions ranging from Ellington's "Prelude to a Kiss" and "A Foggy Day" to "Eleanor Rigby" by the Beatles and Henry Mancini's "Theme From Mr Lue." Doc Severinsen takes the trumpet solos and Kime himself is soloist on flugelhorn but the most notable feature is the dimensional effect obtained by Command Records who seem to lead the field in reproducing pure musical sound.

★ ★ ★

MIRIAM MAKEBA IN CONCERT.

Reprise stereo RS6253.

Interest: Vocal folk artistry.
Performance: Real greatness.
Quality: Lifelike.
Stereo: O.K. by me.

The concert which produced this album took place this year at the new Philharmonic Hall in the Lincoln Centre for the Performing Arts, New York. The repertoire of this remarkable artist is drawn from all over the world thus precluding any possibility of monotony and she sings—as Leonard Feather says—in enough languages to fill her concerts with Berlitz students. Her range of ex-



Why specify Precision Windings' printed circuits?

As Australian industry moves into an electronic era new applications for printed circuits are developed every day . . . and design engineers expect their printed circuit suppliers to be versatile and flexible.

Constant research and scientific evolution of production techniques at Precision Windings' plant assures first grade manufacture; even relatively small quantities can be produced economically.

PW's photographic process does have many advantages . . . definition is crisp and clear, negatives are readily available for alterations, quality control during manufacture is precise. This is why more and more industrial organisations specify Precision Windings printed circuits.

Delivery is prompt and prices most competitive . . . and advanced technical advice is yours for the asking. Ask for a "no obligation" estimate!



52 Cambro Road, Clayton, Vic.

Tel. 544 7370



THE WHARFEDALE Linton

**The compact
speaker
system
that's taking
America
by storm!**


During the past twelve months Wharfedale speakers have been responsible for over 30% of the total speaker exports of the United Kingdom* . . . and the Linton has proved extremely popular in the United States where the market for compact speaker systems is most competitive.

Wharfedale *sound* is superior. Wharfedale's international success may be attributed to advanced design, constant research (backed by over 30 years' experience) and modern production technology. The Linton is the *most compact* speaker system made by Rank Wharfedale Ltd. — although it measures only 19" x 10" x 10", frequency response is 40-20,000 Hz. covering the complete musical spectrum.

This multiple-speaker system incorporates a new type of 8" bass reproducer and a 3" tweeter which has been developed from the well-known "Super 3"; both units employ substantial magnet assemblies which offer higher sensitivity. Transient performance of the Linton is quite remarkable — clarity and attack are particularly obvious. An entirely new surround — Flexiprene — and a long-throw voice coil assembly used in the bass unit results in most effective reproduction of the lower registers.

Make your choice from selected mahogany, teak and walnut veneers: finish is quite impeccable. See and hear this popular Wharfedale enclosure at all reputable audio stores.

*British Board of Trade statistics.



Australian National Distributors:

Simon Gray Pty. Ltd.

Head Office:
28 Elizabeth Street, Melbourne, Vic. Tel. 63 8101 *
Sydney Office:
22 Ridge Street, North Sydney, N.S.W. Tel. 92 3890

INTERSTATE REPRESENTATIVES:

S.A.: Eilco Sales Pty. Ltd., 7-9 Osmond Terrace, Norwood, S.A. Tel. 63 4844
Q'land: Sydney G. Hughes, 154-158 Arthur St., New Farm, Brisbane. Tel. 58 1014
W.A.: Athol M. Hill, 613-615 Wellington Street, Perth. Tel. 21 7861
Tas.: K. W. McCulloch Pty. Ltd., 109 York Street, Launceston. Tel. 2 5322
A.C.T.: Australian Physical Laboratories, P.O. Box 225, Canberra City.
Tel. 4 3010 (Mr. J. E. Howe)
N.T.: Pfitzner's Music House, Smith Street, Darwin. Tel. 3801

pression keeps broadening, but I still like her best when she remains the Xosa tribeswoman in numbers such as "Jolin-komo" which is a song of courage sung by the Xosa maidens to the warriors before they go into battle. She has changed her musical accompaniment which has now taken on a somewhat cosmopolitan character by using Severio de Olevorio, a guitarist from Rio de Janeiro, who also plays accordian. Completing the trio are Leo Fleming, a percussionist from Puerto Rico and Alex Layne, a New York bassist.

All my life I've tried to like singing but to this day can count only a handful of performers who really break through to me. Miriam Makeba is one. She is something very special — something you find only once in a generation. This to my mind makes any record by her an event, and this album is just that.

★ ★ ★

RAY NOBLE: RCA Vintage Series. mono. LPV-536.

Interest: Mid-thirties.

Performance: Elegant.

Quality: Expert remaster.

Here's yet another excellent offering from RCA's Vintage Series. The choice of material is always interesting and the general production including the first-class remastering is a feature of this most worthwhile series. One could not wish for more information from the sleeve—full data on personnel, exact dates and running times of all tracks and biographical notes by someone who knows what he's talking about.

Ray Noble, an Englishman, was a composer and bandleader who took his singer, Al Bowlly and drummer-manager Bill Harty to America in the mid-thirties and landed a job in the New York's swank Rainbow-Room with a band organised for hire by Glenn Miller. This top-notch array of musicians included such names as Bud Freeman, Charlie Spivak, Will Bradley, George Van Eps and Claude Thornhill; but the big attraction was the voice of Al Bowlly, who was tragically killed in the London blitz after he returned to England. Bowlly, a intense and warm person, had already highlighted many of the English recordings made under Noble's baton and the unique quality of the voice which won him fans all over the world can be heard to great advantage on this album—particularly on those lilting versions of "The Touch of Your Lips" and "Down By The River."

This is period music of the highest order and for those of you who like myself used to dwell on each of Ray Noble's 78s as they came out, the nostalgia alone is worth the re-listening.

★ ★ ★

MANCINI '67. Henry Mancini and his Orchestra. RCA stereo LSP3694.

Interest: Big band sound.

Performance: Brilliant.

Quality: As good as you'd wish.

Stereo: Used to great effect.

As an arranger, Henry Mancini is very much at home with a jazz-oriented big band. We know him well for his background scores for films, his best-selling records and his hit compositions such as "Moon River" but the big band is his first love, stemming from his days as a young pianist-arranger in the Tex Beneke orchestra.

Here, we have five trumpets, five trombones, four French horns, five woodwinds four rhythm and two percussion. Ex

Oscar Peterson, bassist, Roy Brown, works wonderfully with drummer Jack Sperling and together with Jimmy Rowles (piano) and Bob Bain (guitar) they form a most dependable and swinging rhythm section.

There is unusual treatment of Ray Noble's composition "Cherokee" where five piccolos are used. Peter Candoll takes the trumpet and Mancini himself plays the motor horn in Alpert's "Tijuana Taxi." There is some lovely piano from Jimmy Rowles in "Autumn Nocturne," the arrangement of which was inspired by an old record by Claude Thornhill. Other titles include Ellington's "Satin Doll" and Thelonious Monk's "Round Midnight" and "The House of the Rising Sun."

The studio music on this album give a wonderful interpretation of Mancini's scores and the dynamics are most exhilarating in the very "live" Dynagroove recording.

★ ★ ★

ANYTHING GOES. The Dave Brubeck quartet plays Cole Porter. C.B.S. stereo SBP223395.

Interest: Brubeck music.

Performance: Glowing.

Quality: Warm realism.

Stereo: Not important.

I shuddered before I heard this record. All the old Porter tunes of 30 years ago, churned out since by every band all over the world; sung by bad singers in worse pubs; used as opening and closing ballet sequences, and murdered by the pit orchestras playing them; used as chasers for juggling acts in nightclubs; and orchestrated by Jimmy Lally, the semi-pro dance bands benefactor.

But that's all forgotten now — or is it that the tune doesn't matter much anyway when Brubeck's playing it? For a start it's unusual for Dave Brubeck to make an album comprising anything but his own compositions, but if you like Brubeck and Desmond, I find that it really doesn't matter whether they are playing "Three Blind Mice," "I Get a Kick out of You" or one of Dave's own tunes. After all when it comes to this sort of jazz, the performer is the composer, regardless of what the title says.

You'll find all the well-known Porter tunes here — "Night and Day," "Just One of Those Things," "Your the Top," etc., and there is plenty of hard driving improvising on this album with the freedom one doesn't always encounter on some Brubeck tracks.

★ ★ ★

BING AND LOUIS. Encore — (E.M.I.) mono VO29233.

Interest: Bing and Louis vocals.

Performance: Balanced.

Quality: Good.

The mutual admiration society of Bing Crosby and Louis Armstrong made many appearances together, including films, TV shows and recordings and this album is a re-issue of 10 tracks made by the "Old Groaner" and "Satchmo" backed up by Billy May. It is mostly vocal but Louis plays some beautiful trumpet here and there — particularly on "Sugar," where he floats around with some glorious variations behind Bing's singing.

"Dardanella," "At the Jazz Band Ball" and "Muskrat Ramble" are some of the tracks, and the sympathy these two great stars have always had for one another and their sense of fun can be felt when listening to this happy but otherwise uneventful album.

SALE OF SURPLUS EQUIPMENT

**MUST BE SOLD—INSPECT NOW
BEST OFFER!**

- ★ A.W.A. Industrial TV Eye. Type HC-1 M1-36250.
- ★ Philips H.F. Oscillator GM2893.
- ★ Philips Square Wave Generator GM2324.
- ★ Philips Oscilloscope GM5650.
- ★ Philips Pattern Generator GM2891.
- ★ Philips V.T.V. meter GM7635.
- ★ Philips Volt meter (G.P.) GM6009.
- ★ Palec Tube tester model ET 4a.
- ★ S.T.C. Heavy duty Volt Amp meter B.S.S. Spec. 171/1936.
- ★ Smiths Electrical Timer B/0CU/2500/ACU2.

Inspect during business hours

H. G. PALMERS WAREHOUSE

159 ELDRIDGE ROAD

BANKSTOWN, N.S.W.

Telephone 709-2716

ALWAYS RELY ON R.D.S.

SPECIALS for AUGUST

**R
D
S**

We now have in stock the following **FAIR-CHILD TRANSISTORS**

2N3565 - 2N3638

2N3642 - 2N3645

2N4360 - SE4010

VTVM COMPLETE

\$42.25 net

MULLARD MINI SPEAKER BOXES


\$11.75 net

Suppliers of all Radio and TV Components
Meter and Multimeters
H200 Multimeter **\$512.25 Net**
CT500 Multimeter **\$512.25 Net**


The Independent Wholesaler
RADIO DESPATCH SERVICE,
Radio and Electrical distributors,
869 GEORGE STREET, SYDNEY.
Cnr. George and Harris Streets.

Phone 211-0816, 211-0191


Open Saturday mornings.




PLAYMASTER 106
Stereo Amplifier with
in-built tuner.
Full kit . . . \$94.50



**PLAYMASTER UNIT
4 STEREO
AMPLIFIER**
R. TV and H., March
1962.
Full kit . . . \$74.50.



**PLAYMASTER III
WIDEBAND TUNER**
Electronics (Aust.),
Oct.-Nov., 1965.
Full kit . . . \$38



**PLAYMASTER 110
TAPE AMPLIFIER**
Electronics (Aust.),
March-April, 1965.

POPULAR KITS — TOP QUALITY — LOWEST PRICES

INSTRUMENTS.

- 1 5in Wide Range C.R.O.
- 2 * 3in F/C C.R.O.
- 3 3in C.R.O. (1966).
- 4 C.R.O. Electronic Sw.
- 5 C.R.O. Wide Band Preamp.
- 6 Standard Audio C.R.O.
- 7 Project Multimeter 20K/V.
- 8 Meterless Voltmeter.
- 9 Millivoltmeter (A.C.).
- 10 Trans Millivoltmeter (A.C.).
- 11 Noise-Distortion-Millivoltmeter.
- 12 VTVM.
- 13 1966 — VTVM.
- 14 1969 Audio OSC.
- 15 1962 Audio GEN.
- 16 6-Band OSC. RF and AF.
- 17 Trans Service OSC.
- 18 STD. Audio OSC.
- 19 Trans Audio OSC.
- 20 D/R A/F Meter.
- 21 Simple Signal Injector.
- 22 Trans Signal Tracer.
- 23 Trans Wave Meter.
- 24 G.D.O. Adaptor.
- 25 Wide Range G.D.O.
- 26 1966 Basic Test OSC.
- 27 Square Wave GEN.
- 28 XTAL Locked STD.
- 29 Electronic Tuning STD.
- 30 Pattern GEN.
- 31 Trans Pattern GEN.
- 32 5.5 and 36 MHZ Sweep GEN.
- 33 Sweep and Marked GEN.
- 34 Silicon Diode Sweep GEN.
- 35 Silicon Diode Noise GEN.
- 36 R.C. Bridge.
- 37 1966 R.C. Bridge.
- 38 Geiger Counter.
- 39 Direct Reading Impedance Meter.
- 40 Simple Proximity Relay Alarm.
- 41 Electronic Anemometer.
- 42 Light Beam Relay Alarm.
- 43 Electronic Stethoscope.
- 44 Valve and Transistor Tester.

- 45 Resonance Meter.
- 46 Moisture Alarm.
- 47 Trans Alarm.
- 48 Flasher Unit.
- 49 Photo Timer.
- 50 Pipe and Wiring Locator.
- 51 S.W.R. Indicator.
- 52 Electronic Pistol Range.
- BATTERY CHARGERS.**
- 53 Universal Battery Charger.
- 54 Battery Charger—1 AMP.

REGULATED POWER SUPPLIES.

- 55 Trans REG. 9v P/Sup.
- 56 Trans Fully Protected.
- 57 1966 H.T. REG. P/Sup.

VOLTAGE/CURRENT CONTROL UNITS.

- 58 Model Train Control Unit.
- 59 Vari-Watt Power Controller.
- 60 Vari-Tach Motor Speed Control.
- 61 2KW — Automatic Light Dimmer.
- 62 4KW — Automatic Light Dimmer.

TACHOMETER.

- 63 6 or 12 Volt Kit.
- 64 6 or 12 Volt Mullard.
- 65 6 or 12 Volt Tach and Dwell Angle.
- 66 Tach and Dwell Angle Unit for Service Stations.

TRANSISTOR IGNITION.

- 67 6 or 12 Volt (RO-FO).
- 68 6 or 12 Volt Ign. (TX type).
- 69 Automotive V/Meter.

DC-DC CONVERTER.

- 70 DC-DC 60 W.
- 71 DC-DC 40 W. 12V IN.
- 72 DC-DC 70 W. 12V IN.
- 73 DC-DC 100 W. 12V IN.
- 74 DC-DC 140 W. 24V IN.
- 75 DC-DC 225 W. 24V IN.

HIGH FIDELITY AMPLIFIERS. MONO UNITS.

- 76 HI-FI 3.
- 77 Mullard 3-3.

- 78 Mullard 5-10.
- 79 Mullard 2-20.
- 80 * Wireless World 20-20. 20w. (Trans.).

STEREO UNITS.

- 81 Mullard 3-3.
- 82 Mullard 5-5 (Trans.).
- 83 Mullard 10-10 (Trans.).
- 84 Mullard 10-10.
- 85 * Wireless World 20-20.
- 86 Playmaster Unit 3.
- 87 Playmaster Unit 9.
- 88 Playmaster Twin 10.
- 89 Playmaster 101.
- 90 Playmaster 105 (Trans.).
- 91 Playmaster 113 (Trans.).
- 91A Playmaster 115 (Trans.).

P.A. and GUITAR. AMPLIFIERS.

- 92 10 Watt Stand. or Guitar.
- 93 25 Watt Standard.
- 94 35 Watt Standard.
- 95 100 Watt P.A.
- 96 25 Watt Guitar.
- 97 35 Watt Guitar.
- 98 50 Watt Guitar.
- 99 20 Watt Golden Series.
- 100 Playmaster 102 Guitar.
- 101 Playmaster 103 Guitar.

CONTROL UNITS AND PREAMPS.

- 102 Playmaster No. 9.
- 103 Playmaster No. 10.
- 104 Playmaster No. 104.
- 105 Playmaster No. 111.
- 106 Playmaster No. 112.
- 107 Philips M'Watt Unit.
- 108 Mullard 2V. Unit.
- 109 Mullard 3V. Unit.
- 110 Mullard Preamp and W/B Tuner.
- 111 Transistor Mono Preamp.
- 112 Transistor Stereo Preamp.
- 113 Sil/Trans. Mono Preamp.
- 114 F.E.T./Trans. Mono Preamp.
- 115 F.E.T./Trans. Stereo and Preamp.
- 116 DYN MIC. PREAMP.

117 4-CHAN. Audio Mixer. TUNERS

- 118 P'master Unit Style.
- 119 P'master 114.
- 120 Mullard Wide Band Tuner and Preamp.
- 121 Philips M'watt Hi-Quality Tuner.

RECEIVERS.

- 122 Fremodyne 4.
- 123 Communications RX.
- 124 Deltahet RX.
- 125 1965 Communications RX
- 126 Amateur Band RX.
- 127 3-Band D/Change S/Het.
- 128 * 1967 Interceptor 5.
- 129 ALT. T'sistor Car Radio.
- 130 Transporta 7 (RF).
- 131 Little General 1961.
- 132 3-Band 8 Transistor.
- 133 3-Band 3- (AC).
- 134 Interstate 5 (AC).
- 135 All Wave T'sistor 3.

TRANSMITTERS.

- 136 144 MHZ Linear Final (50w).
- 137 144 MHZ TX (20w).
- 138 144 MHZ TX (75w).
- 139 144 MHZ TX (18w).
- 140 144 MHZ S.S.B. TX.
- 141 3-Band AM. TX.
- 142 Basic 3-Band TX.
- 143 5-Band DBS TX.
- 144 S.S.B. T.

V.F.O. UNITS

- 145 Remote V.F.O.
- 146 769 HF and VHF.
- 147 All Transistor.

MODULATORS.

- 148 Modulator 50w.
- 149 MOD-PA and P/Supply Unit.

CONVERTERS—RECEIVER.

- 150 Short Wave Unit.
- 151 2-Band S/Wave Unit.
- 152 3-Band S/Wave Unit.
- 153 Basic S/Wave Unit.

LARGE STOCKS OF—SPEAKERS, TRANSFORMERS, RECORD PLAYERS, TAPE DECKS, VALVES, DIODES, TRANSISTORS, MICROPHONES, INSTRUMENT CASES and all other items—write for your price list

ELECTRONIC DEVELOPMENTS PTY. LTD.

Phones 63-3596
63-5973

232 FLINDERS LANE
MELBOURNE . . . VICTORIA

Phones 63-3596
63-5973

**K
I
T
S**


Public Address Units — Geiger Counters — Metal Locators — Decade Boxes — Mixers — Battery Chargers — Oscillators — Bridges — Parts Supplied for Projects in Electronics (Aust.), Wireless World, Practical Wireless, Electronics World, Electronics Illustrated, Practical Electronics, etc.

**K
I
T
S**

MULLARD STEREO 3-3

Full kit \$54.50.

(As per Mullard leaflet).



1966 VTVM KIT.
ELECTRONICS (Aust.), Feb., 1966.

BATTERY CHARGER 1A
ELECTRONICS (Aust.), Feb., 1966




PLAYMASTER 102 and 103
GUITAR AMP.

R. TV and H., Oct. }
Nov. } 1962
Dec. }
Jan. 1963

3-BAND SHORT-WAVE CONVERTER
ELECTRONICS (Aust.), May, 1966.

REGULATED POWER SUPPLY
190-270V D.C. at 40 mA.
ELECTRONICS (Aust.), June, 1966.



R/C BRIDGE

All-transistor
Electronics (Aust.)
May, 1966.

PUBLIC ADDRESS and
GUITAR AMPLIFIERS

10, 25, 50 and 100 watt
units




3-BAND DOUBLE-CHANGE RECEIVER
ELECTRONICS (Aust.), April, 1966.

1966 3in CRO
ELECTRONICS (Aust.), May, 1966.

5 BAND DSB TX

Electronics (Aust.),
Nov., 1965.




FOUR-CHANNEL AUDIO MIXER
ELECTRONICS (Aust.), Feb., 1966.


3-BAND 3-RECEIVER
ELECTRONICS (Aust.), Nov., 1966.

TRANSISTOR MILLIVOLT
METER

Electronics (Aust.),
R. TV and H., Jan., 1965.



Excellent frequency
response. Low distortion
figure. High input
sensitivity. All
controls self-contained.
10 watts per
channel.



*Enjoy your
leisure time
and build*

MINIWATT TWIN 10 STEREO — COMPLETE KIT \$99.50

"GOLDEN SERIES"
20 WATT GUITAR
AMPLIFIER
(with Vibrato)

MULLARD 3-3
STEREO
AMPLIFIER

MULLARD 10-10
STEREO
AMPLIFIER

50 & 144 MC
CONVERTER
KITS

PLAYMASTER
108
STEREOGRAM

PLAYMASTER 115 STEREO
TRANSISTOR KIT
PLAYMASTER 103
GUITAR AMPLIFIER WITH REVERB AND VIBRATO
Write for particulars

HI-FI 3
MONAURAL
AMPLIFIER

ELECTRONIC DEVELOPMENTS PTY. LTD.

Phones 63-3596
63-5973

232 FLINDERS LANE
MELBOURNE VICTORIA

Phones 63-3596
63-5973

it's
no secret
now



golden is silence

only I.R.C. volume controls have the Exclusive Gold plated collector ring, for a quiet life . . .
plus . . .

☐ Pressure Balanced Alloy Contactor

THEY FEEL RIGHT!

☐ Multi-flow precision element


THEY SOUND RIGHT!

☐ Piece part perfection

THEY'RE PRECISELY RIGHT!

☐ Stereo matching for the connoisseur

THE VERY BEST THEY SAY!



Coupon: for complete technical information on the I.R.C.

☐ CTS-45 controls ☐ CTS 200 controls ☐ 2W potentiometer ☐ presets.

NAME _____

ADDRESS _____

IRC67/VC

Take advantage of IRC's superior quality.
Choose from the most complete range of
carbon and wire wound pots and presets.



Manufactured in Australia under licence to CTS Corporation, Elkhart. Indiana U.S.A.

International Resistance Co. (A/sia) Pty. Ltd.

a subsidiary of International Resistance Holdings Limited.

THE CRESCENT, KINGSGROVE. N.S.W.

PHONE 50-0111



DEPEND ON IRC COMPONENTS—THEY ARE MADE FOR YOU

TRADE REVIEWS AND RELEASES

EMPIRE 888SE PICKUP CARTRIDGE

Messrs Recorded Music, of 23 Collins St, Melbourne, have submitted for review the latest in the Empire line of magnetic cartridges, the 888SE. Using a bi-radial diamond stylus, it lays claim to extremely wide frequency response, very high compliance and low distortion.

Through the years, Empire have offered a wide range of magnetic cartridges, for the most part representing a progressive development of the one basic theme — a very light stylus assembly integral with a moving cone in a multi-magnet assembly.

The model 888SE, distinguished by a bright blue plastic "nose," which carries the stylus assembly, is credited by the manufacturers with the widest frequency response. Actual figures quoted in their sales literature are 6-32000Hz, although this is not accompanied by any definition of the relevant dB limits.

The compliance figures quoted are also the most ambitious in the Empire range, being a very considerable 25×10^{-6} cm/dyne. This, combined with a low claimed (but unstated) figure of effective stylus tip mass, and a 15-degree tracking angle, holds promise of an excellent "trackability" characteristic—the ability of the stylus and cartridge to track deeply modulated grooves without displacement or serious distortion.

Of particular interest are the dimensions of the bi-radial "elliptical" stylus: A minimum radius of 0.3mil and a maximum of 0.7.

While there is sound reasoning behind the idea of a bi-radial or elliptical stylus, the actual dimensions have to be chosen in the face of certain compromises.

A large major dimension (e.g. 0.9mil in the case of the earlier Empire 888E cartridge) is an advantage in tracking grooves which are, by design or accident, wider and more extensively radiused than normal. However, the large dimension is a liability with grooves which, with modulation, become unduly narrow between the shoulders. The need for alignment becomes more critical also, involving initial assembly, mounting of stylus and cartridge relative to the head shell, and the tracking of the arm as a whole.

A small minor radius has a theoretical advantage in resolving short wavelengths (i.e. high frequencies) engraved in the groove walls. However, in terms of mass per unit area of contact, the loading would be the same as for a normal conical stylus of radius equal to the minor radius. Obviously, the rate of stylus wear must be greater than with a conical stylus of radius 0.6 or 0.7mil, unless a proportionate reduction can be made in playing weight.

In the new Empire 888SE, the radii are respectively 0.7 and 0.3, representing what is probably the best all-round compromise for the major dimension, and a minor dimension which is probably more practical than the 0.2mil figure featured in the 888PE.

Tested in an SME arm and lightweight shell, the 888SE submitted for our review yielded a frequency response which was within about plus 0.5 and minus 1.7dB over the range 40 to 10,000Hz. This was less flat than reported by "Gramophone" in their review of the same type of cartridge but it was somewhat smoother than reported by "Hi-Fi Stereo Review," whose curve may have been boosted slightly in the bass region by an arm resonance effect.

However, whereas both journals reported a treble resonance of about 3dB at 15-16KHz, the peak in our case appeared to be nearer 12KHz. This was for a playing



weight of 2gm; at 1.5gm the peak was not so apparent but it is likely that this was due to less efficient groove/stylus coupling.

At all test frequencies, waveform on a CRO remained consistently good and cross-talk between channels was commendably low. Though the makers claim a stereo separation of better than 30dB, figures of this order are actually quite difficult to measure in the presence of any kind of motor or building rumble, etc., and most reviewers are happy enough to find figures of 20dB or better over most of the range. On this score, the 888SE leaves no doubts.

Transient response on square wave tracks was good and the cartridge coped well with heavily modulated grooves, although a couple of the more fiendish lateral tracks on CBS STR-110 proved too much for it at normal playing weights.

Overall, our impression was that 1.5gm would be a practical average playing weight. There would undoubtedly be plenty of recordings which the cartridge, along with others, would handle at a lesser weight but, unless one is prepared to make frequent adjustment, it is usually necessary to settle

for a figure that will cope with most, if not all recordings.

Signal output is about average for magnetic cartridges and should present no problems with connection to magnetic pickup preamps, having an input impedance of about 47,000 ohms.

No trouble was encountered with hum pickup and it would appear that integral shielding is sufficient to cope with the kind of hum fields that are likely to be found adjacent to typical playing decks.

No significant magnetic leakage is apparent from the cartridge itself and it may be used with ferrous or non-ferrous turntables, as desired.

Finally, how does it sound?


Exactly as one would expect a cartridge of this quality to do! Reproduction is smooth and clean and the cartridge copes well with heavily modulated passages. In fact, over the past couple of years, we have given the earlier 888P a pretty solid workout and there is every reason to expect that this most recent addition to the range will give an even better account of itself. (W.N.W.).

Solartron in Australia

SOLARTRON AUSTRALIA has been formed, with headquarters at 112 High Street, Kew, Victoria, as part of the Solartron Electronics Group of U.K. They will market in Australia the Solartron range of instruments, which include oscilloscopes, digital instruments, general electronics instruments, dynamic analysis instruments, transducers, data logging equipment and analogue computers. The Solartron Group is part of the large international Schlumberger Company, and Solartron Australia will also market the products of a number of other Schlumberger subsidiary companies.

These include G.P. digital computers, high speed data logging, telemetry, photo-multipliers, and rotary encoders from E.M.R. of U.S.A.; digital instruments, counters, flow metering equipment, transducers, non destructive materials testing equipment and data logging from Rochar, of France; precision frequency measuring and recording equipment from precision signal generators, synthesizers, radar and communication system test and evaluation systems from Schlumberger GMBH of Germany; data tape recorders, digital magnetic tape systems, from Tolana of France.

MODEL C.P.4



NEW!

Polycarbonate Clear Thermoplastic METER HOUSING

... is Tougher—more Heat Resistant
and practically Indestructible!

- Can be supplied for all Moving Coil and Moving Iron ranges and functions.
- The Moving Coil version is normally equipped with Taut Band Suspension and is virtually indestructible (tests included being dropped 25ft. to a concrete path, as well as the usual controlled bump and vibration tests).
- Available with ultra-modern rear-of-panel mounting excutcheon as an optional extra.

For further details contact

PATON ELECTRICAL PTY. LTD.

90 Victoria Street, Ashfield, N.S.W. 71-0381 (6 lines)

PETER SHALLEY

95 YORK STREET,
SYDNEY, N.S.W.

ELECTRONICS PTY. LTD. JUST BEHIND NOCK AND KIRBY

Telephone: 29-3767

FOR COMMUNICATIONS



Contact MK-1

- 14 TRANSISTORS
- LONGER AERIAL
- MICROPHONE SOCKET
- EXT. 12v SOCKET
- GREATER RANGE
- NEW CIRCUITRY
- BATTERY METER
- APPROVED FOR USE BY BUSHFIRE FIGHTING AUTHORITIES

STILL ONLY
\$116 each


Tokai TC 11

- 11 TRANSISTORS
- ALL METAL
- COW HIDE CASE
- EAR PIECE
- 9v EXT. SOCKET
- 100 MW
- SQUELCH
- SUPERB CLARITY

\$49.75 each

**Also Tokai TC 9
and 911 without
squelch.**

\$44.75 each



S.S.B.

For Army, Air Force, Gov. Departments, Flying Doctor, Shipping, Oil Fields, Research, etc. We will be offering the most modern range of S.S.B. equipment in the world.

From 10 watts to 2½ megawatts. Frequency Synthesizers. Complete systems including air-conditioned shelters available.

This equipment is being used by U.S. Armed Forces and the Forces of 14 other countries. We regret at this stage details can only be supplied to industrial and Government users.

YOUR SUPPLIER OF
RADIO, TV AND
ELECTRONIC
EQUIPMENT SUPPLIES...

sarlon

HI-FI GRILLE FABRICS

*Follow the lead of Australia's Leading
TV & Stereogram Manufacturers*

**USE SARLON the only grille fabric
scientifically woven to ensure
PERFECT SOUND REPRODUCTION AT
ALL FREQUENCIES**



★ In easy-to-apply, ready-cut packs



See the new
glamorous range
in a variety of
patterns & textures

SARLON INDUSTRIES PTY. LTD.

47 McEvoy Street, Waterloo, N.S.W.

UA70—A NEW AUTOMATIC/MANUAL TURNTABLE FROM B.S.R.

A newcomer to the audio field is the B.S.R. UA70 automatic/manual turntable which offers features not previously available with units in its price range.

Those setting up an audio system on a limited budget will appreciate the features of this new turntable from the B.S.R. company, since it represents a reasonable compromise between price on the one hand and performance on the other. The UA70 is pleasingly styled in the popular satin black and brushed aluminium finish. The 11in diameter pressed steel platter is basically satin black, and the black rubber mat has inlaid brushed aluminium rings. Accessories supplied as standard are interchangeable spindles for automatic or manual operation, four plastic mounting feet and a full-size paper template for making a mounting base-board.

The unit has all the usual facilities of the automatic turntable: changing mechanism with capacity up to eight records; four speeds (78, 45, 33-1/3 and 16-2/3 rpm); automatic cycling and shut off. However, the unit has a number of features not usually found in lower priced turntables. It has a low mass tubular metal arm with coarse and fine counterweight adjustment for setting static balance, and a dial type adjustment for setting playing weight; a "cueing lever" for raising and lowering the arm, which allows manual operation without the risk of damage to stylus or disc; and an arm lock which automatically clamps the arm to its resting column when the operating lever is in the OFF position.

Horizontal ball bearing pivots are fitted to the arm bearings to keep arm friction to a low order, although our tests indicated that friction is still rather higher than that of the separate arms sold for use with transcription units. The normal type of four-pole motor is used, suspended on butyl rubber mountings to minimise rumble. Drive is transmitted to the turntable rim by a rubber idler wheel which is automatically disengaged when the unit is stopped, thus preventing the formation of "flats."

There is no provision for mixed operation for discs of different sizes, and the user selects the playing diameter by means of a lever. Playing speed is selected in the same manner. The other operating control has OFF, START and REJECT positions.

Although designed as an automatic changer, the UA70 can be used as a manual unit, and is supplied with a separate centre spindle for this purpose. The cueing lever is, no doubt, also intended primarily for the person wishing to use the unit manually.

The arm has a removable headshell (rather difficult to remove and replace, incidentally, because of the inconveniently positioned fixing screw) and this is fitted with a small plastic plate upon which the cartridge is mounted by standard 1/4in centre holes. Unless otherwise specified, the unit is supplied with a ceramic cartridge (B.S.R. C1) and diamond stylus. For those requiring a higher standard of performance than can be obtained from the relatively inexpensive ceramic cartridge, the distributors recommend a magnetic cartridge such as the Pickering V15/AM2. If required, they can supply this cartridge already fitted.

We did at first have some reservations about the use of magnetic cartridges with this turntable for two main reasons: The arm sets down rather heavily, particularly at the 45rpm and 78rpm speeds and, even at 33-1/3 rpm, we felt the set-down was rather too fast for other than a "ruggedised" magnetic cartridge. Also, the arc of the arm carries it quite close to the plane of the motor, with the possibility of induced hum from the magnetic field.



We accordingly fitted a medium quality magnetic cartridge, and connected the turntable to a wide-range amplifier for music listening tests. Under these conditions there was no noticeable hum, neither was there any detectable rumble or distortion from wow and flutter. We do, however, recommend that those using a normal magnetic cartridge should make sparing use of the automatic changer facility, for preference operating the unit manually by means of the cueing lever.

As a matter of interest, we point out that at least one prominent supplier of audio equipment in the U.S.A. supplies a complete system using this turntable fitted with a magnetic cartridge. (The UA70 is known in the U.S.A. as the B.S.R./Macdonald.)

Our tests also indicated that about 24 grams playing weight is required for satisfactory operation with the type of medium quality magnetic cartridge suggested by the distributors. On the other hand, all of 5 grams is normally necessary for the ceramic. These results were obtained with discs having a reasonable amount of modulation, and it may be necessary to go higher for heavily modulated discs.

The turntable platter showed slight warping, but not more than is common with the pressed steel type of construction and, in any case, not sufficient to affect operation. As already mentioned, the automatic mechanism sets down rather heavily, and in our opinion too heavily for continuous operation with a non-rugged magnetic cartridge. Even with the ceramic cartridge, set up for a playing weight of five grammes, some bouncing was noticeable at the 45rpm speed, and more still at 78rpm. The cueing lever is situated at the usual rather inconvenient place at the base of the arm spindle. On the sample unit, the lever did not return to the rest position itself after release, but tended to support the arm, thus effectively reducing the playing weight and impeding normal tracking movement. The lever had to be firmly pushed down to ensure correct operation.

To summarise, this is not the turntable for the person seeking the ultimate in high fidelity but, in the context of ceramic cartridges and matching quality amplifiers and speaker systems, should provide excellent service. We found it to perform quite satisfactorily with a magnetic cartridge subject to the safeguards mentioned. It fits

the gap between the low-priced turntables, as fitted to commercial radiograms and the expensive transcription units and, as such, should find a ready market among that large body of buyers who want something better than average but cannot afford the best.

Goldring Engineering, who are the Australian distributors of the UA70, advise that the retail price of the turntable alone, without cartridge, is \$43.75. Fitted with the B.S.R. C1 ceramic cartridge and diamond stylus, the price is \$47. Goldring recommend the Pickering V15/AM2 for those requiring a magnetic cartridge, and this

can be fitted for an extra \$26. All these prices are inclusive of sales tax. The UA70 should be available from the usual retail and trade channels, or direct from the distributors at 443 Kent Street, Sydney.

For those intending to make up a unit amplifier system in conjunction with the UA70, Goldring are making available a special base, in teak finish, fitted with a Plexiglass top, with suitable cutout for the unit. We have not yet seen this base, but we understand there will be room under the turntable for a small amplifier. The base, with cover, will sell for \$30 retail. (H.A.T.)

NEW AMAZING "RAPAR" ANTISTATIC RECORD CLEANER

at the
ECONOMY
PRICE
\$1.95

"RAPAR" Anti-static record cleaner with cleaning cloth will clean and preserve your precious records.

OBTAINABLE
AT ALL
RECORD BARS
TRADE ENQ.,

RADIO PARTS

562 Spencer Street, West Melbourne.
P.O. Box 124, North Melbourne.
Phone 30-1251.

THOUGHT POWER

Acclaimed "A PROVEN FACT" by scientists, now makes possible the building of a peaceful, secure, abundant happy life through simple "Thoughtcasting" methods. Read pages of letter-extracts in free, 18-page book that explains how problems can be solved.

Send 13c stamp to:—
Sect. EA, 44 Victory Lane, Leura, N.S.W.



AUSTRALIA'S LARGEST Radio, Television and Hobbies SPECIALISTS


307 ELIZABETH STREET, MELBOURNE - 60-1442



We have everything for the Radio Hobbyist



MODEL 200H 20,000 Ohms per Volt DC 10,000 Ohms per Volt AC.



Specifications:

DC Volt: 0-5,
0-25, 0-50,
0-250, 0-500,
0-2,500.

AC Volt: 0-10,
0-50, 0-100,
0-500, 0-1,000

DC Current:
0-50. Micro-
amps res.
0-25, 0-250
Milliamperes.

R e s i s t a n c e:
0-60K Ohms,
0-6 Meg-
ohms.

Capacity: 0-01-
0.3mfd (at
AC 5 volt
0.0001-01mfd
at AC 250
Volt).

Decibel: minus 20db plus 22db.
Output Range: 0-10, 0-50, 0-100, 0-500, 0-1,000
Battery used: UM-3-1, 1 piece.
Dimensions: 3 1/4in x 4 1/4in x 1 1/4in.
Complete with internal battery, testing leads
and prods.

PRICE \$11.95

Including Sales Tax
Plus Postage, 35c.

Capacitor Substitution Box, 1,000
VW \$5.50
Resistor Substitution Box, 1 Watt.
Plus Post, 20c. \$5.00

TRANSISTOR AERIALS

4in extends to 27in \$1.60
5in extends to 39in \$1.70
6in extends to 43in \$1.40
6in extends to 32in \$1.00
6in extends to 28in \$1.20
7in extends to 39in \$1.60
9in extends to 39in \$1.40
10in extends to 39in 95c

Plus Postage, 15c.

CRYSTAL SET BUILDERS

Coils 60c
Diodes 35c
Headphones \$2.50
Tuning Conds \$1.85
Terms Ea. 12c

Plus Postage.

TAPE RECORDER ACCESSORIES

2 1/2in spools 30c
3in spools 35c
5in spools 40c
7in spools 50c
2 1/2in x 100ft tape 45c
2 1/2in x 300ft tape \$1.20
3 in x 600ft tape \$2.25
5 1/2in x 850ft LP Tape \$1.50
5 1/2in x 1,200ft tape \$2.50
7in x 1,800ft tape \$3.95
5in Plastic Tape, boxes 60c
7in Plastic Tape, boxes 90c

Plus Postage.

KEW METERS

MR-2P 0-1 m/A \$3.65
MR-2P 0-50 u/A \$5.80
MR-2P 0-100 u/A \$5.30
MR-2P 0-500 u/A \$5.50
VR-2P V.U. Meter \$5.80
MR-2P Stereo Balance \$5.25
MR-2P 0-20v. D.C. \$4.00

All meters in white plastic case.

PIEZO PICK-UPS AND CARTRIDGES

PU-86 Pickup LP/78 T/O
Crystal cartridge. Length
204mm Ea. \$2.33

Y700 Cartridge. Mon LP/78 \$2.00

PU-86 Pick-up Ster-LP/78.
T/O Cartridge. Length
204mm Ea \$3.65

Y200 Cartridge. ST. LP/78 .. \$2.90

PU-54 Pick-up LP/45 only.
Length 1.25mm Ea. \$2.10

Y400 Cartridge. LP/45 \$1.20

Sapphire Replacement Styli
Each 30c

SUB MINIATURE

I.F. TRANS, 7 x 7mm

In sets of 3.

\$3.20 per set.

OSC. COILS, 7 x 7mm

To match I.F. Trans.

\$1.10 ea.

5K SUB-MIN POTS, w/switch. 65c.

CO-AX MIC. CABLE

Grey P.V.C. Cover.

15c yd \$14.50 100yds.

STANDARD THIN MIC. CABLE

Grey P.V.C. Cover.

10c yd, \$9.00 100 yds.

4c SHIELDED P/U FLEX

P.V.C. Covered, 25c per yd.

PIEZO MICROPHONE INSERTS

MC-3 Crystal. 50- 7K. 35 x 25 x 8 mm. -57DB. \$1.10 ea.
MC-7 Crystal, 100- 7K. 39 mm Round x 11 mm. -56 DB. . . 90c ea.
MC-8 Crystal, 50- 8K, 48 mm Round x 17 mm. -50 DB. . \$1.80 ea.
MC-9 Crystal 50- 8K. 25 mm Round x 9 mm. -68 DB. . \$1.80 ea.
MC-33 Crystal 50-10K, 33 mm Round x 9 mm. -60 DB. . \$1.10 ea.
MD-5 Dynamic, 100-15K, 33 mm. Round x 14 mm. -55 DB .. \$1.80 ea.

TRANSISTOR SET ACCESSORIES

Magnetic Earpiece with 3.5mm
Plug 75c
Crystal Earpiece with 2.5mm
Plug 75c
Crystal Earpiece with 3.5mm
Plug 75c
Jacks, 2.5 and 3.5mm 20c
3.5mm Plug and Cord ext. Jack
Pair 50c

Metal Co-axial Plugs and line
Sockets Pr 65c
"Din" and "Hirschmann," 2, 3, 4
and 5-pin Plugs, Chassis and
Line Sockets, carried ex stock
Prices on application.
P.M.G. type Plugs from 55c
P.M.G. type Jacks from 35c
P.M.G. Line Jacks from 55c

307 ELIZABETH STREET, MELBOURNE

PHONE 60-1442

RESLO PROFESSIONAL MICROPHONES FROM BRITISH MERCHANDISING

The type SR1 studio ribbon microphone pictured is representative of the comprehensive range of professional quality microphones manufactured in the U.K. by Reslosound Limited and distributed in Australia by British Merchandising.

Other models in the range include a broadcasting-quality miniature ribbon (type VRT), a semi-professional miniature ribbon (type RB), a cardioid ribbon (type CR2), a "lavalier" ribbon (type RL1) and a semi-professional pencil dynamic (type PD).

The model SR1 professional type ribbon was recently developed by Reslo for use by broadcasting authorities and professional recording studios. It features a larger magnet assembly and longer ribbon than usual for improved sensitivity, together with a minimum of internal protective screening in the interests of extended frequency response. Specifications of the unit are thus most impressive, with a 300ohm sensitivity of -73dB below 1V/dyne/cm² and a frequency response of 30-20,000Hz plus/minus 2dB. The nominal directional response characteristic is the usual "figure 8" pattern, although both the frequency and directional characteristics may be restricted for speech use by means of acoustic damping pads supplied with the instrument. Alternative output impedances are available, a suffix "M" signifying 250-300 ohms and an "L" signifying 30-50 ohms.

Size of the SR1 is quite small, the frame width being 1½in while the overall height of microphone and transformer base is 5.78in; head weight is 11oz (0.312Kg).

The case has a non-reflective satin bronze finish. The microphone is supplied complete with a matching Reslo mounting plug unit fitted with 18ft of sheathed screened and twisted cable, a set of fitting adapters, a polished and padded wooden storage case, acoustic damping pads and an instruction booklet giving an average response curve.

Connected in our laboratory to a high-quality amplifier and loudspeaker system, the performance of the sample SR1 sent for review gave strong support for the manufacturer's specifications. Response was extremely smooth and well balanced, and sensitivity was quite impressive while vibration sensitivity was low. (A full instrument check was not feasible as the performance of the microphone exceeds that of our acoustic testing facilities.)

Quoted price of the SR1 is \$110.40 plus 12½ p.c. sales-tax where applicable. For further information on Reslo microphones and the comprehensive range of accessories also available, inquiries should be directed to British Merchandising Pty. Ltd. at Shaw House, 49-51 York Street, Sydney. (J.R.)



one edge. This is quite inadequate and, in the sample unit, the bracket had already been distorted in transit to our office. In normal laboratory and service workshop use it is likely that the transformer would eventually come adrift and damage other components. A more secure method of mounting would be highly desirable.

Also questionable is the way in which the heat-sink extrusion plate is fastened to the case via four small "self-tapping" screws engaging into small Perspex blocks. From a servicing viewpoint this seems rather poor construction, since the hole in the plastic would probably strip all too easily.

Inside the case there are also a number of examples of "floating joints," despite the fact that there are a number of unused tags on the resistor panel used to support the minor components. Making better use of the tags would probably give a worthwhile improvement in ruggedness and reliability.


Price of the unit is quoted as \$84 plus 12½ p.c. tax where applicable, and the postal address of the manufacturer is P.O. Box-16, Balaclava, Victoria. (J.R.)

TRANSISTORISED FM RADIOTELEPHONE

What is believed to be the first fully transistorised VHF FM radiotelephone to be made in Australia is now being marketed by Telecommunication Company of Australia Pty. Ltd.

The unit is designed to meet Australian Post Office requirements for narrow band (30KHz) systems, but can be supplied for use in existing wide band (60KHz) systems. Models with output powers of 10W and 25W are available. The unit operates from a nominal 12V DC source, but optional extras enable operation from 24V or 32V DC sources. Units can be ordered for multi-channel operation (up to 6 channels) or converted later to provide this facility. Electronic muting is standard to all units.

A high order of reliability has been achieved in the design by the elimination of thermionic devices, and attention to reliability factors in the design of the equipment.



A high proportion of the solid state devices used are of the rugged silicon types. Other factors contributing to reliability are the conservative rating of components; the almost exclusive use of printed wiring cards; and the choice of an aluminium die-cast housing to make the set dust proof, insect proof and splash proof.

The unit is extremely compact—case dimensions excluding projections being 9-1/8 x 9 1/4 x 2 1/2in—and thus may be mounted under the vehicle dashboard without difficulty. Included with each unit is a flexible stainless steel whip aerial.

The following ancillary items are available for use with the unit. "Clearline" rejects messages from other systems sharing the channel allowing only the user's messages to be heard. Vehicle Selective Alarm enables the base station to attract an absent driver's attention by sounding an alarm or the horn. Selective Calling System provides the facility to individually call up to 120 vehicles.

Further information can be obtained from the head office at 113 Tapleys Hill Road, Hendon, South Australia, or from offices and agents throughout Australia.

VARIABLE LOW-VOLTAGE SUPPLY

SWE-CHECK INSTRUMENTS market the variable low-voltage regulated power supply shown, which is intended for general purpose operation and servicing of low-voltage equipment, and also for battery charging. Called the "Zen-Tra-Stab," the unit can supply up to 15VDC variable in two overlapping ranges, at up to 40 watts load and with a ripple of less than 1 p.c. The output is stabilised against mains voltage variations of up to about 15 p.c. and is continuously monitored by a voltmeter and ammeter on the front panel. A thermal cut-out gives protection against sustained overload. The output is fully floating above earth.

The circuitry of the unit is along conventional lines, employing the cascaded emitter-follower principle, and under test in

our laboratory it performed substantially as claimed. On this score we had no misgivings.

The case in which the instrument is housed is of steel with a covering of grey, bonded plastic cloth. The panel is black, with lettering in natural aluminium, as shown, and with red pickout for the name and terminal connectors.

However, internal inspection of the unit supplied for review — which may have been a prototype — suggested a need to improve the mechanical construction if the unit is to withstand any kind of rough handling.

Particularly disappointing was the way in which the heavy mains transformer is fastened to the case by only a light sheet-metal bracket and two small screws along



LOTRING

BRINGS YOU THE INCOMPARABLE PICO 30TS



The 30TS is a precision soldering tool. It has been developed for the modern production line and technician, and proves to be a universal tool for the entire radio, telephony and electronics industry.

This is due to its optimum thermal and physical characteristics.

Here are some of these:— Watts: 30; Weight: 2½ ozs.; Max. tip temp.: 410°C; Heating time: 1.8 mins.

Write or call for illustrated leaflet.

LOTRING AGENCIES

ADELAIDE
C. J. HUMPHRIES
248 Gillies Street

MELBOURNE
CORNELIUS & BALLANTYNE PTY. LTD.
42-44 Little Lark Street

BRISBANE
NEIL ROBINSON AGENCIES
838 Oxley Road, Corinda


PERTH
O. F. GAMBLE PTY. LTD.
888 Hay Street

Manufactured under licence by

MATSON

AUTOMOTIVE INDUSTRIES Pty. Ltd.
Beresford Avenue, Greenacre, N.S.W.

LOOK AT THESE... SPECIAL OFFERS FOR AUGUST — UNBEATABLE VALUE



ARMSTRONG 221.
Integrated Stereo Amplifier.

<p>1 Empire 888P Cartridge P34 Turntable, Schaub Lorenz 20 watts per channel stereo amplifier, 2 Wharfedale Super 10in RSDD loud speakers. TOTAL PRICE \$420</p>	<p>2 Leak Stereo 30, integrated Amplifier 10 watt RMS per channel, Empire 888P cartridge, Dual 1009 turntable, 2 Goodmans 10in Twinaxiom loudspeakers Frequency response 40 — 18,000 cycles. TOTAL PRICE \$384</p>	<p>3 Star SA400 Leecraft 605L turntable or balance arm, Empire 808 cartridge, 2 Goodman 8in Thinaxle loudspeakers. TOTAL PRICE \$240</p>
<p>4 Pioneer 161 AM and AMTuners, 11 watt per channel, Dual 1010 turntable with B and O diamond magnetic cartridge, two 10in A and R loudspeakers. TOTAL PRICE \$270</p>	<p>5 Armstrong 221 Garrard Lab. 80 turntable, Empire 888 cartridge, 2 Jordan-Watts loudspeakers. TOTAL PRICE \$350</p>	<p>6 Armstrong 226 AM FM 10 Watts RMS per channel, frequency response 20-20,000 cycles, plus-minus 10B DB PE34 Hi-Fi Turntable, With Empire 888P cartridge two Jordan watts loudspeaker, TOTAL PRICE \$470</p>
<p>7 2 Empire Model 8000P Grenadier loudspeakers, Armstrong 221 Dual 1019 Hi-Fi turntable, Empire 888SE cartridge. TOTAL PRICE \$1,030</p>	<p>8 Harmon Kardon 210 stereo amplifier, 50 watt output, frequency response 8-25,000 cycles, plus-minus 10B, 2 Jordan Watts Modular loudspeakers, Empire Troubadour turntable, Empire arm, Model 980, Empire 888SE cartridge. TOTAL PRICE \$900</p>	<p>9 Schaub Lorenz Dirigent B/C S/W FM tuner amplifier, complete with Schaub Lorenz speaker system in beautifully designed cabinets, Dual 1009 SK turntable complete with Dual Diamond cartridge. TOTAL PRICE \$400</p>
<p>10 Pioneer 204B stereo tuner amplifier, 16 watt per channel, 2 Wharfedale 10in RSDD golden loudspeakers, Garrard SP25 turntable, Empire 808 cartridge. TOTAL PRICE \$304</p>	<p>11 Armstrong 127 AM FM tuner amplifier, PE72 Hi-Fi turntable complete with cartridge, Two R & A 10in Hi Fi loudspeakers. TOTAL PRICE \$250</p>	<p>12 Armstrong 222 amplifier, Garrard AT6 turntable, Decca Deram cartridge, 2 Wharfedale 8in Bronze speakers. TOTAL PRICE \$202 The same with Wharfedale Super 8in speakers or Goodmans 8in Twinaxlette speakers. TOTAL PRICE \$218</p>

World's finest tape recorders always in stock exclusive to R.M.S. Ampex Model 813, 1153, 1163, 2163, Telefunken—full range, Oki—Schaub Lorenz. Also available full range, Tantberg—full range, Siemens, Akai, etc.

We will care-pack and freight anywhere. If you require goods not listed above please write for prices. R.M.S. is famous for world's best quality. Our prices are indisputably the cheapest in Australia.

RECORDED MUSIC SALON

C. PINCZEWSKI

TRUE FIDELITY

WHOLESALE AND TRADE ENQUIRIES WELCOME

23 COLLINS STREET,
MELBOURNE
Telephone 63-6257

FAIRCHILD'S NEW LOW-COST LINEAR INTEGRATED CIRCUITS

Fairchild Australia Pty. Ltd. has announced availability of three new low-cost linear integrated circuits. The prices of these show a marked reduction on previously available types.

The three types so far made available in the low price range are the uA702C high gain wideband DC amplifier, priced at \$12 each; the uA710C high speed differential comparator, \$7.50 each; and the uA703C RF-IF amplifier, \$4.10 each. The usual substantial discounts apply for quantity purchases.

Brief technical data on these three types follow.

uA702C High-gain wideband DC amplifier. This is a complete DC amplifier constructed on a single silicon chip, using the Fairchild Planar epitaxial process. It is intended for use as an operational amplifier in miniaturised analogue computers, as a precision instrumentation amplifier, or in other applications requiring a feedback amplifier useful from DC to 30MHz.

ABSOLUTE MAXIMUM RATINGS


Max. total supply voltage between V + and V — terminals 21V
Peak output current 50mA
Maximum internal dissipation TO-5 200mW
Flat pack 150mW
Operating temperature range 0-70 deg. C
Differential input voltage plus or minus 5V
Input voltage plus or minus 1.5 to 6V

uA710C High-speed differential comparator. This is intended for applications requiring high accuracy and fast response times. It is constructed on a single silicon chip using the Fairchild Planar epitaxial process. It is useful as a variable threshold Schmidt trigger, a pulse height discriminator, a voltage comparator in high-speed A-D converters, a memory sense amplifier or a high-noise immunity line receiver. The output for the comparator is compatible with all integrated logic forms.

ABSOLUTE MAXIMUM VALUES

Positive supply voltage 14V
Negative supply voltage 7V
Peak output current 10mA
Differential input voltage plus or minus 5V
Input voltage plus or minus 7V
Internal power dissipation TO-5 300mW
Flat pack 200mW
Operating temperature range 0 to 70 deg. C

uA703C RF-IF amplifier. This device, constructed on a single silicon chip, is intended for use as a limiting or non-limiting device, harmonic mixer, or oscillator to 150MHz. The low internal feedback en-



sure a higher stability-limited gain than that available from conventional circuitry. The biasing network is included in the same package, thereby reducing the number of external components required, and increasing reliability and versatility of the device.

ABSOLUTE MAXIMUM RATINGS

Supply voltage 20V
Output collector voltage 24V
Voltage between input terminals plus or minus 5V
Internal power dissipation 200mW
Operating temperature range 0 to 70 deg. C

Further details and technical literature can be obtained by writing to Fairchild Australia Pty. Ltd., 420 Mt. Dandenong Road, Croydon, Victoria.

Philips Capacitors

Philips Miniwatt draw attention to their range of C281 capacitors, which should be of particular interest to manufacturers of custom built and high grade communication or other equipment where reliability is a major requirement.

The C281 is a metallised foil type capacitor, using both polycarbonate and polyester foils. Advantages of the metallised foil type capacitors are small physical size and self healing properties in the event of a breakdown. Further advantages are provided by the polyester and polycarbonate dielectrics, such as low temperature coefficient, very high resistance—normally in excess of 30,000 megohms—and high reliability.

These capacitors are made in a wide range of capacitances and voltage ratings. Currently available are 100V polycarbonate types ranging from .068uF to 5.6uF in preferred values, 250V polyester types ranging from .01uF to 2.2uF, and 400V polycarbonate types ranging from .01uF to 1.0uF.

Due to become available in the near future are 630V, 1000V and 1600V polycarbonate types ranging in value from .01uF in all cases to .47uF, .15uF, and .068uF respectively. Tolerances are 10 p.c. or 20 p.c. for all types.

Philips also draw attention to type C280, which is a lower cost version of the C281. The difference is mainly in the shape and finishing material, the capacitor being otherwise similar in performance to the C281.

Both capacitors are dearer than the conventional polyester capacitors of the same voltage and capacitance values, the C280 by about 15 p.c. and the C281 by between 30 and 35 p.c. However, the higher cost of either type is fully justified where the special qualities of these capacitors can be used to improve the performance of the equipment.

Further details of these capacitors may be obtained from the Miniwatt Electronics Division, Philips Electrical Pty. Ltd., 20 Herbert St, Artarmon, N.S.W.

TRADE RELEASES — IN BRIEF

ASTRONIC IMPORTS has stocks of a 4-port fail-safe coaxial transfer switch (model F7223), newly developed by Sage Laboratories, Inc. in the U.S.A. This will provide 1.2 VSWR (max.) with 0.2dB insertion loss (max.), and 50dB isolation (min.) from DC to 1.4MHz. Operation is remote (solenoid drive) with a switching time of 10mS (max.).

Also from Astronic Imports comes news of additions to the range of miniature microwave balanced mixers with replaceable diodes manufactured by Sage Laboratories, which has now been expanded to 16 models. The new line covers 1—12GHz in four bands. The new models have the following specifications: VSWR typical 1.5-1.7; minimum isolation 6dB; typical noise figure 9dB. Also available are various high-

performance coaxial electromechanical switches with special form-factors to meet virtually any packaging requirement. Inquiries to the head office at 622-626 Nicholson Street, North Fitzroy, Vic., or offices in other States.

AMALGAMATED WIRELESS (AUSTRALASIA) LTD. announces that the Engineering Products Division has moved to 422 Lane Cove Road, North Ryde, N.S.W. The postal address is P.O. Box 96, Ryde 2112. The new telephone number is 88-6666.


RACAL ELECTRONICS PTY. LTD. has pointed out that the Racal Universal Counter-Timer reviewed in the April, 1967 issue has a sensitivity of 100mV and not 100V as published.

ELECTRONIC INDUSTRIES LTD. recently announced that it had sold its 50 per cent investment in Anodeon Ltd., of Auckland, New Zealand, to EDAC (Electronic Development and Applications Co. Ltd.) of Wellington, for a cash consideration.

BROADWAY ELECTRONICS PTY. LTD. has announced the availability of a range of all-over labels which are suitable for the Playmaster 112, 115 and 117 Amplifiers. They can be obtained in the following styles and sizes:

- Silver-white with brown letters, 12 1/2 in x 4 1/2 in, \$2.80.
- Silver-white with brown letters, 11 1/2 in x 3 3/8 in, \$2.80.
- Gold with black letters, 11 1/2 in x 3 3/8 in, \$2.00.

Inquiries should be addressed to the company at E.S. & A. Bank Building, Corner Broadway and City Road, Sydney, N.S.W.



Heating Systems have produced etched labels for both the Model Train Controllers described in recent issues. (February and March, 1967). They are screen printed on 19 gauge aluminium and will add a professional touch to the hobbyist's work. Sloping front cases to fit these panels are also available. Further details, prices, etc., from Heating Systems Pty. Ltd., 24-32 O'Riordan St., Alexandria, N.S.W.

STOCK TRANSFORMERS for Popular Projects!

PUBLICATION	PROJECT	A & R TRANSFORMER TYPE
ELECT. AUST. AUG. 1967	60 Watt Guitar Amplifier	PT5893 OT2842
ELECT. AUST. JUNE. 1967	40 Watt Guitar Amplifier	PT5892, OT2843
ELECT. AUST. APR. 1967	Logic and Counting Demonstrator	PT2150 or 2 x PT5579
ELECT. AUST. APR. 1967	Optical and Magnetic Preamp for Sound Projectors	PT1992
ELECT. AUST. APR. 1967	All Silicone Playmaster Amplifier	PT6232, Z3252
ELECT. AUST. NOV. 1966	Stereo Public Address Amplifier	PT5891 Z3239 OT4005 (2 req'd)
ELECT. AUST. OCT. 1966	3 Band Receiver with Switched Coils	PT1992 Suitable Speaker Trans. from A & R Range.
MINIWATT DIGEST AUG./SEPT. 1966	Electronic Photo Cell Circuits	PT5991
OUTLOOK MAY-JUNE 1966	3 Watt Transistor Stereo Amp.	PT5990
ELECT. AUST. JUNE 1966	Regulated Power Supply	PT1940
ELECT. AUST. JUNE 1966	Basic Stereo Amplifier	PT1889, Z3040, K5/15 (2 Reg'd.)
ELEC. AUST. MAY 1966	A Battery Charger for your Car	PT5786
ELEC. AUST. MAY 1966	1966 R-C Bridge	PT2150
ELEC. AUST. MAY 1966	THREE Band Short Wave Converter	PT5890
ELEC. AUST. APRIL 1966	Twin 5 Watt Class A Transistor Stereo Amp.	Z3200 (2 req'd)
OUTLOOK JULY-AUG. 1965	Protected DC Supply	Z3212
OUTLOOK JAN.-FEB. 1966	3 Band Double Change Receiver	PT5755
ELEC. AUST. APRIL 1966	Playmaster 113 Stereo Power Amp.	PT2150
ELEC. AUST. APRIL 1966	A Four Channel Audio Mixer	PT2062
ELEC. AUST. FEB. 1966	Playmaster 112 Transistor Control Unit	PT5721
ELEC. AUST. FEB. 1966	The 1966 Vacuum Tube Voltmeter	PT TD19 (2 req'd)
ELEC. AUST. JUNE 1965	A Two Band Short Wave Converter	PT2150 (for AC Supply)
ELEC. AUST. DEC. 1965	A Simple Public Address Amp.	PT2150 (for AC Supply)
ELEC. AUST. OCT.-NOV. 1965	Playmaster Program Source	PT5890
ELEC. AUST. SEPT. 1964	A Powered Monitor for Radio Systems	PT5890
ELEC. AUST. AUG. 1964	A Practical Photographic Timer	OT E7/15
		PT1993
		PT5890

Available from all leading Stockists!

A & R TRANSFORMERS PTY. LTD. 42-46 Lexton Rd., Box Hill, Vic. (Box Hill P.O. Box 170) Phone 89 0238

Come to —


Convoy

FOR SOUND SATISFACTION

This month we offer you these superb systems:—

PEAK NIKKO TRM40 solid state quality amplifier 15 watts rms per channel less than 1 per cent distortion. Dual 1009 Turntable with Shure M55E magnetic cartridge and teak base. Pair Wharfedale Super 8 RS DD Speakers in teak enclosures.

Convoy Price—\$339.00





Fisher X-100A Amplifier 17 watts RMS per channel with best Fisher quality. Dual 1019 turntable with Shure magnetic cartridge and teak base. Pair Goodmans Twin Axiom 10 speakers in teak enclosures.

Convoy price . . . \$459

Star SA30 Amplifier 12 watts per channel less than 1 per cent distortion. Garrard AT60 player. Pair Wharfedale 8in bronze speakers in teak enclosures. Your choice of Deram Cartridge or our new low cost high quality magnetic type.

Convoy price . . . \$218



Quality sound at a price to suit your pocket.

We are at 449 Kent Street (just down from the Town Hall). Tel. 29-6475.

If you are planning your first Hi-Fi stereo system or thinking of upgrading your present equipment then don't hesitate to consult us first. At Convoy you are assured of a warm welcome and friendly, expert advice with first class after sales service.

We have one of the finest showrooms in Australia where you may choose from a very wide range of quality equipment. We can

supply all leading brand names such as— Sony, Fisher, Akai, Wharfedale, Trio, Goodman's, Dual, Leak, Elac, Quad, etc.

In addition we are able to offer you some exciting new brands at down to earth prices.

Don't forget to enquire about our good used and secondhand units. Always ask for a Convoy quotation. Mail enquiries welcome.

PLESSEY AUTOMATION has developed data transmission systems specially designed for use in commercial establishments where there is a low volume of information to be communicated. It can be operated in either the simplex or duplex mode, and other features claimed are clean tape output, reliability and low cost. Transmission of 18.2 characters per second may be over public telephone networks or over private wire circuits. The equipment can be switched to handle any five, six or seven channel code, or an eight channel code containing a parity bit. Further information is available from Plessey Automation, 13-17 Botany Street, Redfern, N.S.W. 2016.

RACAL ELECTRONICS PTY. LTD. has sent details of its new TRA 905 100W single-sideband transistored radio transmitter. This has been designed for use in radio telephone systems where high reliability and stability are required, and is capable of providing clear telephone-quality communications for remote parts of Australia and other areas where it is not practical to install land lines. The frequency stability is such that stable operation over periods of several months is possible without the need for adjustments. The transmitter is rated for full operation from -10 deg. C. to 50 deg. C. Weight is only 42lb.

The TRA 905 covers a frequency range from 2 to 12.5MHz, using lower sideband SSB telephony. The mode of operation is essentially simplex but different frequencies may be used for transmission and reception. Two channels of two frequency simplex or four channels of single frequency simplex operation are available. Channel switching may be performed at the front panel controls. Extended or remote control is available so that the transmitter can be situated away from the telephone and control unit. Further information can be obtained from the company at 75-77 Chandos Street, Crow's Nest, N.S.W.

AURIEMA (AUSTRALASIA) PTY. LTD. has established offices at 443 Kent Street, Sydney, N.S.W. It is a member of the Ad. Auriema international group and represents the following American companies:

Aerovox Corp. (manufacturers of capacitors, resistors, and attenuators); Apelco Co. (marine and general equipment); Barber-Colman Co. (relays, motors, and control systems); Electronized Chemicals Corp. (laminates, dielectrics and insulators); E.R.A. Acoustics Corp. (speakers); Kepco Inc. (power supplies); Knight Electronics Corp. (kits and educational kits); James B. Lansing (amplifiers, pre-amplifiers and speakers); Micro-State Electronics Corp. (microwave semiconductors); National Company Inc. (radios and power supplies); Omni Spectra Inc. (microwave components); Rotron Manufacturing Inc. (fans and blowers); Sanders Associates Inc. (microwave components); Sarkes Tarzian Inc. (semiconductors); Sigma Instruments Inc. (relays and magnetic amplifiers); Stackpole Carbon Co. (resistors, capacitors, switches and ceramic magnets); TEL Instrument Electronic Corp. (electronic equipment for laboratory, commercial and communications uses); The Turner Company (microphones); Uniform Tubes Inc. (microwave coaxial cable and delay lines); Western Microwave Laboratories Inc. (microwave components).

Further details may be obtained from Auriema (Australasia) Pty. Ltd.

MINNESOTA MINING AND MANUFACTURING (AUSTRALIA) PTY. LTD. (the 3M Company) announces a new computer tape, called "Scotch" Brand No. 777. It is certified error-free at all packing densities up to and including 1600bpi. A special oxide binder formula enables the product to deliver greatly extended error-free performance under heavy usage as well as the temperature and humidity extremes encountered during shipping and long time storage. The company feels that it is a breakthrough in terms of its extended performance reliability. Further details can be obtained from the 3M Public Relations Department, at 2 Wentworth Avenue, Darlinghurst, Sydney, N.S.W.

ANDREW ANTENNAS PTY. LTD. are to manufacture microwave dish antennas in their new plant at Henty Street, Reservoir, Victoria, and will also stock co-axial cable and wave guide. All future inquiries for Andrew products should be directed to the head office at 437 St. Kilda Road, Melbourne.

Andrew Antennas also announces the appointment of Mr Christopher Lin, A.I.E.A., as sales engineer. Formerly with the radio division of the P.M.G., he will assist in the marketing of microwave dish antennas and antenna systems equipment.

AUSTRALIAN GENERAL ELECTRIC PTY. LTD. has notified the availability of the following semiconductors.

The GE type L1V is a planar PNP light activated silicon controlled switch that features an "extra lead" which is claimed to completely eliminate rate effect (dv/dt) and voltage transient problems without compromising triggering sensitivity or transient response. The L1V is expected to be particularly useful in applications such as optical tape and card readers, isolated switching and counting. The trade price is \$3.98 each for 1-9 quantities.

The GE type D5K1 complementary unijunction transistor operates in an opposite polarity mode as compared with standard unijunctions, and can produce both a negative and a positive trigger pulse. Increased stability is claimed for the device which can be built into oscillators up to 100 KHz. The trade price is \$8.75 each for 1-9 quantities.

The GE type D5E29 is a new economy silicon unijunction transistor. It has a maximum power dissipation of 300mW and a peak emitter current of 2A. The maximum emitter reverse voltage is 30 volts, while the maximum interbase voltage is 35 volts. The intrinsic standoff ratio is 0.68 to 0.82 and is essentially constant with interbase voltage. The trade price for 1-9 quantities is \$1.32 each.

For further information and specifications on any of these devices contact the company at 103 York Street, Sydney, or at 552 Lonsdale Street, Melbourne.

PLESSEY has announced the appointment of Mr Robert R. Long as Deputy General Manager (Engineering and Production) of the Telephone and Electrical Industries (T.E.I.) Division of Plessey Telecommunications. He has resigned his posi-

tion as Assistant General Manager (Technical) of the Overseas Telecommunications Commission (Australia) to take up his new appointment. Mr Long joined the O.T.C. in 1953 after 14 years with STC Australia as a design engineer responsible for telecommunication systems.

Mr Long holds an Honours Bachelor of Electrical Engineering degree from Melbourne University. He is a Fellow of the Institution of Electrical Engineers, Member of the Institution of Engineers Australia, and Senior Member of the Institution of Radio and Electronics Engineers Australia. He will be located at the headquarters of the T.E.I. Division at Meadowbank, N.S.W.

Mr Daryl E. Hooper has been appointed to the senior engineering staff of the Central Research and Development Laboratory operated by Plessey Pacific Pty. Ltd. at North Melbourne. Prior to his new appointment, Mr Hooper was senior lecturer in electrical engineering at Melbourne University. Before that he was a research associate with the U.K. Atomic Energy Commission at Harwell and a research engineer with the G.E.C. Research Laboratories in U.K.

EIMAC DIVISION of Varian has introduced a new line of miniature planar triodes for advanced airborne and space applications. The valves are of rugged ceramic/metal construction and feature large contact areas for improved electrical paths. They use arc-resistance cathodes and are claimed to provide high-frequency efficiency through the S-band. Cooling is by forced air or heat sink. For further information contact Varian Pty. Ltd, 38 Oxley Street, Crow's Nest, N.S.W.

EMERSON AND CUMING, INC. of Canton, Massachusetts, U.S.A., has released information on the following new products.



Eccosorb FGM is a 1/8in flexible microwave absorber based on silicone rubber. It is claimed to have an average reflectivity of 12dB down from 2 to 12GHz over a wide range of incidence angles.

Ecco Reflectors, devices based on the Luneberg Lens, are spherical passive devices which reflect and return to its source a radar signal almost as effectively as a flat metal plate of the same diameter. They are capable of reflecting simultaneously radar signals from many directions over a broad viewing angle.

Details may be obtained from Australian agents, Wm. J. McLellan and Co. Pty. Ltd., The Crescent, Kingsgrove, N.S.W.

more than 500 switches

in the current Cutler Hammer
Appliance type Switch Catalogue
— a design for every purpose
and an unsurpassed reputation
for reliability.



Please write or phone for copy of latest broadsheet listing current stock types.

MANUFACTURERS SPECIAL PRODUCTS PTY. LTD.
47 York Street, Sydney. 2 0233

ADELAIDE: Newton McLaren Ltd. 51-0111. **BRISBANE:** Chandlers Ltd. 31-0341. **HOBART:** Amalgamated Wireless (Australasia) Ltd. 3-3836. **LAUNCESTON:** Amalgamated Wireless (Australasia) Ltd. 2-1804. **MELBOURNE:** J. H. Magrath & Co. Pty. Ltd. 32-3731. **PERTH:** Atkins (W.A.) Ltd. 21-0101; Carlyle & Co. (1959) Pty. Ltd. 21-9331. **SYDNEY:** Electronic Parts Pty. Ltd. 560-7566; George Brown & Co. Pty. Ltd. 29-7031; Broadway Electronics Pty. Ltd. 211-4224.


TUDOR RADIO

L. E. CHAPMAN
ESTABLISHED 1940

103 ENMORE ROAD, ENMORE, N.S.W.
PHONE 51-1011

Knobs long shaft, push on. Dozen \$1.20
Knobs for concentric shaft. Dozen \$1.20
250 mixed screws. BA, Whit., self-tapper bolts, nuts, etc. \$1 bag plus 25c post.
Crystal microphones, good quality, ideal tape recorders, etc. \$2.80.
Transistor speaker transformers, single ended, 5 watt. \$1.50.
Dutch Philips 3 pin flexible jacks, 40c each.


ZEPHYR — CRYSTAL MICROPHONE



\$2.50, pack and post 20c.

SPEAKERS

MSP 20928 mod 12 PQ \$13.50
MSP 8in twin cone 15 ohm .. \$5.50
MSP 12in twin cone 15 ohm .. \$7.50
MSP 7 x 5, 3 and 15 ohm \$3.50
MSP 3 1/2 inch \$2.00
Rola 5 x 4, 3 and 15 ohm \$2.50
Rola 4 x 3, 10, 15, 27 ohms .. \$2.00
Rola 5 B 3 ohms \$2.00
Rola 8 x 4 15 ohm \$3.50
6 x 9 single cone 15 ohm \$3.50
8 inch single cone 15 ohm .. \$4.20
3 1/2 inch 47 ohm \$2.00
6 x 4 33 ohm \$2.50
2 x 3, 15 ohm \$2.00
5 x 3, 47 ohm \$2.00
5 x 3, 27 ohm \$2.00
12P.G. M.S.P. 21622 20 watts \$17.50



English push-button on/off switches, 75c each. Pack and post 10c.

Mini cable, 4 strand shielded, lots of uses, including microphone cable, extension speakers etc. 10c yard
Radio knobs, push on 50c doz.
Miniature valve sockets 7 and 9 pin 15 cents each.
Picture tubes, all sizes, new in cartons. \$25.00. With your dud. Bonded extra.
Philips IFT's 455KC 75c each
Aerial and oscillator coils .. 50c each


Scope soldering iron, standard; mini scope. Scope De Luxe. Vibra scope; National scope transformer.

Vinyl insulating tubing, 13MM wall thickness .030, 25 yards .. \$1

Transistor IFs, medium size, 75c each

Record Changers. Garrard AT 6

Transistor Amplifier and tuner, new working \$10
Speaker \$2 extra



Steel speaker baffle unit 6 x 9, 7 x 5 speaker, \$1.00.

Pack and post 15c.

Transistor speaker and drive transformers, large and midget type .. \$1.00
Speaker transformers 15,000 and 25,000 to 3 ohms 6 watts \$1.50 each
5,000 to 3 and 15 ohms .. \$1.25 each
Transistor speaker chokes .. \$1.50 each

Here's value in pots.

Pots, single log and linear:
3K, 7 1/2K, 10K, W.W., 20K, 25K, 50K, 100K, 200K, 250K, 500K, 1 Meg, 2 Meg. 50c each
1.5 Meg. Dual Concentric .. \$1.00

Pack and post 50c.

Pots dual ganged 10K, 50c. 1 Meg. \$1.25

Pots concentric. 100K + 50K, 100K + 2 1/2K, 100K + 10K, 250K + 250K, 500K + 500K, 1 Meg + 1 Meg., 1 Meg. + 500K. Various others 50c each

TV power Transformers 300 mill 225v a side, suit amplifiers up to 50 watts voltage doublers available, \$8.00 each
TV safety glass per sheet \$3.50
Garrard plug in stereo heads \$4.00
TV masks, 17, 21, 23in \$1.50 each
Tuning condensers 2 and 3 gang, \$1.00



STEREO AMPLIFIER KIT SETS

Without Speakers \$5 less.

TU 10, 3.5 watt per channel .. \$24.00

TU 11, 3.5 watt per channel has facilities for tape and microphone channels. \$28.00

TU 12, 5 watt per channel .. \$27.00

TU 13, 5 watt per channel with TU 11 facilities \$32.00

Each kit set includes valves, speakers and all components.

Single stage amplifier kit set:


5 watt per channel \$22.00

Transistor ear plugs 3 for \$1.00


Tag strips, mixed types .. Dozen, 60c

Switches, oak 4 position .. 50c each

2 position 40c each



Metal Rectifier \$1 each



Push-button Tuner \$3.50

TV AERIALS

Famous Make

All types \$3.50 to \$20.00 plus post.
TV aerial lead in 8c yard
TV aerial chimney mount kits .. \$3.50
Wall stand-off brackets, pair .. \$1.90

HEAVY DUTY 3 CORE FLEX

50yds, \$2.50

THREE WATT AMPLIFIERS,

complete with speaker.

NEW. \$10.00

2 amp fuses \$3.50 per 100
Special, 12in speaker, 2 ohm Rola, \$6.00 pack and post, 75c.

Transistor plastic outer case, 50c each

Transistor carrying straps .. 20c each

Stereo pick-up arms, with Xtal, \$6.00 ea.

Metal rectifiers for battery and electric portables 50c each, post. 10c

Pilot lamp holders 30c per doz.

TV or cabinet castors 4 for \$1.00

100 Mixed Knobs including TV channel changers \$10.00

240v AC Record Changers, stereo

\$21.50, Mono \$20.00. Pack and post,

N.S.W. \$1.50, interstate \$2.50.

Gramophone motor and pick-up, 240v

AC \$11.50. Pack and post, N.S.W.

\$1.00, interstate \$1.50.

OA 70 diodes 40c each

Morganite and IRC resistors. At least

33 values. Suit transistors, radios, TV,

etc., \$2.00 per 100. Pack and post, 25c.

3, 5, and 10 Watt IRC wire wound resistors. Many values.

20c each, 12 for \$2.00

100 mixed condensers, micas, ceramics,

tubular. Fresh stock.

\$2.00. Pack and post 25c.

50 + 24, 350 vw + 100 mf 25vw,

75c each

30, 30mf 350 vw 350vp .. 75c each

Many others. Invaluable for service.

SHEPHERD CASTORS, \$3.00 set of 4.

SMALL AMPLIFIER OR TUNER

CHASSIS, \$1.50 each. Pack and post

25c.

ALPHA 200VAC 1/2 amp push-on

switches, 30c each. Ideal for fridges.

90 deg. PICTURE TUBE SOCKETS

25c each. 152 valve sockets, 25c each.

Transistors AC127, 2N384, 2N217,

2N218, OC71, OC75.

\$1.00 each. Post and pack 5c.


TRANSISTOR CLOCK RADIOS,

LIMITED QUANTITY, famous make,


\$50 each

VALVES


12AU7 .. \$1.25	6CJ6 \$1.50
12AX7 .. \$1.25	12BH7 .. \$1.25
6SA7 \$1.25	6L18 \$1.00
6V490	ECL85 .. \$1.25
6BU8 \$1.25	SP61 \$1.00
6M5 \$1.25	U99 \$1.00
6AN7 \$1.25	6BL8 \$1.00
6N8 \$1.25	12BE6 .. \$1.00
6BM8 \$1.50	6BD7 \$1.00
1S5 \$1.00	6AU4 \$1.00
1T450	




TV. IF video and sound strips .. \$10
With Valves \$15




TV IF Coils, ideal for Coil Formers
..... \$1 dozen.



SPEAKER BOX for 6 x 9 or 7 x 5,
\$5.00. Speaker, \$4.00 extra.



SPEAKER BOX SLIMLINE, 19 x 13
x 6 \$15.00
8in bass speaker, 3in tweeter.
Without speakers.



MULLARD BOOKSHELF "MINI"
SPEAKER CABINET, 6in 6WR.
3TC speakers \$25.00

TWO-GANG TUNING CONDENSER.
Stromberg Carlson 50c

TV Chassis. Famous make, new
half complete \$8
Pack and post \$1.75

Dial drums 5 inch, 3½, 3¼ .. 50c each

National speakers 8 inch built-in
Tweeter, Cross over net work. \$15
10 inch Bass, mid range
Tweeter combined. \$32

Magnavox GWR, 8 WR, 10 WR,
12 WR. Tweeter 3, 4 or 5 inch

Speaker Plugs, 4 pin .. 15 cents
Speaker Sockets 15 cents

TUDOR RADIO

L. E. CHAPMAN

Established 1940

103 ENMORE ROAD,

ENMORE, N.S.W.

PHONE: 51-1011

Sorry no C.O.D.

Pack and post for all goods

**SHORTWAVE AND BROADCAST
SWITCH BANKS** \$2.50 each
Pack and post, 20c.

SPECIALS

**TRANSISTOR AUDIO TRANS-
FORMERS**, medium size .. 75c each
PHILIPS GRAMOPHONE MOTOR.
4-speed. New. 6-volt \$5.00
Pack and post, 10c.

**TRANSISTOR OUTPUT AND DRIVE
TRANSFORMERS**, Medium size, \$1.50
pair.

Pack and post, 10c.

SPEAKER TRANSFORMERS, 5,000
to 8 ohms 10 watt \$1.90 each
Pack and post, 20c.

Large Ferrite Rods and Coils .. \$1.50

DYNAMIC MICROPHONES, good
quality \$7.50

8-STRAND WIRE ONE SHIELDER,
20c per yard.

CARAVAN TV AERIALS .. \$10.50

SILICON DIODES 210 3254G HR15,
75c each

CAR RADIOS, new push-button trans-
istor 8 \$50.00

Pack and post, 50c.

**TV IF STRIP, WELL-KNOWN
MAKE**, printed circuit video and sound,
complete except valves \$15.00

CABINET CLOTH, best quality, 50c
sq. ft.

SPEAKER 4in 27 ohm, 47 ohm \$2.00
each.

Pack and post, 20c.

TV CABINETS, 19 SLIMLINE, with
screw-on legs. Brand-new and polished
maple, packed in original cartons. Ideal
for speaker enclosures, etc. \$10.00

ELECTROLYTIC CAPACITORS, 20,
400, 450, 10, 400, 450 \$1.50
50, 65 50c each

Pack and post, 10c.

500, 10VW, 12VP 30c
400 MFD, 10V 30c
00.5MFD, 2000 DD.CW HERMSCEAL,
20c

**TRANSISTOR TUNER AND AMPLI-
FIER**, well-known make \$15.00

Tested. In perfect working order.

Pack and post, 20c.

**TRANSISTOR SPEAKER TRANS-
FORMERS**, 500 to 30 ohm 50c

Pack and post, 10c.

TRANSISTOR CHOKES, 2 ohm 50c
Pack and post, 10c.

NEW RADIOGRAM, chassis, mono,
complete, valves, speaker .. \$13.50

GARRARD, 32 volt, 3 speed record
changer \$15


**DE LUXE RECORD CHANGER
CASES**, perspex. TOP \$19

Pack and Post \$1.

Garrard tape deck Cartridge,
battery operated \$20

Goldring Cygnet de luxe, 4-speed battery
record player, Auto. stop. \$17


Sangamo time motor units. 1/3
Revs. 1 Hour \$4




PLAYMASTER, SUPER BOOKSHELF.
Two 6WR, one 3TC speakers .. \$37.00



26 x 17½ x 10½ 8in **BASS SPEAKERS.**
5in tweeter. Crossover networks, \$37.00



INSTRUMENT CASE, suit record
player, etc. \$7.00 each
Pack and post, 50c.




STEREOGRAM CHASSIS VALVES.
Complete except speakers \$25.00
Pack and post, \$1.50.

Lenco Swiss gramophone motor
and pick up. Auto stop. De luxe \$17

Dial scales, 5in 11½ x 6, 10½, 3½,
9½ x 1 50c

ELECTRONICS ARE GOING PLACES



A radio-equipped turtle is tracked by orbiting satellites to check its migratory voyages in the Atlantic Ocean. One of the million incredible uses of electronics for commerce and industry.

EARN BIG MONEY as an ELECTRONICS ENGINEER

STUDY AT HOME IN YOUR SPARE TIME

You know as well as we do that electronics is the big new field that's here to stay. Industry is using electronics in fields many people hadn't dreamed of a few years ago.

TRAINED MEN ARE NEEDED. Australia's industries need, and must have, Electronics Engineers urgently. Salary scales are rising fast and electronic engineering specialists are making big money. Trained Australian Electronics Engineers can choose jobs anywhere in the world—the lack of these trained men is world-wide. Training is the key—qualifications are what matter.

BE HIGHLY PAID IN THE WORK YOU LIKE MOST. You already have the interest you need to be successful in electronics—you can get the training you need through

International Correspondence Schools. You can train for your career in electronics at night, in your own time, with the help of a School of Electronics as close as your mail box.

ACT NOW! Fill in the coupon below and send it to I.C.S.—we will send you by return mail our Free Book "Your Career in Electronics." You could be earning more money, doing the work that you like, sooner than you think.

INTERNATIONAL CORRESPONDENCE SCHOOLS
Dept. 528, Division of Electronics
400 Pacific Highway, Crows Nest, N.S.W.

*Which of these specialised I.C.S.
Home Study Courses interest you most:*

- | | |
|--|---|
| <input type="checkbox"/> Audio: Hi-Fi, Stereo | <input type="checkbox"/> Communications |
| <input type="checkbox"/> Automation Electronics | <input type="checkbox"/> Monochrome and Colour TV |
| <input type="checkbox"/> Automatic Controls | <input type="checkbox"/> Electronic Drafting |
| <input type="checkbox"/> Industrial Applications | <input type="checkbox"/> Printed Circuits: Conventional |
| <input type="checkbox"/> Nuclear Instrumentation | <input type="checkbox"/> Printed Circuits: Micro Integrated |
| <input type="checkbox"/> Digital Techniques | <input type="checkbox"/> Fringe Equipment |
| <input type="checkbox"/> Transistors & Semi Conductors | Also Computer Programming for Commerce, Research, Industry |

International Correspondence Schools

Dept. 528 Division of Electronics, 400 Pacific Highway, Crows Nest, N.S.W.

Please send me, without cost or obligation, your Free Booklet "Your Career in Electronics" and full information about _____

Name (Mr., Mrs., Miss) _____ Age _____

Address _____

Phone _____

Occupation _____ Dpt. 528

TECHNICAL BOOKS AND PUBLICATIONS

Digital Computers

BASICS OF DIGITAL COMPUTERS, by John S. Murphy. Published by John F. Rider Publisher, Inc., New York, 1958. Seventh Printing, 1966. Four volumes, 6in x 9in, in soft covers, approx. 135pp. per volume. Many circuits and diagrams. Price in Australia \$8.78 complete.

Although this book is substantially unchanged since it was written in 1958, much of the material which it presents is far from being outdated in 1967. In fact, from the point of view of content the book is probably of almost as much value now as it was originally. Yet despite this I can't really commend it as a worthy "first introduction" to digital computers, and for the same reason which would have stopped me from doing so when it was first published: its presentation just isn't good enough.

Part of the problem seems to be that the author has relied too heavily on a "picture-book" approach, and has simply not provided enough solid explanation as written text. A picture may indeed be worth a great many words, yet pictures alone—or almost so—are hardly adequate for effective communication of abstract and complex technical concepts.

But it seems to me that the main cause of the poor presentation is that there has been confusion as to the class of reader for which the book has been written. This has resulted in a rather strange conglomeration of electronic and logical concepts at not one, but a number of stages of specialisation and elaboration. Perhaps the idea was to provide something for everybody; yet the result would appear to this reviewer to be of dubious value to anyone.

In his preface, the author states that the book was developed for the training of computer technicians and field engineers. Even allowing for what one might genially term the "broadness" of American usage of these titles, one is surely justified in assuming from this that the intended reader will necessarily have at least a basic knowledge of electronics. Yet in volume 2, following on the heels of a section explaining the operation of the univibrator or "one-shot," we find a whole section devoted to an explanation of germanium diode operation at the most elementary level. This was apparently thought necessary as introductory material to a section dealing with diode damper and clamp circuits, just in case the would-be computer specialists didn't know what a diode was...

There are quite a few cases of this sort of thing. Another notable example is in volume 3 where the section on magnetic drum, disc and tape storage starts right

Pulse Generators — New Edition

PULSE GENERATORS, edited by G. N. Glasoe and J. V. Lebacqz. Published by Dover Publications, Inc., New York. Soft covers, 5-3/8in x 8 1/2in, 741 pp., many circuits and diagrams. Price in Australia \$3.75.

This volume is a Dover republication, unabridged and unaltered, of the work first published in 1948 by McGraw-Hill as volume 5 of their now-classic "M.I.T. Radiation Laboratory Series." It may be remembered that the latter series was the outcome of much of the development work carried on at the Massachusetts Institute of Technology Radiation Laboratory during World War II, and has long been recognised as one of the most distinguished and comprehensive series ever published on radio engineering.

As its title suggests this volume deals with pulse generation, shaping and transformation; and as one might expect it is orientated mainly towards magnetron tubes and radar applications. However, the theoretical treatment is sufficiently general in most sections to be applied quite easily to more modern devices and applications. The book is therefore far from being worthy only of historical interest. Rather it probably deserves a place on the reference shelf of most engineers and physicists working in the pulse field.

The chapter headings give a fairly clear idea of the material given and its order of treatment: 1 — Introduction; 2 — The

Output Circuit of a Hard-Tube Pulser; 3 — Vacuum Tubes as Switches; 4 — Driver Circuits; 5 — Particular Applications; 6 — The Pulse-Forming Network; 7 — The Discharging Circuit of the Line-Type Pulser; 8 — Switches for Line-Type Pulsers; 9 — The Charging Circuit of the Line-Type Pulser; 10 — Performance of Line-Type Pulsers; 11 — Particular Applications; 12 — Elementary Theory of Pulse Transformers; 13 — Pulse Transformer Design; 14 — Effect of Pulse Transformer Parameters on Circuit Behaviour; 15 — Materials and their Uses in Design.

The treatment throughout is at engineering level, and assumes a fairly solid mathematical background. However the text is well written and although concise is quite readable. Bibliography is distributed through the book as footnotes. There are two appendices, one dealing with oscilloscopic and other measuring techniques and the other giving a discussion of the concepts of duration and amplitude as pulse parameters. The book ends with a list of symbols and an index.

To summarise, **Pulse Generators** seems a worthwhile republication of the book which might still be regarded as the classic work in this field.

Our copy came from the Australian distributors for Dover, who are Grenville Publishing Company Pty. Ltd. However we understand that copies are already available from the major bookstores. (J.R.)

Laboratory Instrument Practice

ELECTRONIC LABORATORY INSTRUMENT PRACTICE, by T. D. Towers, M.B.E., A.M.I.E.E., A.M.I.E.R.E. Published by Iliffe Books Ltd., London. Advance proof copy. 164 pages 8 1/2 x 5 1/2in.

In compiling this book, the author presumably has had three potential reader groups in mind: (1) Advanced amateurs and technicians who need to be "filled in" regarding instruments commonly found in electronic laboratories; (2) Graduates who may be strong in basic theory but unfamiliar with practical test equipment and (3) Executives and administrators who have been away from the bench long enough to get out of touch.

Systematically, he talks about the instruments and methods encountered in everyday laboratory practice, with basic circuits to indicate principles and pictures to illustrate typical instruments. Due attention is paid to orders of accuracy, both inherent in the various class of instrument, and as affected by connection of the equipment to the circuit under test.

Following a preliminary discussion the chapters deal with the following subjects: (2) Direct current and voltage measurements; (3) Signal generators, audio, RF and pulse; (4) Alternating current and voltage measurements; (5) Measurement of resistance; (6) Impedance, capacitance and inductance; (7) Oscilloscopes; (8) Measurement of power and gain; (9) Audio amplifier measurements; (10) Measurement of frequency; (11) Transistor testing; (12) Bench power supplies.

While the text is right up to date, including due reference to digital instruments, it is highly readable and confined to instruments and techniques which are familiar in most laboratory situations. The author does not become involved in special-

purpose instruments or techniques, as might be needed for research or process control.

Examination of the contents and sample reading indicated a practical and lucid approach, which could be most helpful to the classes of reader whom the writer has had expressly in mind. (The copy examined was a proof edition made available by the Technical Book and Magazine Company Pty. Ltd., of 289-299 Swanston St, Melbourne. They advise that properly bound copies will be available shortly for \$5.80 (plus postage.)(W.N.W.)

TEL-LEIGH-TUBES

Tel-Leigh-Tubes have pleasure in introducing "Golden View" tubes at a most competitive price.

These tubes are fully reconditioned and rescreened and are acceptable by insurance companies.

Broken necked, marked or discoloured screened tubes are acceptable for exchange (ion-burn excepted).

ALL SIZES IN STOCK — INCLUDING LAMINATED TUBES

"Tel-Leigh-Tubes" the top-quality regunned tubes are also available.

All tubes as advertised are first-quality and are guaranteed for 12 months.

Telephone
56-8498

Same day delivery service.

Telephone
56-8498

TEL-LEIGH-TUBES, 51 REUSS STREET, LEICHHARDT, SYDNEY, N.S.W.

Country and Interstate customers: Please rail old tubes to Petersham Station.

COLLINS BOOK DEPOT

TITLE	No. Pages	Price	Post	TITLE	No. Pages	Price	Post
Radio Amateurs' Handbook A.R.R.L.	740	\$5.85	25c	Electronics Made Simple . . .	192	\$1.35	10c
HOW to fix Transistor Radios and Printed Circuits, 1 and 2	160	7.30 ea.	13c ea.	Electronic Communication — Shrader	682	10.00	25c
Radiotron Designers' Handbook. 4th edition	1498	7.50	40c	Ham Antenna—Stanley . . .	160	4.10	10c
Transistor Radio Handbook. Editors and Engin.	848	13.00	40c	How to Read Schematic Diagrams—Herrington . . .	128	3.05	10c
Repairing Transistor Radios . .	160	4.40	10c	Colour T.V. Guidebook . . .	102	1.25	10c
Mini-Watt Technical Data: Philips	224	3.00	25c	Colour T.V. Servicing Guide . .	112	4.75	16c
A.B.C. of Television	96	2.45	7c	Colour T.V. Trouble Clues . .	128	3.05	10c
Reference Manual of Transistor Circuits; Mullard	308	1.50	13c	101 Ways to use your Colour T.V. Test Equipment	144	4.05	10c
R.C.A. Transmitting Tubes . .	320	1.30	10c	Colour T.V. Repair	160	3.70	10c
Magnetic Recording for the Hobbyist	128	3.40	10c	Servicing Transistor T.V. . . .	222	5.10	10c
Rapid Auto Radio Repair . .	158	3.70	10c	Servicing T.V. Remote Controls	158	3.40	7c
Records and Gramophone Equipment	124	1.50	7c	Solving T.V. Tough Dogs . . .	128	3.15	7c
Solid State Power Supplies and Converters	110	3.40	10c	T.V. Sinc and Deflection Cir- cuits	160	3.70	7c
Charts and Nomographs for Electronics, Technicians and Engineers	96	7.45	22c	T.V. Troubleshooters' Reference Handbook	128	3.40	7c
Test Equipment Maintenance Handbook	160	3.70	10c	Radio and T.V. Alignment Handbook	156	3.70	7c
Servicing Record Changers . .	224	3.60	10c	Handbook of Transistor Circuits	224	5.95	10c
Aust. Radio Amateur Call Book, 66-67	64	75c	10c	A.B.C. of Electronic Drafting	96	2.45	7c
Silicon Controlled Rectifier De- signers' Handbook	306	3.00	19c	Troubleshooting Amateur Radio Equipment	128	2.88	7c
Basic Electronics — Bureau of Naval Personnel	460	3.45	19c	Design of Communications Systems	110	3.45	7c
S.E.C. Victoria Wiring Regula- tions 1961, with 1966 supple- ment	293	95c	16c	Closed Circuit Television Hand- book	286	7.15	13c
Mechanical World Electrical Year Book, 1967	360	1.45	10c	Frequency Changers	224	5.95	10c
General Electric Transistor Manual	660	3.60	25c	Electronics For The Beginner . .	192	4.25	10c
Programmed Course in Basic Transistors	474	6.25	25c	Bench Servicing Made Easy . .	160	4.05	10c
Radio and Electronics, 2 vol- umes—Reyner	1070	18.90ea.	79c	Electronic Engineers and Tech- nicians' Reference Handbook	224	5.10	10c
It's Easy to use Electronic Test Equipment	186	5.00	13c	Tube Substitution Handbook .	124	2.15	10c
				Amateur Radio Mobile Hand- book	160	4.05	10c
				Design and Operation of Regu- lated Power Supplies	112	4.05	10c
				Industrial Transistor and Semi- conductor Handbook	254	5.10	10c
				Acoustical Tests and Measure- ments	192	5.10	10c
				Transistor Circuit Manual . . .	254	5.95	13c
				Basic Piezoelectricity	128	3.40	10c
				Servicing A.G.C. Circuit . . .	204	4.95	10c

Write for a list of Books on your subject

• HI-FI STEREO • RADIO • TV • COMPUTERS • ELECTRICAL ENGINEERING • ELECTRONICS • TRANSISTORS

359-369 SWANSTON STREET, MELBOURNE, (opposite Public Library) Telephone 32-3787

back at the level typified by "a magnetic recording head is an electromagnet shaped like a loop..."

Again, there are many diagrams which to my mind at least belong more in a kindergarten primer than in an introductory computer text. To illustrate something or other about the fact that a flip-flop stores both a binary digit and its complement, for example, we find a drawing of a cute little shopping basket with two eggs in it, accompanied by the caption "two eggs in one basket." And in the section dealing with timing and control—fairly advanced concepts, surely—there is a delightful little sketch of a lot of tiny cartoon hillbillies doing a barn dance, under a caption proclaiming "Standard timing is like a barn dance, where everyone finishes the dance with his original partner."

Finally, there are various places where either the text or the diagrams seem to me to be either inaccurate or ambiguous. Here are two examples. In volume 2, the most rigorous definition of an OR logic element I can find in the appropriate section is "an element which allows signals to pass from any one of a number of inputs to a common output, without allowing any interaction among the inputs." This definition has so much wrong with it that one hardly knows where to start; suffice perhaps to say that it is broad to the point of irrelevance, yet narrow to the extent that it completely excludes the widely used "wired-OR" function.

As a second example, in the same volume there is a diagram showing four thermionic valves silhouetted against a background of valve circuit symbols. The caption reads, "Vacuum tube envelopes and their schematic symbolisations." The block and its caption occupy a good half page, yet they seem both trite and irrelevant.

If you're seeking a basic introduction to computers and digital electronics, I'm afraid I can't advise that you consider this one.

Incidentally, our copy came direct from the Australian agents for Rider, who are Grenville Publishing Company Pty. Ltd. Copies should be already available from the major bookstores. (J.R.)

For Radio Amateurs

RADIO HANDBOOK, 17th edition, by William I. Orr, WS6AI. Published by Editors and Engineers Ltd., New Augusta, Indiana, U.S.A. Stiff, heavy, cloth cover, 847 pages, 9 1/2" x 6 1/2", generously illustrated with line drawings, together with some tables and photographs. Price in Australia, \$13, plus 35 cents postage.

The seventeenth edition of this already well known publication is still living up to its reputation. More particularly at technical level, it is a good book on general theory and, as such, it is an excellent reference work. The practical aspect of radio, leaning towards the construction of amateur radio equipment, is also given consideration. However, it does leave something to be desired in this field, as far as the keen home builder is concerned. This is possibly due to the fact that amateur equipment is so readily available in the United States and the urge to build one's own is not so great in that country. In spite of this comment, there are some excellent practical articles.

With a volume of this size, it would be a lengthy undertaking to review it completely. Unfortunately, the writer does not have immediate access to the sixteenth edition. However, the fourteenth edition is available and comparisons will be made against this one. This may not be unrealistic, as most readers would not purchase each edition of such a textbook and this comparison should be a worthwhile guide. Without going into great detail, here is a chapter comparison between the two volumes.

Chapters 1, 2, 3, 4, 6, 9 and 11 in the new volume are substantially the same as previously. Chapters under the headings:—

Frequency Modulation (Ch. 13), Transmitter Design (Ch. 17), High-Frequency Directive Antennas (Ch. 22), VHF and UHF Antennas (Ch. 23), Workshop Practice (Ch. 32), and Radio Mathematics and Calculations (Ch. 33), are also substantially the same, except that the chapter numbers have been changed.

Chapters headed:— Amplitude Modulation (Ch. 13), Television and Broadcast Interference (Ch. 18), Radiation, Propagation, and Transmission Lines (Ch. 20), Antennas and Antenna Matching (Ch. 21), and Rotary Beams (Ch. 24), have had some material added, either to enlarge on subject treatment or to bring the chapter up to date.

Chapter 5, Transistors and Semiconductors, has been up-dated and includes material on field effect transistors.

Chapter 7 has some new material covering linear amplifiers and intermodulation distortion.

Chapter 8 discusses the use of the oscilloscope for SSB measurements.

Chapter 10 includes information on Q multipliers and product detectors.

Chapter 12 is new, with subject matter on RF Feedback.

Chapter 15 has been added and is devoted to Radio Teletype Systems.

Chapter 16, Sideband Transmission, has been brought up to date and contains much useful information.

Chapter 19, Transmitter Keying and Control, has material added on differential keying and vox circuitry.

Chapter 27, Low-Power Transmitters and Exciters, is an added chapter and is made up of a number of constructional projects.

Ch. 25, Mobile Equipment Design and Installation; Ch. 26, not named, deals with the construction of receiving equipment; Ch. 28, High Frequency Power Amplifiers; Ch. 29, Speech and Amplitude-Modulation Equipment; Ch. 30, Power Supplies; Ch. 31, Electronic Test Equipment. All these have in varying degrees, been revised or rewritten.

This volume, from an appearance point of view, is at first sight very attractive, having a white binding. Unfortunately, as is evidenced in our review copy, the white binding is showing signs of soiling already. However, this could be avoided with a plastic protective cover.

To sum up, if you do not already have this or a recent edition, it is well worth a place on any engineer's, technician's, or radio amateur's bookshelf.

Our copy came from the Technical Book and Magazine Company Pty. Ltd. of 289-299 Swanston Street, Melbourne. (I.L.P.)

"Novice" Stations

BUILDING YOUR AMATEUR RADIO NOVICE STATION, by Howard S. Pyle, W7OE. Originally published in U.S.A. by Howard W. Sams and Co. Inc. This edition is published and distributed by W. Foulsham and Co. Ltd., Slough, Bucks., England. It has an introductory chapter printed in Great Britain, with the balance printed in U.S.A. Hard covers, with 103pp, 11 1/2" x 8 1/2". Well illustrated with many pictures and drawings. Price in Australia is \$4.75.

As the title implies, this book was intended originally for the American Novice Amateur. An introductory chapter has been added for the benefit of readers in Great Britain. This brings out certain points relating to the availability of components and different practices between the two countries. Although the Australian requirements are different again in some respects, the chapter is valuable in that it alerts the reader to watch for possible problems.

The book is quite well written and each aspect covered is given in so much detail that it should be possible for the absolute beginner to follow all instructions and explanations. This is taken to the point where there are several pages in the back of the book which include templates to assist in

the construction of some of the projects described. With this all in mind, this could be an excellent book for one starting out even as a short-wave listener, who wished to build his own first receiver.

Chapter 1, called Initial Considerations, deals with such items as tools, soldering, quality and standard of workmanship, along with various hints and tips on how to go about construction work.

Chapters 2 to 6 are devoted to the construction of a simple but well thought-out multi-band short-wave receiver. As the number of chapters would indicate, the amount of detail devoted to this little receiver, could scarcely be enlarged upon.

Chapters 7 and 8 are devoted to constructional details of a simple multi-band transmitter. This transmitter is crystal controlled and uses a 6DQ6B valve and it is intended for CW mode only. The same comments as the receiver also apply here.

To give an idea of the contents of the rest of the book, here is a list of the other chapters:

Chapter 9—The Antenna System. Chapter 10—Station Accessories. Chapter 11—Speaker-Amplifier-Control Unit. Chapter 12—Arranging the Station. Chapter 13—Future Construction Projects. Chapter 14—Looking Ahead.

To sum up, a very good book for raw, and not so raw beginners. The price is a little high but this is possibly due to the multiple printing costs. Our copy came from the Grenville Publishing Co. Pty. Ltd., 154 Clarence St, Sydney. Copies should be available from technical book shops. (I.L.P.)

RADIO ENTHUSIASTS

Learn
amateur radio
in your spare time.

Whatever your interests are in amateur radio, there's a Stott's Radio course for you. Easy to follow.

Practical. Modern. Guidance all the way by top-flight radio engineers.

Radio for amateurs

Learn the exciting skills of building modern radio receivers. Learn about the latest advances in electronics, design, construction and operation.

Let Stott's show you how.

Amateur Operator's Certificate Course: Broadcasting is fascinating. Stott's offer an entirely new course that enables you to sit for the Amateur Operator's Certificate of Proficiency

Examinations with complete confidence.

Get full details now on Stott's Radio Courses.

Stotts

TECHNICAL CORRESPONDENCE COLLEGE

159 Flinders Lane, Melbourne. 383 George St., Sydney. 290 Adelaide St., Brisbane. 45 Gilles St., Adelaide. 1130 Hay St., Perth.

Post this coupon:

TO STOTT'S: Please send me, free and without obligation, full particulars of your Courses in Radio for Amateurs.

MR./MRS./MISS.....

ADDRESS.....

AGE.....

I understand no representative will call. RH867

G. A. Briggs writes on Hearing

ABOUT YOUR HEARING. Editor G. A. Briggs. Sub-Editor J. Moir M.I.E.E. Published by Rank Wharfedale Ltd., Bradford, England. First edition 1967. Stiff paper cover, 132 pages 8½ x 5½ inches, with many illustrations.

It is some time since we have reviewed a book carrying the name of G. A. Briggs and I was therefore not surprised when this new one turned up — his eighteenth — direct from the author's firm. I was somewhat surprised, however, by the title, for I had not thought of the Briggs' interest in ears going beyond their role as re-

ceptors for the sound from his highly commendable — and highly commercial — line of Wharfedale loudspeakers. However, it seems that friend Briggs has been thinking about ears hard enough and long enough for him to want to write about them.

In so doing, he lays no claim to having created a book of either medical or engineering significance. His aim has been to write in a fashion which will interest and educate those of us who regard ears as organs which can help support spectacles, need washing at regular intervals, ache occasionally and, more particularly, become

less efficient with the passing years. And this last appears to be the main focus of the book.

The author begins by talking about ear trumpets and aids of another century, the resonance of seashells and so on. He then goes on to sound and hearing generally, with a chapter on the ear itself. Succeeding chapters deal with deafness, tests for loss of acuity, modern hearing aids, and some of the surgical resource that is now available to the incapacitated.

Inevitably there is a chapter on noise which, among other things, warns young people about the hazard of excessively loud music in pop-group situations, plus another chapter on sound reproduction, mainly involving headphones.

According to the preface, the material in the book has been carefully checked by experts in the various subjects and at least four chapters have been contributed by outside authors. The stamp of G. A. Briggs is firmly upon the book, however, in the way of interspersed quotations, humorous remarks and cartoons. As I said before, this is not a textbook but it is nevertheless a book that should prove entertaining and instructive to anyone whose interest has been quickened, for any reason, in those convolute receptors on either side of his head. Our copy came from the publishers but supplies should be available in due course through regular technical booksellers. (W.N.W.)

★ ★ ★

ABC'S OF CAPACITORS, by William F. Mullin. Originally published in the U.S.A. by Foulsham-Sams Technical Books. This edition published in the U.K. by W. Foulsham and Co. Ltd. with an introduction for the English reader by W. Oliver. Hard covers, 5½in x 8½in, 96pp. Price in Australia, \$3.40.

This book has been written primarily for the serviceman. While it includes essential theory, it is more concerned with the operation and use of capacitors, and their replacement in circuits. The added introduction points out the differences between American and English circuit symbols, and also warns against relying on the colour code set out in the book because of the differing standards.

The contents of the book are: What is a Capacitor? — this chapter includes definitions and explains basic construction and units; Capacitor Theory — including dielectrics, losses, time constant and reactance; Capacitor Construction — the construction with dielectrics of air, mica, glass, paper, plastic-film (polyester, polystyrene and polycarbonate), and ceramic, and of aluminium and tantalum electrolytic capacitors; Capacitor Applications — giving some of the possible uses of capacitors in circuits; Capacitor Replacement — considerations when replacing faulty components; Capacitor Testing—simple tests to check suspected capacitors.

Within its rather narrow field, this book is quite sound and should be of assistance to the up and coming serviceman and student technician.

Our review copy was supplied by Grenville Publishing Co. Pty. Ltd., 154 Clarence Street, Sydney. Copies should be obtainable from leading book sellers. (J.H.)

★ ★ ★

DICTIONARY OF RADIO AND TELEVISION, by W. E. Pannett. Published by George Newnes Ltd. Tower House, Southampton Street, London W.C.2. Hard covers, 5in x 7½in, 373pp. Price in Australia, \$5.90.

This book has a wider scope than is indicated by its modest title "Dictionary," and by the words "Radio and Television." The definitions, in some cases, are quite extensive and include some on telecommunications, semiconductor and thermionic devices, audio engineering, radio navigation and radio astronomy. Elementary principles and circuits are described briefly, but more complex and newer devices are covered in greater detail, where necessary, to

NEW TELEVISION ENCYCLOPAEDIA



**5 Volumes
5000 Subjects**

CONTENTS INCLUDE

**1850 Pages
Fully Indexed**

Television Servicing Methods, Alignment of Video I-F Amplifiers, Picture Tube Input Circuits, The Sync Sections, Sweep Oscillators, Automatic Control of Sweep Frequency, Sweep Amplifier and Deflection Circuit, Picture Tube Service and Adjustments, Television Modulation, Measurements at High Frequencies, Analysers and Multimeters, Electronic Voltmeters, Signal Generators and Test Oscillators, etc. etc.

SEE THESE BOOKS — AT OUR RISK!

We will send you this complete 5 volume set for 10 days FREE TRIAL. Read and fill in coupon today.

CLIP THIS NOW

STANDARD PUBLISHING CO. PTY. LTD.,
45 Chandos Street, St. Leonards, N.S.W.

Please send me for 10 days' trial the complete 5-volumes set Television Encyclopaedia. I am at liberty to return these books within 10 days of my receipt of them. If I decide to keep them I will pay \$2.00 deposit and \$4.00 per month until the total sum of \$34.00 is paid.

NOTE: The books cannot be purchased separately.

NAME

ADDRESS

OCCUPATION

SIGNATURE

PARENTS OR GUARDIAN'S SIGNATURE
(if under 21)

E.A., Aug. '67.

make the principle or mode of operation clearer.

To supplement the definitions, a number of useful appendices is included at the end of the book. The subjects covered by these appendices are: symbols for units with abbreviated prefixes; classification of radio waves; frequency-wavelength conversion; semiconductor symbols; abbreviations; colour codes; and, circuit symbols.

This book should prove of value to technical personnel engaged in one field of electronics who wish to check the definition of a term encountered in some other field. It will also be very useful to students and hobbyists, when confronted by an unfamiliar term or who wish to build up their background of knowledge by simply treating the book as a study text.

Our review copy was supplied by Hicks Smith and Sons Pty. Ltd., 301 Kent Street, Sydney, who have copies available from stock. (J.H.)

★ ★ ★

TV FAULT FINDING, Data Book Series No. 5. Edited and revised by J. R. Davies. Published by Data Publications Ltd., 57 Malda Vale, London, W.9. Stiff paper covers, 8½ x 5½ in, 124 pp, numerous illustrations. Price in U.K. 8/6.

It is obvious that a book with a mere 124 small format pages can lay no claim to being a comprehensive work on TV servicing, and the editor acknowledges this fact in a short introduction. He says he assumes the reader to have already a basic knowledge of TV theory and practice, and in view of this the early part of the text, which is an elementary discussion of TV standards, seems rather unnecessary. From there on the book contains a considerable amount of useful data on faults which commonly develop, the visual and/or audible symptoms, and the causes and cures. The text is clearly and concisely written, and is illustrated with numerous diagrams and photographs of fault symptoms seen on the picture tube.

The value to the Australian reader is diminished by the necessity to cover both the 405 and 625 line standards now used in U.K. but the greater part of the text is applicable to both systems.

Chapters are entitled: The RF Stages — Receiver Alignment — Interference — AGC Circuits — TV Aerials — The Timebases — Power Supplies — Cathode Ray Tubes. There are two appendices entitled Transmission Frequencies and Fault Finding Guide. The former has no interest for the Australian reader, as it lists the channel frequencies used in U.K., which differ from those in use here. The latter is a tabulation of 50 common faults, listing symptoms, probable causes, and the relevant section(s) of the text.

While there are obviously many better books dealing with this subject, this modest work could well find a place in the bookshelf of the person who is not himself an electronics engineer but likes to do his own servicing, and the modest price in U.K. leads one to believe that it is likely to sell here for well under \$2. The review copy came direct from the publishers, and we have no information on availability or selling price in Australia. No doubt the larger booksellers will be in a position to supply in due course. (H.A.T.)

LITERATURE—in brief

MINIWATT DIGEST, Vol. 6, No. 7 (May 1967), features a single article entitled "An experimental alphanumeric store and display unit using an electromagnetic cathode-ray tube." The display system enables digitally encoded characters, stored in four registers, to be displayed as dot-delineated patterns on the screen of a conventional 11in TV picture tube. The circuitry for achieving the storage, transfer and the inputting of new information makes up the larger part of the system. This is described after a discussion on the methods of character display.

Miniwatt Digest is published by the Miniwatt Electronics Division of Philips Electrical Pty. Ltd., 20 Herbert Street, Artarmon, N.S.W. Subscription rates are \$3 post free per volume, and 50c post free for a single copy.

TELECOMMUNICATION JOURNAL, Vol. 34, No. 5 (May, 1967), the monthly review of the International Telecommunication Union (ITU), features an article by J. Uecker on the telephone exchange of the ITU; and a study by A. Kachel on "Compatible single-sideband transmission for amplitude-modulation sound-broadcasting services." Some information is given on the SEACOM Pacific submarine cable and on "Telecommunications in modern meteorology." The series describing ITU conferences continues with the International Telegraph Conference held in Vienna, 1868, and the International Telegraph Conference held in Rome, 1871-1872.

Telecommunication Journal is published in separate editions in English, French and Spanish. Subscription rates are: one language, 20 Swiss francs a year; two languages, 30 Swiss francs a year; three languages, 40 Swiss francs a year. Price for single copies is 2 Swiss francs. The journal can be obtained from the Publications Service of the International Telecommunication Union, Place des Nations, 1211 Geneve 20, Switzerland.

MINIWATT ELECTRONICS DIVISION has published short-form catalogues listing semiconductors and valves. The semiconductor catalogue gives essential characteristics and outlines of available types including silicon and germanium transistors, integrated circuits, zener diodes, silicon power diodes, silicon controlled rectifiers, microwave mixer diodes and tunnel diodes.

The valve catalogue lists characteristics and base connections of valves and picture tubes for TV receivers, audio applications and mains-operated radio receivers. Inquiries to: Philips Electrical Pty. Ltd., 20 Herbert Street, Artarmon, N.S.W.

BELLING AND LEE (AUSTRALIA) PTY. LTD. has published its 1967 electronic components catalogue. This gives essential details of a wide range of components, including screened and unscreened plugs and sockets, terminals, and circuit protection devices. A miscellaneous section includes TV accessories, interference filters, and lists overseas agencies held by Belling and Lee. A trade price list is also available. Inquiries to the head office at Canterbury Road, Kilsyth, Vic., or to 170 Burwood Road, Burwood, N.S.W.

STC COMPONENTS REVIEW, Vol. 4, No. 6 (June, 1967) includes information on the following products: types 24 and 25 relays; thermistors; Lorenz hi-fi loudspeakers; VHF power transistor summary; data on 2N3553 VHF-UHF power transistor. The application note describing VHF-UHF power transistor amplifier design is continued. Inquiries to Standard Telephones and Cables Pty. Ltd., Moorebank Avenue, Liverpool, N.S.W.

TECHNICAL NEWS BULLETIN, Vol. 51, No. 5 (May, 1967), published in the U.S.A. by National Bureau of Standards, includes the following articles: NBS Develops Computerised Industry Model; Ad Hoc Cryogenic Committee Formed; Frequency Range of Calibration Vibrators Extended; Thermal Convection During Crystal Growth; Shock Tube Produces Controlled Pyrolysis. Subscription rate for the publication is \$US2.25. Inquiries to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402, U.S.A.

RADIOTRONICS, Vol. 32, No. 1 (February, 1967), published quarterly by the Amalgamated Wireless Valve Co. Pty. Ltd., features the following articles: Second breakdown effects of transistor applications; Design trade-offs for RF transistor power amplifiers; Practical and usable methods for evaluating thermal runaway in transistor audio output stages. Also included is infor-

PLAN YOUR FUTURE

CHOOSE a career in the field of **ELECTRONICS*** — the Nation's most progressive and fastest expanding industry.

✱ Advancement in this modern science demands technical ability, a sound knowledge of basic principles and applications.

YOU can master the subject by training at the **MARCONI SCHOOL** and be ready to grasp the opportunities that occur in the three fundamental branches of Radio-technology.

KNOW WHERE YOU'RE GOING

A = APPLIED SERVICING

Comprehensive training in the maintenance and repair of radio and television receivers offers substantial rewards to competent technicians. Marconi School training covers all aspects of radio and television receiver circuit applications, practical exercises in fault finding and alignment procedures.

B = BROADCASTING

A thorough and practical grounding is available to students in broadcasting transmitter performance standards and maintenance techniques, with individual instruction in station operation and studio control and testing.

C = COMMUNICATIONS

Combines all the foregoing, together with radio aids to navigation, mobile telephony, marine service application and international wireless telegraph regulations, qualifying the successful student for the Commonwealth Government Certificate of Proficiency and the Marconi School Diploma in Radiotechnology. Classes are conducted at 21 Pier Street, Sydney (at the foot of Goulburn Street).

Daily: 9.30 a.m. to 4.30 p.m.

Evenings: 6 p.m. to 8.30 p.m.

or by Home-Study Courses (except practical instruction on equipment).

STUDY NOW

Student enrolments close 9th October, 1967. Classes commence 2 days later. Send for training syllabus. There is no obligation.

NAME.....

ADDRESS.....

the **MARCONI SCHOOL** of wireless

G.P.O. Box 2516, Sydney

A Service of Amalgamated Wireless (Australasia) Ltd.

mation on new products: bi-planar image tube RCA-C33012A, and beam power tube RCA-Dev. No. A2814. Radiotronics is available at a cost of 50c per copy from the Sales Department, Amalgamated Wireless Valve Co. Pty. Ltd., Private Mail Bag, Ermington, N.S.W.

PROCEEDINGS of the 1967 National Association of Broadcasters Engineering Conference held April 3-5, 1967 will be available from the publishers, TAB Books, 18 Frederick Road, Thurmont, Md. 21788, U.S.A., from August 30, 1967. The volume includes the 23 technical papers presented at the conference, plus a transcript of the Government/Industry Panel discussion. The "Proceedings" has 224 pages, 8 1/2 in x 11 in and is comb-bound for convenient use. The special prepublication price, \$US7.95, applies until September 30, 1967: after that date the regular list price is \$US10.

MANUFACTURERS SPECIAL PRODUCTS PTY. LTD. has available a leaflet giving advance information on the MSP speaker type 12UA designed especially for guitar amplifiers. This speaker is claimed to represent a breakthrough in design for this application. Other leaflets which can be obtained from MSP describe the following products: Hi-Flux standard speakers; 8TAX Hi-Flux twin-cone speaker; car radio replacement speakers; MSP shelf enclosure design; MSP column enclosure design; Hi-Flux hi-fi vented enclosure. Inquiries to the manufacturers at 47 York Street, Sydney, N.S.W.

STANDARDS ASSOCIATION OF AUSTRALIA has issued two Australian standard specifications laying down general performance characteristics and other requirements for sound level meters. The new standards, AS Z37 covering general purpose meters and AS Z38 covering precision meters, are virtually identical with recommended standards of the International Electrotechnical Commission.

The two standards describe instruments

that provide a practical combination of characteristics aimed at achieving a high degree of stability and accuracy. Among specified characteristics are the frequency range to be covered, microphone sensitivity, accuracy of the indicating instrument, various effects on the amplifier, and calibration and sensitivity of the meter. Each standard sets out the information which must be given on the descriptive leaflet accompanying the sound level meter. Copies of AS Z37 and AS Z38 are available from the various offices of the Standards Association for 80c and \$1 a copy respectively.

INTERNATIONAL TELECOMMUNICATION UNION has published the "General plan for the development of the international network in Asia and Oceania, 1965-1970." This plan was prepared at a meeting held in Melbourne from September 7-19, 1966. It is the work of the Joint Plan Committee for Asia and Oceania, one of four regional Plan Committees, of the International Telegraph and Telephone Consultative Committee (CCITT) and the International Radio Consultative Committee (CCIR).

The book of the Melbourne Plan, 1966, is published in a single three-language edition (English, French and Spanish). It comprises: tables of forecasts of international telephone, telegraph and telex traffic; maps of existing and planned international routes; maps of existing and planned earth stations for satellite telecommunications; forecasts of telephone, telegraph and telex circuits drawn up at the meeting, in particular for meteorology and civil aviation; the telephone and telex numbering plan for Asia and Oceania.

I.T.U. has also published "General plan for the development of the International Network in Africa," the last of the five volume series covering the whole globe. Inquiries should be addressed to the Sales Service, International Telecommunication Union, Place des Nations, 1211 Geneva 20, Switzerland.

STANDARDS ASSOCIATION OF AUSTRALIA has issued an Australian standard AS Z46 setting out basic information on the metric system in its most recently developed form, the Systems International d'Unites (SI), and giving the names of the principal units.

The standard points out that the SI was adopted by the 11th General Conference on Weights and Measures in 1960, and that SI units have begun to replace older systems in several branches of science and technology. In addition to giving the names of units, the standard includes descriptive definitions of basic units and of derived units, e.g. force, energy. It also sets out values of some British units in terms of SI units. Copies of standard AS Z46 may be purchased at the various offices of the Standards Association for 60c each.

STC COMPONENTS REVIEW, Vol. 4, No. 5 (May, 1967) has information on the following: general purpose NPN silicon planar epitaxial transistors 2N2217-22; rectifier diodes EM400 series; interlocking plastic trays; Beyschlag deposited carbon film resistors; voltage variable capacitance diodes. Also included in this issue is a continuation of an application note on VHF/UHF power transistor amplifier design. Inquiries should be addressed to Standard Telephones and Cables Pty. Ltd., Moorebank Avenue, Liverpool, N.S.W.

TECHNICAL NEWS BULLETIN, Vol. 51, No. 4 (April, 1967), published by National Bureau of Standards in the U.S.A., includes the following articles: FOSDIC IV reads microfilm weather data for computer; Chemical bonding gives stronger dentures; Data obtained for optical design; Research associate program expands; Photolysis of nitrogen compounds; Photodetector uniformity increased. Subscription rate for the publication is \$US2.25. Inquiries should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C., 20402, U.S.A. ■

ANNOUNCEMENT



ZEPHYR PRODUCTS PTY. LTD.

70 BATESFORD ROAD, CHADSTONE, VICTORIA




H.E. Herrold Pty. Ltd., 123-125 Charlotte Street, Brisbane. Qld. Homecrafts Tasmania, 199 Collins Street, Hobart. Tas. Newton McLaren Ltd., 82 Gilbert Street, Adelaide. S.A. Atkins (W.A.) 894 Hay Street., Perth. W.A.



ARE PLEASED TO ADVISE THEIR APPOINTMENT
AS SOLE AGENT IN AUSTRALIA FOR

PLUGS & SOCKETS

IN-LINE CONNECTORS



CREI TRAINING COURSES

"... of a high standard"

The Capitol Radio Engineering Institute, in Washington, D.C., U.S.A., was established in 1927 and it is now stepping up the promotion of courses in this country, as well as New Zealand. A short resume of the courses available and other aspects relating to the programs, are given below.



Like other systems of instruction, home study courses have been developed to a high standard and it is now possible to study successfully, a wide variety of subjects.

Courses for home study now make it possible for a student to take up a course of his choice, start a course at any time and proceed at a speed which fits in with his particular circumstances.

The Capitol Radio Engineering Institute offers home study programs dealing with a wide range of aspects of electronics. Each program is identified by a number and various programs are combined to form a course of study, to suit the needs of the individual student.

The Base Program 200—Electronic Engineering Technology—provides a comprehensive coverage of the theory and application of advanced electronics in relation to components, systems and devices. Because those who move ahead in any engineering organisation must possess qualities of leadership, Program 200 includes a series of assignments dealing with the principles of engineering management. These are interspersed with technical assignments. Program 200 is a basic foundation for the Major Elective which the student may choose and so lead to specialisation in one of the following fields.

Major Elective 300 — Communications engineering—deals with the fundamentals of communications and communications systems.

Major Elective 400—Aeronautical and Navigational Engineering. In this program, the principles of electronics are covered as they apply to systems currently used in navigation of military, airline and space vehicles.

Major Elective 500—Television Engineering—covers the principles and design of transmission and receiving equipment, including colour television.

Major Elective 600—Servomechanism and Computer Engineering — is recommended for those seeking specialisation in automation, radar and navigational control systems.

Major Elective 700 — Nuclear Instrumentation and Control. Nuclear physics, reactor technology, heat and thermodynamics, automatic control and instrumentation are the study areas covered here.

Major Elective 1100 — Aerospace Radar Engineering — deals with the applications of radar in aerospace, in both air surveillance and air traffic control.

Major Elective 1200 — Space Data Systems — covers data acquisition, processing and recording, analog and digital computers, computer design and components.

Major Elective 1300 — Spacecraft Tracking and Control — provides the student with an overall appreciation of space technology problems, such as the environment, orbit calculation and prediction, and with inertial guidance fundamentals.

Major Elective 1400 — Radar and Servo Engineering — is planned for men who wish to specialise in modern radar systems.

Major Elective 1500 — Communications Theory — covers such important areas of

knowledge as information theory, micro-electronics, modulation theory, Masers and Lasers, and infrared techniques.

One of the foregoing Major Electives, together with the Base Program 200, constitutes a complete Diploma Program in its own right. However, if the prospective student has had less than two years of practical experience with modern electronic equipment, or if he feels that he needs a review of arithmetic, algebra, etc., it may be necessary or desirable for him to take Program 100. This is an Introduction to Electronic Engineering Technology. Program 100 is not available separately.

Option M — Contemporary Mathematics — is designed to be combined with any Diploma Program and is recommended for students who wish to build upon the mathematics already studied in the basic program. It is not available separately.

In addition to the Diploma Program in Electronic Engineering Technology, just covered, there are three more Diploma Programs available.

Program 2000 — Nuclear Engineering Technology — covers the technical knowledge needed for a career in the application of nuclear power or in nuclear instrumentation. If necessary, Optional Program 100 may be taken as preparation for the main program. Program 2000 includes the series of assignments dealing with the Principles of Leadership.

Program 2500 goes into such subjects as: Introduction to Analog and Digital Computers, Data Processing, Logic, Logical Design, Analog to Digital Conversion, Problem-Solving Techniques, etc. Optional Program 100 may also be taken with Program 2500, which also includes the series of assignments on the Principles of Leadership.

Program 2600 has been developed to help men who work in electronics get the additional knowledge they need to move successfully into this field. This program covers such subjects as: Relays and Switches, Introduction to Thermodynamics, Applications of Light Energy, Ultrasonic Principles and Applications, etc. Program 2600 also includes the series on the Principles of Leadership and Optional Program 100 may also be taken.

Two Certificate Programs are also available separately. Program 2200 covers the Principles of Leadership. This program consists of 20 assignments and includes such subjects as: The Behaviour of Leaders, Leadership Through Communications, The Art of Interviewing, Counselling, Decision Making in Management, Creativity and Problem Solving, Leadership and Helping Others Grow, Scientific Management Concepts, etc.

Program 2300 is designed for students not enrolling for a Diploma Program. This Program treats such areas as: Differential and Integral Calculus, Determinants, Complex Variables, Fourier Transforms and Bessel Functions, Network Analysis and Synthesis, etc.

Finally, there are two Special Programs. Special Program 800 gives a broad coverage of electronics for qualified engineers who have not had previous experience in electronics. This program must include one

of the Major Electives, which have already been listed as available with Program 200.

Special Program 900 is an up-dating program covering the modern developments in electronics, and is intended for engineers already qualified. Like special program 800, one of the Major Electives must also be taken.

At the completion of any C.R.E.I. Diploma Program, the student will qualify for his diploma if he has earned passing grades in all the assignment examinations. In addition, he must successfully complete a proctored comprehensive final examination covering his entire program. This rather stringent requirement adds real value to the C.R.E.I. Diploma.

The writer is well on the way through one of the diploma programs and this places him in a good position to evaluate the material which C.R.E.I. presents to its students.

All the program material is prepared by the staff of C.R.E.I. The level is very high and may be considered as "college level." With the exception of a book of mathematical tables, slide rule and valve data books, which are provided where necessary, all the material to be studied is included in durable, loose-leaf spring-back binders. Most binders contain seven assignments.

The printed material is well laid out, so the diagrams, tables, etc., are as near as possible to the relevant text. The fact that other texts do not have to be referred to, also makes study easier.

The texts are reviewed as often as is necessary and this ensures that the material presented is up-to-date. Such subjects as Basic Semiconductor Physics and various aspects of transistors, are kept abreast of the times.

As there are both good and not so good lecturers, so there are times when the printed page is not as well written as may be desired. Not surprisingly, the C.R.E.I. papers have their share of sections which might have been better phrased or ordered.


However, when a student gets into difficulties with an assignment, he has only to seek help from the C.R.E.I. staff and a prompt explanation is sent to the student, which sets matters right again.

Should a student have any comments or constructive criticism of any papers, this is welcomed by the C.R.E.I. management and staff.

Considering the study material overall, the writer is of the opinion that it is of a high standard, and has no hesitation in commending it to prospective students. These remarks apply in equal force to the assignments on the Principles of Leadership. These papers meet a great need for the guidance of people who are qualified in a particular field but do not have much idea of handling and guiding people in their charge.

Full details of all programs are given in well prepared catalogues. Readers who are interested may obtain full information, including fees for the various programs, by writing to the representative for Australia and New Zealand: C.R.E.I., Box E8, St. James P.O., Sydney, N.S.W. (I.L.P.)

A Range of Miniature Plug-in Relays



Suitable for electrical and electronic applications.


Open types also available.

Voltages: 6-120V D.C.

6-240V A.C.

Contact rating up to 5amp 240V A.C.

Prices from \$3.00 each



ASSOCIATED CONTROLS PTY. LTD.

14 ENTERPRISE AVENUE, PADSTOW, N.S.W.

Telephone 77-8793, 77-4405

Vic.

Eastern Instrument Services Pty. Ltd.,
38 Milton Parade,
MALVERN S.E.4 Phone. 20-1156.

Qld.

Instrument Engineering Pty. Ltd.,
32 and 40 Annerley Road,
WOOLLOONGABBA. Phone 91-5111.

Agents:

S.A.

Teknis Pty. Ltd.
Box 45,
LOWER MITCHAM. Phone 76-3224.


Austral Lighting Pty. Ltd., Higgs Street, BREAKFAST CREEK. Phone 62-2811



SWAN SW350

The most popular choice in ALL BAND TRANSCEIVERS

EQUIP YOUR HOME STATION WITH TRANSCEIVER POWER SUPPLY AND MIKE FOR \$611.80



Look at what you get for your money, all modes of operation, AM, CW, 140 watts, SSB 400 watts PEP., AALC, AVC, velvet-touch two speed vernier dial with direct readout, large clearly calibrated cathode meter large clear S meter, RF, and AF, gain controls, large range PI coupler with fine and coarse adjustment, 20 ohms to 300 ohms resistive, ceramic VFO anti drift coils, and anti click circuitry. Extra good engineering with super smart appearance and don't forget all the optional extras that can be added later. Extra VFO, station control unit, opposite side band, VOX, etc.

AUSTRALIAN DISTRIBUTORS & SWAN WARRANTY STATION

W. F. S. ELECTRONICS SUPPLY CO.
227 Victoria Rd., Rydalmere, N.S.W.
638-1715, 638-1355.

ATLANTIC RADIO
36 Oxford St., Woollahra, N.S.W.
31-7811.

AMATEUR BAND NEWS AND NOTES

Australis OSCAR A — Technical Details

The Australis amateur radio satellite is now in the U.S.A. for final testing prior to being launched into orbit

By Pierce Healy, VK2APQ*

After formally delivering the Australian amateur satellite, Australis OSCAR A, to the project OSCAR organisation, Richard Tonkin, Owen Mace and Paul Dunn, returned to Sydney en route to Melbourne on June 17th.

During their stay in the United States they had detailed discussions with the OSCAR personnel on the design and operation of the Australis satellite. They also discussed plans for a second Australis satellite designed to carry a repeater.

They all expressed their appreciation of the hospitality that was extended to them and the opportunity they had to inspect a number of Aerospace Companies and facilities to observe first hand the latest satellite techniques which will undoubtedly assist in later Australis projects.

They reported that the package arrived in perfect condition and to the great amusement of the Americans, as well as the Australians present, was found to be prominently labelled MADE IN AUSTRALIA and had a large sign reading "God Save the Queen." The satellite was thoroughly checked out in the OSCAR laboratory and found to be operating perfectly.

The design and construction of the satellite was highly praised by those who inspected the package. Some minor improvements in construction techniques will be considered prior to launching. If necessary, one or two back-up modules will be constructed and sent to the United States.

The technical details of the package have been supplied by Owen Mace, and appear on page 157.

REGION 1 NEWS

From the bulletin of Region 1 of the International Amateur Radio Union, received by courtesy of John Clarricoats G6CL, come several items of interest.

Concerned about possible attacks on amateur radio at future I.T.U. conferences and believing that many telecommunications authorities are not sufficiently familiar with amateur radio and its accomplishments, the American Radio Relay League two years ago contracted with the Stanford Research Institute to conduct an appraisal of the service.

This has now been done and, because the A.R.R.L. believes the report can be useful in explaining the importance and value of amateur radio to government officials around the world, two copies have been sent to each member society of the I.A.R.U. One copy is intended to be presented to the appropriate official in government telecommunications.

*News and notes of Divisional and Club activities submitted for inclusion in these columns should be forwarded direct to Pierce Healy, 69 Taylor St., Bankstown, N.S.W.

Although rather extensive, the importance of the report cannot be over-estimated. The title refers to amateur radio as "an international resource for technological, economic, and sociological development." It is considered that the Stanford report is of outstanding merit as a contribution to the literature of amateur radio.

ITALY

The new Italian amateur licensing regulations came into force on January 18, 1967. Most of the changes are favourable but one is retrograde. Additionally, two old problems remain unsolved.

On the credit side a simplified procedure for obtaining a licence has been introduced and the morse code examination has been reduced to 40 characters a minute for all three classes of licence. The age limit for obtaining a licence has been reduced from 18 years to 16 years, the validity of licences has been increased to five years and the input power allowed to holders of the 1st class licence has been increased from 50 to 75 watts.

When the need arises, amateur stations will be authorised by the Ministry of Posts and Telecommunications to handle emergency communications.

On the debit side operation on frequencies between 146MHz and 21GHz is no longer authorised but as the new Act gives the Ministry power to modify the allocation of frequencies it is hoped that a few channels in the 432MHz band will be allocated to Italian amateurs. The previous limitation of two narrow channels totalling 34KHz in the 3.5MHz-3.8MHz band is to continue.

To the great disappointment of many Italian amateurs the new regulations make no provision for mobile licences, neither do they permit a licence to be issued to a foreigner. However, a foreign amateur can obtain an operator's licence which authorises operation from the station of any licensed Italian amateur.

BELGIUM CONVENTION

The third Annual International Convention organised by the Knokke section of the U.B.A. with the support and in the name of the Belgium national society, will take place in the Casino, Knokke, on September 15, 16 and 17, 1967.

The trip to Knokke will be planned on the lines of an international amateur radio mobile rally, starting from London. Paris, Brussels, Amsterdam, Bonn, Geneva and other European cities. A competition for the "Grand Prix d'Honneur du Casino de Knokke" will take place on Saturday, September 16, followed on Sunday, September 17, by a VHF/UHF meeting under the chairmanship of R.S.G.B. council member Mr J. Foster, G2JF.

Several well-known amateurs will attend the meeting as guest lecturers. Further information on the convention can be obtained from Mr Lucien Vervaecke, ON4LV,

Lippenslaan 284, Knokke 1, Belgium, who is secretary of the organising committee. Victor Claeys, ON4UM, is in charge of public relations.

MALTA

Among the overseas magazines that were received during the past month was a new one entitled "SIGMA," the official monthly bulletin of the National Radio Club, Malta. One thing in common with most other clubs and societies is the plea for members to take an active part in the work of running the organisation. Notice was given of the annual meeting, set down for Sunday, April 16, 1967, at 9.30 a.m.

The bulletin also carried an article giving helpful hints to S.W.L. members, on the art of QSL'ing, including an example report. The club is also preparing details for a DX competition.

For those wishing to contact the club, the address is: The National Radio Club, 35 St. Anthony Street, Balzan, Malta, G.C.

EUROPEAN FOX HUNTING

The president of the Central Radio Club of Czechoslovakia, Milos Svitak, is the chairman of a special committee set-up to organise the 1967 Fox Hunting championships which are expected to take place during the last week in September in an area about 50 miles south of Prague.

The championships will be organised by the C.R.C.C. in accordance with rules circulated, plus any minor modifications the international jury may decide upon prior to the start of the first event. Plans are being made by the organisers to provide all who attend the championships with the opportunity of visiting places of historic and cultural interest in Czechoslovakia as well as industrial centres in that country.

CYPRUS AMATEUR RADIO

The Cyprus amateur radio society have become a subscribing member of the Region 1 I.A.R.U. The society has 25 members, of whom 15 were licensed as at January 1st 1967. The president is Major Cyril Collins ZD4SC and the secretary is R. H. Etherington.

A single-class licence is available to those who can pass the necessary examination, including a 12 word per minute Morse Code test. The licence fee is equal to \$A5.00 but a separate station licence is required, for which the initial fee is equal to \$A6.00. Thereafter the annual fee is equal to \$A3.00.


Maximum DC input power is 150 watts on all frequencies generally available to amateurs in Region 1. Amateur television is permitted but mobile operation requires special authorisation. Third party traffic is prohibited.

HERTZ or CYCLES

Standardisation on the use of the term Hertz (Hz) as the unit of frequency is not restricted to telecommunications. The I.T.U. General standardisation organisations, such as the International Electrotechnical Commission (I.E.C.) and the International Organisation for Standardisation (I.S.C.) have, in close liaison with the Commission for Symbols Units and Nomenclature (S.U.N. Commission) of the International Union of Pure and Applied Physics (I.U.-

Custom Built . . .

A phrase that means equipment specially tailored to your needs whether it is a console in timber or sheetmetal or a bracket to hold a component.




We are specialists in close tolerance work for the communications industry in light engineering, sheetmetal, timber or plastics. If your problem involves one or more of these fields, it will pay you to see us—
WE COULD HAVE THE ANSWER.

SCEL PTY. LTD.

BOX 63 NIDDRIE
TELEPHONE: 379-7743

A DIVISION OF SCOPE LABORATORIES

BULLA ROAD, AIRPORT WEST, VICTORIA



NEW IMPROVED
30 WATT


12v. All Transistor P.A. AMPLIFIER

No. 598—Complete Kit of parts to smallest screw. \$57. No. 656—Wired ready to operate, \$60. Freight extra. Size: 6in w. x 3in h. x 8 1/2in d. Weight 6 1/2lb.

MAGNETIC STEREO PRE-AMP

In 5Mv. out 500Mv. Bass and treble 18 D.B. No. 700C. \$29. Wired ready for use. \$31. Postage 30c.

COILS & IF's 455 Kc
Aer. R.F. osc. and IF's . . . \$1.70 ea.
Ferrite Aer . . . \$2.
No. 265 Universal Tape OSC coil, \$4.
Postage 10c. Write for details and price



STEREO

MULLARD 12 TRANSISTOR

5 watt x 5 watt.
Distortion 1% of 1%. Frequency response 30 cycles to 18Kc. Output 15 ohm speaker.
12in lg. x 7in d x 4in h.
Pre-Amplifier kit No. 616C \$26.00
2—5w Main Amplifiers No. 675C . . . \$34.00
1—5w Power supply No. 681C \$16.00
Steel chassis, plated No. 649 \$ 2.30
COMPLETE KITS, nuts, screws, etc. No. 471C . . . \$78.50
Wired and tested, No. 471D, extra \$5.00. Freight extra. Write for blue-print list of parts.

R.C.S. PRINTED CIRCUITS

For all R. & M., E.A., Mullard, Philips and other designs. Clearly coded. White letters and numbers, easy assembly and service, polished and resined for easy soldering. With blue-print parts list.

SPECIALS: To your drawing under 6in x 6in. \$4.

New Printed Circuits

700 Magnetic pre-amp \$3
703 Mull. 7W. stereo \$3
704 Pre-amp 67P3 \$2.50
707 10W stereo. 67. P3 \$2.50
708 10W. amp. 67. A3 \$2.50
709 Pre-amp 67P5 \$2.50

Recent Designs

Part No. \$2.50
675 Hi-Fi 5W. amp. \$2.50
684 Pre-amp. 65P16 \$2.50
685 Pre-amp. 65P12A \$2.50
686 Pre-amp 65P12B \$2.50
690 Philips 10W. amp \$2.50
695 Electronic Flash. \$2.50

Write for full list. Immediate despatch. Postage 10c.



Postage \$1.

R.C.S. COMPLETE DO-IT-YOURSELF KITS

Peak reception, low price. No expensive test equipment. Everything fits. 1964 RF Transporta 7. Complete kit—No. 640 . . . \$42.50
Portable car radio, identical to 640 above, plus extra switch and car coil, etc. No. 642 . . . \$46.00
(Write for booklet on 640 and 642.)

HI-FI BROADCAST TUNER UNIT 4 TRANSISTORS—HI SENSITIVITY

R.F., mixer, I.F., pwr. dectr. stages, adjustable aerial coupling. Complete as illust., wired and tested with 461 dial, knobs and switch pot. No. 474, \$31. Complete kit of parts for above, No. 474C, \$30. postage 40c.



WHISTLE FILTER
for above, No. 128, \$4 Post. 10c.

IMPROVED BATTERY SAVER KIT

4 1/2, 6 or 9 volts. Replaces transistor battery power input 240 volts A.C. Maximum milliamps 100. Hum-free operation. Size 3 1/2in l. x 2 1/2in w. x 1 1/2in h. No. 657, \$6.50 (post 10c).



PERSONAL PORTABLES

Range 30 miles, 200 2 TRANSISTORS with short aerial and earth. Ear-piece only, no speaker. Wired ready to use, No. 666D, \$10. Postage 20c.



Do-it-yourself kit, No. 666C, \$9.00.

1 TRANSISTOR—1 DIODE
582 Do-it-yourself kit . . \$5, post. 10c.
593 Wired ready to operate, \$4, post. 10c.

DIAL KITS

Scale gold with white letters. Size 6 1/2in. x 2 1/2in. to match.

- No.459 300pf gang, \$4.00
 - No.461 200pf gang, \$4.00
- Post 20c.

NEW AUDIO AMPLIFIER

4 transistors. 1/2 or 1 watt. Small size: cabinet 3 1/2" x 2 1/2" x 1 1/2" plastic. Suitable crystal P.I. up, intercom., microphone radio, etc. (9 volt)



Do-it-yourself kit 665, \$10 (Post 10c).
Wired ready for use, 665D; \$11.50.

NEW TRANSISTOR PREAMP KITS:

SIZE 3 x 2 x 1 1/2 req. for Stereo.
LOW IMP. Input 2 trans. 672C \$6.50
Wired ready for use, 672D . . . \$8
HIGH IMP. silicon 2 tran. 680C \$6.50
Wired ready for use, 680D . . . \$8
HIGH IMP. silicon 3 tran. 682C . . \$8
Wired ready for use, 682D . . . \$9.50
Postage 10c each. Write for data.

R.C.S. Order by Mail Order, Postal Note or Money Order (add post.), direct to—
RADIO PTY. LTD., 651 FOREST ROAD, BEXLEY, N.S.W., 58-3491, 58-5385

P.A.P.), decided to use the term Hertz. The decisions of the Conference General des Poids et des Mesures (C.G.P.M.) have thereby been followed completely.

For full information on all symbols, reference should be made to I.E.C. Publication 27, "Letter Symbols to be used in Electrical Technology" 1966 Edition, obtainable from the Central Bureau I.E.C., Geneva.

JAMBOREE-ON-THE-AIR

Since preparing the notes which appeared last month, on the Jamboree-on-the-Air, a copy of the report of the 1966 activities prepared by the Boy Scouts World Bureau, in Ottawa, Canada, has been received from Noel Lynch, Australian national organiser of J.O.T.A.

The report summarises the reports received from all over the world from scouting groups who participated in the event. It was very pleasing indeed to see mention made of the article that appeared in these notes in the October, 1966 issue and the inclusion among news cuttings from all over the world, used as a composite illustration on the cover, a full page of these notes.

In the general summing-up, the activities of the Australian scouting groups and amateur operators were highly praised and photos of a New South Wales and a Victorian were included in a selection of world-wide pictures. Several countries reported on special station call-signs allocated by the local communication authorities, for use during the Jamboree weekend.

Countries known to have taken part in the 1966 J.O.T.A., and, where known, the number of stations operating in each country were given. These were:

Algeria	1	Italy	1
Antigua	—	Jamaica	1
Argentina	9	Japan	8
Australia (including Papua and New Guinea)	450	Libya	—
Austria	80	Luxemburg	2
Belgium	1	Malta	3
Bermuda	—	Malaysia	2
Bolivia	3	Maldives Islands	—
Brazil	3	Mexico	26
Canada	400	Mozambique	7
Canary Islands	—	Netherlands	6
Ceylon	6	Netherlands	—
Chili	—	Antilles	—
Columbia	58	New Zealand	—
Costa Rica	—	Nicaragua	—
Denmark	4	Nigeria	5
Dominican Rep.	—	Norway	43
Ecuador	2	Pakistan	—
Finland	5	Panama Republic	—
Fiji Islands	—	Paraguay	—
France	1	Peru	3
Germany	10	Philippines	5
Ghana	1	Portugal	4
Great Britain	194	Rhodesia	2
Greece	1	Salvador	—
Guatemala	8	South Africa	128
Hong Kong	—	Singapore	1
Iceland	1	Spain	1
India	4	Sudan	1
Iran	—	Sweden	12
Ireland	11	Switzerland	5
Israel	1	Trucial Oman	—
		U.S.A.	1500
		Uruguay	7
		Venezuela	22

Despite the fact that the world-wide "CQ" DX Contest was held on the same weekend, thereby possibly reducing the number of stations that participated, the effect of this was far less than was expected.

A total of 453 scout groups and 59 girl guide companies were officially listed as having participated in Australia.

The success of any activity can only be judged by the information received in reports from participants. Therefore all participating groups are requested to send in reports on the J.O.T.A. weekend together with photos and press coverage of the event. Address them to Mr N. Lynch, Australian National Organiser, J.O.T.A., Boy Scouts Association, Box 50, P.O. Broadway, Brisbane, Queensland.

WIRELESS INSTITUTE ACTIVITIES

All six divisions of the Wireless Institute of Australia have ratified in full the recommendations of the Federal Council, made at the 21st Federal Convention, held in Hobart last Easter.

The most important subject recorded in the minutes of the convention relating to the overall administration of the institute, is the final agreement on several matters regarding the new federal constitution.

This agreement will now allow the federal executive to complete the work on the articles of association for the incorporation of the federal body under the Commonwealth Uniform Company's Act. While the full benefits of this move may not at first be apparent, it is considered to be an important step towards future expansion and facilities the Institute as a whole can offer the Australian amateur service.

The present W.I.A. federal constitution has been in operation since 1947 and although changes had been mooted for many years, it was not until 1962 that the matter was opened for formal discussion. The initial discussions highlighted many problems and weakness in the proposals submitted. This situation was further aggravated by the fact that Federal Council met only once each year and also by the varying numerical strength and assets of individual divisions.

In the final agreement, the rights and assets of all divisions will be protected by a collateral agreement between divisions and the federal body, appertaining to certain matters of finance and voting powers of each division.

It will probably be 1968 before all formalities are completed and a new era in the history of the Wireless Institute of Australia will begin. A point of interest is the fact that the W.I.A. is the oldest amateur radio organisation in the world, having been founded in 1910.

NEW SOUTH WALES

The May meeting of the New South Wales division drew the largest attendance of members for several years and could be referred to as a milestone in the activities of the division. A special meeting was called to consider the decision of council that a full time administrative secretary be employed. After many questions had been asked of the division's legal adviser and auditor, the meeting of more than 150 members voted unanimously in favour of the decision of council.

The discussions at the meeting also cleared up a contentious point in the thoughts of some members regarding the power of council to make such decisions, and put them into operation without referring their decisions to a general meeting. Under the constitution, council need only refer such matters as they think necessary for decision at a general meeting.

A unanimous vote of confidence in council was also passed by the meeting.

Subsequent to the meeting, council made the appointment and plans are being completed for the administrative secretary to take up duties and be at the Wireless Institute Centre, 14 Atchison Street, Crows Nest, during specified business hours.

Intending members and those interested in amateur radio will be able to visit the centre for information, while members will be able to avail themselves of the library facilities more readily. Other innovations for the benefit of members are under consideration of council. The appointment will considerably speed up and

BRIGHT STAR CRYSTALS

PREFERRED BY LEADING MANUFACTURERS
THROUGHOUT THE COUNTRY FOR—

ACCURACY - STABILITY - ACTIVITY - OUTPUT



All types of Crystals Available.
Such As DC 11, FT 243 HC 6U CRA
B7G, HC18U, ETC.

TOLERANCES: .0015%, .002%,
.003%, .005% ETC.

Consult us for Crystals for any mobile Radio.
Prices depend on tolerance and frequency required.

DISCOUNT FOR QUANTITY ORDERS

Established 36 Years

AMATEUR AIRCRAFT and ULTRASONIC CRYSTALS also AVAILABLE

Our new Factory employing the most modern equipment allows us to offer you PROMPT DELIVERY for all your CRYSTAL requirements.

DEVOTED EXCLUSIVELY TO THE MANUFACTURE OF

PIEZO ELECTRIC CRYSTALS

Contractors to Federal and State Government Departments

REPRESENTATIVES AUSTRALIA AND NEW ZEALAND—MESSRS. CARREL & CARREL,
BOX 2102, AUCKLAND.

MESSRS. ATKINS (W.A.)
LTD., 894 Hay Street,
PERTH.

MESSRS. A. E. HAROLD
PTY. LTD., 123-125
Charlotte Street, BRISBANE

MESSRS. UNITED
DISTRIBUTORS PTY.
LTD., 175 Phillip Street,
SYDNEY.

MESSRS. LAWRENCE &
HANSON ELECTRICAL
(VIC.) PTY. LTD.,
34 Brisbane Street,
HOBART, and
29 St. John Street,
LAUNCESTON,
TASMANIA.

BRIGHT STAR RADIO

546-5076

LOT 6 EILEEN ROAD, CLAYTON, VICTORIA

546-5076

accuracy \pm 0.1%

Price: \$720

F.O.B. Sydney exc. duty & sales tax

**on specification, performance and value for money
Marconi instruments challenge comparison
with any in the world**

0.1% UNIVERSAL BRIDGE **TYPE TF 1313A**

The trend is towards components of close tolerance – often better than 1%. This new version of Marconi Instruments famous TF 1313 Universal Bridge employs bridge standards of higher accuracy with closely controlled temperature co-efficients, circuits of greater refinement and new balance controls giving improved resolution. The detector sensitivity has been increased so that, on every range, 0.1% error corresponds to an unambiguous meter deflection.

Inductance: 0.1 μ H to 110H in seven ranges


Capacitance: 0.1pF to 110 μ F in seven ranges

Loss (L & C): Q 0.05 to 31 at 1 kHz in two ranges

D 0.0005 to 3 at 1 kHz in two ranges,

giving continuous Q cover from 0.05 to 2000

Resistance: 0.003 Ω to 110M Ω in eight ranges



mi

**MARCONI
INSTRUMENTS**



Engineering Products Division

422 LANE COVE ROAD NORTH RYDE NSW 88 6666

AMALGAMATED WIRELESS (AUSTRALASIA) LTD

MELBOURNE
67 9161

BRISBANE
4 1631

ADELAIDE
51 0111

PERTH
28 3425

LAUNCESTON
2 1804

improve the services to country members and interstate and overseas visitors.

At the general meeting that followed the special meeting, the minutes of the 1967 federal convention were presented for ratification by the Federal Councillor, Pierce Healy VK2APQ. After some discussion the motion was put and carried, there being only five dissenting.

Hunter Branch

There was a good attendance at the June meeting of the Hunter Branch to hear Tony Mullen, VK2ZCT, lecture on his five-transistor transmitter. The transmitter has been designed to fit on a printed circuit board 120mm by 70mm. The unit described is capable of an output of half a watt on the 144MHz band and used the popular 2N3564 transistor.

In addition to the transmitter the companion modulator was described and demonstrated, it being possible to power the complete unit from a dry battery source. By using modern techniques of printed circuit construction it has been possible in this design to reduce space taken to the absolute minimum and still retain a high degree of efficiency.

It is now the custom to screen films of technical interest at Hunter Branch meetings before the general business section. At the June meeting an interesting film "On Solder" was shown and proved to be a most interesting survey on this much neglected subject. The film is another in the series which depicts modern methods of electronic construction.

A full program of lectures and films has been arranged for branch meetings during the remainder of the year. In August there will be a film on valve manufacture to support a series of lectures by branch members.

Hunter Branch meetings are held in Room 6, Clegg Building, Newcastle Technical College, Tighes Hill, on the first Friday of every month excluding January. Visitors, whether Wireless Institute members or not) are always welcome.

Plans are well in hand for the Hunter Branch Field Day to be held on Sunday, October 15, at Bolton Point Park on Lake Macquarie. There will be a full day's program of transmitter hunts and competitions for both licensed amateurs and Youth Radio Scheme members. The charge for admission will this year include lunch. Full details of the event will be given in next month's notes.

WICEN Exercise

A full day's exercise of WICEN equipment was conducted early in June when five mobile stations took part in a simulated search operation in the area west of Newcastle. It was supposed that a party of scouts was lost in the rugged country of Mt Yango region near Wollombi and VHF carphones were used to advantage to relay messages from the search area back to the Central Control at Bolton Point.

Many useful lessons were learned from the exercise and it is hoped that a further operation of this type will be held as soon as the new aerial equipment is erected at the Westlakes Radio Club, Teralba. From field tests conducted, this appears to be the site from which VHF communications can be maintained over a large part of the Central Coast and Lower Hunter region. It is hoped to have a base station in operation from the Club within the next two months.

Central Coast Branch

The feature of the June meeting of the Central Coast Radio Club held on Friday 16, was a most interesting lecture by Mr Lyle Ronalds of Fairchild Aust. Pty. Ltd. Lyle, with the aid of a short film and a number of diagrams, outlined the "Planar process" used in the manufacture of silicon planar transistors.

The mass production of tiny wafers ten-thousandths of an inch square and four-thousandths of an inch thick, prompted many questions from those present. Despite very unpleasant weather, the meeting was very well attended. Visitors are always welcome to meetings of the Central Coast Branch which are held on the third Friday

Weather Service for Small Ships

Sydney's Volunteer Coastal Patrol advise that they have instituted a special hourly weather service for small ships. The service consists of the current weather report as issued by the Weather Bureau, supplemented by a "weather observation" compiled from local weather conditions and reports from patrol boats and other craft in the area. Purpose of the broadcasts is to reduce emergencies caused by inexperienced boating enthusiasts who may not fully appreciate the possibility of sudden weather changes.

The reports are broadcast from the V.C.P. transmitter on the shores of Botany Bay, and are made at 15 minutes past the hour, during weekends and public holidays. Frequency of the channel is 4120KHz.

of each month in the School of Arts, Gosford, commencing at 8 p.m.

QUEENSLAND

SSB or AM? This question has been discussed in relation to the VK4WI news broadcast to members each Sunday morning, on the 7MHz band. Suggestions supporting both modes have been received by the divisional council. However, for a couple of years now 7MHz SSB has given an improved and reliable coverage and at the present time it is not practical to house privately a high-power AM station.

Following discussions at general meetings, and at the state convention at Alexandra Headland, council has decided to implement the motion passed at their June meeting—that the W.I.A. news continue to be radiated from VK4WI on 7MHz SSB, 3.5MHz AM and if possible on 14MHz SSB.

Slow Morse Code practice sessions are conducted by the Queensland division every Tuesday and Thursday evenings between 7.30 p.m. and 8.15 p.m. on 3580KHz in the 80 metre amateur band.

WESTERN AUSTRALIA

The June issue of the VHF bulletin of the West Australian division has a very interesting article about improving receivers for weak signal reception. Several helpful suggestions are given and observation on the fact that even the best commercial type receivers use in general the same type of components as those available to the home constructor. Articles such as this are one of the benefits that membership of the group provides.

The group meets on the fourth Monday of each month in the D.C.A. workshop canteen, 86 Guildford Road, Maylands, Perth, at 8 p.m. Visitors are welcome.

RADIO SOCIETY OF EAST AFRICA

The Radio Society of East Africa, one of the oldest radio societies on the continent of Africa, is the official society for Kenya, Uganda and Tanzania. It has about 70 members of whom 30 held 5Z4, 3H3 and 5X5 calls as at January 1st 1967. The president is Major Roy Jarvis (retd), 5Z4IR, and the secretary Major D. S. Kent. The official address is P.O. Box 5681, Nairobi, Kenya, with branch offices in Dar-es-salaam, Tanganyika, P.O. Box 2387, and Kampala, Uganda, P.O. Box 3433.

A single-class licence is available to any one over the age of 14 years who can pass the necessary examination including a Morse Code test of 12 words per minute. The licence fee is equal to \$A8.50 but a separate licence is not required. All Region 1 bands are available from 3.5MHz to 144MHz with 1.8MHz also available on special application. Maximum DC power input is 150 watts. Maritime mobile operation is allowed with special authorisation but mobile operation and third party traffic are prohibited. The R.S.E.A. maintains an emergency corps.

HAM RADIO SUPPLIERS

(Established 1947)

5a Melville St., Hawthorn, Vic. 86-6465

NEW CITY BRANCH
323 ELIZABETH STREET,
MELBOURNE PHONE 67 4286
(2 DOORS LITTLE LONSDALE ST.)

STEREOGRAM AND TUNER CHASSIS

Medium Fidelity, 4 Valve (2 x 6BM8, 1 x 6N8, 6N7). Aust. made. Straight line dial, mono tuner, 15 ohm, approx. 3 watts per channel output, as new. Fully tested, ideal for use as Tuner or Built-in Unit, etc. PRICE: \$30 inc. NEW valves or \$25 less valves. MSP 6" speakers to suit, \$4.50 ea.

STEREO RECORD CHANGER
Balfour "Princess" STEREO, 4-speed, Automatic 10 record changer. Made in England. Complete with Ronette Ceramic Cartridge. Brand new in carton.

PRICE: \$25, inc. post.

STEREO RECORD PLAYER, as above. Less Automatic Mechanism. Player only, including Cartridge. Manual operation.

PRICE: \$14, inc. post.

STEREO RECORD PLAYER.
Very well-known make. Semi-automatic operation, Ronette Ceramic Cartridge, 4-speed.

PRICE: \$19.50.

WALKIE TALKIES

50 Milliwatt, 4 Transistor, operating frequency 27.240 Mc. Crystal locked Transmitter, 1 to 4-mile range. In open country

PRICE: \$35 a PAIR TO CLEAR.

GRID DIP METER TE-18

360 Kc—220 Mc in 8 bands, plug-in coils, can also be used as a Field strength meter or signal Generator. Few only at this price: \$34.00.

STEREO PREAMPLIFIER

(4 Transistor).

Solid State Phono-Tape Stereophonic Pre-amplifier, Matches most types of Magnetic Cartridges and Tape Heads.

SPECIFICATIONS:

Power Amplitude: 45 db plus or minus 1 db.

Maximum OUTPUT: Plus 11 db in distortion of less than 1 p.c. (900 mV).

Freq. Response: 35 to 18 K/c c/s. Noise Ratio: Minus 45 db or more. Max. Input: Minus 35 db (16 mV). Normal Input: Minus 45 db (5 mV). Power: 240V AC.

Complete in Metal Cabinet.


PRICE: \$19.50.

RADIO HOUSE PTY. LTD.

306-308 PITT ST., 6 ROYAL ARCADE AND 760 GEORGE ST., SYDNEY

SPECIAL PURCHASE

Set of three posted \$3.75



CHROME VAN

German screwdriver and pocket tester.

1. 6-12 volt model auto test.
2. Sparkplug tester.
3. 110-380 volt mains tester.

\$1.25 each



Actual Size

"KEY LITE" \$3.95

Free. One spare mercury cell.

With fob keyring, attractive gold finish case. Simply squeeze. Illuminates car and house locks, etc.

\$4.00 Posted anywhere

MULTIMETER TESTERS

Model RH-50

Modern Design, 33 Micro Amp Meter.

30,000 Ohms per Volt D.C.

13,000 Ohms per Volt A.C.

1 p.c. Multipliers and Shunts used, Printed circuit.

Clear Scale, rugged moulded case.

SPECIFICATIONS

DC Voltages: 0-0.3-1.2-3-12-30-120-300-600-1,200 V at 30,000 Ohms per volt.

AC Voltages: 0-3-12-30-120-300-600-1,200 V at 13,000 Ohms per volt.

DC Current: 0-0.06-6-60-600 mA, 0-12 A.


Resistance: 0-60K-6M-60M (350, 35K, 350K at mid-scale).

Decibels: minus 20 to plus 57 dB (0 dB equals 1 mW, 600 ohms).

Audio Out: Capacitor in series with AC volt ranges.

Short Test: Internal buzzer.


Accessory: 1 pr. heavy test leads.



Price \$31 (£15/10/)
with leather case, \$38.00.
Postage 50c to \$1 extra.

Batteries: 1 (1.5V), 1 (15V).
Size: 3 5-16" x 6 5-16" x 2 1/2"
Weight: 1.4lb approx.

STOCKTAKING SUPER SPECIAL



Multitester model 62-H

RANGES:

DC Voltages: 10-50, 250, 1000.

AC Voltages: 10-50-250, 1000 Volts.

DC Current: 0-50uA ohms, 0-250MA.

Resistance: 0-60K, 0-6mg ohms (300 ohm and 30K at centre scale).

Decibels: -20 to +22DB 20,000 ohm per volt AC, DC.

\$14.00

including Sales Tax
Postage anywhere

LIMITED STOCK ONLY

Model RH-10

RANGES:

DC Voltages: 0-10-50-500-1,000 V at 2,000 Ohms V.

AC Voltages: 0-10-50-500-1,000 V at 2,000 Ohms V.

DC Current: 0-500uA 0-500 mA.

Resistance: 0-10K-1Meg: 60 ohms, 6K ohms at centre scale.

Capacitance: 250uF to 1uF, in two ranges.

Decibels: -20 to plus 36db, two ranges.

Output: 0-1,000 V in four ranges.

Size: 5in x 3 1/2in x 1 1/2in.

Weight: 13oz approx.

Price \$10.75 (£5/7/6)

Postage 50c to \$1 extra.



TRANSISTOR HEARING AID

First Phone Model 3 Transistors
This Hearing Aid is an ultra-modern unit. It incorporates the following outstanding features:

- Ample power and clear tone.
- Compact.
- Precision printed circuit design.
- Magnetic earphone.
- Separate Tone and Volume Controls.
- Standard size torch cell.
- Packed in a presentation case.

New Model \$31.50

Replacement Battery only 12c.

Postage 50c extra.

Model RH-5

- High sensitivity-20,000 Ohms/V DC, 10,000 Ohms/V AC.
- 3in Meter.
- Handy pocketable size.

SPECIFICATIONS

DC Voltages: 0-10-50-250-500-1000 V (20,000 Ohms/V).

AC Voltages: 0-10-15-250-500-1000 V (10,000 Ohms/V).

DC Current: 0-50uA, 0-5-30-500mA.

Resistance: 0-10K, 0-100K, 0-1Meg, 0-10 Meg.


(62 Ohms, 620 Ohms, 6.2K, 62K at centre scale).

Capacitance: 0.0001uF-0.005uF, 0.05uF-1uF.

Decibels: minus 20db to plus 36db in 2 ranges.

Dimensions: (3 1/2in x 1 1/2in x 1 1/2in).

Weight: 15oz approx.



Price \$18 (£9/-/-)

Postage 50c to \$1 extra.

Complete with internal battery, testing leads with prods.

TRANSISTOR POWERED TELEPHONE



\$12.00 each

any number can be connected together.

Latest Stand type with Call Button on each unit.

Ideal for office or home installation.

WANTED

SALESMAN FOR OUR RADIO ELECTRICAL COUNTER

Enquiries phone 61-3832 or write to 306 PITT STREET, SYDNEY

W.I.A. YOUTH RADIO SCHEME

The Y.R.S. conference convened to discuss various aspects of the scheme, with the view of streamlining some facets and expanding the organisational structure, was held at Sydney Grammar School, Sydney, on Saturday afternoon, June 3, 1967.

The conference opened at 2.30 p.m., with 17 persons in attendance.

Present were: Mrs M. Swinton VK2AXS. Messrs: C. E. Whiting VK2ACD, I. M. Agar VK2AIM, J. Oosterveld VK2BJO, K. Howard, VK2AKX, D. A. Craig, K. J. Watson V2ZKW, D. Jeanes, VK2BSJ, J. W. Flynn, R. Davis, VK1RD, G. Hough, C. L. Matthews VK2BAI, J. Webster VK-22CW, D. J. Williamson, P. J. Healy VK2APQ, H. W. Rider VK3ZJY, Victorian Supervisor, M. E. Plummer, Secretary, Victorian Y.R.S.

Apologies were received from: H. Burtoft VK2AAH, T. Ivins VK2SS, Rev. Bro. Kinsella VK2AXK, J. Scougall.

In reviewing the aims and activities of the Youth Radio Scheme it was agreed that: "The Y.R.S. is an educational organisation of the Wireless Institute of Australia and its activity is to provide information, instruction and advice and to encourage and assist all persons interested in any or all aspects of amateur radio." It was also agreed that there would be no age limit for those wishing to participate.

When discussing the general administration of the scheme emphasis was placed on the work done by Rex Black, VK2YA (who is at present overseas). It was considered that the scheme had progressed to such an extent that an administrative body was now a necessity in New South Wales.

Nominations were called for and the following officers elected:

Secretary/Treasurer: J. Flynn. Management Committee: D. Craig, D. Williamson, J. Webster. Ex officio member W.I.A. Liaison officer.

When discussing finance it was agreed that as far as possible the scheme should be self-supporting and to cover such expenses it was decided that a registration fee be set at \$2.

Reviewing the examination papers and the certificates for the various standards provided quite a lengthy discussion and it was resolved that examination papers be standardised on a national level. This would be of a practical benefit to members moving from one State to another, as the requirements and syllabus would be uniform.

Mr K. Howard, VK2AKX, was directed by the conference to review in conjunction with the Victorian supervisor the academic level of the intermediate certificate paper and those of higher levels.

The subject of novice licences was discussed and following an explanation of the W.I.A. policy on the subject, by the chairman, the conference affirmed: "That this Y.R.S. Conference supports in full the W.I.A. Federal policy in regard to novice licences."

Mr H. W. Rider, Victorian supervisor, displayed a Y.R.S. lapel badge and a pocket badge. It was agreed that New South Wales would adopt the same badge, and it would be made available to those who had obtained their elementary certificate. The coat pocket badges would be available to holders of junior certificates.

Following the conference the Postal Group system has been modified to allow for better administration. In future this section will be known as "the Correspondence Section of the Youth Radio Club Scheme of Australia" and it will be administered by the Victorian division.

The office-bearers of this section are:-- Supervisor/secretary Roger Davis VK1RD Treasurer Miss Alison Stewart. Publicity officer David Jeanes VK2BSJ Committee members Howard Rider VK3ZJY: Michael Plummer.

Inquiries regarding membership should be addressed to The Secretary, 14 Hovea Street, O'Connor, Canberra City, A.C.T.

The objectives of the Correspondence Section are:—

(a) To develop in young people an interest in radio and electronics as a vocation or as a hobby throughout life.

(b) To provide school students with a hobby activity which will reinforce their school activities in science and mathematics.

(c) To assist present and future group leaders of correspondence groups to instruct student members of such groups by providing ready made programs of activity.

(d) To co-ordinate the activities of all group leaders and to promote co-operation and interchange of ideas among group leaders.

(e) To give encouragement and recognition to members who attain certain specified standards of skill and knowledge in the field of radio by award of certificates.

(f) To provide all State divisions of the Youth Radio Scheme with facilities for an efficient correspondence program of study for those desiring to become members of the Y.R.S. but who are unable for some reason or another to join in their local Y.R.S. activity.

MAITLAND YMCA RADIO CLUB

Under the direction of Kev Watson, VK2ZKW, president and club leader, the Maitland YMCA Radio Club has made excellent progress since its formation last February. The room housing the library and canteen has been completed while the completion of the workshop will enable a start to be made on the construction of the club's electronic equipment. Members will also be able to start on projects of their own.

The club meets in its own rooms in the YMCA Building, 264 High Street, Maitland, N.S.W., every Friday night at 7.30 p.m., and also on Saturday afternoons at 2 p.m.

There is an active membership of 29, and a newsletter is published each month. The club is a member of the W.I.A. and the Youth Radio Scheme. Application has already been made for the allocation of a call sign for the club station.

Full details of the club activities can be obtained from the Secretary, P.O. Box 54, East Maitland, or telephone 33-7286.

Office-bearers are:—

President and club leader, Kev Watson VK2ZKW
Secretary, Margaret Watson
Librarian, Mathew Ingle
Advisory council, Bruce Watson, Keith Ingle, Norm Blacktop, Bill Rimmer.

O.T.C. Presentation

On Friday, June 23, at the general meeting of the New South Wales division Mr Thatcher, of the Overseas Telecommunication Commission, presented the O.T.C. prize to a young Youth Radio Scheme member, David Frazer.

Of particular interest in Mr Thatcher's remarks was the point made regarding Y.R.S. training. The O.T.C. viewed favourably applicants for junior employment who had a substantial background of Y.R.S. training.

Youth Radio Scheme certificates carry with them the prestige of the Wireless Institute of Australia and as such are valuable qualifications for young job seekers in the electronics field. However, this is only one aspect of their value, for from the ranks of Y.R.S. today come the amateurs of tomorrow.

UNITED TRADE SALES

PTY. LTD.

MILLER IF STRIPS

455 Kc at 6dB
Centre Frequency 455 Kc plus or minus 2 Kc.

Transistorised, \$8.70 each.

AUDIOCRAFT SPEAKER

Enclosures filled with two Rola
8 CMX Speakers, 20 x 13 x 7,
\$38 each.

L.S.G.11 SIGNAL GENERATORS.

120 Kc to 350 Mc. \$30 each.

WIRE WOUND POTENTIOMETERS.

Wide range available from 5 ohms to
100 K. ohms. 40c each.

RESISTORS

Carbon $\frac{1}{2}$ and 1 watt \$2 per 100.

CAPACITORS.

Assorted values Mica and Ceramic,
80 for \$2.

KYORITSU V.T.V.M.

Model K142.

Ranges 1.5v—5v—15v—50c—150v—
500v—1,500v AC and DC. Resistance
Rx 1 x 10 x 100 x 1K x 10K x 100K
x 1 meg. \$56.25.

VALVES. 6AL5.

20c.

6AC7, 12 for \$2, 6J6, 50c. 815, \$1.
6AM5, 50c. 7C7, 10c. 6C4, 50c.
6FQ5, 50c. TZ40, \$1.25.

SPECIAL.

416B Planar Triodes Hot front end
tubes, excellent on 432 Mc, only \$4.

VARIACS.

115v, 18A, \$18 each or \$32 pair.

TRANSCEIVERS.

Eico 753, 55B Transceiver Triband
solid state VFO, 180 watts. P.E.P. all
modes. —KIT \$328.78 inc. tax.

FIRST RELEASE. IMPORTED 100Kc XTAL CALIBRATORS.

Size 2 $\frac{1}{2}$ in x 1 $\frac{1}{2}$ in, contains 100 Kc
xtal, 2 transistors on printed circuit
board. Ideal for communications RX,
\$22.

UR70 72ohm

Coax. Cable, 27yd Length w/- Bel-
ling-Lee Connector on end.
\$2.00 length plus 75c postage.

PERSPEX SHEETS

16 x 4 x 1/8. Optical.
30 cents per sheet.

ALL Prices Freight and Packing
Extra.

FOR SURPLUS ELECTRONIC
EQUIPMENT, SEE ADVERT. IN
"AMATEUR RADIO."

UNITED TRADE SALES

PTY. LTD.

280 LONSDALE STREET,
MELBOURNE. Phone 32-3815
(opposite Myers)

THE "MOSQUITO"

A SIGNAL SOURCE FOR EVERY ELECTRONIC APPLICATION

PRICE
\$15.00
NETT

MODEL
MS-130



*Any magnetic type device can be inductively coupled by placing the Mosquito a few inches away from it.

... pocket size instrument finds defective circuits—**IMMEDIATELY!**

For every technician or engineer who must find defective circuits quickly and exactly, the new MOSQUITO with detachable probe — pocket size, cordless, pen-type instrument which generates and injects a rich signal covering the audio, IF and RF spectrum!

The Mosquito contains a transistor oscillator, powered by a single 1.5 volt pen light cell, which completely eliminates the need for a large, expensive signal generator. It can be coupled into magnetic pickups and circuits **without leads**. And the MOSQUITO oscillates at approximately 1,000 cycles per second, with a wave form which is rich in harmonics. This is truly the simplest, fastest, **most effective**, most economical way to find defective circuits — it belongs in your pocket now!


Some typical applications for the new MOSQUITO Transistorized Signal Injector

- Radio — AF, IF and RF section of vacuum tube, transistor and auto radios
- Television — AF, RF section
- Tape Recorders
- Movie Projectors (sound)
- Telephone Circuits
- Sound Systems
- Hearing Aids
- Amplifiers
- Transformers
- Reproducers — Speakers and ear-phones
- Resistors and Capacitors — continuity check
- Coded Practice Oscillator
- Oscilloscope Voltage Calibrator and Time Calibrator
- Sound Pickup Cartridges — microphones phonograph pickup (Piezo-electric crystal, ceramic and magnetic types*)

WILLIAM WILLIS & CO. PTY. LTD.

430 ELIZABETH STREET, MELBOURNE, C.I.
TELEPHONE 34-6539

TCXO



The curves indicate the effect of compensation on a typical crystal characteristic.

The temperature-sensitive network is designed to vary a reactance in the oscillator circuit, in order to restore the crystal frequency to its nominal value at any temperature in the required range. (e.g. -20°C to $+70^{\circ}\text{C}$ or -55°C to $+105^{\circ}\text{C}$).

The permissible frequency tolerance and the temperature range define the degree of compensation required which, in turn, greatly influences the cost. Discussion between your engineers and ourselves is therefore necessary.

Engineers in the Pye Crystal Division have been developing high accuracy TCXO's for several years, in conjunction with government departments. The knowledge obtained is now available to the communication industry and we invite your enquiry for specialised frequency sources of this type, particularly where economy of operation and limitation in size are required.

The letters TCXO represent the military designation adopted in the U.S.A. for a "Temperature-Compensated Crystal Oscillator."

In these days, when economy in the use of the frequency spectrum is becoming more important, attention is being focused on the use of frequency control devices with increasingly higher accuracy. It is in this direction that the TCXO has an important role to play, particularly where fully solid-state equipment is concerned.

power consumption, accuracy of frequency control previously obtainable only from an oscillator used in conjunction with a temperature-controlled oven maintaining constant crystal frequency. In many cases, the average power required for the smallest oven of this type far exceeds that necessary to supply the whole of the rest of the equipment.

The TCXO has the ability to provide, at very low power consumption, accuracy of frequency control previously obtainable only from an oscillator used in conjunction with a temperature-controlled oven maintaining constant crystal frequency. In many cases, the average power required for the smallest oven of this type far exceeds that necessary to supply the whole of the rest of the equipment.

Basically, a TCXO consists of a high stability crystal in a stable oscillator circuit and a complex network of temperature-sensitive components. The high stability crystal possesses characteristics predetermined for this application.



PYE PTY. LTD.

CLARINDA ROAD, CLAYTON, VICTORIA.
P.O. BOX 105. TEL.: 544-0361 (8 LINES)

Melbourne — Sydney — Brisbane — Adelaide — Perth — Hobart



TECHNICAL DETAILS OF AUSTRALIS SATELLITE

Australis OSCAR A is a simple developmental satellite carrying two telemetry transmitters with seven data channels and one identification channel. The system has been tailored to suit the equipment available to most amateur radio operators and decoding instructions will be given later.

In order that experience may be gained in command techniques, a command receiver and decoder have been included to control the operation of the high frequency transmitter while the very high frequency transmitter remains continually running. The transmitters operate in the 10-metre and 2-metre amateur bands.

The command system controlling the high frequency transmitter is to be operated by a limited number of strategically placed Command Tracking Stations (CTS), and will not be available for general use. For that reason details of the system will not be published. A block diagram of the electronic systems aboard Australis is given in Fig. 1. A drawing of the package in orbit is given in Fig. 2.

Telemetry Encoder Unit: The Telemetry Encoder sequences the sampling of seven data channels and one identification channel. It encodes this information as an audio tone which is then fed to the two transmitters as modulation.

The master clock is an astable multivibrator with a period of about 7 seconds, and it is synchronised with the "HI" keyer. The sequencer is a set of three bistable multivibrators that successively divide the pulse repetition rate to once every 70 seconds. Each successive sensor is sequentially sampled by logic circuits. The sampled voltages are fed to a voltage controlled oscillator, the output of which is amplified and sent to a phase splitter. The two out-of-phase outputs are then used to modulate the two transmitters. The channel sequence and decoding details will be given later when describing tracking and decoding procedures.

The telemetry sequence consists of:

0. "HI" identification — two "HI's" in Morse (di-di-di-di-di-di-di-di). These "HI's" will consist of an audio tone switched from about 400Hz to 1KHz for the space and mark periods respectively. The "HI's" are in synchronisation with the telemetry sequencer.
1. Battery current drain sensor.
2. X axis horizon sensor.
3. Battery voltage.
4. Y axis horizon sensor.
5. Battery temperature.
6. Z axis horizon sensor.
7. Inside skin temperature.

Each channel is maintained for 7 1/2 seconds before switching to the next channel. It should be clearly understood that, unlike OSCARs I and II, the "HI's" carry no information and that any variation in their period is not necessarily an indication of the temperature in the satellite.

'HI' Keyer: This electronic switching unit provides the identification channel of

the telemetry. The output is a voltage waveform with square pulses corresponding to the word HI in Morse Code and is produced by electronic oscillators and logic.

All circuits were designed to operate with transistors $\beta > 14$ and resistor tolerance $\pm 40\%$. The flip-flop ($\div 2$) was checked for tolerance by computer. All circuits were designed for low current drain and maximum reliability.

HF Transmitter: The HF transmitter is a ground commandable transmitter with a nominal output power of 250 milliwatts on 29.450MHz. It is switched on and off by signals received from ground stations via a command receiver and decoder. The transmitter carries the 8-channel telemetry, when on.

The power amplifier is a class C common-base circuit. This configuration was chosen for high efficiency and stability and to keep within transistor breakdown restraints. The transmitter is in fact switched on and off at an audio rate by the telemetry unit. The rise time has been softened to reduce high harmonic sidebands.

All stages are common base, and are double tuned between stages to reduce harmonic output. In fact, all spurious signals are at least 35dB below the fundamental carrier.

VHF Transmitter: The VHF transmitter has a nominal output of 50 milliwatts at 144.053MHz. It is continuously operating, functioning until the battery is exhausted, i.e. about two months. Telemetry modulates the transmitter in a manner similar to the HF transmitter and the comments which applied to that transmitter apply here.

Command Receiver: The command receiver detects commands transmitted to the satellite from ground stations. The detected audio is fed direct to the command decoder which decides whether a valid command has been sent and acts accordingly, to switch the HF transmitter on or off.

The command receiver is a double conversion superheterodyne receiver with detector and limiter to produce the audio output for the decoder. The receiver and decoder combination will reliably switch the HF transmitter with a signal to noise ratio of 10dB or a few microvolts received at the input.

Command Decoder: The purpose of this unit is to provide a gate voltage for the HF transmitter to bias the oscillator (and so the whole transmitter), on or off as required by ground stations. The decoder receives two audio tones from the receiver and determines whether these tones have correct pitch, length, spacing, etc. to constitute a valid command. When such a valid command is received, a flip-flop gate operates as required by the circuit. All circuits use either feedback or saturation to ensure that operation is independent of transistor characteristics and environment.




Fig. 2

Magnetic Attitude Stabilisation System: The magnetic attitude stabilisation system (MASS) consists of two separate sections. The functions of these sections are detailed:

(a) **Hysteresis Rods:** These are special mu-metal rods with a very large hysteresis loop at the very low magnetic flux densities encountered in space. As the satellite rotates, the rods are cycled through their hysteresis loop and in doing so dissipate a small amount of rotational energy. Thus spin imparted at ejection into orbit is slowly reduced to a negligible value after one or two weeks. The horizon sensors will give a very good indication of the spin rate.

(b) **Bar Magnet:** Two small but very powerful magnets connected as a single bar magnet align the satellite with the Earth's magnetic field and thus give the satellite some degree of stabilisation. This should markedly reduce the fading of signals due to this rotation.

It should be pointed out, however, that theoretical predictions are notoriously unreliable, due to the uncertainties of eddy current losses and other factors.

Package: The package is a very strong assembly designed to withstand the stresses of launch. It has been made with the skin thermally insulated from the interior compartments containing the electronics modules and battery. This technique should maintain the inside at a more even temperature than would otherwise be possible.

The battery, being the most massive single item, is mounted in the centre with the electronics modules mounted on bulkheads attached to the battery pack. A diagram of the package is shown in Fig. 3. Note that the axis directions are defined for the horizon sensors.




Fig. 1




Fig. 3

New Electrolytic Condensers

These condensers are miniature pigtail type insulated new stock in packets of 12, each packet containing; 3, 16mfd 300V.W., 2-32 mfd. 300V.W., 1 25mfd. 450 V.W. and 6 low voltage electrolytics. \$2.50.

Post and packing 20c extra.

NEW IMPORTED 4" P.M. SPEAKERS

Available with a 4 or 16 ohm voice coil. \$2.50.

Post and packing 30c extra.

Imported National Transistorised Shoulder Megaphone

These shoulder megaphones manufactured by National Radio Japan have an output of 4 watts, and are supplied complete with inbuilt horn type speaker, batteries and microphone. List price \$78.

Special Price \$50. Post extra

Other types also available.

NEW IMPORTED SLOT CAR KITS AT

LESS THAN HALF PRICE



Complete kit of parts including 12V motor and full instructions.

\$2.50 post 25c

NEW AMERICAN TWIN TELESCOPE TV AERIAL

Extends to 36in, each section can be used singly for car or portable .. \$1.50. Post 20c.

SINGLE TELESCOPIC

Aerial 12in extends to 33in. 60 cents. Post 10 cents.

NEW 4-SPEED STEREO

PLAYER F.O.R. .. \$17.50 (£8/15/)

NEW STEREO CHANGER.

4-SPEED F.O.R. .. \$21.50 (£10/15/)

SLIDER-SWITCHES


10 pole 2-way silver plated contacts 38c

POWER TRANSFORMER

Prim. 240V Sec. 350 volts a side. 60 M.A. One 6.3V, one 5V F11.

\$2.75

Post N.S.W. 60c, Interstate 80c.



LEADER SIGNAL GENERATOR LSG11


240V A.C. operated, 6 band 120KC to 390 megs. Provision for crystal. Post N.S.W., 75c; Interstate, \$1.25. **\$29.50**

BATTERY CHARGER RECTIFIERS

New Selenium Rectifiers, 6 or 12 volt at 4 amp., \$3.75. Post, N.S.W., 20c; Interstate, 20c. Transformer for above rectifier tapped for 6 to 12 volt, with circuit for charger, \$4.75. Post, N.S.W., 75c; Interstate \$1.00. As above, 6 or 12 volt, at 2 amp., \$2.75. Post, N.S.W., 35c; Interstate, 45c. Transformer for above, \$3.75. Post, N.S.W., 35c; Interstate, 45c.

NEW 240V. A.C. MOTORS

These small motors, size 5in x 3in x 3 1/2in, are 1-12 h.p., but are only suitable for intermittent use. \$2.95. Post N.S.W. 35c; Interstate 50c.



\$9.75 (£4/17/6) POST FREE

NEW AMERICAN TV POWER BOOSTER UNIT AT LESS THAN HALF PRICE

(EX LIQUIDATION STOCK H. G. PALMER)


These TV POW-R boosters can be used in two ways. Firstly as a "straight-thru" circuit giving extra boost to the TV signal for improved performance on one receiver. Secondly to boost signal strength to two or three TV receivers coupled to the one aerial.

Full instructions supplied with each unit. 240 volt A.C. operation.

THE NEW COLLARO 3-SPEED 4 TRACK TAPE-DECKS

\$48.00

The ideal deck for the home constructor, as amplifier and all controls can be mounted on deck.



- 3-speed 1 1/2, 3 1/4, 7 1/2. • Pause control. • Takes 7in. spools.
- Simplified controls. 4 Tracks, \$48; OSC Coils, \$1.50.

NEW 4" EXTENSION SPEAKERS


These 4" speakers are mounted in polished cabinets suitable for use as intercom, units or extension speakers. LIST PRICE .. \$12 SPECIAL PURCHASE ENABLES US TO SELL THESE UNITS AT \$4. Post and packing, N.S.W., 68c. Interstate, 98c.



A PREAMP FOR MAGNETIC PICK-UP OR TAPE HEADS

SUITABLE FOR USE WITH THE COLLARO OR B.S.R. TAPE DECKS

Using 3 silicon transistors as featured in October Electronics Australia complete with kit of parts including transistors mono \$7.50, stereo \$13.00, 240 power supply for above \$7.00. Please specify if required for pick-up or tape heads.



25 WATT .. \$53.75. £26/17/6
17 WATT .. \$43.75. £21/17/6
Post Extra on 15 Watt.
N.S.W., 10c; Interstate, 15c.
25 Watt by Rail or Air.
Too Heavy for Post.

NEW 17 & 25 WATT P.A. AMPLIFIERS

The 25 Watt Amplifier uses 5 valves plus 2 rectifiers including two EF86 low noise valves as microphone preamplifier and two EL34 valves Ferguson push-pull output.

All amplifiers are fitted with Ferguson output transformers with voice coil tapings of 2 to 15 ohms. The 25 watt amplifier can be supplied with line output transformers tapped from 100 to 600 ohms if required at \$2.00 extra.

Inputs provided for microphones, pick-up, and radio with mixing facilities and tone control. The 15 watt is as above but using two 6BQ5 valves in push-pull output.

12in speaker for above (10 watt) .. \$6.75 .. 67/6
Crystal Microphones for amplifier .. \$4.75 .. 47/6

NATIONAL RADIO SUPPLIES

332 PARRAMATTA ROAD, STANMORE, N.S.W. PHONE 56-7398.



\$23.75 (£11/17/6)

NEW TRANSISTOR SIX PORTABLE KIT AT LESS THAN HALF PRICE

(DESIGNED TO SELL AT OVER £30/-/-)

Excellent fidelity is obtained in this new kit set by the use of large speaker and polished timber case with attractive gold metal front panel. By using heavy duty batteries it is economical to operate and is ideal for portable use or that second set. Complete kit of parts is supplied with full instructions. CAN BE SUPPLIED WIRED AND TESTED AT £2/10/- EXTRA. Post and packing N.S.W., \$1.25 — Interstate, \$1.75.

RESISTORS, CONDENSERS AND POTENTIOMETERS

We have purchased the resistor and condenser stock of manufacturers including S.T.C. and Stromberg-Carlson who have ceased the manufacture of television and radio receivers and can offer the same at less than 25 per cent of list price. The resistors are mainly I.R.C. and Morganite in values from 200 ohm. to 5 meg. in 1/2, 1 and 2 watt ratings and include some wire wound resistors.

List price, \$9.00 per 100. Our price, \$2.00 per 100. Post and packing 25c extra.
The condensers are in most popular makes and include mica, ceramic, paper, and electrolytic in standard values. List price, \$11 per 100. Our price, \$2.06 per 100. Post and packing, 35c extra.

The potentiometers are all current types and include switch pots, dual concentric and T.A.B. pots. List price, \$12 per dozen. Our price, \$2.50 per dozen. Post and packing, 25c extra.


FREE For a limited period with each lot of resistors, condensers or potentiometers purchased we will supply free: One New Type Valve Type 6U7G, 6X5GT or IT4.

SPECIAL — OFFER

Complete KIT for TRANSISTOR 6 PORTABLE \$17.50

The complete kit of parts for the transistor six includes six transistors, printed circuit board, coil kit, 4in speaker, Ferguson driver and output transformers, heavy duty battery and all necessary parts to complete the set with full instructions. Set is housed in attractive plastic case as illustrated.

Dials available for all States. Post and Pack: extra. N.S.W., \$1.00, Inter., \$1.30.



NEW ENGLISH MAZDA TRANSISTORS

TYPE
XA101
XA102
XB103

EQUIVALENT
OC43
OC44
OC75

R.F. Transistor 85c
Osc. Transistor 75c ea.
AUDIO general purpose 75c

Ducon type SFT 123 equiv. OC74 75c ea.
Available in matched pairs at \$1.50 pair
AUDIO OUTPUT
Post and packing on transistors 15c any quantity.

A.W.A. 23" E.H.T. transformers and 23" 110 deg. deflection yokes. New manufacturer's stock E.H.T. units \$5.00. Deflection yokes \$5.00. Post free

NEW VALVES AT BARGAIN PRICES

807 \$1.75
1A7GT 95c
1C7G 30c
1D8GT 95c
1K5G 40c
1K7G 40c
1M8G 40c
1P5G 25c
1Q5G 25c
1T4 45c

3Q4 75c
3S4 \$1.00
5V4G \$1.00
6B8 \$1.00
6C8G 80c
VR99A equiv. 6J8G \$1.50


6H6G 35c
6K7G 45c
6K8G 45c
6U7G equiv. 6D6G \$1.00
6SA7GT 95c
6SH7 85c

6S7 95c
6N7GT 95c
6SS7 equiv. 6SK7 85c
6U7G 45c
6X5GT 75c
7C7 35c

12A7T \$1.00
1L5G 95c
12A6 80c
12K7 80c
12SK8 80c
12SH7 80c
866 1.00
944 25c
955 25c
EK32 68c

Please add postage on all valves.

NEW 4-SPEED STEREO & MONO PLAYERS AT LESS THAN HALF PRICE



**PHILIPS 4-SPEED
6V BATTERY PLAYER
MONO \$9.75
STEREO \$11.75**



Post and Packing, N.S.W., 75c.
Post and Packing, Inter., \$1.25 Extra.

NEW 240V. ELECTRIC MOTORS



3300 R.P.M. can be supplied with or without 4-speed reduction mechanism. Size 3 1/4" x 2 1/4 x 3 1/2, including spindle.

\$2.75




NEW PORTABLE RECORD PLAYER CASES TO SUIT THE ABOVE TURNTABLE

Attractive two-tone cabinet with plastic trim. Supplied with 5in x 7in speaker in felt-lined enclosure. Space for amplifier and batteries or power supply.

\$11.50

Dimensions: 15in x 13in x 7in.
Post and Packing: N.S.W., 90c; Interstate, \$1.20.



NEW MINIATURE MOTORS

Ideal for models, toys, etc. 1 1/2 to 3 volts, 6,000 r.p.m. 39c each or \$3.50 per doz. Post 10c.

EXTENSION SPEAKERS

\$8.50 New 9 x 6 speakers in case. Post: Interstate, 55c; N.S.W., 40c.

NEW POWER TRANSFORMERS

60mA prim.: 240v with 230v tapping Sec. 285 x 285 with 6.3v filament winding. 60mA, \$3.00. Plus Postage: N.S.W., 35c; Interstate, 52c.
Prim.: 240v, Sec. 385 x 385 at 80mA, fil. 6.3 and 5v, \$4.50. Post.: N.S.W., 40c; Interstate, 75c.
60mA H.T. Chokes, 75c. Post.: 20c.

T.M.K. MULTIMETERS

Before buying see our range of T.M.K. test instruments. As advertised in April issue of Electronics Australia.

TYGAN AND SARLON SPEAKER GRILLE FABRIC

List price \$8.00 per yard.
To clear at \$5.50 per yard.
Postage and packing N.S.W., 3/6.
Interstate, 4/6.

NEW MIDGET POWER TRANS.

40mA prim., 240v. Sec 225 x 225 with 6.3v. Fil. Winding. **\$3.25** Postage: N.S.W., 25c; Interstate 45c.
30mA 240v Prim. 150 x 150v. Sec. with 6.3v Fil. Winding. **\$3.25** Postage: N.S.W., 25c; Interstate 35c.

NEW B.S.R. TAPE DECKS

These new 3-speed B.S.R. Decks are fitted with a digital counter and will take 7in spools. 2 Track, \$35, 4 Track, \$40.

NATIONAL RADIO SUPPLIES



332 PARRAMATTA ROAD, STANMORE, N.S.W. PHONE 56-7398.

IR® 10D SERIES DIODES

prove that good things come in small packages!

They offer:

- 1 Full one Amp. rating
- 2 Subminiature epoxy package
- 3 High temperature range
- 4 Silver leads
- 5 Low reverse leakage characteristic



For precisely what your circuit needs...choose from the world's finest range INTERNATIONAL RECTIFIER available only from



WARBURTON FRANKI

ADELAIDE: 233-233; BRISBANE: 51-5121; CANBERRA: 4-7755; HOBART: 2-1841; LAUNCESTON: 2-1318; MELBOURNE: 69-0151; MOUNT GAMBIER: 2-3841; NEWCASTLE WEST: 61-4077; PERTH: 8-4131; SYDNEY: 29-1111; WOLLONGONG: 2-5444.



LISTENING AROUND THE WORLD

Art Cushen's monthly report on long-distance short-wave, television and broadcast band reception.

More Power For Cook Island Radio

Radio Rarotonga, in the Cook Islands, is to boost its power on three frequencies to 5KW shortly, and increase its program hours to cover morning, lunch hour and evening.

The station was established 15 years ago when, at first, it used the Post and Telegraph transmitter at Rarotonga for its broadcasts to the Island territory. Mr Percy Henderson, a New Zealand schoolteacher, introduced the broadcasting service into the Cook Islands, and is now Manager of the Cook Island Broadcasting Service. The station started with a 30-minute program each week on the Post and Telegraph communications station. Later, station personnel built some transmitters, and also used second-hand equipment from the New Zealand Broadcasting Corporation. Week-ends were spent in building their own studios, a large one for concerts and audience participation and two smaller ones.

The station has now ordered three 5KW transmitters to replace the present 500W unit on broadcast band 820KHz, and 250W unit on short wave 5045, 3265KHz.

The station schedule is now 10 a.m. to 1 p.m., and 6 p.m. to 10.30 p.m. local time, or 2030-2330, 0430-0900GMT, the first session being of an educational nature, other programs being in English and Cook Island Maori in equal parts. Radio New Zealand news is relayed at 0730GMT in the evening service. The station plans to operate a breakfast session soon, to be on the air 1630-1930GMT. Nine members form the staff of the station. Mr Henderson is the only non-Cook Islander on the staff.

LEBANON CHANGES

Radio Beirut in Lebanon has made further frequency adjustment in its schedule to the American continent. The service in Arabic, Spanish and Portuguese to Latin America has been heard at 2300-0100 on 17765KHz. The service to North America 0130-0400 is now on 11965KHz and provides good reception. This service is in English 0230-0300; French 0130-0200; Spanish 0330-0400; and Arabic 0200-0230, 0300-0330GMT.

The 16M band frequency is well received, but with some sideband interference from Rome, and Radio New Zealand, both on 17770. On 11965KHz the worst interference is from Moscow using 11970KHz.

LATIN AMERICAN NEWS

The afternoon and late evening listening periods in the Pacific provide some interesting signals on the 90, 60 and 48 metre bands.

Mexico station XEXG, which operates on 6065KHz, has been heard at sign off at 0600GMT. The station relays XEX and uses the slogan "La Voz de Mexico." It radiates only 1KW of power and is seldom reported in this area, as normally good reception is prevented by Radio Sweden, which uses the same frequency. The station's programs are also carried by six other medium wave stations.

Peruvian stations OAX6E Radio Continental Arequipa, on 5930KHz, closes at

0500. The same sign-off time is used by OAX8V Radio Echo at Iquitos using 5010KHz. Radio America in Lima, on 6010KHz, which uses the callsign OAX4V, closes at 0600 GMT.

Radio Amazonas, using 4815KHz, was heard at good level at 1100GMT with its identification and its location as Iquitos, Peru. Radio Tropical has been tuned, on 4934KHz (opening at 1055GMT with the Peru National Anthem, followed by identification at 1100GMT and reference to the parallel frequency on 9710KHz, reports the Australian Radio DX Club bulletin.

Venezuelian station Radio Bolivar, is reported at 1030GMT on 4770KHz. The station has the callsign YVEW, and is reported to confirm reception by letter and pennant. Radio Rumbos, Caracas, with the call YVLK, operates on 4970KHz to 0630GMT on Sunday, when it signs off with the National Anthem. It also is heard opening at 1000GMT.

Ecuadorian signals on 60M provide some excellent reception. David Auld, of Grey-mouth, N.Z., reports HCJS1 on 4830KHz opening at 1100GMT. Radio Cenit de Portoviejo, on 4770KHz, has been heard from 1115GMT till after 1200GMT. La Voz de Rio Tarqui, on 3995KHz, is operating on Sunday, to sign off at 0700GMT, with a fair signal, and is reported to be using 500W. The callsign is HCJA5. La Voz de Esmeraldas, on 4875KHz, has been noticed at 0650GMT, when it left the air; the call, HCVE4, is assigned to this frequency. Radio Catolica is on 5060KHz, and has been received at sign-on, at 1100GMT, with identification followed by a religious broadcast.

Colombia station HJ1W confirmed our reception after a year with a letter and small pennant. Verification card was also enclosed. The station operates on 6095KHz, with 1KW, and the slogan is "La Voz de Centro," and the station address is Apatado 70, Espinal, Colombia. Verification is signed by Jesus A. Yara Villareal, the director of HJ1W.

Guatemalan station TGFB Radio Nacional, Tikal, has been heard at 1145GMT at fair level on 6205KHz. The station suffers side interference from the Costa Rican station Radio Reloj on 6201KHz. Radio Nacional in Guatemala City, on 6180KHz, provides good reception up to its 0600-GMT sign off.

BBC RELAY STATIONS

Schedules of the two BBC relay stations in Africa show an extension of the schedules with the recent 24-hour-a-day operation of the World Service. Francistown in Botswana, operates on 4845KHz at 0400-0445, 1630-2045GMT; also on 7295KHz at 0600-0830GMT. The program is also carried on medium wave on 602 and 926KHz.

The West African relay base is located at Monrovia, in Liberia, and carries programs

on the single frequency of 9555KHz. The schedule is 0545-0915 and 1030-2015GMT. The station carries mainly the world service and has been heard in New Zealand at 0710GMT with some interference from Prague in its transmission to the Pacific area, using 9550KHz.

ROUMANIA USING 1172KHz

Radio Bucharest, Roumania is using the new 11725KHz channel for its three transmissions to North America. The new frequency is very well received at 0100-0130, 0300-0330 and 0430-0500GMT, and provides the best reception here of the station's North American service in this area. The transmission includes news commentary and features.

Bucharest is using 15250, 15225, 11940, 11810, 11725 and 9590KHz for the first two transmissions and at 0430-0500GMT adds 9570KHz to the program.

AFRICAN SIGNALS

Reception of signals from a great number of African stations during our early morning and afternoon listening periods continues to make this area one of the most listened-to parts of the world. This month several New Zealand readers — including Tony Marr, of Auckland, Theo Donnelly, of Hamilton, and Brian Clark, of Wellington — and Bob Padula, of Melbourne, supply news of the stations they are hearing from the African area.

South Africa—The home program of the South African Broadcasting Corporation, from Johannesburg, is heard with English at 0500 to 0530GMT using 6075KHz. The service seems to be on this channel for only 30 minutes. The same frequency with the Overseas Radio program is heard on 2326GMT to 0325, with an announcement that the channel is in use for test broadcasts. SABC is also being heard at 0530-GMT with the Johannesburg program on 6095KHz.

Ivory Coast — Radio Television Ivoirienne, Abidjan, heard on 3242 and 4940KHz, opens with National anthem at 0600GMT. Both signals fade out at about 0700GMT.

Angola — Radio Commercial de Angola has been noted at 1800GMT, with a typical Portuguese program. In Australia signals are heard at 2200GMT. CR6RZ on 4820KHz in chain with 7235KHz has been heard from 0500GMT, and reported also at 2000GMT.

Nigeria (Biafra) — Enegu in Eastern Nigeria is heard on 4855KHz, opening in English at 0500GMT in this break away part of Nigeria. Lagos on 4990KHz is good at 0550GMT with the usual English program.

Mozambique — Radio Pax, operating on 7205KHz and broadcasting from Beira, is heard in Portuguese at 0450GMT.

Mauritania — Radio Mauritania, Nouakchott, opens at 0700GMT on 4855KHz, and has news in French at 0725GMT. Previously it was on 3222KHz, now used by Radio Lome Togo.

HIGHER POWER FOR PAKISTAN

Radio Pakistan states that new 100KW SW transmitters are to be installed at the new capital, Islamabad, near Rawalpindi; also at Dacca in East Pakistan. The three transmitters are of Russian manufacture. They will aid the external broadcasting activities of Radio Pakistan.

When it became independent, Radio Pakistan had three transmitters, located at Lahore, Dacca and Karachi. The number in use has now been increased to 12 medium

foster

hi-fi speakers

High Compliance tweeters

FT-502



SPECIFICATIONS
 Size: 50 mm (2 in.)
 *Impedance: 8 or 16 Ω
 Frequency Range: 2,000~20,000 c/s
 Sensitivity: 100 dB
 Power: 30 W max., 8 W nom.
 Dimensions: 82 x 82 mm, 29 mm depth
 Magnet Weight: 193 g (6.81 oz), Ceramic
 Weight: 615 g (1 3/8 lbs)
Price \$8.04.
Plus Sales Tax \$1.68.

High Compliance woofers

FW-162



SPECIFICATIONS
 Size: 160 mm (6 1/2 in.)
 *Impedance: 8 or 16 Ω
 Resonant Frequency (f_0): 40~50 c/s
 Frequency Range: f_0 ~2,000 c/s
 Sensitivity: 97 dB
 Power: 30 W max., 10 W nom.
 Dimensions: 166 x 166 mm
 81.6 mm depth
 Magnet Weight: 500 g (1 1/4 lbs), Ceramic
 Weight: 1,660 g (3 5/8 lbs)
Price \$12.00.
Plus Sales Tax \$2.50.

FW-202



SPECIFICATIONS
 Size: 200 mm (8 in.)
 *Impedance: 8 or 16 Ω
 Resonant Frequency (f_0): 30~40 c/s
 Frequency Range: f_0 ~2,000 c/s
 Sensitivity: 98 dB
 Power: 45 W max., 15 W nom.
 Dimensions: 208 x 208 mm
 90.8 mm depth
 Magnet Weight: 830 g (1 3/4 lbs), Ceramic
 Weight: 2,760 g (6 1/8 lbs)
Price \$23.64.
Plus Sales Tax \$4.93.

Double-cone speakers



PW-65A
 Size: 160 mm (6 1/2 in.)
 *Impedance: 8 Ω
 Resonant Frequency (f_0): 70~100 c/s
 Frequency Range: f_0 ~15,000 c/s
 Sensitivity: 97 dB
 Power: 6 W max., 5 W nom.
 Dimensions: 164.9 ϕ mm, 86.2 mm depth
 Magnet Weight: 77.6 g (2.73 oz)
 Weight: 476 g (1 1/8 lbs)
Price \$6.60.
Plus Sales Tax \$1.35.

*at 400 c/s; †at 3,000 c/s

High Compliance wide range speakers

FE-103



Size: 100 mm (4 in.)
 *Impedance: 8 or 16 Ω
 Resonant Frequency (f_0): 65~95 c/s
 Frequency Range: f_0 ~18,000 c/s
 Sensitivity: 96 dB
 Power: 5 W max., 3 W nom.
 Dimensions: 105 x 105 mm, 46.6 mm depth
 Magnet Weight: 193 g (6.81 oz), Ceramic
 Weight: 630 g (1 3/8 lbs)

Price \$8.64.
Plus Sales Tax \$1.04.

FE-163



Size: 160 mm (6 1/2 in.)
 *Impedance: 8 or 16 Ω
 Resonant Frequency (f_0): 40~60 c/s
 Frequency Range: f_0 ~20,000 c/s
 Sensitivity: 98 dB
 Power: 10 W max., 5 W nom.
 Dimensions: 166 x 166 mm, 73.7 mm depth
 Magnet Weight: 398 g (14.04 oz), Ceramic
 Weight: 1,260 g (2 3/4 lbs)

Price \$14.64.
Plus Sales Tax \$3.05.

Coaxial speakers

FX-201




with horn tweeter

Size: 200 mm (8 in.)
 *Impedance: 16 Ω
 Resonant Frequency (f_0): 45~75 c/s
 Frequency Range: f_0 ~18,000 c/s
 Sensitivity: 101 dB
 Power: 10 W max., 5 W nom.
 Dimensions: 206 ϕ mm, 137.5 mm depth
 Magnet Weight: 240 g (8.46 oz)
 Weight: 2,200 g (4 7/8 lbs)

Price \$23.88.

Plus Sales Tax \$4.98.

FX-200 G2



with 2 1/2" tweeter

Size: 200 mm (8 in.)
 *Impedance: 16 Ω
 Resonant Frequency (f_0): 45~75 c/s
 Frequency Range: f_0 ~18,000 c/s
 Sensitivity: 101 dB
 Power: 10 W max., 5 W nom.
 Dimensions: 206 ϕ mm, 140.7 mm depth
 Magnet Weight: 234 g (8.21 oz)
 Weight: 2,200 g (4 7/8 lbs)

Price \$21.60.
Plus Sales Tax \$4.50.

2-way network



LC-100
Price \$6.60.
Plus Sales Tax \$1.38.

2 or 3-way network



LC-300

Crossover Freq.: 2,500 or 3,500 c/s
 Impedance: 16 Ω
 Attenuation: 6 dB/oct.
 Dimensions: 63.1 ϕ mm, 69 mm height
 Weight: 280 g (9.88 oz)

Crossover Freq.: 350 or 700 c/s, 2,500 or 5,000 c/s
 Impedance: 8 or 16 Ω
 Attenuation: 6 dB/oct.
 Dimensions: 83 H x 200 W x 134 mm D
 Weight: 1,430 g (3 1/8 lbs)

Price \$22.20.
Plus Sales Tax \$4.63.

tweeter



FHT-1

Price \$11.04.
Plus Sales Tax \$2.30.
 †Impedance: 16 Ω
 Frequency Range: 2,500~16,000 c/s
 Sensitivity: 100 dB
 Power: 10 W max., 5 W nom.
 Dimensions: 110 mm height, 95 mm depth
 Weight: 330 g (11.75 oz)

(SOLE AGENT)



ZEPHYR PRODUCTS PTY. LTD.

70 BATESFORD ROAD, CHADSTONE, VICTORIA

wave and 11 short wave transmitters. Radio Pakistan plans to use the three 100KW transmitters to extend its overseas services, and to increase the foreign language content of the programs.

CHANGES FROM CAIRO

The Egyptian Broadcasting System in Cairo is now using the 13M band for its services to South and South-East Asia. The frequency is 21615KHz, and the operating schedule is 1115-1230GMT in Indonesian, 1230-1330 in Malay, 1330-1430 in Siam. The frequency of 15360KHz has also been used by Cairo to replace 11980KHz.

It is used 1100-1200GMT in Arabic, 2230-2330 in Arabic to Latin America, 2330-0030 in Portuguese, 0030-0130 in Spanish.

English from Cairo is broadcast 0630-0700GMT on 7075, 11915KHz; 2145-2315 on 9475, 12005KHz; 0130-0300 on 9475-KHz; 2045-2215 on 15135KHz; 1300-1430 on 17690KHz; 1930-2015 on 17690KHz. Reports should be sent to Radio Cairo, Monitoring and Propagation Department, P.O. Box 1186, Cairo, Egypt.

FINLAND SCHEDULE

The present schedule of the Finnish Broadcasting Company in Helsinki, shows that transmissions have been extended, in particular to North America. The English language service effective until September 3 is: to Europe, Friday 2100-2200GMT on 6120, 9555, 15185, 11805KHz. Saturday 1215-1315, 1600-1630, Sunday 1215-1245. Fridays 1600-1700GMT, on the same frequencies.

To North America the Helsinki transmission is operating 2300-2315GMT on 15185-KHz. This transmission is also being heard well in New Zealand with its sign-on at 2300GMT, and the channel of 1518KHz is relatively free from interference.

HCJB ADDS NEW 50KW OUTLET.

Radio HCJB in Quito, Ecuador, has added a further 50KW transmitter for its gospel programs, and has extended some of its services. The South Pacific transmission, on the air—0700-1000GMT, is now also carried for reception in Europe, and HCJB is using 15325KHz for this service. The transmission to the South Pacific is 6050, 9745, 11915KHz and this program also is beamed to Europe on the new 15325KHz outlet.

The service to the South Pacific includes the "DX Party Line" program on Wednesday at 0930GMT, which has items of DX news in the 30 minute program. The service to Europe is from 1330-2130GMT, on 17885, 15325KHz.

MONTREAL DROPS 21460

After only three weeks of operation on 21460KHz for its European and African Services, Radio Canada has reverted to the old 21595KHz channel. The frequency is in operation 1055-1212, 1345-2152GMT. Another change is that 15325KHz replaces 15365KHz, 1055-1832GMT, and then 15320KHz is used 1833 to 2152GMT sign off. The problem of finding clear frequencies for the Montreal transmission is a rapidly growing one. Some idea of the growth in demand for frequencies can be gained from the case of the BBC, which five years ago was using 60 frequencies. The present schedule of the BBC's world-wide transmissions shows over 150 frequencies in use from the 75 to the 11 metre bands.

SUNSPOT RAPID RISE

The rapid rise in the sunspot count is such that it is expected to pass the century mark by October. These conditions have resulted in some excellent HF reception by short-wave listeners. The Swiss Short-Wave Service in its monthly review of the sunspot movement shows that the increase continues to make rapid strides to the projected maximum of the 11-year cycle next year.

The review of the past and predicted counts show them to be as follows: April 65, May 84, June 87, July 91, August 94, September 98 and October 101.

FLASHES FROM EVERYWHERE

EUROPE

BELGIUM: Radio ORU Brussels carries its overseas service to Africa, Far East, North and South America. Daily transmissions are 1000-1215GMT (French, Dutch, Congolese), on 17860, 21510, 21580KHz; 1215-1230 (French, Dutch) on 11760, 21510, 11885KHz; 1600-1715GMT (Congolese) on 11715, 17860, 9740KHz; 1715-1830GMT (Congolese) 11715; 1715-1830 (French, Dutch) 17860, 9740KHz; 1830-2100GMT (French, Dutch) 15335, 9615, 9740KHz; 2315-0100GMT (French, Dutch) 11895, 9615, 9740KHz.

BULGARIA: Sofia is using the new frequency of 5920KHz. Swiss report states the program is in Esperanto at 2015-2030 and then in Italian 2030-2100GMT.

DENMARK: Copenhagen is reported to open at 0100GMT on 9520KHz, with program to North America. Danish is carried to 0145GMT, then English at 0145-0215GMT.

HUNGARY: Radio Budapest is now scheduled to operate in German 1730-1800GMT on 7100, 7220, 9833, 11910, 15160, 17890, 21685KHz. For the period 1945-2000GMT, 3995KHz is also used. English to Europe is 2130-2230GMT on 3995, 6234, 7100, 7220, 9833, 11910, 15160, 17890, 21685KHz. At 2330-2400GMT English is on 3995, 6234KHz. To North America 0030-0100, 0300-0400, 0430-0500GMT using 6234, 2720, 9833, 11910 and 15160KHz. To Australia and New Zealand the schedule is the same as to North America. The DX Program is on the air in English to the Far East on Wednesday 0800-0815GMT, and Friday at 1015-1030GMT both on 11910, 15160, 17890KHz.

VATICAN: Radio Vatican in its service to Africa now operates 1000-1030, 1035-1130, 1155-1225GMT on 17840, 21485-KHz; 1600-1705, 1710-1740, 1840-1845, 1900-1945GMT on 11705, 15135KHz. To Australia and New Zealand 2200-2220GMT on 11740, 15120KHz, and 1130-1150GMT on 11705, 17840KHz.

YUGOSLOVIA: Radio Belgrade has transmissions in English 1830-1900GMT and 2200-2215GMT on 6100KHz. Programs in Spanish are 0000-0030, 0100-0130GMT on 7200KHz. English transmission at 2200GMT which we have been hearing is also announced as being on 7200 and 9500KHz as well as on 6100KHz, which gives the best reception.

DENMARK: Copenhagen has rearranged some of its programs, but has not altered its schedule. The DX session is now carried on Wednesday instead of Tuesday, as formerly, and is in the English half hour. The transmission is at 0145GMT on 9620KHz; 0745, 1245, 1445, and 1915GMT all on 15165KHz. The service at 0745GMT is for listeners in the Pacific area.

ALBANIA: Radio Tirana in a verification card gives its English sessions as 0000-0030GMT on 7265KHz; 0630-0700GMT on 6175KHz; 2000-2030GMT on 7265 and 6025KHz; 2200-2030GMT on 7265KHz; 0230-0300GMT on 9715KHz; 0400-0430GMT on 7265, 7095KHz; 1500-1530GMT on 7265 and 7095KHz.

AFRICA

GHANA: Radio Accra in its External Service in English operates to East Africa and Asia and the Far East 1400-1430GMT on 17910KHz; 1815-1900 on 15285KHz. To North America 2000-2100 on 11850, 9760KHz. To South Africa 1500-1545 on 17910KHz. Central Africa transmissions and to Australasia, 1500-1545GMT on 21545KHz. West Africa program is 1400-2215GMT on 6130, 4980KHz. Europe service 2045-2215GMT on 9545KHz. East Africa service 1400-1430GMT using 17910KHz, 1500-1545 on 21720KHz, 1645-1730 on 15285KHz, 1815-1900 on 15285KHz. Ghana address is Radio Ghana, P.O. Box 1633, Accra, Ghana.

SOUTH AFRICA: Radio South Africa, from Johannesburg, is using new frequencies. The session in French is 1755-1856GMT on 17735, 21500KHz; English 1856-1955GMT on 15285, 17735KHz; German 2025-2125GMT on 11755, 15285KHz; Dutch 2126-2225GMT on 9760, 11900KHz, all beamed to Europe. The English program to North America 2325-0325 is on 9705, 11875KHz. A test frequency is in use, reported to be 15350KHz. The same program is also on 6075KHz.

ETHIOPIA: Radio ETLF at Addis Ababa, is using the new 31M band frequency of 9615KHz. Station opens at 0330GMT, and at 0400GMT a program is carried in English. The station is heard in North America at fair level, but in this area Latin American stations dominate the frequency.

LIBERIA: Radio ELWA, Monrovia (a gospel broadcaster) has announced that it plans to add one 50KW and two 100KW transmitters soon. The station is best received on 15155KHz with Arabic at 1930GMT, and is also heard on 4470KHz, opening at 0615GMT.

NIGER: Radio Niger, P.O. Box 361, Naimy, operates to the following schedule: Friday 0530-0630, 1130-1330, 1500-2130GMT on 7260KHz. On Sunday the schedule is 0700-1630 using 7155KHz, and 1630-2115GMT on 3260KHz. On all other days the schedule is 0530-0630 on 3260KHz; 1130-1315 on 7155KHz; 1700-2115GMT on 3260KHz.

CANARY ISLANDS: Radio Nacional de Espana relay station from Madrid has its relay base at Tenerife, and verifies correct reports with a large red-and-gold pennant. The station schedule is 15380KHz 50KW, 2345-0430GMT, with the Spanish program from Madrid. Samson Voron, Coogee, N.S.W., reports the other frequencies as 9660KHz (50KW 1400-1600GMT) and 11800KHz (50KW 0000-0300GMT). Reports should be sent to Radio Nacional de Espana, Tenerife, Canary Islands.

TUNISIA: Tunis is reported to be using 11970KHz with programs in Arabic. Best reception is at 0805GMT after Radio Liberation leaves the frequency. Tunis is also heard well on 6195KHz at 0600GMT, but suffers interference from the BBC, London, who are on this channel with the World Service.

BOTSWANA: Using 9590KHz Radio Botswana Gaborone, has been testing with a 400W transmitter at 0500-1500GMT. The signal is parallel with 5965KHz which uses 10KW, reports "Sweden Calling DXers." The tests are Wednesday and Thursday. Regular transmissions are daily, 1530-1900GMT on 971 and 4836KHz.

ASIA

MALAYSIA: Kuala Lumpur uses 9710KHz at 1100GMT. The station has Malay programs at this time on this unlisted frequency, but suffers interference from Trans World Radio to 1100GMT. Programs are the same as carried on 4790KHz.


IRAN: Radio Teheran has its program in English beamed to Europe 2000-2030GMT. Frequencies are 11705 and 15105KHz. News follows the station opening announcement.

AFGHANISTAN: Kabul Radio uses the 16M band frequency 17825KHz with news in Pushto at 1130GMT. Signals at 1800GMT on 11770KHz are beamed to Europe and identification is in German and English at this time.


TAIWAN: Broadcasting Corporation of Chian, Taipei, has English programs 0200-0350GMT to North America and Japan on 7130, 15125, 15345, 17720, 17780, 17890KHz; and at 0200-0350 and 1030-1100GMT to Australia and New Zealand on 11825KHz. To Africa 1700-1900GMT on 9685, 9765, 11725, 11825, 15125, 17890KHz in French and English.

IMPORTED SPEAKER ENCLOSURES—HANDCRAFTED TEAK/WALNUT FINISHES!


A wide range of "Sonics" multiple speaker systems is now available . . . budget conscious music lovers and tape enthusiasts wishing to upgrade their speaker systems will appreciate the excellent value of these beautifully finished oiled teak/walnut enclosures. Mail orders will be carepacked and despatched anywhere. All "Sonic" systems are 8 ohms impedance.




Model AS-40A. A miniature 2 speaker system 10½" x 7" x 6" with a wide frequency response. Special floating suspension in the bass speaker **\$19.50**



Model AS-61. A slimline 5 speaker system with four bass/mid range units and a tweeter. Enclosures are only 4½" deep — ideal for bookshelf installations. Will handle up to 20 watts music power. Size is 21½" x 17½" x 4½". Legs are detachable **\$35.50**



Model AS-302. A 2 speaker system with a 12" woofer and a horn type tweeter. Frequency 20 watts music power. Size is 21½" x 17½" x 11½" **\$47**



Model AS-63. The AS-63 is a special bookshelf size speaker enclosure with a 6½" floating suspension woofer and a horn type H.F. unit. Although only 14½" x 9½" x 8½" reproduction is excellent; used with more elaborate speaker systems a magnificent "spread" of stereophonic sound becomes available **\$39.50**

Model AS-60. 18½" x 12½" x 15". \$25. An excellent slim profile enclosure for a modest outlay. See and hear "Sonics" enclosures at Encel Stereo Centres in Sydney or Melbourne . . . they're exceptionally good value at these low Encel prices!



THE PLANET MG-1504 STEREO AMPLIFIER — AN ENCEL WINNER FOR ONLY \$59!

Few stereo amplifiers have excited as much interest as the Planet MG-1504. Although it's only \$59, frequency response is 30-20,000 Hz. plus or minus 2 db. and power output totals 15 watts I.H.F.M. Inputs are provided for stereo pickups, tuners and tape recorders . . . and sensitivity is suitable for magnetic cartridges. Twin pre-amplifiers and power amplifiers are combined on one easily serviced chassis; separate bass and treble controls are provided for each channel. Stereo headphones plug into the socket provided.

Specifications:

Valve complement: 12AX7 x 3, 6BQ5 x 2, 6CA4 x 1.
Input sensitivities: Mag. pickup 5 mV, Tape head 5 mV, Crystal pickup 80 mV, Microphone 5 mV, Tuner 100 mV, Aux. 5 mV.
Size: 12" wide x 8" deep x 4¼" high.

ENCEL PRICE: \$59.

MICRO TONE ARMS

Very highly regarded in the United Kingdom and on the Continent, MICRO tone arms and cartridges have earned an enviable reputation for precision engineering and detailed workmanship. Performance easily justifies the use of the best available amplifiers and speaker systems. Feature for feature MICRO tone arms offer more value for every dollar; design is technically advanced and finish is impeccable.

MICRO MA-88 PROFESSIONAL 16 in. TONE ARM

Designed to provide effortless tracking with the most delicate cartridges, the MA-88 accepts S.M.E. and ORTOFON head shells as well as the MICRO head shell. The latter may be used with any standard ¼ in. mounting cartridge and cartridge location is adjustable by a fore and aft movement of approx. ¼ in. vertical and lateral movement is almost friction-free and is estimated at less than 20 milligrams. Height is adjustable and a bias scale and bias hook system eradicates lateral pressure of the stylus. Stylus tracking pressure is adjustable from 0.5 grams and is clearly indicated on the out-rigger scale. **Encel price \$35.50**



MICRO MA-77S and MA-77 TONE ARMS

Very similar in construction to the MA-88, these tone arms are 12 in. and 14 in. long respectively. A unique eccentric counter balance weight is employed with the "77" series. Connections of all MICRO arms are plug-in types to eliminate soldering, general construction is of machined solid brass and finish is satin chrome. All MICRO arms pivot on miniature ball races. Both these models incorporate the bias hook and weight system to eradicate lateral pressure. **Encel price \$29.50**

READ THE REVIEWS!

Your April, 1966, copy of "Electronics Australia" contains a review of the MICRO MA-77 tone arm on pages 126-127. If you subscribe to "Hi-Fi News" look up your February, 1966, copy for an extensive review of the MICRO MA-77 tone arm and the M-2000/5 magnetic cartridge. This particular review extends over 4 pages!




MICRO MAGNETIC CARTRIDGES OFFER UNEQUALLED VALUE

For only \$19.50 you can now purchase a top quality magnetic cartridge with diamond stylus . . . the Micro VF-3000. Response of this new model is 20-25,000 Hz. The Micro M 2000/5 is Encel priced at only \$16.50, 's of similar electronic design and has a response of 20-22,000 Hz. Both feature a 15° vertical tracking angle. Performance is comparable with cartridges twice the Encel price . . . call in to your nearest Encel Stereo Centre and hear just how effective are the modestly priced Micro moving magnet cartridges. Inc. sales tax: **\$19.50**

M 2000/5

\$16.50



MICRO DUST PICK-UPS

This most effective record cleaner automatically removes dust and static charges as the record is being played **\$3.50**

Encel

ELECTRONICS PTY. LTD.

Head Office: 431 Bridge Rd., Richmond, Vic. Tel. 42 3762
Sydney Store: 257 Clarence St., Sydney. Tel. 29 4563, 29 4564
Australia's Greatest Hi-Fi Centre
* Wholesalers * Trade-Ins Accepted

SOUTH KOREA: Seoul Radio uses 15430KHz for the English transmission to North America 0300-0400GMT, and to Europe 0600-0700GMT. South East Asia service is 0800-0830GMT on 9640KHz, 1430-1500GMT on 15430KHz. The General Service in English 0500-530, 1030-1100, 2100-2130GMT is on 9640KHz.

MONGOLIA: Ulan Bator has its English service Monday, Tuesday, Thursday, Friday, from 2200GMT to 2300GMT on 9540, 11850KHz. A repeat is at 1350-1450GMT on the same days on 7340, 9540KHz, according to verification from the station.

PAKISTAN: Karachi has transmissions to Turkey 1845-1930 and to the United Kingdom in English and Urdu 1945-2030GMT. Frequencies used are 11672 and 15365KHz. Reports on the transmission to Europe are of particular value to the station, which now confirms reception with a new card, and also sends its transmission schedule to listeners.

SINGAPORE: Radio Singapore is heard with its local program on 5052KHz at 1345GMT. This is in English, but from 1400GMT the program is in Malay. Singapore is also the site of the British Forces Broadcasting Service, which uses 5010KHz. The station has been frequently heard at 1120GMT when a news bulletin in English is transmitted.

SABAH: Radio Sabah, Jesselton, is received on 4970KHz, with programs in Malay at 1230GMT. English is broadcast at 1330GMT, with the usual Radio Malaysia announcement as identification.

SOUTH KOREA: The American Forces' Korean Network, which has long operated medium wave service, is soon to be heard on short wave. This will be a 24-hours-a-day transmission and will use the frequencies of 7525 and 14425KHz. The power is to be 100W into a dipole horizontal antenna. It is presumed the short wave relay will be to aid in internal network communication.

THAILAND: The Thai Television Company, Bangkok is now broadcasting 24 hours a day on both its medium wave channel of 1500KHz, and the new short wave channel of 6010KHz. Power on the 6010KHz frequency is reported to be 10KW.

IRAQ: Radio Baghdad in its Arabic service is making use of new channels. On 11785KHz reception has been at 0530-0700, 1200-2200GMT; 15400KHz, at 0930-1200; 9555KHz at 1200-2200; and 7180KHz 1600-2230GMT. The European service, on the air 1930-2200GMT, remains unchanged on 6030 and 6095KHz. English is on the air at 1930-2020GMT.

NOTES from readers should be sent to ARTHUR CUSHEN, 212 Earn Street, Invercargill, N.Z. All times are Greenwich Mean Time, add 8 hours for Perth, 10 hours for Sydney and 12 hours for Wellington time. All frequencies in kilohertz (KHz) previously shown as kilocycles (KC).

LEBANON: The Beirut station has a relay of its Home Service, using omnidirectional aeriads. Program is on the air 0430-0730GMT on 5980KHz, 0925-1600GMT on 9545KHz. Both frequencies have programs in Arabic only.

CEYLON: Radio Ceylon, in Colombo, operates its Commercial Service program in English, 0130-0300GMT on 5020KHz; 0300-0330 on 6130KHz; 0730-0930 on 6130KHz; 1230-1730 on 4870KHz. Its All-Asia Service is carried 0130-0430 on 9670, 15320KHz; 1230-1645 on 9670KHz. The National Service is broadcast week days 1130-1730GMT on 5020KHz; and on Sundays 0430-0730 on 6130KHz; 1130-1730 on 5020KHz.

JORDAN: Radio Amman, on 15170KHz, transmits to South America in Spanish at 2330 with good level. The English transmission at 1700GMT is now carried on 677KHz medium wave only. The station address is Ministry of Information, Hashemite Broadcasting Service, P.O. Box 909. Amman, Jordan.

World Radio Club

The BBC began transmission last month of its new "World Radio Club" program, designed to assist listeners to understand the principles of short wave radio, to indicate new techniques being evolved which will allow better reception, and to explain how listeners can use their equipment to best advantage. Other items of general interest in the new program will include regular news features, notes for DXers, and more specialised technical talks.

Membership of the World Radio Club is open to anybody, simply by writing in. Producer John Pitman hopes that listeners will take an active part in this program, by sending in their suggestions by mail. He particularly wants to know the type of information listeners will find useful, especially the sort of information which they find hard to obtain from other sources. Listeners should send their letters and requests for membership cards to World Radio Club, BBC, Bush House, London, W.C.2.

The BBC World Radio Club is best received in the Pacific area on Saturday at 0745GMT, when it is carried on 7150, 7295, 9510, 9640, 11955, 15070 and 17810KHz. Other times are Sunday at 0245GMT on 6110, 7130, 9510, 9580, 11750, 11780, 15070, 15140 and 15260KHz; Tuesday at 2100GMT on 9410, 9580, 11820, 11860, 12095, 15070, 15260, 15400, 15435, 17790, 21550 and 21710KHz; Thursday at 1245GMT on 11750, 15070, 15420, 15435, 17705, 17790, 17885, 21470, 21550, 21660, 21710 and 25650KHz.

THAILAND: Bangkok reports that a 1000KW station to be known as the Voice of Free Asia is being completed and is expected to be in operation at the end of the year. The site is Tak Li, about 300 miles north of Bangkok. The station will broadcast in Cambodian, Chinese, English, French, Laotian, Malay and Vietnamese, reports "Sweden Calling DXers."

ISRAEL: The present schedule from Jerusalem shows that Kol Israel is on the air to Europe daily at 1545-2000GMT in various languages, including German and Yiddish at 1600 and 1830GMT respectively. The frequency 9009KHz is used with 50KW, 9625KHz with 20KW, 9725KHz with 100KW. English for South Africa is on the program at 2015-2030GMT on 9009KHz, French is at 2045GMT, and English 2115-2130GMT on 9009, 9625, 9275KHz beamed to Europe. Arabic is on the air daily, 0430-0515, 1100-1215 and 1530-2115GMT on 7189KHz with 20KW.

PHILIPPINES: A further new gospel station is to be built in the Philippines. The station will be located in Manila, and its programming will be linked with those of the Voice of the Gospel in Addis Ababa, Ethiopia, station ETLF. The station will be erected at an early date. Its target area will be South-East Asia.

THE AMERICAS

UNITED STATES: Radio WINB Red Lion, Pennsylvania provides good reception of its programs on two frequencies which carry its gospel sessions. WINB is at present operating 1700-2000GMT on 17720KHz, and 2002-2200GMT on 11795KHz. The station has the mailing address, Radio WINB, P.O. Box 88, Red Lion, Pa., U.S.A.

GUYANA: Radio Demerara, Georgetown, using 5980KHz is now better received since the VOA vacated 6985KHz. Station opens at 0915GMT week days and on Sundays at 0942GMT with National Anthem and full identification of the network and stations. Commercial programs follow and, at 0950GMT, English news. Programs of Hindi music make up the rest of the broadcast.

CANADA: Newfoundland station CKZN at St. Johns has been heard on 6160KHz at 0900GMT. The station, with call sign Radio Canada, has an all-night transmission of music. The station break at 0900GMT includes reference to CBN St. John. The Vancouver station CKZU on 6160KHz is also heard at the same time, with its relay of CBU. Both stations have the music program of the all-night Canadian Broadcasting Corporation network.

ECUADOR: HCJB Quito, commenced recently to use a further 50KW transmitter, and is heard in the South Pacific transmission on 15325KHz. Program at 0700-1000GMT is beamed to Europe on this channel and directed to Australia and New Zealand on 6050, 9745, 11915KHz. HCJB is also using 15325KHz 0130-0300GMT in its North American service, and as well uses 15115KHz.

WINDWARD ISLAND: WIBS at Grenada operates to the Eastern Caribbean 1545-1800 on 9550KHz; 1545-2245 on 5010KHz; 2135-0215 on 3280KHz. To Jamaica, 1545-1800, 2000-2245 on 15105KHz; 2315-0215 on 11970KHz. To Ascension Island 2315-0215GMT on 11970KHz; to British Isles 2015-2130GMT on 15105KHz; 2015-2130 on 11920KHz.

The power of the station at present is 5KW, but the Windward Island Broadcasting Service plans to increase this to 100KW.

CUBA: Radio Havana, Cuba, in its English transmissions is broadcasting to Northern Europe 2010-2040GMT on 15285KHz; and to North and South America, 2050-2150GMT on 15270, 15300KHz. Further transmissions are 0100-0450GMT on 6170KHz; 0100-0600GMT on 11760KHz; 0330-0600GMT on 6135KHz; 0630-0800 GMT on 9655KHz.

HAITI: Radio Diffusion Capoise, Cap Haitien, is a new broadcaster which has started test broadcasts on 6175KHz, with 500W. Operation is 1100-1500: 2100-0300GMT weekdays, and 1700-0300GMT Sundays. Reports should be sent to Victor C. Jaar, P.O. Box 393, Port au Prince, Haiti.

ECUADOR: HCJB is using the new frequency of 6130KHz to Europe. The station operates 0430-0630GMT in chain with 9645 and 11915KHz. The station is heard with gospel programs at this time. The frequency of 17885KHz is used 1825 to 2200GMT, also carrying programs to Europe.

NEDERLANDS ANTILLES: Trans World Radio Bonaire, is using 15245KHz for its program to Europe. Schedule is German 2030-2100 and then English 2100-2130GMT. Programs to South America on 9605KHz has Portuguese at 0910 and Spanish at 1000GMT. English to North America on 11780KHz from 0630GMT.


PARAGUAY: Radio Encarnacion, Paraguay, station ZPA5, is being heard at 0015GMT on 11945KHz in North America. This is the only station in Paraguay on the air on short wave at the moment reports A1 Niblack of Indiana U.S.A. in a recent Radio Australia DX Session.

PERU: Radio Union, Lima, using 6115KHz is one of the strongest signals from this country and is heard with sign on at 1100GMT. In New Zealand the sign off at 0600GMT is also received at good level. OAX8V Radio Echo Iquitos on 5010KHz closing at 0500GMT and Radio America Lima on 6010KHz closing at 0600GMT have also been received at good level.

COSTA RICA: Radio TIQ, Radio Casino, Puerto Limon, is heard with sign off in English on 5955KHz. The station has, at times, some interference from Moscow on 5960KHz and on other occasions from Dakar which opens transmission on 5960KHz at 0600GMT. Radio Reloj, on 6205KHz, is noted at 0500GMT and also at 1200GMT when the station plays "Ave Maria" as an identification signal. TIRICA San Jose, using 9615KHz, has been heard with typical Spanish program at 0230GMT.



BATTERY CHARGER



240 Volt A.C. Operation
3 Rate 6V, 12V TRICKLE CHARGE

Trickle Charge Position suits all Batteries. 2V to 12V at rate of 200 to 500 M.A.

STANDARD

2 amp. 6V, 12V, TRC .. \$11.50
3 amp. 6V, 12V, TRC .. \$12.25
4 amp. 6V, 12V, TRC .. \$15.25

DE LUXE

3 amp. \$16.75
4 amp. \$19.75
6 amp. \$21.75
10 amp. \$27.75

Post. N.S.W. 75c. Interstate \$1.25.


Roll or Air Freight on.

MULLARD MAGNAVOX

BOOKSHELF ENCLOSURE
Maple, Teak or Walnut
Complete \$26.00

SUPER BOOKSHELF \$40.50
Post: N.S.W. 50c. Interstate \$1.00.

PLAYMASTER
BOOKSHELF UNITS
6in 8in 12in
\$29.50 \$33.50 \$36.50



GUITAR AMPLIFIERS

10-Watt, Two Channel, with Twin Cone Speaker .. \$53.55 £26/15/
14-Watt, 4 Inputs, Bass and Treble Boost, 2 Twin Cone Speakers .. \$63.00 £31/10/
17-Watt, Four-Channel, Bass and Treble Boost, Two Twin Cone Speakers \$76.25 £38/2/6

35 WATT

4-Channel, Bass and Treble Boost, 4 Twin Cone Speakers .. \$109.95 £54/10/6
Vibrato with foot control and 2 preset controls for frequency and intensity. \$10.50 (£5/5/6) extra on above models.

14 plus 14 WATT

With Reverberation. May be used as 25 Watt or as 14 Watt plus 14 Watt Reverb. Two 9 x 6 Woofer Speakers. Two 9 x 6 Twin-Cone Speakers. 4 Channels, Bass and Treble Boost. Foot Vibrato control included.

\$163.50 £81/15/-

SLAP BASS OR BASS GUITAR 40 WATT AMPLIFIER
4 Input Channels, Bass and Treble Boost. Two 12in Radial Beam Speakers. Perfect reproduction on 20 cycles.

\$159.75

PIGGY BACK GUITAR AMPLIFIER

30 Watt .. \$79.75
45 Watt .. \$99.75
60 Watt .. \$119.75
4 Inputs, Bass and Treble Boost. Vibrato if required, \$10.50 extra.

PLAYMASTER 116

GUITAR AMPLIFIER

Kit Set .. \$79.95
Wired and tested .. \$91.95

PLAYMASTER 117

60 Watt.

\$99.95

Wired and tested, \$111.95.

REVERBERATION- PRE-AMPLIFIER

2-Channel input. Fully transistorised.
A.C. Powered.
Plugs into and matches any Guitar, Organ or P.A. Amplifier.


£29/17/6 \$59.75

TAPE ECHO UNIT

Suits any Guitar amp.
without any alteration.
JUST PLUG IN.

\$139.50

PLAYMASTER 106 AND 107



Feb. and March Elect. Aust.

106

WIRED AND TESTED. \$88.75

107

WIRED AND TESTED .. \$79.00

V.T.V.M. MODEL TE-40 MILLIVOLTER

Spec. A.C.V. Inv.—300 Vrms. 10 ranges. Accuracy 5 cps—1.2 mc. plus-minus 2dB. 10 cps—1 mc. plus-minus 1dB. 20 cps—250 KC. plus-minus 0.2dB.
dR. Scale: 40-30-20-10-0. 10-20. 30-40. 50 dBm. 240 V.A.C.

\$47.50.



MODEL TE-65 V.T.V.M.

D.C.V. 0-1.5-5-15-50-150-500-1500 V. Rms. A.C.V. 0-1.5-5-15-50-150-500-1500 V Rms. 0-1.4-4-14-40-140-400-1400-4000 V. P.P. Resistance RX10,100, .1K, .10K, .100K, .1M, .10M. Decibel—10db, minus-plus 65dB.

240 V.A.C.

\$42.50

TEST EQUIPMENT




WIDE BAND OSCILLOSCOPE

5 Meg. Bandwidth. Push-pull vertical and horizontal Amplifiers. 8 position, high sensitivity vertical Amplifier, Frequency Compensated on all positions. Calibrated .02 to 600 volt. Hard-time base, 20 cycles to 75K. Latest American R.C.A. circuitry. Complete with probe.

3-inch \$99.75; 5-inch \$111.50

T.O.2 TV portable service unit 2" oscilloscope \$59.50.
C.R.O. DOUBLE BEAM SWITCHING UNITS \$39.75



T.E.46

RESISTANCE- CAPACITANCE

Bridge and Analyser.
Capacity 20 pfd to 2,000 mfd.
Resistance 1 ohm to 200 megs.
Also tests power, factor, leakage, impedance, transformer ratio, insulation resistance in 200 megs. at 600V.
Indications by eye and meter.

\$47.75

LEADER SWEEP & MARKER GENERATOR SMG 532

TV and F.M. 2 to 270 Mecs. 5.5 Meg. Crystal for TV sound. Sweep width to 12 Mecs. Model 531.

\$170.00

Post., N.S.W. \$1.50; Interstate, \$2.50


SIGNAL GENERATOR

DeLuxe Model TE-20D.

Freq. range 120 KC—500 Mcs. 7 Bands. Accuracy 2 per cent. Output 8V. Provision for Xtal. Suitable for self calibration. Marker generator. Printed circuit. 240 V.A.C.

\$27.50

Post., N.S.W. \$75c; Interstate \$1.25.



VALVE TESTER

Tests all valves, diodes, rectifiers, checking filaments, shorts. Merit on direct readings. Good-bad meter. Complete with tube chart.

\$26.75

Post. N.S.W. 25c; Interstate \$1.25.

T.E. 50.—99—5011

Checks, Nu Vistas. Compactrons, etc.

\$34.25

G.D.O. UNITS

Leader. \$10. 6-Band. 2 Meg to 260 Meg Navistorised, 240 V.A.C. Operation. Modulated. Calibration. Accuracy 2 per cent.

\$41.50

T.E. 18 Lafayette. 8 Bands. 360 K.C. to 260 Mecs. 240 V.A.C. operation

\$39.50

Post. N.S.W., 50c; Interstate, 75c. T.E. 15 Transistorised. 7 Band. 360 Kc to 270 Mecs.

\$34.75

AUDIO GENERATOR

DeLuxe Model TE—22D.
Freq. range. Sine 20 cps—200 KC. SQ. 20 cps—25KC. Output voltage. Sine 7V. SQ. TV P.P. Output impedance 1000 ohms. Acc. 5 per cent. Distortion less than 2 per cent. 4-range attenuation. 1/1, 1/10, 1/100, 1/1K. Printed circuit.

240 V.A.C.

\$41.50

Post. N.S.W. \$1.00; Interstate \$1.50

PLAYMASTER 115

The new solid state Stereo-Amp-lifier. April Issue.

Wired and Tested .. \$104.00

Kit Set .. \$90.00


Pre-amp to suit magnetic cartridge .. \$12.00

PLAYMASTER 118


Wired and tested \$83.50.

Fitted with Pre-Amp to suit Magnetics Cartridge.

\$95.50.



LAFAYETTE Hi-Fi Amplifiers




LA-350A \$159.50

A superb amplifier which cannot be bettered at any price. At Lafayette's low price, this is an absolute bargain.



LA-248 \$169.50

Lafayette's popular transistorised amplifier at a new low price. First-class performance in every respect.



LA-340A \$146.50

A medium-priced amplifier of high performance. Sounds really good when used with two LAFAYETTE "Criterion 50" speaker systems.



LA-224T \$99.50

A "Remarkable" value by any standard of comparison. Destined to become Lafayette's most popular amplifier in the low price field.

FOR THOSE WHO WANT THE VERY BEST! 70-WATT STEREO AMPLIFIER.

- 7 Tubes 5 Diodes.
- Response 1db 15 to 30,000 cps.
- Power 70-Watts Music; 28 Watts per Channel Continuous.
- DC on Preamp Filaments for Minimum Hum.
- 6 Pairs of Stereo Inputs for All Sources.
- Complete Stereophonic Control Facilities.
- Handsome Extruded Aluminium Front Panel.

50-WATT SOLID STATE STEREO AMPLIFIER

- 19 Transistors 5 Diodes.
- Response 1db 20 to 20,000 cps.
- Power 50-Watts IHFM; 25-Watts per Channel.
- 5 Pairs of Stereo Inputs for All Sources.
- Complete Stereophonic Control Facilities.
- Compact size with Attractive Styling.

40-WATT SOLID STATE STEREO AMPLIFIER

- 19 Transistors 4 Diodes.
- Response 1db 30 to 20,000 cps.
- Power 40-Watts IHFM; 20 Watts per Channel.
- 5 Pairs of Stereo Inputs for All Sources.
- Controls — Bass, Treble, Dual Volume, 4-Position Mode, 5-Position Input, Power On/Off, Speaker/Phones.

NEW! 30-WATT SOLID STATE STEREO AMPLIFIER

- 19 Transistors 8 Diodes.
- Response 2db 30 to 20,000 cps.
- Power 30-Watts IHFM; 15-Watts per Channel.
- Input Sensitivity (Mag. Input) 3 mv at 1-Watt; Tuner/Auxiliary 250 mv.
- Controls — Bass, Treble, Dual Volume, Mode (Mono, Stereo), 3-Position Input, Power On/Off, Speaker/Phones.

LAFAYETTE ELECTRONICS

Division of Electron Tube Distributors Pty. Ltd.

All Mail Enquiries and Orders to:

VICTORIAN SALES CENTRE
AND HEAD OFFICE,
15A WELLINGTON STREET
WINDSOR, S. 1, VIC., 51-6362.

See LAFAYETTE Hi-Fi equipment also at:

A. VICTOR & CO., 196 Elizabeth Street, Sydney, N.S.W.

C. A. PEARCE & CO. PTY. LTD., 33 Bowen Street, Brisbane, Q'LAND.

BROADCAST BAND NEWS

Continued from page 165

AUSTRALIA—The Postmaster-General, Mr Alan Hulme, has introduced legislation into Federal Parliament designed to forestall any attempts by commercial interests to establish "pirate" radio stations operating in international waters off the coast of Australia. Clause 4 of the Bill makes it an offence for any person "to establish or maintain a transmitter on a ship in waters adjacent to Australia for unauthorised broadcasting purposes." It will also be an offence for any person to assist in unauthorised broadcasts or to render services for the operation of the ship and the transmissions.

Clause 5 extends the jurisdiction of Australian courts to deal with offences arising from these activities. Mr Hulme said the Bill would be enforced as necessary in full accordance with Australia's international rights and obligations. He continued, "The Bill is much less comprehensive than the legislation which it has been found necessary to introduce, for example, in Britain in order to deal with the pirate radio problem in Europe. Nevertheless, it is expected that the Bill will be adequate to deal with the situations which are likely to arise in the Australian environment. However, the matter will be kept under close study, and if, perchance, this legislation is found to be deficient, the Government will be prepared to consider more comprehensive provisions."

Introducing the Bill, the Postmaster-General pointed out that the pirate stations operate outside the law; they pirate radio frequencies and use them without Government authority. He said:

"They represent a challenge to the lawful control of radio communications including broadcasting, and upset the good order and discipline essential to ensure a service free from interference for the thousands of lawful users of the various frequencies. These include sound broadcasts, television, aircraft and ship navigation, public communications, police, fire protection and the host of other ways in which radio communications are now utilised. The radio frequency spectrum is public property, and the public is entitled to the assurance that appropriate control is being exercised."

He pointed out that Australia was a signatory to the International Telecommunication Convention and the associated radio regulations. One regulation specifically prohibited the establishment and use of broadcast stations on ships, and another laid down that no transmitter may be established or operated without an authorisation from the Government in question.

While Australia had not till now been troubled with pirate broadcasters, some abortive attempts had been made to establish unauthorised transmitters off the coastline, and there were indications that a fresh attempt was to be made in the Gold Coast area. It was because of this that the Government had decided to bring down the present legislation.

AUSTRALIA—Three new Queensland commercial stations are expected to be on the air within the next two months. 4GG Gold Coast, 1200KHz (2KW) is scheduled to open on September 1. The new Atherton station, 4AM, on 560KHz with 2KW, is scheduled to come into operation in about two months' time. The third station, 4KZ, at Innisfail, is to use 800KHz with 2KW and is also scheduled for September 1 opening.

ANSWERS TO CORRESPONDENTS

When writing to us:—

- Please give you name and full postal address including the State.
- Write the above information clearly or, for preference, print it in block letters. Your co-operation will facilitate delivery of replies by mail, where such are called for.

MORE SIMPLE PROJECTS: I know many boys who buy electronics magazines looking for simple things to build but most of the projects are too complex. (A.S. Wollongong, N.S.W.).

The problem of trying to provide for an increasingly diverse readership is one which has faced all electronics magazines for some years and it is one which we have remarked upon a number of times. We can't promise to re-shape the journal for our younger readers only, but your request adds weight to the plea for more simpler projects.

INPUT IMPEDANCE: Would the 4-channel mixer published in the February, 1967, issue match the input impedance of my tape recorder which is 20K? The mixer has an input impedance of 5M. Must I use microphones having the same impedance? (K.L.J., Lucindale, S.A.).

The subject of impedance matching — when it is important and when it isn't — is one which seems to be worrying a lot of readers lately. We have earmarked it for discussion in detail when the opportunity occurs. As a general rule matching is most important when we wish to transfer the maximum amount of power from a generator, such as an amplifier output stage, to a load, such as a speaker. The correct load will enable maximum power to be developed across the load while ensuring that the generator operates under the correct conditions for minimum distortion. Almost equally important is the situation where the generator is a predominantly reactive device, such as crystal or ceramic pickup or microphone. In this case a correct load is necessary to ensure adequate output at the lower frequencies. Too low a load value and the bass response falls off seriously. Neither of the problems posed here is as serious as this. The use of a 10K source impedance (the mixer) to feed a 20K load (the tape recorder input) should present no problems at all. In fact, almost any value of load from about 10K upwards would be satisfactory. In the case of the microphone inputs, we went to a lot of trouble to produce a transistor circuit with a high enough input impedance — about 5M — to suit crystal microphones. However, as we stated on the second page of the article, microphones needing lower values of load for best performance may be easily accommodated by shunting the input circuit with a suitable value resistor, typically 47K.

TAPE BIAS CONNECTION: Could you please explain why, in some tape recorders, some of the erase signal is fed to one side of the "record" winding and the signal to be recorded to the other side? (B.A. Brisbane, Qld).

What you refer to as "some of the erase signal" is the high frequency bias which must be introduced into the record head simultaneously with the signal to be recorded, if the magnetic pattern on the tape is to be distortion-free. The bias voltage and audio voltage are often fed to the one side of the record head, the other side being earthed or at least bypassed to earth. This can lead to a certain amount of difficulty, in that the bias feed circuit can act as a shunt on the audio signal feed, tending to bypass the higher audio frequencies back

to earth through the windings of the oscillator coil. By feeding the audio and bias signals to opposite ends of the record head coil, this trouble can be minimised. Whether or not it is convenient to arrange matters this way depends to some extent on details of the circuit and also on the accessibility of leads from the head. In some tape decks, for example, one end of the record coil is earthed adjacent to the head and it can be rather tricky to isolate the wire and provide the necessary extra lead.

FLUIDIC DEVICES: I have read a lot recently about the application of fluidic systems being used to control industrial operations. In view of the recent excellent series on electronic logic, why not a coverage of fluid logic, with particular reference to the fluidic/electronic interface? I notice that the Plessey Group appears to be very active in this field and, in America, the Corning Glass Works. (D. J., North Melbourne, Vic.).

Normally, non-electronic devices would not qualify for coverage in an electronics magazine but the whole thinking so parallels electronic techniques that it invites comparison and coverage. We will certainly keep your suggestion in mind — without making any promises for the immediate future.

WHAT QUALIFICATIONS? Will you advise me what education I will need for a career in electronics? (D.H., Palmyra, W.A.). It will depend entirely on what level of achievement in the industry you aspire to, D.H. You will need at least the School Certificate or its equivalent since this is usually asked by employers accepting young

persons as apprentices or cadets. If you are aiming at a higher level, such as a university degree, you will have to satisfy the matriculation requirements of the university concerned. We published a three-page article on the subject "Careers in Electronics" in our December, 1966, issue. If you cannot lay hands on a copy of this, the article can be obtained through our Query Service for 20c.

SUBSTITUTE TRANSISTOR: Can an OA95 diode be used instead of the OA202 used in your design for a three-band super-het receiver, described in the April, 1966, issue? If not can you suggest a suitable replacement? (R.R., Vermont, Vic.).

We are rather puzzled as to why you should be seeking a replacement, because the OA202 is readily available and not particularly expensive. The OA95 is not a suitable substitute in this case, since it is a germanium type with much lower reverse resistance and it would prejudice operation of the AGC system. A suitable substitute would be the BA100.

VARIOMETER COILS: Could you please tell me the number of turns for coils on a variometer? (J.W., Timaru, New Zealand). The number of turns required depends on the circuit in which the variometer is to be used. As we have never published a circuit using a variometer, we cannot supply any information on the subject.

AUSTRALIAN BROADCASTING: Could you publish any information about Australian broadcasting—networks, private and Government stations, etc.—and also future development of broadcasting, especially in the television field? (A.G.W., Auckland, N.Z.).

We publish an annual (January) summary of Australian (and New Zealand) broadcasting stations, including television channels, with the frequency, call sign and power of each. We also publish in "News" any information which we receive about developments planned or carried out.

"ELECTRONICS Australia" Information Service

As a service to readers "ELECTRONICS Australia" is able to offer: (1) Photographs, dye-line prints and other filed material to do with constructional projects and (2) A strictly limited degree of personalised assistance by mail or by reply through the columns of the magazine. Details are set out below: **REPRINTS:** For a 20c fee, we will supply circuit data, as available from our files. The amount of data available varies but in no case does it include material additional to that already published in the magazine. For complicated projects involving material extracted from more than one issue, an extra fee may be requested. As a rule, requests for circuit data will be answered more speedily if the circuits are positively identified and the request is not complicated by questions requiring the attention of technical personnel. Where articles are not on file, we can usually provide a photostat copy at 20c PER PAGE.

PHOTOGRAPHS, DYE-LINE PRINTS: Original photographs are available for most of our projects, from 50c plus 8c postage for a 6in x 8in glossy print. In addition, chassis dye-line prints are available for most projects for 50c each; these show dimensions and the positions of holes and cut-outs for metal-working but give no details of wiring.

BACK NUMBERS: A fairly good selection is available. On issues up to 6 months old there is a surcharge of 5c. On issue from seven to 12 months old the surcharge is 10c. Over 12 months, it is 20c. Package and postage is 10c extra.

REPLIES BY POST: This provision is made primarily to assist readers in matters relating directly to articles and projects published in "ELECTRONICS Australia" within the last twelve months. Note, however, that we cannot provide lengthy answers, undertake special research or modifications to basic designs. A 20c query fee must be enclosed with letters to which a postal reply is required; the inclusion of an extra fee does not entitle correspondents to special consideration.

OTHER QUERIES: Technical queries which fall outside the scope of "Replies by Post" may be submitted without fee and may be answered through the columns of the magazine at the discretion of the Editor. Technical queries will not be answered by telephone.

COMMERCIAL EQUIPMENT: "ELECTRONICS Australia" does not maintain a directory of commercial equipment, or circuit files of commercial or ex-disposals receivers, amplifiers, etc. We are therefore not in a position to comment on proposed adaptation of such equipment, or on its general design. Prices, specifications or other assistance must be sought from the appropriate advertiser or agent.

REMITTANCES: These must be in a form negotiable in Australia. Where the charge may be in doubt, an open cheque, endorsed with a limitation, is recommended.

ADDRESS: All requests for data and information, as set out above, should be directed to The Assistant Editor, "ELECTRONICS Australia," Box 2728 G.P.O., Sydney, New South Wales. Other correspondence should be directed to The Editor.

SOUND PROJECTORS
Cinevox Perfect 16mm in good working order. 240v operated, complete with speaker and amplifier.
£57-10-0 \$115.00

CIRCULAR SLIDE RULE

3 1/4in diameter. Will do the same work as the conventional slide rule. Instruction book included.

12/6 \$1.25 each
Post 10 cents

REFLECTOR GUNSIGHT

Contains these lenses:

1 Lens 1 1/2in Focus, 1 1/2in diam.
1 Lens 1 1/2in Focus, 1 1/2in diam.
1 Air-spaced Lens, 1 1/2in diam.
1 Filter Lens, 1 Graticule.
1 Lampholder.

18/6 \$1.85

Post: N.S.W., 30c; Interstate, 40c.

P.M.G. TYPE TELEPHONES

Standard desk type with magneto calling device. Range 30 miles. Uses standard batteries at each phone. Any number can be connected together on single line.

£11-10-0 \$23.00

(2 TELEPHONE SETS)

30c cartage to rail. Freight payable at nearest attended railway station.

AERIAL CAMERAS

F.24 Mark IV 2.9 Lens, stops 11, 8, 5.6, 4, 2.9.
With 3in x 8in F1 Dallmeyer Lenses complete with wooden case.

£19-10-0 \$39.00

50c Cartage to Rail. Freight payable at nearest attended railway station.

SHIPS' CLOCKS

(No. bell). Smith's 8-day, fully jewelled. Original cost \$120. Special 7in brass \$25. 10 1/2in Seth Thomas splash-proofed bakelite

£15 \$30

Post N.S.W., 70c; Interstate, 95c.

MINIATURE ELECTRIC MOTORS

1 1/2 to 3 volts DC. Ideal for model boats, cars, planes, etc. Strong torque.

39 cents each
(Post 7c)

TELEPHONE WIRE

21 gauge copper, plastic covered. Ideal telephone or bell wire. 1.320m coil of twir (equal 1/2 mile). \$7.00 per coil.
Post, N.S.W., 70c; Interstate \$1.20.

3000 TYPE RELAYS

P.M.G. 200 Ohm — 1,500 Ohm Coils, £1.25 each.

AWA OSCILLOSCOPE

Calibrated with delay time base. 8in, 240 vac., perfect.

£97-10-0 \$195.00

AMPLIFIER

Subminiature 4-Transistor, Audio Push-Pull.

£3-10-0 \$7.00 Post 50c

GOOSE NECK LAMP

NEW. IDEAL FOR DESK or WORK BENCH. Adjustable shade, strong metal lacquered base and frame. Height 18in. Complete with lead.

12/6 \$1.25


Post and packing, \$1.00.

HAND BEARING BOAT COMPASS

With magnifying prism illuminated. Brand new in wooden carrying case. Complete with batteries. Ideal for pin-pointing your secret fishing spot.

\$35.00 (£17-10-0)

Post, N.S.W., 70c; Interstate, 95c.



P.M.G. Phone Jack and plugs, 25c each, 45c the pair.
Post 7c.

NIFE CELLS

1.2 Volt fully charged, 4in x 3in x 1in 4 AH.

10/- \$1.00 each

Post, N.S.W., 25c; Interstate, 35c.
1.2 volts 15 AH, 8in x 4in x 2in, \$2.95.


2.4 volt 10 AH, 6in x 2 1/2in x 2in, \$2.50.
Post, N.S.W., 30c; Interstate, 40c.

PERSPEX

Slightly domed shape, 16in x 12in, \$1.55. 2ft 6in x 18in tapering to 6in, \$1.75. 2ft 6in x 2ft, \$2.45. Domed approximately 3ft 6in x 2ft, \$3.50.
50c cartage to rail. Freight payable at nearest attended railway station.



P.M.G. TYPE KEY SWITCHES.
45c each. Post, 15c.



30 x 30 Power Coated Lens.
Brand new.

37/6 \$3.75

60 magnification with a 60mm coated objective lens.
With Tripod.

£11-10 \$23.00

As illustrated.
Postage, 95c; Interstate \$1.20.

HIGH STABILITY RESISTORS

I.R.C. brand new 1/2w., 1w, 2w, tolerances between 1 and not exceeding 5% including 100, 360, 560, 750, 15K, 22K, 27K, 100K, 180K, 220K, 560K, 820K, ohms. Usual price 40c each, 50 assorted different values for only

37/6 \$3.75

Post 15 cents

GENUINE VARIACS

0-115 V.A.C. 18 Amps, \$29 each, or couple 2 together for 240 V.A.C.

The two for **\$45**

Genuine American

Zenith Variacs

0-115 V.A.C. 7.5 Amps, \$19.50 each or couple two together for 240 V.A.C.

The two for **\$36**.

50c cartage to rail. Freight payable at nearest attended railway station.

522 TRANSCEIVERS

100 to 150 m/c.

£17-10-0 \$35.00

KLYSTRON MIXER/DUPLEX units, 9375 megs, complete with crystals, \$13, £6/10/- each. Post, N.S.W., 45c; Interstate, 50c.

FRACTIONAL 240V AC MOTOR

1/25 h.p., new, with coupled 2-speed gearbox, 1428 and 300 r.p.m. Ideal for rubber, etc.

£10-0-0 \$20.00

Post N.S.W., 70c; Interstate, 95c.

SWITCH BOARD FRAMES

Steel ex-P.M.G. Height 4 1/2in x 27in x 3 1/2in will make ideal test bench. £5 — \$10.

Freight payable at nearest attended railway station.

VALVES

BRAND NEW

IN CARTONS.

Special discount for quantity

807	\$1.75	6AG5	50c
6SN7GT	95c	12AU7	\$1.00
89	\$1.00	X61M	\$2.20
12SA7	\$1.25	CV850	\$1.50
6116	45c	1H6G	30c
41	\$1.25	832	\$5.00
5U4G	95c	6F13	75c
77	\$1.00	6AK5	\$1.50
VR150-30	\$1.00	6X4	\$1.00
5CPI	\$3.95	6F8	75c
EF50	35c	6N7	\$1.00
6U7	75c	12SK7	50c
V1103	\$1.00	VR1120	80c
VH120	75c	VR118	75c
IL4	\$1.00	VR69	25c
5Y3	\$1.50	VT4C	75c
6C4	50c	AU5	\$1.00
CV2184	\$2.35	80	\$1.25
2 x 2	75c	6AK8W	\$1.50

PLEASE ADD POSTAGE ON ALL ARTICLES.

TELESCOPES

30 x 40 with Tripod

£3-19-6 \$7.95

ASTRONOMICAL TELESCOPES

3 1/4" Reflector, 126 Magnification complete with 4X Finder and Equatorial Mount.

£29-10-0 \$59.00

Post N.S.W., 70c; Interstate \$1.20

C.M.A. CABLE

240 volt 3/.036 black, new and perfect. 100 yds. rolls, \$3.00, 6 or more.

£1-5-0 \$2.50

30c cartage to rail. Freight payable at nearest attended railway station.

MICROMETERS

Brand new Goodell-Pratt, 0 to 1in, \$7.50; Slocumbe, 1in-2in, \$7.85; Starrett 1in-2in, \$9.85.

Post, 32c.

CHOKES, 7.5H, 60mA 95c

VIBRATORS, 6 volts, 7-pln, 75c each.

UNISELECTORS, 4 BANK, \$4.00

INVERTERS, 26v-118v 2Kw 400 cycle

HAND MICROPHONES, with Press-to-Talk Switch 95c ea.

Post, N.S.W., 25c; Interstate, 30c.

INSTRUMENT TRIPODS, sturdy wooden frame. Telescope extend to 4ft 6in \$15.00

SELSYN MOTORS MAGSLIP Mk. II \$3.25 ea.

No. 19 1-way radios, with hand set, power supply, leads, \$35.00

Meggers, bridge type, complete and tested \$75.00

EVERSHED and VIGNOLES, 500 volts.

BINOCULARS

PRISMATIC, Coated Lenses.

Brand new. Complete with case.

8 x 30 \$18.75

7 x 50 \$22.15

10 x 50 \$23.07

12 x 50 \$23.95

20 x 50 \$24.75

Post, N.S.W., 70c; Interstate, \$1.20

ELECTRONIC KIT

With solar cell can experiment with 20 different circuits. Including wireless, microphone, morse code, transistor radio, audio frequency amplifier, telegraph, transmitter, intercom., signal tracer, etc. No tools, no soldering. Easy to assemble. Assembly manual included.

\$19.95

Post N.S.W., 45c; Interstate 60c.

MINE DETECTORS

Ex A.M.F. No. 2 Mk. 3, with Instruction Book. Complete in wooden case. Ideal for plumbers, councils for locating buried pipes, etc. Freight payable at nearest attended railway station.

\$39.00

4 DIGIT RELAY COUNTERS

50-volt D.C., suit slot car. Lap counters, etc.

\$1.25, 12/6 each.

Post 15c.

RECORDING TAPES

SCOTCH BRAND.

EX-WOOLMERA.

SLIGHTLY USED.

PERFECT ORDER.

Ideal for professional quality audio recording.

1200ft 7in reel 1/4in \$2.75. Post 12c.

600ft 5in reel 1/4in \$1.65. Post 12c.

200ft 3in reel 1/4in 65c. Post 10c.

CRYSTAL CALIBRATOR

With 500kc crystal up to 32 m/cn. used, good condition. £4/17/6 (\$9.75).

ALTEC STUDIO MICROPHONES

639B Western Electric, top grade, original cost \$250. Ideal Broadcast Studio, music recording, Church and play recording etc., £45, \$90.

SCOOP PURCHASE

Gramo. Motors. New. Made in U.S.A. 4-speed. 240 volt A.C. 50 cye. Only \$2.75 each. Post, N.S.W., 30c; Interstate, 40c.

240-110 VOLT 6KVA TRANSFORMERS

Encased, including switches, no new, \$50, £25.

SPECIAL lucky dip valve offer. 15 new valves in cartons for only \$2.00. We haven't got time to sort them, so you reap the benefit. Post, 30c.

SOLENOIDS

Plunger Type 12V 300M.A. Suit electric camera control, miniature trains, radio, etc.

\$1.25, Post 10c.

200 Mill. amp., 24 volt, 1/6in push movement.

\$1.25, Post, 10c.

BATTERY CHARGER

6 or 12-volt. 2 1/2 amp, without meter, \$10.50, £5/5/-.

2 1/2 amp with meter, 4 amp with meter \$14.50 \$12.50, £6/5/-.

Post, N.S.W., 70c; Interstate, 95c.

TELEPHONES

Sound Powered. Can be used as Microphone and Receiver. New. With 50ft cable.

\$3.85 pnb.

Post, 25c; Interstate, 40c.

CARPHONES

A.W.A. or S.T.C. Two-way radio. 75-80 megs, cycles, 12-volt operated. £22/10/ (\$45) each.

EX ARMY TELESCOPES

4 x 40 Handley, \$6.50.

7 x 40 Otway angle telescope, \$9.85. Freight payable at nearest attended railway station.

Deitch Bros.

70 OXFORD STREET, SYDNEY

SORRY, NO C.O.D.

ANSWERS TO CORRESPONDENTS - continued

COLOUR TV COSTS: "Broadcasting" magazine for January, 1967, quotes a figure of \$350,000 (U.S.) as the cost of equipping an average TV station for colour, though some stations spend nearer \$1,000,000. Colour operation adds about \$40,000 per year to operating costs, although some stations spend nearer \$100,000. Advertisements cost more to produce and are more costly to the sponsor but there has been a rapid increase in colour penetration on all fronts. (G.F., Toorak, Vic.)

Thank you for the information, which we had not seen in this particular form. A lot of dollars will have to be spent before colour can be brought to Australian homes!

CAPACITOR ANALYSER: Would you consider publishing construction details for a capacitor analyser similar to a commercial one advertised in your magazine? I think this is a long-felt want (G.F.J., Fairfield, N.S.W.)

It is possible there is some need for this type of equipment among some of our readers, G.F.J., but, considering the cost of development of such a piece of equipment and the cost of construction, we feel that this is a little too ambitious an idea.

"PLAYMASTER" AGAIN! Upon opening your issue for April I was shocked to see yet another "Playmaster." This series seems to be getting as bad as "Dr Paul" or "Dad And Dave" on the radio and is quite out of keeping with the stream of fantastic articles on other subjects. Surely your staff should all have a Playmaster of their own by now! Also, I don't like the new term Hertz/sec. (J. McL. Christchurch, N.Z.)

When society stops producing people with an awakening interest in high fidelity sound reproduction, and limited funds to meet that interest, we'll stop producing Playmasters! Far from being a project to fill up space, the 115 in the April issue represented up-to-the-minute techniques with silicon transistors and was the result of many requests for something along these lines. If the 115 worried you, you will have had apoplexy when you saw the 118 in the July issue; yet this, too, was the result of pressure to up-date a design that had remained a good seller for years. The saving feature is your description of other articles; you'll just have to put up with the Playmasters! Inevitably, there will be readers who tend to think the other way round. As regards your reference to Hertz/sec, we wouldn't like such expression, either. The term "Hertz" means "cycles per second" and, as such, has the merit of economy of expression. Some people like it, some people don't but our own feeling is that its adoption is inevitable. That's why we changed.


TESTING MICROPHONES: In the March issue "The Serviceman" commented on the danger of testing a microphone with an ohmmeter, due to possible damage to any mu-metal transformer. Some years ago I had occasion to return a microphone to the agents for repair, and was advised that it had been damaged by the application of an ohmmeter. Could you comment on the risk to (a) the transformer, and (b) the microphone element. (J.C.R. Wallsend, N.S.W.)

As you imply, there appear to be two different risks associated with tests of this kind. The more serious one, to our way of thinking, is that associated with the transformer. The nature of mu-metal is such that the passage of DC through an associated winding can cause a serious shift in its magnetic characteristics, resulting in reduced inductance in the transformer windings and attenuated bass response in the microphone system. The other risk is to the suspension system of the microphone voice coil, in the event that a continuity measurement passed enough current through

the coil to cause excessive movement. The greatest risk here would arise from use of low ohms ranges on simpler types of multi-meters, where a current of 100mA can flow, in conjunction with microphones with no internal transformer and direct access to the voice coil. In short, the rule would seem to be not to use the conventional ohmmeter at all where a transformer might be involved, and to use it with due regard to the current involved where the voice coil only is involved.

FREMODYNE FOUR: I am trying to build the Fremodyne Four Receiver (March, 1967) but I am in doubt as to how to wind the balun coil. Could you oblige with a rough sketch? Enclosed with parts I purchased was (I surmise) a small ferrite balun former like this (sketch enclosed). Am I correct? (R.E., Belmont, W.A.)

FOUR TURNS, 24 B & S ENAMELLED
COPPER WIRE, CENTRE TAPPED.



The ferrite former you have depicted is the one intended for the balun. The winding details were given on page 57 of the original article, but may not have been sufficiently detailed for some of our less-experienced readers. We have therefore prepared the accompanying drawing. It may be easiest to regard the winding as consisting of four turns, with a centre tap. It is wound over the centre of the core, by passing the wire through one hole in one direction, then back through the adjacent hole in the opposite direction. This is repeated until four turns have been wound on the centre leg. It may be convenient to provide the tapping after the second turn is complete by doubling over a couple of inches of wire and twisting it to form a lead.

SPEED "RADAR:" Have you any intention of describing a device to warn motorists when they are under speed radar surveillance? A leaflet (copy attached) describes such a device, which can also be used on boats to indicate when they are within a radar scan, alerting them to the appropriate time to release a distress flare, or take evasive action if the radar is on a ship which may not see them. Would such a device be legal? (P.M., Pitt Street, Sydney.)

We have not had any direct experience with a commercial unit such as the one you mention, nor have we any plans to describe such a unit for home construction. The device would probably be classified as a receiver and would scarcely qualify for any kind of a licence. In the event of the authorities deciding to take action, they would probably be able to do so, using such legal processes as apply to the operation of unlicensed radio receivers. We do not find all the talk about marine use very convincing, nor are we impressed by the advice that one's "priceless" licence should be protected by driving soberly and carefully and using a The sober careful driver is the very one who has least cause to worry about speed checks!

STEREO EXCHANGE: I got my start in stereo with your Playmaster 101 and my first record was the Black Dyke Mills Band, to which you gave a good review—and deservedly so. Most of my records have been bought on the strength of your reviews or recommendations from friends. Is there some way you could accommodate in your columns a kind of stereo penfriend record-exchange system, so that enthusiasts could exchange information, records, etc.? (N.W., Ferny Grove, Qld.)

We are glad to know that you set so much store by our record reviews. The idea of a free "wanted to exchange" or "penfriends wanted" column closely parallels other recent requests for a free section to cater for tape enthusiasts and yet another to support the disbursement, exchange or acquiring of surplus components. This kind of activity can rapidly get out hand and also cuts right across the purpose of our classified advertising columns. Any reader who wants to acquire pen friends or put himself in the market for the exchange of records or tapes can do so by buying three or four lines of space in occasional issues. The cost would be modest compared with the value of the planned activity.

VALVES

Brand	New Post Free	in Cartons
OC3	75c	6N7 50c
IL4	30c	6SC7 50c
2A3	\$1.50	6SJ7 50c
5MK9	75c	6SL7 75c
5Z4GT	75c	6U5G 75c
6AT6	75c	12K5 75c
6AK5	60c	15DQ8 75c
6AF6	75c	807 \$1.50
6C4	40c	868 \$1.00
6CH6	\$1.00	VR105 75c

TRANSFORMERS \$5.00

240 volt-50 cycle primary with two secondary windings, 6 volt at 12½ amp and 6 volt at 2½ amp.
Post and Packing \$1.00.

ALUMINIUM OFFCUTS 30c

Hard aluminium sheet offcuts, suitable for chassis panels, etc. 10¼in x 15¼in x 20g.
Post and packing 15c per sheet.

FM TRANSMITTERS AND RECEIVERS \$25 pair

80 MC A.W.A. type FJ52860 Transmitter and FC52859 Receiver in good condition but less output valves, crystals and control unit.

SPECIALS!

2N3565 Audio Transistors. (BC108)	75c
2N3693 RF Transistors	75c
1-5 PF Ceramic Trimmers	5c
250K Log Pots	20c
240 Volt Miniature Neons	40c
SP DT 5 Amp Toggle Switches	45c
5mf 6VW Miniature Electrolytic	10c
PMG. Jack Plugs and Sockets	35c
PMG. Key Switches	20c
2 Henry 500 ma Choke, (75c post)	\$1.00

SPECIAL DISCOUNTS FOR QUANTITY PLEASE ADD POSTAGE

METERS \$3.75

Brand new, 3¼in Diameter, English G.E.C. meters; .5-0-5 milliamper movement with a 50-0-50 scale that can be illuminated.
Post and Packing 30c.

P.M.G. RELAYS 70c.

500, 1000, 1500, 2000 and 5000 Ohm. Heavy duty 3000 type with plenty of contacts.
Post and Packing 10c.

RESISTORS

3 ohm 75w Flat	\$1.00
150 ohm 25w	20c
330 ohm 10w	5c
1000 ohm 8w	20c
1800 ohm 30w Slider	30c

Please add postage.


RELAYS \$2.00

Brand New, 3000 type relays, 45 ohm coil with approximately 10 amp. 240 volt. make contacts.
Post and Packing 10c.

HARE & FORBES PTY. LTD.

180 George Street, Parramatta, N.S.W. Ph: 635-9947, 635-6096.
Open Saturday Morning — Inspections welcome.
Please print name and address clearly.
Please add full Post and Packing any excess shall be refunded.

A COOL 400V



Delco Radio's new DTS 413 and DTS 423 power transistors, are conservatively rated at 75 and 100 watts. Our standard TO-3 package assures low thermal resistance (junction to heat sink 1.0°C per watt) for cool power. The silicon element gives you high voltage protection, high frequency response and low saturation voltage.

The price is low (less than 3c. a volt for sample quantities) for two reasons: special inter-digitated geometry of the devices and our unique 3D* process for high yields.

Now you can reduce current, the size of other components, and increase efficiency in high energy circuits. Vertical and horizontal TV outputs, for example.

Your Delco Radio Semiconductor distributor has these two new power transistors on his shelf. Call him today for data sheets, prices and delivery.

*Triple sequential diffusion

RATINGS	DTS 413	DTS 423
VOLTAGE		
V _{CEO}	400 V (Max)	400 V (Max)
V _{CEO} (Sus)	325 V (Min)	325 V (Min)
V _{CE} (Sat)	0.8 (Max)	0.8 (Max)
	0.3 (Typ)	0.3 (Typ)
CURRENT		
I _c (Cont)	2.0A (Max)	3.5A (Max)
I _c (Peak)	5.0A (Max)	10.0A (Max)
I _B (Cont)	1.0A (Max)	2.0A (Max)
POWER		
	75 W (Max)	100 W (Max)
FREQUENCY RESPONSE		
f _t	6 MC (Typ)	5 MC (Typ)

INDUSTRIAL AND DOMESTIC EQUIPMENT COMPANY

(Division of General Motors-Holden's Pty.Ltd.)

Princes Highway, Dandenong, Victoria. Offices at Sydney, Brisbane, Adelaide



**AUTHORISED
DISTRIBUTORS:**

New South Wales: Anodeon, 443 Concord Road, Rhodes, Sydney. Phone 31 0311


Victoria: Anodeon, Astor House, 161-173 Sturt Street, South Melbourne. Phone 69 0300

South Australia: Anodeon Sales Division, Astor House, 101 Flinders Street, Adelaide. Phone 23 4022

D.T.1

WE CONFESS!

We've boobed. And the end result is all **your way** if you're interested in building your own tape recorder incorporating some of the world's finest decks. You see, we overestimated the size of the tape deck market in Australia when we ordered overseas and we have large stocks of decks we wish to clear . . . **AT LESS THAN COST!** All are **brand new** and **fully guaranteed**.



FAMOUS FERROGRAPH MODEL 6G STEREO DECKS

Three speeds, erase-record-playback heads included, three motors including synchronous capstan motor, all "Ferrograph" features. Wow and flutter is less than 0.16% at 7½ ips. A truly professional tape deck—it's little wonder they're called "The incomparable Ferrograph"!

\$149

** Now's the time to build that tape recorder you've been waiting for!*

ENCCEL ELECTRONICS PTY. LTD.

MELBOURNE

Head Office: 431 Bridge Rd., Richmond, Vic. Tel. 42 3672

SYDNEY

Sydney Store: 257 Clarence St., Sydney. 29 4563, 29 4564

Australia's Greatest Hi-Fi Centre

ANSWERS TO CORRESPONDENTS - continued

TRAIN CONTROL SUGGESTIONS. Your recent articles on electronic train control prompts me to suggest the following projects: RF carrier control of model locomotives with a different frequency for each loco; Train detectors able to detect the presence of a train on a section of track whether the train is moving or stationary; Whistles emanating from a miniature ear-piece mounted in a locomotive. (G.D.T., Cambridge, England).

We published an article on RF carrier control in April, 1960, using transistors in a similar circuit to that which you suggest. The idea of train detectors has been raised by a few other interested enthusiasts and is one which we will keep in mind for a possible future project. Train noises are best left to the ingenuity of the individual but are probably easier to accomplish by using track-side speakers timed to give the required noises as a train passes. There is a practical limit to the total amount of electronics—and complexity—which can reasonably be loaded aboard a model loco.

1965 COMMUNICATIONS EIGHT AND AMATEUR BAND TEN RECEIVERS

At the time of publication of these receivers, ample stocks of the Geloso tuning units were available. However, we have been advised that production of the Geloso tuning units has ceased. In the light of this information, these receivers must now be regarded as obsolete and we advise readers not to consider them as a constructional project. To the best of our knowledge, no alternative are available to the Geloso units.

"FUZZ" UNIT: As a follow-up to your latest guitar amplifiers, would you please work out the design for a suitable "fuzz" unit. (P.T., Moorabbin, Vic.).

As you will have observed, we have already produced a design which should meet your request. Thanks for the letter, nevertheless.

MINIATURE ORGAN: I was intrigued by recent request in these columns for a less complex electronic organ. I am interested in such things myself but a "Wireless World" design (July 1966) would have called for 70 odd transistors and related gear, which would, I imagine, add up to \$160, before even considering the keyboard and other joinery. "Electronics World" (June 1964) has a very simple unit "with full organ sound," but there are gaps in the description. Would you consider reprinting this article with the additional wiring diagrams? (S. H., Noble Park, Vic.).

The two articles merely bear out what we have said in the past—there is no such thing as a simple and really satisfying electronic organ. The "Electronics World" project would be simple, if built as a demonstration toy, with a single monophonic oscillator. If expanded to include a separate oscillator for each of 17 or 18 notes, plus an elementary chord bass section, it would involve a couple of dozen transistors plus all their associated components. For this, one would still not be able to play a satisfactory range of chords, because no notes would be available below middle C to build chords in that vital part of the range. Thus, by the time the "Electronics World" basics were expanded to provide some kind of musical satisfaction, one would be well on the way towards the too-expensive "Wireless World" design. The only way simplicity can be retained is on the "toy" or "monophonic" basis and one can forget about "true organ tone," etc. It may be, one note at a time—but no one ever plays an organ that way! We still

have a one note organ on our list of future projects and will get around to it just as soon as we are able.

BATTERY DEMONSTRATION: Regarding the Eveready battery test, which you described in the June issue, I suspect that this demonstration is akin to the famous but now discredited "razor blade shaving emery cloth" hallucination which was really loose sand on glass! My engineering experience tells me that two flat surfaces one-third square foot in area would require a force of 735lbs to separate them at sea level. Furthermore, all engineers are aware of a fundamental physical phenomenon whereby two surfaces of one square inch area, when lapped together, require much more than the theoretical 14.7lbs to separate them. I am convinced that the (Eveready) device would lift and hold the major proportion of the weight on this basis, the magnet merely tipping the scales as it were. What weight will the device lift with the batteries off? As you may have published the article "tongue-in-cheek," I will simply comment that, even in electronics, things are not always what they seem. (S.H., Noble Park, Vic.).

First off, let's put the record straight. We most emphatically did not publish this article "tongue-in-cheek," nor would we have published it at all had we not satisfied ourselves that it was "fair dinkum." All the questions which you have asked of us, we had already asked of Union Carbide when they supplied the story—at our request. In fact, Union Carbide made a number of tests to satisfy themselves



that no spurious forces were involved. Both surfaces are thoroughly degreased before use and, in this condition, all attempts to "twirl" the two surfaces together, or to enlist the aid of atmospheric pressure, have been unsuccessful. At one stage the two sections were clamped together under extreme pressure without any attraction being noted. The only spurious effect is some residual magnetism, amounting to about 350lbs, but this is normally destroyed by reversing the battery connection, whereupon the two sections come apart by reason of the weight of the armature. Granted, all the theories you have mentioned could be made to work if one set out to do this, but this was not the purpose of the demonstration. We understand that the unit is to be taken to Melbourne for demonstration some time in August, and anyone having doubts such as yours would be welcome to inspect it and see it in operation.

TRAIN CONTROL: I have constructed the thyristor train controller of February 1967. On my Hornby locos of various types it gives "fantastic" results re slow running and pulling at low speeds. But, on my Rivorosi locos, the control at low speed is shocking, producing extremely jerky running. I have found that by adding re-

sistance in series with the motor the performance improves, but the good regulation is naturally lost. (I.D.H., Bilinga, Qld.).

Your problem appears to be a classic case of trying to operate a particular type of loco from too high a supply voltage. As we pointed out in the original article (page 83), at very low settings of the "throttle" the thyristor may fire only once every six or eight cycles, due to minor variations in supply voltage waveform and differences in individual rectifier characteristics. Provided the loco is incapable of starting until the throttle has been advanced some little distance beyond this point, to a point where the thyristor is firing on all cycles, the operation will be quite smooth. On the other hand, a loco which is capable of starting at this setting, i.e., one which is more efficient, will move with a jerky action due to the erratic nature of the thyristor's firing action. The remedy is to reduce the input voltage to a value which prevents the loco from starting until the thyristor is firing on all cycles. Where a variety of locos are involved it should, in most cases, be possible to select a compromise value of input voltage which provides smooth low speed action for the most efficient types and adequate top speed for the least efficient types. If the difference between locos is so great that a compromise is not possible, then a selection of tappings on the transformer secondary should be provided, and used as a "coarse control." Tappings at 12V, 15V and 17V should be adequate for most situations.

SPECIAL INSERTS: I have been a regular reader of your magazine since my arrival from the U.S.A. some months ago. Why not present colour codes and safety first procedures in special inserts designed to be removed from the magazine? Such items would be of value to readers and cost could be covered by advertisers, with better than average budgets, using the reverse side. (W.T., Yarralumla, A.C.T.).

The whole catch is in the phrase "better than average budgets." One could be excused for gaining the impression that advertising budgets constitute a mathematical anomaly: They are all below average! Our advertising department is well awake to the potential of cards, inserts, etc., and will royally welcome any potential advertiser who has an ambition to exploit any such avenue.

TRANSISTORISED SYNCHRODYNE: What are the chances of developing a transistorised synchrodyne to feed into the Playmaster 115 amplifier? (A.J.A., Randwick, N.S.W.).

We have no immediate plans for developing a transistorised version of the synchrodyne, nor can we predict when or if we will attempt such a design.

TV IMAGE REVERSED: I have recently built the 1964, 23in receiver (December 1964). All is well except for the fact that the picture is reversed. Writing reads Chinese fashion from right to left and people shake hands with their left hands. I have been unable to cure the trouble so far, can you help? (C.S. Murrumbena, Vic.).

One cure might be to try looking at the picture via a mirror! Seriously, all that has to be done is to transpose the two leads to the horizontal winding of the deflection yoke.


SIMPLE VHF RECEIVER: I am a newcomer to radio and electronics, but I have become very interested in VHF reception. Is it possible for you to design a very simple one with all the wiring details? I am sure there are many beginners who would be interested. (D.R.J. Morphet Vale S.A.).

The Fremodyne Four receiver, published in March, 1967 is reasonably simple. It would not be easy to simplify a VHF receiver much more than this, but we will keep your suggestion on file and we will look into the possibilities when we have the time and space available. ■

Electronics Technicians



ENJOY HIGHER PAY AND MORE SECURITY



WHY NOT YOU?


Put yourself in this picture! With training through T.T.I., you could qualify for a start in the Electronics Industry as a:

- Radio-television technician • Telecommunications technician • Instrumentation technician • Business machine technician • Automatic control technician • Industrial electronic technician—and many other skilled positions.

WILL YOU FILL THE BILL WHEN THE TIME COMES?

The "good job" you hold down today may offer you less and less opportunity for advancement as Electronics increase their impact in all branches of industry.

TECHNICAL TRAINING INTERNATIONAL, a world-wide company with over 27 years' experience in the field of specialised technical training, now offers the latest Electronics training programmes available in Australia.



THIS IS A PRACTICAL PROGRAMME

You receive—and keep, the practical tools to complete your training—from tool kit to oscilloscope.



IF YOU ARE BETWEEN 18 AND 45 YEARS, AND EARNING LESS THAN \$80 PER WEEK . . . IF YOU ARE SERIOUSLY INTERESTED IN TRAINING FOR A CAREER IN ELECTRONICS, FILL IN THIS COUPON FOR FURTHER INFORMATION WITHOUT OBLIGATION.

E To: Technical Training International Pty. Ltd.
P.O. Box 83, Double Bay, N.S.W.
Please tell me more about T.T.I. Electronics Training, without obligation to me.

Name.....
Address.....
Age..... Present occupation.....
T.T.I.—The Industry-approved Technical Training Organisation EA

MAGNETIC PICKUP PREAMP FOR THE PLAYMASTER 118

(Continued from page 85)

board it will be seen that the board is earthed to the support bracket from both earth tags to solder lugs under the adjacent mounting screws. For the input signal cable we used a twin conductor type with a common outer shield. The input earths are connected together at the sockets and the input cable shield connects to one earth lug on the board. Do not earth the input connectors at the rear of the chassis.

The output cables from the preamp have their shields connected to the appropriate earth lugs on the board and also the earth lug on the selector switch. The earth return for the zener diode network is made to the 12AX7 spigot. Apart from the above details all earth returns for the amplifier are made as described in the July article. All earth returns for the 12AX7 preamp stage are made to a point adjacent to the 12AX7 socket.

The 9-volt supply is derived from HT1 via a zener diode network. This network and the 100K "tape-outlet" isolating resistors were mounted on an extension of the tagboard for the right channel, as shown in the accompanying sketch. Readers building the complete amplifier could obviously use a 22-tag panel for the right channel. The 33K 5W HT dropping resistor may not normally be available over the counter. Readers can "make up" a suitable resistor with value ranging from 33K to about 50K by "parallelling" higher values, e.g., two 100K2W or three 150K1W.

Moving to the other end of the same tag-board, the pair of tags mounting the 100pF feedback "phase correction" capacitor were removed and the capacitor was connected directly across the feedback resistor. In the vacated space we mounted a small aluminium (tinplate will suffice) shield which eliminates radiation from the output wiring into the pickup input sockets, which are of the unshielded type. As a further precaution, we also re-routed the output transformer secondary leads away from the pickup inputs.

PARTS LIST

- 1 Printed wiring board, 4in x 3in type 65/p10.
- 2 NPN silicon transistors, BC108, 2N3565, etc.
- 2 NPN silicon transistors, BC109, SE4010, etc.
- 2 PNP transistors; 2N3638, OC44N, etc.
- 6 0.1uF L.V. (low voltage) plastic.
- 2 6800pF L.V. plastic.
- 2 3900pF L.V. plastic.
- 2 64uF/6VW electrolytics.
- 1 500uF/10VW electrolytic.
- 1 12-volt zener diode, OAZ213-15% or similar.

RESISTORS

(All ½-watt unless specified)
1x33K 5W (see text), 1x3.3K, 2x3.3M, 4x470K, 2x390K, 2x56K, 2x47K, 2x22K, 2x10K, 2x4.7K.

MISCELLANEOUS:—20-gauge steel preamp shield (see diagram), solder lugs, shielded cable, mounting screws, tagstrip, etc.

SPECIAL NOTE:—Where provision is to be made for magnetic pickup input, constructors should use a low radiation power transformer, i.e., one fitted with a copper shorting strap. (Ferguson PVD111FT, etc.)

CLASSIFIED ADVERTISING

Advertisements in these columns cost \$0.60 per line. Each line contains the equivalent of five words each of nine letters. Minimum size of advertisements is two lines. Please note **PAYMENT MUST ACCOMPANY ALL ADVERTISEMENTS EXCEPT THOSE PLACED BY ACCREDITED AGENCIES.** Your advertisement for the September issue must reach our office before August 8. Address your advertisement to the Advertising Manager, **ELECTRONICS Australia, Box 2728, G.P.O., Sydney.**

FOR SALE

HOBBIES and model supplies. Triang railways. Rivarossi railways. Peco railways. Scalextric model motor racing. Cox slot cars. Minic Motorways. Dinky toy Matchbox models. Meccano. Write for free price lists. Please indicate interests. Free packing and postage on all orders. P.J.P. Productions, 15 Hamilton Street, Gisborne, Vic.

SELL all back issues "ELECTRONICS Aust." in stock all times. 1939-56 copies. 30c; 57-63. 40c; 1964 to date. 50c. Post incl. T. WEIR, 55 O'Connor Street, Haberfield, Sydney. 71-2569.

RECORDING TAPE new, boxed guaranteed. 3in x 20ft. 5c; 5in x 60ft. 1.35; 7in x 120ft. \$1.50. Empty reels 30c; 7in. 50c. Write for free list (inc. BASF). All Mail Order goods supplied. ALMO, Box 15, Footscray, Vic.

RESISTOR SPECIAL. Miniature 1/2W. 5 p.c. tol. Top grade. Will supply 3 only resistors of each preferred value between 10 ohms and 1 meg. (57 different values), totalling 171 resistors. Full price \$5.84 each, inc. postage. HALLARD ELECTRONICS, Box 58, P.O. Campsie, N.S.W.

HIGH IMP. PRE-AMP. Uses 2 transistors (silicon). High gain, low noise. 9V Electronics Aust. circuit. Price \$4.95 kitset form. \$5.95 wired and tested. KITSETS AUST., Box 176 P.O. DEE WHY, N.S.W.

TRANSISTOR AMP. 750 mw. Total current 18mA. Input sens. 50mV. 15 ohm output. Size 2in x 2in. 9V. Guaranteed. Price \$9.16 (\$4.95). KITSETS AUST., Box 176, DEE WHY, N.S.W.

BROADCAST RECEIVER BOOSTER KIT. This transistorised RF Amplifier will increase sensitivity, selectivity and signal-to-noise ratio. No alterations to receiver necessary—output of unit connects to receiver aerial socket. Power gain 25dB. Reception of distant stations made clear. Stops fade. Full price \$3.50. Prompt service. HALLARD ELECTRONICS, Box 58, P.O. Campsie, N.S.W.

SIGNAL INJECTOR KIT. 5000cps—2MC. Very handy instrument indeed. 2 transistors. Small size 2 9/16 (\$2.95). 35/ wired and tested. Post free. Prompt service. KITSETS AUST., Box 176, P.O. DEE WHY, N.S.W.

SHORTWAVE RECEIVER BOOSTER KIT. Enables distant stations to be received clearly. Stops fade. Power gain 25dB. Freq. 3.2-12MC. Size 2in long, 1 1/2in wide and 1 1/2in high. Output connected to receiver aerial socket. Price 45/ (\$4.50). Wired and tested \$5.50. KITSETS AUST., Box 176 P.O. DEE WHY, N.S.W.

MODEL Compound marine engine (1 1/2in x 1 1/2in). New design. Bolton, 72 King Street, Sydney. 2000. Catalogue. 80c.

MICROPHONE stands. Grey baked enamel TR1 base with chrome tube extending to 6ft. \$9.75. Trade supplied. Rambler Recording Co., 39 Swanston St. Mentone, Vic. Tel. 93-4545. A.H. 787-2465.

CUSTOM Built Transformers—Power, Audio, etc. Single or quantity production. Amplifiers, P.A. systems, battery chargers. Rectifiers, electric motors, transistor radios. General engineering, fitting and turning, sheet metal work, etc. Parkinson Transformers, P.O. Box 523, South Brisbane. Phone Beenleigh 33, Qld.

ELECT. Aust. 39/67. Radio/TV books, cheap, write list. 1 Soudan St., Coburg, Vic.

BOX of radio parts, inc. keyswitches, pots, coils, spkrs., radio chassis, etc., \$5. 1200ft tapes 10/. TR1936 no xtals genemotor. \$10. Atc freight. Foot, 65 Wave Ave., Mt. Waverley, Vic.

SELL Recording studio, going concern, Brisbane central city position. Initial inquiries, Box 141 P.O., Broadway, Brisbane, Qld.

TRANSFORMERS wound. Output or mains, and specials to order. Paris Radio Electronics, 7A Burton St., Darlinghurst, N.S.W. 31-3273.

R. TV & H. Electronics, most copies from 56 to date. Best offer. Melb., 56-3315, Vic.

FET-VOM. Field effect transistor volt-megohmmeter, completely wired, all range switches, etc. less 0.1 Ma meter, less cabinet. TV held service tested many months. \$25.60. D. Haltermann, 4 Mt. Albert Rd., Geelong, Vic.

BC611 Walkie Talkie. Pair with xtals, valves, untested. \$40. O.N.O. 23 Lambert St., Frankston. Ph. 783-5200, Vic.

2 FIELD Telephones, type "F" MK. Good working condition. \$24. 8 Edward St., Kew., Vic. Ph. 80-1644.

MAY, 1966. 3in CRO, \$50, partly complete. July, 1963, 3in CRO, \$25. 10 Clifton Parade, Warrawee. 46-4858. N.S.W.

TV Picture Tubes—14in to 24in. Trade only. New \$12, rebuilt, 2-year warranty \$12. 1-year \$11. Bonded 23in new \$26, rebuilt \$24, seconds \$15. All prices plus freight and dud or deposit on dud. 14in-21in 70 \$5.90, \$8, 21in 110 \$8, 23in \$10, 23in bonded dud deposit \$9. Extra charge for scratches \$2. Extra if air in dud \$3 (bonded \$6). Available at slightly higher price at 1120 O'Leary Road, Oyster Bay, Brisbane. Buy duds, Sure Brite, 22a Victoria St., Lewisham, N.S.W. Phone 56-6363.

READER SERVICE

PRE-RECORDED TAPE LIBRARY. Tape recorder owners. Join the Australian Tape Recording Society and have access to over 1500 top-quality tapes at 60c hire. Bi-monthly magazine, news tapes, tape and equipment discounts. Send S.A.E. to ATRS, Box 9, P.O., Crow's Nest, N.S.W.

TRANSFORMERS wound output or mains and specials to order. Paris Radio Electronics, 7A Burton St., Darlinghurst, N.S.W. 31-3273.

REPAIRS to receivers, transmitters, construction, testing; TV alignments. Xtal conv., specialised electronic equip. Eccleston Electronics 146a Cotham Road, Kew, Vic. 80-3777.

TAPE to disc service. Take advantage of W. and G. Records professional experience when next needing a tape to disc service. W and G. Record Processing Co., 185a Beckett Street, Melbourne. Tel. 329-7255.

ELECTRONIC ORGANS. Do not build yourself an organ without first consulting us. Send for initial information on the superb Schober (U.S.A.) build-it-yourself kits. No stamps required. The Electronic Organ Co., 124 Livingstone Avenue, Pymble, N.S.W. (Mail only.)

MICRO-GROOVE Discs from your tapes, also tape copying service. Highest quality discs at all speeds. Prompt service, moderate charges. Country and Interstate inquiries welcomed. Vitatone Recording Studios, Box 18, Post Office, Lane Cove, N.S.W. Phone (Sydney) 42-6154.

WANTED

NEW S.T.C. Carphone converted to 146. All plus. Xtals and Manual avail. Good price for good job. 22MU. 78 Aberdare Rd., Cessnock, N.S.W.

FREMODYNE Rec., or tuner, made to Electronics Aust. spec. No Jap parts to be used. As demo. model. Price and particulars, J. Palmer, Box 77, P.O. Annandale, N.S.W.

TV Signal generator or B&K analyst. Details, T. Randall, Box 32, Bourke, N.S.W.

ARB Receiver in working order. Price and particulars to K. Doessel, Railway Parade, St. Lawrence, Qld.

WANTED

BYER or Rola 66 or 77 recorder. Must be in good cond. Rambler Recording Co., 39 Swanston St., Mentone, Vic. 787-2465.

78 rev. records. Theatre pipe organ music. Robertson, 17 Carinya Rd., Mt. Colah, N.S.W. 47-3807.

PAIR used 12in co-axial speakers. Goodman or Wharfedale standard. Sydney. 88-2931. N.S.W.

TR1196; Fremodyne; RA18/J receivers. 78 Battve Avenue, Kogarah, N.S.W. 58-4550.

SERVICE

BILL TURNBULL offers you service on Hi Fidelity equipment Tape Recorders, Communication Receivers and Electronic Test Equipment.

25 years experience
All work guaranteed

BILL TURNBULL

11 ELLALONG ROAD,
CREMORNE, N.S.W. 90 4825

AUSTRALIAN RADIO DX CLUB

Join Australia's only club for DX listeners and receive up-to-the-minute news in short wave, broadcast bands, utility and amateur stations. The Australian Radio DX club has active branches in most States and has a weekly DX program on 3NE at 1035 p.m. A.E.S.T. which is the only one of its kind in the world. A monthly publication is available to 21 members and sample copies can be obtained by writing to the club. Annual subscription to Australian Radio DX Club is only \$3.00.

Write for full information to—

AUSTRALIAN RADIO DX CLUB P.O. Box 227, BOX HILL, VICTORIA. 3128.

TACHOMETER METER



MODEL CS-260-T

45 ALBANY ST CROWS NEST SYDNEY 43-5596

HERRIER
ELECTRICAL INSTRUMENTS

YES! A METER FOR EVERY ELECTRONICS AUST. PROJECT. LOW IN PRICE GUARANTEED
WRITE FOR CATALOGUE WHICH WILL BE SENT WITH PLEASURE

ADVERTISING INDEX

A & R Transformers Pty. Ltd.	136
A.C.E. Radio	166
Adcoia Products Pty. Ltd.	162
Agia Manufacturing Co. Pty. Ltd.	44
Agia-Gevaert Pty. Ltd.	50
Akai Electric Co. Ltd.	54
Amalgamated Wireless (A'sia) Ltd.	86, 137, 152
Amalgamated Wireless Valve Co. Pty. Ltd.	56
Amplion (A'sia) Pty. Ltd.	104, 117
Arrow Electronics Pty. Ltd.	108
Asdic Stereo Specialists	103
Associated Controls Pty. Ltd.	148
Astronic Imports Division	32
Audio Engineers Pty. Ltd.	93
Australian Radio DX Club	175
Aust. Radio and TV College Pty. Ltd.	Back cover
Bright Star Radio	151
Broadway Electronics Pty. Ltd.	64
Broadway Electronics (Sales) Pty. Ltd.	2, 3
Carter, P. Radio and TV Service	115
Chapman, Maurice and Co. Pty. Ltd.	60, Inside front cover
Classic Radio	118
Classified Advertisements	175
Collins Book Depot Pty. Ltd.	12
Comtel International (Vic.) Pty. Ltd.	75
Control Data Australia Pty. Ltd.	45
Convoy International Pty. Ltd.	136
C.S.I.R.O.	77
Cunningham, R. H. Pty. Ltd.	53
Danish Hi-Fi Pty. Ltd.	117
Deitch Bros.	170
Dept. of Supply	4
Ducon Division	28
Elco (Australasia) Pty. Ltd.	68
Electronic Developments Pty. Ltd.	126, 127
Encei Electronics Pty. Ltd.	19, 58, 76, 122, 164, 172
Fairchild Australia Pty. Ltd.	5, 6, 7
Ferguson Transformers Pty. Ltd.	40
Ferrier Electrical Instruments	175
G.E.C. (Australia) Pty. Ltd.	100
General Accessories	94
Goldring Eng. (A'sia) Pty. Ltd.	34, 116
Goodmans Industries Ltd.	72
Gray, Simon Pty. Ltd.	22, 74, 124
G.R.D. Instruments Pty. Ltd.	Inside back cover
Green Corporation Ltd.	106
Haco Distributing Agencies Pty. Ltd.	10
Ham Radio Suppliers	153
Hare and Forbes Pty. Ltd.	171
H.B. Radio Sales	107, 115
Homecrafts Pty. Ltd.	132
Industrial & Domestic Equip. Pty. Ltd.	172
International Correspondence Schools	140
I.R.C. (A'sia) Pty. Ltd.	78, 128
Jacoby, Mitchell and Co. Pty. Ltd.	38, 66
J.H. Reproducers Pty. Ltd.	96
Johnston, D. R. and Co. Pty. Ltd.	103
Klapp Electronics Pty. Ltd.	113
Kodak (Australasia) Pty. Ltd.	98
Kuenzli, Ernest Pty. Ltd.	113
Lafayette Electronics Division	168
Leak, H. J. (Aust.) Pty. Ltd.	110, 111
Lempriere, O. T. and Co. Ltd.	109
Letrasat Australia Pty. Ltd.	81
Magrath, J. H. and Co. Pty. Ltd.	92
Manufacturers Spec. Prod. Pty. Ltd.	16, 59
Marconi School of Wireless	143
Mastersound Sales Pty. Ltd.	90
Matson Automotive Ind. Pty. Ltd.	134
McLellan, Wm. J. and Co. Pty. Ltd.	32
Miniwatt Electronics Division	20
Modern Science Supplies	51
Mullard-Australia Pty. Ltd.	24
National Radio Supplies	158, 159
O'Rourke Industries	39
Palmer, H. G. Pty. Ltd.	125
Paton Electrical Pty. Ltd.	129
Phonotric	103
P.M.G. Dept.	51
Precision Windings	123
Pye Pty. Ltd.	156
Quad	102
Radio Despatch Service	125
Radio House Pty. Ltd.	104, 154
Radio Parts	131
RCA of Australia Pty. Ltd.	46, 47, 120
R.C.S. Radio Pty. Ltd.	150
Recorded Music Salon	88, 112, 134
Rola Company (Aust.) Pty. Ltd.	26
Sansul Electric Co. Ltd.	80
Sarion Industries Pty. Ltd.	130
SCEI Pty. Ltd.	150
Shalley, Peter Electronics Pty. Ltd.	130
Standard Publishing Co. Pty. Ltd.	144
Standard Telephones & Cables Pty. Ltd.	14
Stott's Tech. Correspondence College	143
Technical Training Int. Pty. Ltd.	174
Tel-Leigh-Tubes	141
Thomas Electronics of Aust. Pty. Ltd.	70
"Thought Power"	131
Trio Corporation	114
Tudor Radio	138, 139
Turnbull, Bill	175
United Radio Distributors Pty. Ltd.	35
United Trade Sales Pty. Ltd.	155
University Graham Inst. Pty. Ltd.	64
Warburton Franki Ltd.	62, 160
Watkin Wynne Pty. Ltd.	103, 109
W.F.S. Electronics Supply Co.	148
Willis, S. E. Trading Co.	121
Willis, William and Co. Pty. Ltd.	156
Wireless Institute of Australia (N.S.W.)	39
Wireless Institute of Australia (Tas.)	93
Wireless Institute of Australia (Vic.)	55
Wonder Wool Pty. Ltd.	119
Zephyr Products Pty. Ltd.	30, 146, 162

CLASSIFIED ADVERTISERS

USE THIS FORM FOR YOUR NEXT ADVERTISEMENT TO APPEAR IN THE
ELECTRONICS Australia Classified Columns

To the Advertising Manager,
ELECTRONICS Australia,
Box 2728 G.P.O.,
Sydney.

ENDORSEMENT
ADDRESS

STATE

• Please insert the following
advertisement in the
..... issue

• I enclose P. Note/Cheque for \$.....
being full payment for..... lines at \$0.60 per line.

☐ FOR SALE ☐ WANTED ☐ READER SERVICE ☐ POSITION VACANT

Please write in block letters with ink or ball-point pen.

Number of insertions

"ELECTRONICS Australia" SPECIAL ORDER FORM

Guarantee yourself a complete set of issues for
your library with no copies missing.

SUBSCRIPTION RATES

	PER YEAR
Commonwealth, Fiji, N. Guinea	\$4.10
United Kingdom & N. Zealand	\$4.60
British Dominions	\$4.60
Elsewhere	\$5.60

POST THIS COUPON TO:—

The Circulation Manager, **ELECTRONICS Australia**,
Box 2728, G.P.O., Sydney, Australia.

Name

Address

Enclosed is \$..... for years. Start with

(Please use cheque, money order, etc. Do not enclose cash)

At \$59.00 THE LABCRAFT SRT 643

is the *ONLY* turntable anywhere near this price
that gives you these
OUTSTANDING ADVANTAGES:-

SEE YOUR NEAREST G.R.D. RETAILER



**MODEL 643
STEREO RECORD
PLAYER**



<u>Victoria</u>		
Danish Hi-Fi P/L.	66 Mayston St.	Haw. E.
Douglas B.J. Trading.	197 Russell St.	Melb.
Douglas Radio.	199 Darling Rd.	E. Melv.
E. & S. Trading Co. P/L.	234 High St.	Ashburton.
Electronic Developments.	232 Flinders Lane.	Melb.
Hannams(Sales) P/L.	8 Station St.	Mitcham
Herbert Small's Camera	193 Princes H'way	Morwell
Macey & Rose	465 Centre Rd.	Bentleigh.
Magrath J. H. & Co.	208 Lit. Lonsdale St.	Melb.
Malvern Star Stores	161 Sturt St.	S. Melb.
Master Electrics P/L.	547 Elizabeth St.	Melb.
Myer (Melbourne) Ltd.	Lonsdale St.	Melb.
McPhersons Hi-Fi Centre	205 Dorset Rd.	Boronia.
Radio Parts P/L.	562 Spencer St.	Melb.
S.T.A. Electronics	731 Centre Rd.	E. Bentl.
South City Electronics	280 Clarendon St.	S. Melb.
Suttons Pty. Ltd.	105 Elizabeth St.	Melb.
Thomas' P/L.	161 Exhibition St.	Melb.
Warburton Frankl P/L.	220 Park St.	S. Melb.

<u>South Australia</u>		
Audiorama Sales	15 Brigalow Ave.	Blackwood
Elac Automation	224 Hutt St.	Adelaide
MACK'S ELECTRONICS	199 Rundle St.	Adelaide
Spencer Gulf Radio & TV	46 Alexander Street	Port Pirie
Truscott Electronics	62 Hindmarsh Sq.	Adelaide

<u>New South Wales</u>		
Arrow Electronics P/L.	422 Kent St.	Sydney
Bardsley Imp. Tdg. Co.	166D Glebe Rd.	Glebe
Broadway Electronics P/L	206 Broadway	Sydney
Convoy International P/L	449 Kent St.	Sydney
Dickens & Carey(Bathurst)	76 Keppel St.	Bathurst
Lawrence & Hansen Ltd.	188 Parry St.	N'castle W
Radio Despatch Service	869 George St.	Sydney
United Radio Dist.	Shop 32, Ash St.	Sydney
Victor, A & Co.	196 Elizabeth St.	Sydney
Wilson, H. Ben	166 Glebe Road	Glebe

<u>A.C.T.</u>		
Hi-Fi Laboratories	39 Kitchener St.	Hughes
Australian Physical Labs	6 Caladenia St.	O'Connor
J.B. Young Ltd.	Kingston	Canberra

<u>Western Australia</u>		
Alberts T.V. & Hi-Fi	832a Hay St.	Perth
Atkins (W.A.) Ltd.	894 Hay St.	Perth
Carlyle & Co. P/L.	1 Milligan St.	Perth
General Accessories	36 Milligan St.	Perth
Hill, Athol M.	613 Wellington St.	Perth

<u>Queensland</u>		
BRISBANE AGENCIES	76 Wickham St.	Fortitude V.I.
Chandlers Pty. Ltd.	Cr. Albert & Charlotte	Brisbane
Crocker, Jas & Sons	Victoria St.	Mackay
Harrold A.E. P/L.	123 Charlotte St.	Brisbane
Pearce C.A. & Co.	33 Bowen St.	Brisbane
Trackson Bros. P/L.	157 Elizabeth St.	Brisbane
Ward, Norm Electronics	37 Love Lane	Mund'burra Towns.

<u>Tasmania</u>		
Genders, W. & G.P.L.	53 Cameron St.	Launceston
Homecrafts P/L.	199 Collins St.	Hobart
Homecrafts-Tasmania	120 Charles St.	Launceston
Homecrafts-Tasmania	53 Wilson St.	Burnie

<u>Northern Territory</u>		
Pfizzners Music House	2 Darwin Arcade, Smith Street	Darwin

.... OR POST COUPON BELOW

- * Special flexible rim-belt drive from truly vibration-free patented motor suspension which isolates all vibration from base plate - gives perfect performance completely free of "rumble", "wow" and "flutter".
- * Asynchronous motor (not tied to mains frequency) with special governor making motor speed independent of mains voltage and frequency.
- * Speed may be adjusted $\pm 10\%$.
- * Pick-up arm provided with adjustment for both stylus pressure and height; fitted with velvet action lifting and lowering device.
- * Fitted with exceptionally pleasant sounding Merula ceramic stereo cartridge with diamond stylus; interchangeable heads enable use of mono or stereo, ceramic or magnetic cartridges.
- * Drive spindle ground to extremely fine tolerances - nylon and bronze bearings are self-lubricating, virtually service free.
- * Outstanding Danish design, most attractive in Teak or Palisander contrasting with mat black base. (BASE EXTRA)

**BUILD UP YOUR OWN INDIVIDUAL
HI-FI WITH THIS MONEY-SAVING
LABCRAFT 643 Stereo unit**

If you would prefer to mount your own arm, or a famous B & O or All-Balance arm, choose from Labcraft 605, 605L or 655 model turntables!

SOLE AUSTRALIAN AGENTS

G.R.D.

INSTRUMENTS PTY. LTD.


**6 RAILWAY WALK, CAMBERWELL,
VICTORIA. TELEPHONE 82 1256**

G.R.D. INSTRUMENTS PTY. LTD.
6 RAILWAY WALK, CAMBERWELL, VIC.
PLEASE SEND, FREE OF CHARGE, LEAFLETS
WITH PARTICULARS OF THE LABCRAFT TURNTABLE.

NAME _____
ADDRESS _____
STATE _____

GRD.10

Australian distributors
of world-famous
Beocord De Luxe Tape Recorders



THIS FREE BOOK COULD BE THE TURNING POINT IN YOUR CAREER

ASK YOURSELF THESE 3 QUESTIONS

1. Am I in a dead-end job?
2. Can I use my spare time to get ahead?
3. Am I capable of earning more money?

If the answer is yes, there is room for you in radio-television. Does your job really offer security — worthwhile prospects? If not, now is the time to do something about it. Send the coupon below for the free booklet "Careers in Radio and Television" which shows you just how A.R.T.C. training can help you to a bright future with good prospects.

TRAIN AT HOME OR AT THE COLLEGE

With A.R.T.C. you can obtain the training you need at the benches and lecture halls of Australian Radio and Television College or in your own home by correspondence . . . you can be taught every important aspect of radio-television, details of the fundamental principles of Electronics.

GET INTO ONE OF THESE PROFITABLE CAREERS IN RADIO/TELEVISION

There is a profitable career for you in the many phases of radio-television including manufacturing, radio servicing, television servicing, research, sales, broadcasting and television executive, armed forces. A.R.T.C. can help you gain one of these much-sought-after positions, but remember, it is only the trained men who succeed and A.R.T.C. can give you the complete training which is necessary for success in Electronics.

Make Spare-Time Money

If you wish, you can make your spare time earn money for you by training at home and many students make extra money after only the first few weeks. However, if it is not convenient for you to train at home, then you may use the modern A.R.T.C. workshops. The course is intensely practical and individual. Safeguard your future . . . mail the coupon today.

A.R.T.C. CAN TRAIN YOU AS IT HAS THOUS- ANDS OF OTHERS!

Thousands of ambitious men have realised the benefits offered by A.R.T.C. training and are now making money in radio. You can join the ranks of the skilled men. . . and it costs only pence a day.

MAIL COUPON NOW


You are invited to mail the coupon below which can be your first step towards securing a job or business of your own with good prospects, security and big money. A.R.T.C. will mail to you, by return, at no obligation to you, the big free booklet "Careers in Radio and Television." This booklet will show you definite steps you can take for a better job . . . how you can succeed in life. Post the coupon, phone or call NOW.

AUSTRALIAN RADIO AND TELEVISION COLLEGE

PTY. LTD.

E. S. & A. BANK BUILDING,

Cnr. Broadway and City Road, Sydney.
(Opp. Grace Bros.) Phone 211-4244 (3 lines.)



AUSTRALIAN RADIO & TELEVISION COLLEGE PTY. LTD.,

206 Broadway, Sydney, N.S.W.

Dear Sir,

Please send me, without obligation, your free booklet "Careers in Radio and Television."

NAME

ADDRESS